



Informatica® Edge Data Streaming  
2.5.0

# Installation and Configuration Guide

Informatica Edge Data Streaming Installation and Configuration Guide

2.5.0

July 2019

© Copyright Informatica LLC 2013, 2021

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Big Data Management, and PowerExchange are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

Publication Date: 2021-06-16

# Table of Contents

<b>Preface</b> .....	<b>5</b>
Informatica Resources. . . . .	5
Informatica Network. . . . .	5
Informatica Knowledge Base. . . . .	5
Informatica Documentation. . . . .	5
Informatica Product Availability Matrices. . . . .	6
Informatica Velocity. . . . .	6
Informatica Marketplace. . . . .	6
Informatica Global Customer Support. . . . .	6
<b>Chapter 1: Installation and Configuration</b> .....	<b>7</b>
Installation and Configuration Overview. . . . .	7
Installation Tasks. . . . .	8
Data Flow Migration. . . . .	8
<b>Chapter 2: Pre-Installation Tasks</b> .....	<b>10</b>
Pre-Installation Tasks Overview. . . . .	10
Guidelines for a High Availability Installation. . . . .	11
Prepare for a Secure Installation. . . . .	11
Prepare for Kerberos Authentication Setup. . . . .	12
Get the Edge Data Streaming License Key. . . . .	14
Pre-Installation Requirements for the Administration Components. . . . .	14
Verify Minimum System Requirements for the Administration Components. . . . .	14
Verify Port Availability for the Administration Components. . . . .	15
Pre-Installation Requirements for the Edge Data Streaming Node. . . . .	15
Verify Minimum System Requirements for the Edge Data Streaming Node. . . . .	15
Set the File Descriptor Limit. . . . .	16
Extract the Installer Files. . . . .	16
Extract the Installer Files on Linux. . . . .	16
Extract the Installer Files on Windows. . . . .	17
<b>Chapter 3: Installation</b> .....	<b>18</b>
Installation Overview. . . . .	18
Installing Edge Data Streaming in Graphical Mode. . . . .	18
Installing Edge Data Streaming in Console Mode. . . . .	20
Installing Edge Data Streaming in Silent Mode. . . . .	22
Edge Data Streaming Node Installation. . . . .	25
Installing the Edge Data Streaming Node in Graphical Mode. . . . .	26
Installing the Edge Data Streaming Node in Console Mode. . . . .	26
Installing the Edge Data Streaming Node in Silent Node. . . . .	28

Installing Edge Data Streaming Nodes on Remote Linux Systems. . . . .	29
Configure Passwordless SSH Connections. . . . .	29
Configuring Passwordless SSH Connections. . . . .	29
Installing Edge Data Streaming Nodes on Remote Systems. . . . .	30
<b>Chapter 4: Post-Installation Tasks. . . . .</b>	<b>32</b>
Post-Installation Tasks Overview. . . . .	32
Start the Administrator Daemon. . . . .	32
Starting or Stopping the Administrator Daemon on Linux. . . . .	32
Starting or Stopping the Administrator Daemon on Windows. . . . .	33
Create Multiple Edge Data Streaming Node Services on Windows. . . . .	33
Start the Edge Data Streaming Node. . . . .	33
Starting or Stopping the Edge Data Streaming Node on Linux. . . . .	33
Starting or Stopping the Edge Data Streaming Node on Windows. . . . .	34
Start the Informatica Domain. . . . .	34
Starting or Stopping Informatica Domain on Linux. . . . .	34
Starting or Stopping Informatica Domain on Windows. . . . .	34
Create a Edge Data Streaming Service. . . . .	35
Log In to the Administrator Tool. . . . .	35
Adding a License. . . . .	35
Creating the Edge Data Streaming Service. . . . .	36
<b>Chapter 5: Uninstallation. . . . .</b>	<b>38</b>
Uninstallation Overview. . . . .	38
Before You Uninstall. . . . .	38
Edge Data Streaming Uninstallation. . . . .	38
Uninstalling Edge Data Streaming on Windows. . . . .	39
Uninstalling Edge Data Streaming in Console Mode. . . . .	39
Uninstalling the Edge Data Streaming Node in Graphical Mode. . . . .	39
Uninstalling the Edge Data Streaming Node in Console Mode. . . . .	39
Uninstalling the Remote EDS Node. . . . .	40
<b>Chapter 6: Troubleshooting the Installation. . . . .</b>	<b>41</b>
<b>Appendix A: Configuring Extended JVM Parameters. . . . .</b>	<b>42</b>
<b>Index. . . . .</b>	<b>43</b>

# Preface

The Informatica Edge Data Streaming Installation and Configuration Guide is written for system administrators who are responsible for installing the Edge Data Streaming product. This guide assumes you have knowledge of operating systems, relational database concepts, and the database engines, flat files, or mainframe systems in your environment. This guide also assumes you are familiar with the interface requirements for your supporting applications.

## Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

### Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit <https://network.informatica.com>.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

### Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit <https://search.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at [KB\\_Feedback@informatica.com](mailto:KB_Feedback@informatica.com).

### Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit <https://docs.informatica.com>.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

## Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at <https://network.informatica.com/community/informatica-network/product-availability-matrices>.

## Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services and based on real-world experiences from hundreds of data management projects. Informatica Velocity represents the collective knowledge of Informatica consultants who work with organizations around the world to plan, develop, deploy, and maintain successful data management solutions.

You can find Informatica Velocity resources at <http://velocity.informatica.com>. If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at [ips@informatica.com](mailto:ips@informatica.com).

## Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at <https://marketplace.informatica.com>.

## Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:

<https://www.informatica.com/services-and-training/customer-success-services/contact-us.html>.

To find online support resources on the Informatica Network, visit <https://network.informatica.com> and select the eSupport option.

# CHAPTER 1

## Installation and Configuration

This chapter includes the following topics:

- [Installation and Configuration Overview, 7](#)
- [Installation Tasks, 8](#)
- [Data Flow Migration, 8](#)

### Installation and Configuration Overview

Informatica Edge Data Streaming (EDS) is a highly available, distributed, real-time application that collects and aggregates machine data. You can collect machine data from different types of data sources, transform the data, and write it to different types of data targets.

When you run the EDS installer, it installs the EDS components.

EDS includes the following components:

#### **Administrator Daemon**

The Administrator Daemon is a process that collects statistics and state information from all EDS Nodes, aggregates the information, and sends them to the Administrator tool. The Administrator Daemon sends EDS Node configuration and EDS license details to Apache ZooKeeper. The Administrator Daemon runs an HTTP server. The EDS Nodes use the HTTP server to fetch configuration and libraries from the Administrator Daemon. The database stores configuration details.

The Administrator Daemon installation process also installs the UM Topic Resolution Daemon (LBMRD) and a persistent store. The persistent store provides storage to message streams.

#### **EDS Nodes**

A EDS Node is a Java program within which source services and target services exist. You can run multiple source services and target services on a single EDS Node. Source services collect data from data sources and publish the data. Target services receive and write that data to a data target.


You install EDS Nodes on all the hosts on which you want to run source services or target services. The EDS Nodes download plugins from the Administrator Daemon, and the configuration from Apache ZooKeeper.

#### **Apache ZooKeeper**

Apache ZooKeeper is a centralized service that maintains the configuration information of the EDS Nodes in a deployment. You can deploy ZooKeeper as a standalone instance or, for reliability, as a cluster called a ZooKeeper ensemble. When you start a EDS Node, it fetches its configuration information from ZooKeeper.

You install the EDS components on the machines where Informatica is installed. Ensure that you install the Administrator Daemon on the gateway nodes of the Informatica domain. The EDS Node and Apache ZooKeeper can be installed on other machines. After you complete the installation process, log in to the Administrator tool, create and configure the Edge Data Streaming service.

The following figure shows a sample EDS deployment:



For more information about product requirements and supported platforms, see the Product Availability Matrix on Informatica Network:

<https://network.informatica.com/community/informatica-network/product-availability-matrices>

For more information about the components in the EDS deployment, see the *Informatica Edge Data Streaming User Guide*.

## Installation Tasks

To install EDS, perform the following tasks:

1. Perform the pre-installation tasks to ensure that you can install the EDS components.
2. Get the EDS 2.4.0 license key.
3. Install the administration components, which include the Administrator Daemon, Administrator tool, and Apache ZooKeeper, and the EDS Node.
4. Perform the post-installation tasks. Start the EDS Node, and administration components.

After you perform the tasks in the installation process, log in to the Administrator tool and create and configure the Edge Data Streaming service.

## Data Flow Migration

If you have version 2.3.2 installed, you can migrate the data flows to version 2.4.0. If you have an earlier version of Edge Data Streaming, you must uninstall the previous version and install Edge Data Streaming 2.4.0.

Perform the following steps to upgrade the data flows:

1. Log in to version 2.3.2 and undeploy the data flows.



2. Export the data flows, node groups, and secure parameters.
3. Delete the VDS Service.
4. Uninstall version 2.3.2.
5. Verify that you have installed the required version of the Informatica domain services.
6. Install and configure EDS 2.4.0.
7. Import the data flows that you exported in version 2.3.2 by modifying the version from 2.3.2 to 2.4.0, and deploy them again.

For more information about supported Informatica version, see the Product Availability Matrix on Informatica Network: <https://network.informatica.com/community/informatica-network/product-availability-matrices>

## CHAPTER 2

# Pre-Installation Tasks

This chapter includes the following topics:

- [Pre-Installation Tasks Overview, 10](#)
- [Guidelines for a High Availability Installation, 11](#)
- [Prepare for a Secure Installation, 11](#)
- [Get the Edge Data Streaming License Key, 14](#)
- [Pre-Installation Requirements for the Administration Components, 14](#)
- [Pre-Installation Requirements for the Edge Data Streaming Node, 15](#)
- [Set the File Descriptor Limit, 16](#)
- [Extract the Installer Files, 16](#)

## Pre-Installation Tasks Overview

Before you install EDS or upgrade to a new release, plan the installation to ensure that you can successfully install and use the product.

Before you install EDS, perform the following planning tasks:

- To install EDS in a high-availability environment, review the high availability installation information.
- To configure secure communication between the EDS components, review the security pre-installation information.
- Verify that you have installed supported version of Informatica server and Informatica domain.
- Get the EDS 2.4.0 license key.
- Verify information about product requirements and supported platforms.
- Verify minimum system requirements and port availability for EDS components.

EDS requires Apache ZooKeeper to store configuration. If you already have ZooKeeper installed, you can use it for your configuration. If you have an earlier version, install ZooKeeper for EDS.

# Guidelines for a High Availability Installation

To achieve high availability for EDS, you must have a highly available Informatica domain.

You can configure high availability for the Administrator Daemon and ZooKeeper when you install EDS. You can configure high availability for the EDS Node after you install EDS.

To achieve high-availability, perform the following steps:

1. Ensure that the Informatica domain is configured for high availability. Get information about the gateway nodes of the Informatica domain.
2. For Administrator Daemon high availability, install the Administrator Daemon on the gateway nodes of the Informatica domain.
3. To configure high availability for the ZooKeeper, specify multiple comma-separated IP address and port combinations for the **Apache ZooKeeper URL** property.
4. After you install EDS, log in to the Administrator tool on the master gateway node of the Informatica domain and create the Edge Data Streaming Service.

For more information about configuring high availability for the EDS components, see the High Availability chapter in the *Informatica Edge Data Streaming User Guide*.

For more information about the Informatica domain high availability, see the *Informatica Administrator Guide*.

## Prepare for a Secure Installation

To configure secure communication among the EDS components and secure network authentication, you should install EDS on a secure Informatica domain.

You can set up secure communication between the EDS components and secure user authentication only if the Informatica domain is secure and uses secure network authentication to authenticate users.

When you install EDS, the installer checks the type of network authentication that is enabled for the Informatica domain. Depending on the type of network authentication that is enabled, the installer displays additional screens where you can specify the security configuration.

EDS can have one of the following security options configured:

- SSL certificates. EDS uses the SSL certificates that Informatica provides to secure the domain.
- Kerberos network authentication. Configure EDS to use Kerberos network authentication if the Informatica domain uses Kerberos network authentication. You can also configure Kerberos authentication between the Administrator Daemon and the Administrator tool when the Informatica domain uses SSL certificates to secure the domain. In this scenario, the Informatica domain need not use Kerberos network authentication.

**Note:** You can configure security in EDS only if you have configured security for the Informatica domain and the Administrator tool.

For more information about Informatica domain security, see the *Informatica Security Guide*.

## Prepare for Kerberos Authentication Setup

You can configure EDS to use Kerberos network authentication if the Informatica domain uses Kerberos network authentication to authenticate users and services on a network.

Kerberos is a network authentication protocol which uses tickets to authenticate access to services and nodes in a network. Kerberos uses a Key Distribution Center (KDC) to validate the identities of users and services and to grant tickets to authenticated user and service accounts. In the Kerberos protocol, users and services are known as principals. The KDC has a database of principals and their associated secret keys that are used as proof of identity. Kerberos can use an LDAP directory service as a principal database.

To use Kerberos authentication, you must install and run the Informatica domain on a network that uses Kerberos network authentication. Informatica can run on a network that uses Kerberos authentication with Microsoft Active Directory service as the principal database.

The Informatica domain requires keytab files to authenticate nodes and services in the domain without transmitting passwords over the network. The keytab files contain the service principal names (SPN) and associated encrypted keys. Create the keytab files before you create nodes and services in the Informatica domain.

You can also configure Kerberos authentication between the Administrator Daemon and the Administrator tool when the Informatica domain uses SSL certificates to secure the domain. You require the keytab files for the Administrator Daemon, Administrator tool, and the EDS Node.

Before you configure Kerberos authentication between the Administrator Daemon and the Administrator tool, perform the following tasks:

- Set up the Kerberos configuration file.
- Use the service principal and keytab file name format to generate the keytab files.

### Set Up the Kerberos Configuration File

Kerberos stores configuration information in a file named *krb5.conf*. Informatica requires specific properties set in the Kerberos configuration file so that the Informatica domain can use Kerberos authentication correctly. You must set the properties in the *krb5.conf* configuration file.

The configuration file contains the information about the Kerberos server, including the Kerberos realm and the address of the KDC. You can request the Kerberos administrator to set the properties in the configuration file and send you a copy of the file.

1. Back up the *krb5.conf* file before you make any changes.
2. Edit the *krb5.conf* file.
3. In the *libdefaults* section, set or add the properties required by Informatica.

The following table lists the values to which you must set properties in the *libdefaults* section:

Parameter	Value
default_realm	Name of the service realm for the Informatica domain.
forwardable	Allows a service to delegate client user credentials to another service. Set this parameter to True. The Informatica domain requires application services to authenticate the client user credentials with other services.

Parameter	Value
default_tkt_etypes	Encryption types for the session key in ticket-granting tickets (TGT). Set this parameter only if session keys must use specific encryption types.
udp_preference_limit	Determines the protocol that Kerberos uses when it sends a message to the KDC. Set <code>udp_preference_limit = 1</code> to always use TCP. The Informatica domain supports only the TCP protocol. If the <code>udp_preference_limit</code> is set to any other value, the Informatica domain can shut down unexpectedly.

- In the *realms* section, include the port number in the address of the KDC separated by a colon.  
For example, if the KDC address is `kerberos.example.com` and the port number is 88, set the *kdc* parameter to the following:  

```
kdc = kerberos.example.com:88
```
- Save the `krb5.conf` file.
- Store the `krb5.conf` file in a directory that is accessible to the machine where you plan to install the Administrator Daemon and Administrator tool.

The following example shows the content of a `krb5.conf` with the required properties:

```
[libdefaults]
default_realm = AFNIKRB.AFNIDEV.COM
forwardable = true
udp_preference_limit = 1

[realms]
AFNIKRB.AFNIDEV.COM = {
  admin_server = SMPLKERDC01.AFNIKRB.AFNIDEV.COM
  kdc = SMPLKERDC01.AFNIKRB.AFNIDEV.COM:88
}

[domain_realm]
afnikrb.afnidev.com = AFNIKRB.AFNIDEV.COM
.afnikrb.afnidev.com = AFNIKRB.AFNIDEV.COM
```

For more information about the Kerberos configuration file, see the Kerberos network authentication documentation.

## Generate Keytab Files

If you run the Informatica domain with Kerberos authentication, you must associate Kerberos service principal names (SPN) and keytab files with the nodes and Administrator Daemon. EDS requires keytab files so that services can be authenticated without being prompted for passwords. To generate keytab files, use the SPN and keytab file formats.

The following table describes the SPN format and the keytab file names for the EDS components:

EDS Component	SPN Format	Keytab File Name
Administrator Daemon	<code>admin/&lt;isp domain&gt;@&lt;realm name&gt;</code>	<code>eds_admin.keytab</code>
EDS Node	<code>node/&lt;isp domain&gt;@&lt;realm name&gt;</code>	<code>eds_node.keytab</code>
Administrator Tool	<code>_AdminConsole/&lt;isp domain&gt;@&lt;realm name&gt;</code>	<code>_AdminConsole.keytab</code>

To configure Kerberos authentication for EDS, generate keytab files for the Administrator Daemon and the EDS Node. To configure Kerberos authentication between the Administrator Daemon and the Administrator tool, generate keytab files for the Administrator Daemon, the EDS Node, and the Administrator tool.

The keytab files for EDS components must be available on the machines that host the component. During installation, you can specify a directory on the machine to store the keytab files. The installer picks up the keytab files from the keytabs directory you provide during installation.

After installation the Administrator Daemon keytab file is stored in the following directory:

```
<INFA_HOME>/isp/config/keys
```

The EDS Node keytab file is stored in the following directory:

```
<INFA_HOME>/node/config/keys
```

The Administrator tool keytab file is stored in the following directory:

```
<INFA_HOME>/isp/config/keys
```

## Get the Edge Data Streaming License Key

Contact Informatica Global Customer Support for the EDS license key. After you get the license key, add it to the Informatica domain after installing EDS.

## Pre-Installation Requirements for the Administration Components

Perform the pre-installation tasks on the machine hosting the administration components.

### Verify Minimum System Requirements for the Administration Components

Verify that the machine where you install the administration components meets the system requirements. The installer writes temporary files to the hard disk. Verify that you have enough available disk space on the machine to support the installation. When the installation completes, the installer deletes the temporary files and releases the disk space.

The following table describes the minimum system requirements for the administration components:

Processor	RAM	Disk Space	Operating System
4 CPU Cores	2.5 GB	2.5 GB to run the components 2 GB to run the installer	Red Hat Linux, Windows

For more information about product requirements and supported platforms, see the Product Availability Matrix on Informatica Network:

<https://network.informatica.com/community/informatica-network/product-availability-matrices>

## Verify Port Availability for the Administration Components

The installer sets up the ports for the administration components, and it designates the ports to use on the host where you install the them.

You can specify the port numbers to use for the administration components or you can use the default port numbers provided by the installer. Verify that the port numbers are available on the machines where you install the administration components.

The following table describes the ports used by the administration components:

Port Type	Description
Administrator Daemon HTTP port	Port on which the Administrator Daemon runs an HTTP server from which the EDS Node fetch the configurations. Default is 15381.
Administrator Daemon and Administrator tool communication port	Port for communication between the Administrator Daemon and Administrator tool. Default is 15386.
Topic Resolution Daemon (LBMRD) port	Port for the Topic Resolution Daemon (LBMRD). Default is 15380.
Administrator tool port	Port number used by the Administrator tool. Default is 6008.
Administrator tool shutdown port	Port number that controls server shutdown for the Administrator tool. The Administrator tool listens for shutdown commands on this port.
Monitoring Traffic Port	Port that the Administrator Daemon uses to receive statistics from the EDS Node. Default is 15385.

## Pre-Installation Requirements for the Edge Data Streaming Node

Perform the pre-installation tasks on each machine hosting the EDS Node since you have to install EDS Nodes on multiple machines.

### Verify Minimum System Requirements for the Edge Data Streaming Node

Verify that the machines where you install the EDS Node meet the system requirements. The installer writes temporary files to the hard disk. Verify that you have enough available disk space on the machine to support

the installation. When the installation completes, the installer deletes the temporary files and releases the disk space.

The following table describes the minimum system requirements for the EDS Node:

Processor	RAM	Disk Space	Operating System
2 CPU Cores	128 MB	600 MB to run the EDS Node 300 MB to run the installer	Red Hat Linux, Windows

For more information about product requirements and supported platforms, see the Product Availability Matrix on Informatica Network:

<https://network.informatica.com/community/informatica-network/product-availability-matrices>

## Set the File Descriptor Limit

Verify that the operating system meets the file descriptor requirement.

The Informatica service processes can use a large number of files. Set the file descriptor limit per process to 8192 or higher. The recommended limit is 16,000 file descriptors per process.

## Extract the Installer Files

Before you perform the installation, extract the installer files. EDS includes a combined installer for the Administrator Daemon, the EDS Node, and the Administrator tool, and a standalone installer for the EDS Node.

### Extract the Installer Files on Linux

The installer files are compressed and distributed as .zip files.

EDS includes the following installer files:

- eds-installer-linux-x86\_64.zip. The combined installer for all the components.
- eds-node-installer-linux-x86\_64.zip. The standalone EDS Node installer.

Use a zip utility to extract the installer file that you require to a directory on your machine.

You can extract the installer files in the following ways:

- Installation DVD. Download the Informatica tar file from the installation DVD to a directory on your machine and then extract the installer files, or extract the installer files directly from the DVD to a directory on your machine.
- FTP download. Download the Informatica installation tar file from the Informatica Electronic Software Download (ESD) site to a directory on your machine and then extract the installer files.



## Extract the Installer Files on Windows

The installer files are compressed and distributed as a .zip file.

EDS includes the following installer files:

- eds-installer-win-x86\_64.zip. The combined installer for all the components.
- eds-node-installer-win-x86\_64.zip. The standalone EDS Node installer.

Use a zip utility to extract the installer file that you require to a directory on your machine. Verify that the zip utility version is compatible with the Windows operating system version. When you unzip the file, verify that the zip utility also extracts empty folders.

You can extract the installer files in the following ways:

- Installation DVD. Download the Informatica .zip file from the installation DVD to a directory on your machine and then extract the installer files, or extract the installer files directly from the DVD to a directory on your machine. If you download the .zip file to a directory on your machine, verify that the length of the entire installation directory path, including the .zip file name, is 60 characters or less.
- FTP download. Download the Informatica installation .zip file from the Informatica Electronic Software Download (ESD) site to a directory on your machine and then extract the installer files.

# CHAPTER 3

## Installation

This chapter includes the following topics:

- [Installation Overview, 18](#)
- [Installing Edge Data Streaming in Graphical Mode, 18](#)
- [Installing Edge Data Streaming in Console Mode, 20](#)
- [Installing Edge Data Streaming in Silent Mode, 22](#)
- [Edge Data Streaming Node Installation, 25](#)
- [Installing Edge Data Streaming Nodes on Remote Linux Systems, 29](#)

### Installation Overview

Install the Edge Data Streaming components on the same machine that hosts the Informatica service. The installation loads the EDS component libraries in the installation directory.

You can enable security for EDS if security is configured for the Informatica domain and if the domain uses secure network authentication to authenticate users. You can also configure high availability for the EDS components.

If you choose to enable security for EDS during installation, you cannot revert to a non-secure mode. You must uninstall and perform a fresh installation of EDS.

You can install EDS in graphical mode on Windows and in console mode on Linux.

### Installing Edge Data Streaming in Graphical Mode

You can install EDS in graphical mode on Windows.

1. Log in to the machine with a system user account.
2. Run `install.bat` from the directory where you extracted the installation files.  
The **Welcome** page appears.
3. Click **Next**.
4. Accept the terms of the license agreement.
5. Click **Next**.

The **EDS Installation** page appears.

6. Select the EDS components that you want to install.

The **Component Selection** page displays the following components:

#### **Apache ZooKeeper**

Select this option to install Apache ZooKeeper that is as part of the EDS installation. If you already have ZooKeeper installed, provide existing the configuration information in the **Components Configuration** page.

#### **Administration Components**

Select this option to install the following administration components:

- EDS Components on an existing Informatica Platform. Select this option if you have installed Informatica.
- Administrator Daemon. This option is selected by default.

**Note:** You must configure the administration components with HTTPS if you installed Informatica with HTTPS.

#### **Edge Data Streaming Node**

Select this option to install the EDS Node.

7. To set up secure communication, storage, configuration, and authentication between the EDS components, select **Enable Security**.

If you select **Enable Security**, the installer sets up HTTPS connection between the EDS components.

8. Click **Next**.

The **Informatica Platform Installation Directory** page appears.

9. Enter the path to the Informatica server installation.

10. Click **Next**.

The **Pre-Installation Summary** page appears.

11. Click **Install**.

The **Components Configuration** page appears when the installation completes. The configuration details that you specify depends on the components you selected in the **Component Selection** page.

If you selected the Administrator Daemon, enter the following configuration details:

#### **Unicast Topic Resolution Daemon Port (LBMRD)**

Port for the Topic Resolution Daemon (LBMRD).  
Default is 15380.

#### **Monitoring Traffic Port**

Port that the Administrator Daemon uses to receive statistics from the EDS Node. Default is 15385.

#### **Administrator Tool Monitoring Port**

Port that Informatica Administrator uses to communicate with the Administrator Daemon. Default is 15386.

#### **Daemon HTTP or HTTPS Server Port**

Port on which the Administrator Daemon runs an HTTP or HTTPS server from which the EDS Node fetches configuration. If you selected secure communication for the components, the Administrator Daemon runs an HTTPS server.  
Default is 15381.

If you selected the EDS Node and Apache ZooKeeper components, enter the following configuration details:

#### Apache ZooKeeper IP Address and Ports

The IP address and port that the Administrator Daemon uses to communicate with Apache ZooKeeper.

The IP address and port combination has the following format:

`<IP Address or host name>:<port>`

You can enter multiple comma-separated IP address and port combinations. If you have configured high availability on ZooKeeper and one instance of ZooKeeper is down, the Administrator Daemon connects to the next available ZooKeeper server.

#### Network Interface Address

Select the network interface if you are installing the components on a multi-homed host.

The interface has the following format:

`<IP Address>`. For example, 10.65.43.75

If you have enabled security for the Informatica domain, the installer enables the **SSL Network Authentication** option. EDS uses the same SSL certificates used by the Informatica domain.

If the Informatica domain uses Kerberos authentication, the installer enables the **Kerberos Network Authentication** option.

Optionally, you can configure Kerberos authentication between the Administrator Daemon and the Administrator tool.

Specify the location of the following keytab files:

- Administrator Daemon and EDS Node keytab files. To configure Kerberos authentication for EDS, specify these keytab files.
- Administrator Daemon, EDS Node, and Administrator tool keytab files. To configure Kerberos authentication between the Administrator Daemon and the Administrator tool, specify these keytab files.

12. Click **Next**.

The **Post-Installation Summary** page appears.

13. Click **Done** to close the installer.

## Installing Edge Data Streaming in Console Mode

You can install EDS in console mode on Linux.

1. Log in to the machine with a system user account.
2. On a command line, run `install.sh` from the directory where you extracted the installation files. Assign execute permissions before running the `install.sh` script or run the `sh ./install.sh` command.
3. Press **Enter** to continue.
4. Press 1 to accept the terms of the license agreement.  
The **EDS Installation** page appears.
5. Select the EDS components you want to install.

You can install the following components from the **EDS Installation** page:

### **Apache ZooKeeper**

Enter 1 and Press **Enter** to install Apache ZooKeeper that is part of the EDS installer. If you already have ZooKeeper installed, provide configuration information in the **Components Configuration** page.

### **Administration Components**

Enter 1 and press **Enter** to install the following components:

- EDS Components on an existing Informatica Platform. Select this option if you have installed Informatica.

The Administrator Daemon is installed if you select Administration components.

### **Edge Data Streaming Node**

Enter 1 and press **Enter** to install the EDS Node.

6. Optionally, to enable security, enter 1 and press **Enter**.

If you enable security, the installer sets up HTTPS connection between the EDS components.

The **Informatica Platform Installation Directory** page appears.

7. Enter the path to the Informatica server installation.

8. Press **Enter**.

The **Pre-Installation Summary** details appear.

9. Press **Enter** to continue with the installation.

The **Components Configuration** page appears when the installation completes. The configuration details that you should specify depends on the components you selected in the **EDS Installation** page.

If you selected Administration components, enter the following configuration details:

#### **Unicast Topic Resolution Daemon Port (LBMRD)**

Port for the Topic Resolution Daemon (LBMRD).

Default is 15380.

#### **Administrator Tool Monitoring Port**

Port that Informatica Administrator uses to send statistics to the Administrator Daemon. Default is 15386.

#### **Daemon HTTP(S) Server Port**

Port on which the Administrator Daemon runs an HTTP or HTTPS server from which the EDS Node fetches configuration. If you selected secure communication for the components, the Administrator Daemon runs an HTTPS server.

Default is 15381.

#### **Monitoring Traffic Port**

Port that the Administrator Daemon uses to receive statistics from the EDS Node.

#### **Administrator Tool Monitoring Port**

Port that Informatica Administrator uses to communicate with the Administrator Daemon. Default is 15386.

If you selected the EDS Node and Apache ZooKeeper components, enter the following configuration details:

#### **Network Interface Address**

Select the network interface if you are installing the components on a multi-homed host.

The interface has the following format:

<IP Address>. For example, 10.65.43.75

#### Apache ZooKeeper IP Address and Ports

The IP address and port that the Administrator Daemon uses to communicate with Apache ZooKeeper.

The IP address and port combination has the following format:

<IP Address or host name>:<port>

You can enter multiple comma-separated IP address and port combinations. If you have configured high availability on ZooKeeper and one instance of ZooKeeper is down, the Administrator Daemon connects to the next available ZooKeeper server.

If you have enabled security for the Informatica domain, the installer enables the **SSL Network Authentication** option. EDS uses the same SSL certificates used by the Informatica domain.

If you have enabled Kerberos authentication for the Informatica domain, the installer enables the **Kerberos Network Authentication** option.

Optionally, you can configure Kerberos authentication between the Administrator Daemon and the Administrator tool. Press 1 to enable Kerberos authentication.

Specify the location of the following keytab files:

- Administrator Daemon and EDS Node keytab files. To configure Kerberos authentication for EDS, specify these keytab files.
- Administrator Daemon, EDS Node, and Administrator tool keytab files. To configure Kerberos authentication between the Administrator Daemon and the Administrator tool, specify these keytab files.

10. Press **Enter**.

The **Post-Installation Summary** page appears when the installation is complete.

11. Press **Enter** to exit the installation process.

## Installing Edge Data Streaming in Silent Mode

To install EDS without user interaction, use the `SilentInput.properties` properties file to install in silent mode. The EDS installer reads the file to determine the installation options. The `SilentInput.properties` file is stored in the root directory of the EDS installer files.

1. Use a text editor to open and change the values of the properties in the `SilentInput.properties` file.

Configure the following properties:

`INSTALLATION_MODE`

Set the value as 1 to perform a fresh installation of EDS.

`INSTALL_MODE`

Indicates the installation mode.

Set the value as 1 to install components in custom mode.

`SECURE_MODE`

Indicates if the secure communication, storage and configuration must be enabled for the EDS components.

If the value is 0, secure mode is not enabled. If the value is 1, secure mode is enabled.

INSTALLATION\_TYPE

Indicates whether to install EDS in express mode or custom mode.  
Set the value as 2 to perform a custom installation.

INSTALL\_AGENTNODE

Indicates whether to install the EDS Node.  
If the value is 0, the EDS Node is not installed. If the value is 1, the EDS Node is installed.

INSTALL\_ADMINCOMPS

Indicates whether to install the administration components when the `INSTALLATION_TYPE` is 1.  
If the value is 0, the components are not installed. If the value is 1, the components are installed.

INSTALL\_ADMIND

Indicates whether to install the Administrator Daemon when the `INSTALLATION_TYPE` is 2.  
If the value is 0, the Administrator Daemon is not installed. If the value is 1, the Administrator Daemon is installed.

INSTALL\_ZOOKEEPER

Indicates whether to install ZooKeeper.  
If the value is 0, the Administrator Daemon is not installed. If the value is 1, the Administrator Daemon is installed.

USER\_INSTALL\_DIR

The EDS installation directory. The location must have write permissions enabled. For example, `C:\Informatica\EDS\2.4.0`

LICENSE\_KEY\_LOC

The path and name of the EDS license key file.

IS\_AGREED

Set this to `true` to accept the license agreement.

DOMAIN\_PSSWD **and** DOMAIN\_CNFRM\_PSSWD

The password to the Informatica domain.

If you choose to install the Administrator Daemon, enter the following properties:

ADMIND\_LBMRD\_PORT

Port for the Topic Resolution Daemon (LBMRD).  
Default is 15380.

ADMIND\_HTTP\_PORT

Port on which the Administrator Daemon runs an HTTP or HTTPS server from which the EDS Node fetches configuration.

ADMIND\_MONITOR\_PORT

Port that the Administrator Daemon uses to receive statistics from the EDS Node.

H2\_PORT

Port of the H2 database.

DOMAIN\_PORT

Port on which the domain is started.

If you choose to install the EDS Node, enter the following properties:

#### NETWORK\_INTERFACE

This is an optional property.

If you are installing the components on a multi-homed host, specify the network interface

The interface can have one of the following formats:

- IP Address - <IP Address>. For example, 10.65.43.75
- Interface name. For example, Eth0

#### ZOOKEEPER\_URL

The IP address and port that the Administrator Daemon uses to communicate with Apache ZooKeeper.

The IP address and port combination has the following format:

<IP Address>:<port>

You can enter multiple comma-separated IP address and port combinations. If you have configured high availability on ZooKeeper and one instance of ZooKeeper is down, the Administrator Daemon connects to the next available ZooKeeper server.

#### NODE\_PORTNUMBER

The EDS Node uses this port to send monitoring statistics.

The default port is 15384.

If you are installing all EDS components or only the Administration components when the `INSTALLATION_TYPE` is 2, enter the following properties to enable security:

#### KERBEROS\_CHECKBOX

Indicate if Kerberos authentication is enabled for the Informatica domain.

Specify `set` to enable Kerberos authentication. Specify `unset` to disable Kerberos authentication.

#### KERBEROS\_KEYTAB\_FIELD

Indicate whether you want to provide the location of the keytab files.

Specify `set` to provide the location of the keytab files. Specify `unset` if you do not want to provide the location of the keytab files.

#### KERBEROS\_KEYTAB\_LOCATION

Specify the location of the keytab files.

#### SSL\_CHECKBOX

Indicate whether SSL authentication is enabled for the Informatica domain.

Specify `set` to enable SSL authentication. Specify `unset` if you do not want to enable SSL authentication.

If you are installing the EDS Node when the `INSTALLATION_TYPE` is 1, enter the following properties to enable security:

#### KERBEROS\_CHECKBOX

Indicate if Kerberos authentication is enabled for the Informatica domain.

Specify `set` to enable Kerberos authentication. Specify `unset` to disable Kerberos authentication.

#### KERBEROS\_KEYTAB\_FIELD

Indicate whether you want to provide the location of the keytab files.

Specify `set` to provide the location of the keytab files. Specify `unset` if you do not want to provide the location of the keytab files.



KERBEROS\_KEYTAB\_LOCATION

Specify the location of the keytab files.

SSL\_CHECKBOX

Indicate whether SSL authentication is enabled for the Informatica domain.

Specify `set` to enable SSL authentication. Specify `unset` if you do not want to enable SSL authentication.

If you are installing the EDS Node when the `INSTALLATION_TYPE` is 2, enter the following properties to enable security:

KERBEROS\_CHECKBOX

Indicate if Kerberos authentication is enabled for the Informatica domain.

Specify `set` to enable Kerberos authentication. Specify `unset` to disable Kerberos authentication.

KERBEROS\_KEYTAB\_FIELD

Indicate whether you want to provide the location of the keytab files.

Specify `set` to provide the location of the keytab files. Specify `unset` if you do not want to provide the location of the keytab files.

KERBEROS\_KEYTAB\_LOCATION

Specify the location of the keytab files.

SSL\_CHECKBOX

Indicate whether SSL authentication is enabled for the Informatica domain.

Specify `set` to enable SSL authentication. Specify `unset` if you do not want to enable SSL authentication.

2. Save the properties file.
3. Run the silent installation.
  - In Windows: run `silentInstall.bat`
  - In Linux: run `silentInstall.sh`

**Note:** Assign execute permissions before running the `install.sh` script or run the `sh ./install.sh` command.

The silent installer runs in the background.

If you incorrectly configure the properties file or if the installation directory is not accessible, the silent installation will fail. View the installation log file in the user home directory. For example, `C:\silentErrorLog.log`. Correct the errors, and run the silent installation again.

## Edge Data Streaming Node Installation

Install the EDS Node on all Linux and Windows hosts that run sources and targets.

You can install the EDS Node as part of the complete EDS installation or you can use the standalone EDS Node installer. If you want to install EDS Nodes on multiple machine, you can use the standalone EDS Node.

You must enable security for the EDS Node if you have configured security for the Administrator Daemon.

For more information about EDS entities and monitoring them, see the *Edge Data Streaming User Guide*

## Installing the Edge Data Streaming Node in Graphical Mode

You can install the EDS Node in graphical mode on Windows.

1. Log in to the machine with a system user account.
2. Begin installation. Run `install.bat` from the directory where you extracted the installation files.  
The installer page appears.
3. Click **Next**.  
The **Installation Directory** page appears.
4. Enter the absolute path for the installation directory.  
By default, the installer places EDS in the following location: `<User Home Directory>\Informatica\eds\<version folder>`  
Optionally, enable security.
5. Click **Next**.  
The **Pre-Installation Summary** page appears.
6. Click **Install**.  
The **Configuration** page appears after the installation is complete.  
Enter the following configuration details:  
**ZooKeeper IP Address(es) and Port(s)**  
The IP address and port that the Administrator Daemon uses to communicate with Apache ZooKeeper.  
The IP address and port combination has the following format:  
`<IP Address>:<port>`  
You can enter multiple comma-separated IP address and port combinations. If you have configured high availability on ZooKeeper and one instance of ZooKeeper is down, the Administrator Daemon connects to the next available ZooKeeper server.  
**Network Interface Address**  
Select the network interface if you are installing the components on a multi-homed host.  
The interface can have one of the following formats:
  - IP Address - `<IP Address>`. For example, 10.65.43.75.
  - Interface name. For example, Eth0.If you have enabled security for the Informatica domain, the installer enables the **SSL Network Authentication** option. EDS uses the same SSL certificates used by the Informatica domain.  
If you have enabled Kerberos authentication for the Informatica domain, the installer enables the **Kerberos Network Authentication** option. Specify the location of the keytab files.
7. Click **Next**.  
The **Post-Installation Summary** page appears.
8. Click **Done** to close the installer.

## Installing the Edge Data Streaming Node in Console Mode

You can install the EDS Node in console mode on Linux.

1. Log in to the machine with a system user account.

2. Run `install.sh` from the directory where you extracted the installation files. Assign execute permissions before running the `install.sh` script or run the `sh ./install.sh` command.

The **Welcome** page appears.

3. Press **Enter** to continue.
4. Enter the path to the installation directory.

By default, the installer places the EDS Node in the following location:

```
<User Home Directory>\Informatica\eds\<version folder>
```

5. Press **Enter**.
6. Press **Enter**.
7. Enter the following EDS Node configuration details:

Optionally, to enable secure communication, storage, and configuration, press **1**.

The **Configuration** page appears after the installation is complete.

Enter the following configuration details:

#### **ZooKeeper IP Address(es) and Port(s)**

The IP address and port that the Administrator Daemon uses to communicate with Apache ZooKeeper.

The IP address and port combination has the following format:

```
<IP Address>:<port>
```

You can enter multiple comma-separated IP address and port combinations. If you have configured high availability on ZooKeeper and one instance of ZooKeeper is down, the Administrator Daemon connects to the next available ZooKeeper server.

#### **Network Interface Address**

Optionally, specify the network interface if you are installing the components on a multi-homed host.

Press **1** and press **Enter** and then type the network interface address.

The interface can have one of the following formats:

- IP Address - `<IP Address>`. For example, 10.65.43.75.
- Interface name. For example, Eth0.

If you have enabled security for the Informatica domain, the installer enables the **SSL Network Authentication** option. EDS uses the same SSL certificates used by the Informatica domain.

If you have enabled Kerberos authentication for the Informatica domain, the installer enables the **Kerberos Network Authentication** option. Specify whether to enable Kerberos by pressing **1** or **2**. Specify the location of the keytab files.

8. Press **Enter**.
  9. Press **Enter** to exit the installation process.
- The **Post-Installation Summary** page appears when the installation is complete.

## Installing the Edge Data Streaming Node in Silent Mode

To install the EDS Node without user interaction, install in silent mode by using a properties file that contains the installation options. The EDS Node installer reads the file to determine the installation options.

1. Use a text editor to open and change the values of the properties in the `SilentInput.properties` file.

The following table describes the installation properties that you can change:

`INSTALL_TYPE`

Set the value to 0 to perform a fresh installation of the EDS Node.

`USER_INSTALL_DIR`

The EDS Node installation directory. The location must have write permissions enabled. For example, `C:\\Informatica\\2.4.0\\EDS`.

`ZOOKEEPER_URL`

The IP address and port that the EDS Node uses to communicate with Apache ZooKeeper. The IP address and port combination has the following format:

`<IP Address>:<port>`

You can enter multiple comma-separated IP address and port combinations. If you have configured high availability on ZooKeeper and one instance of ZooKeeper is down, the EDS Node connects to the next available ZooKeeper server.

**Note:** Do not use the `http` prefix with the IP address and port combination.

`SECURE_MODE`

Indicates if the secure communication, storage and configuration must be enabled for the EDS Node.

If the value is 0, secure mode is not enabled. If the value is 1, secure mode is enabled.

`NETWORK_INTERFACE`

Optional. The network interface if you are installing the components on a multi-homed host. The interface has the following format:

`<IP Address>`. For example, `10.65.43.75`

2. Specify the following properties if you install the EDS Node on a machine where the Informatica service is not running and you want to enable security:

`PC_KERBEROS_ENABLED`

Indicate if you want to enable Kerberos authentication. Specify `true` to enable Kerberos authentication.

`KERBEROS_KEYTAB_LOCATION`

The location to the `eds_node.keytab` file.

`PC_TLS_ENABLED`

Indicate if you want to enable SSL. Specify `true` to enable SSL authentication.

3. Specify the following properties if you install the EDS Node on a machine where the Informatica service is running and you want to enable security:

`KERBEROS_KEYTAB_LOCATION`

The location to the keytab files.

4. Save the properties file.

5. Run the silent installation.

- In Windows: run `silentInstall.bat`
- In Linux: run `silentInstall.sh`

**Note:** Assign execute permissions before running the `install.sh` script or run the `sh ./install.sh` command.

The silent installer runs in the background. The silent installation is complete when the `node-install.out` is created.

The silent installation fails if you incorrectly configure the properties file or if the installation directory is not accessible. View the installation log file in the user home directory. For example, C:\silentErrorLog.log. Correct the errors, and run the silent installation again.

## Installing Edge Data Streaming Nodes on Remote Linux Systems

You can install EDS Nodes on remote Linux systems in silent mode.

After you install Edge Data Streaming, the installation process creates the remote EDS Node installation directory `remote_node_utils`, in the EDS installation directory. Place the `eds-node-installer-linux-x86_64.zip` file in this directory before you perform remote installation.

Before you run the remote installation, enable passwordless connection between the machines where you install the administration components and the machines where you install the EDS Nodes.

### Configure Passwordless SSH Connections

Configure passwordless connections between the machines where you install the administration components and the machines where you install the EDS Node. Because the remote installation process runs in silent mode, you might want to configure passwordless SSH connections to avoid asking for input from users.

To configure passwordless connections, you can create an SSH key pair on the machine where you install the administration components. The key pair consists of a public key and a private key. Copy the public key to all the remote hosts.

### Configuring Passwordless SSH Connections

Generate a pair of authentication keys on the host where you install the Administrator Daemon and Administrator tool.

1. To generate a pair of authentication keys, enter the following command:

```
ssh-keygen -t rsa
```

This command creates a public key and private key.

2. To create an SSH directory on the remote system if it does not exist, enter the following command

```
ssh $USER@<Remote machine> mkdir -p ~/.ssh
```

3. To copy the public key to the remote machines, enter the following command:

```
cat ~/.ssh/id_rsa.pub | ssh $USER@<Remote machine> 'cat >> .ssh/authorized_keys'
```

After you configure the passwordless connection, you can run the remote node installation on remote systems.

# Installing Edge Data Streaming Nodes on Remote Systems

To install EDS Nodes on remote systems in silent mode, use a properties file that contains the installation options. The EDS Node remote installer reads the file to determine the installation options.

1. Navigate to the `remote_node_utils` directory.
2. Use a text editor to open and change the values of the properties in the `SilentInput.properties` file.

The following table describes the installation properties that you can change:

`USER_INSTALL_DIR`

EDS Node installation directory. For example, `/home/$USER/Informatica/eds/24`

`ZOOKEEPER_URL`

The IP address and port that the EDS Node uses to communicate with Apache ZooKeeper.

The IP address and port combination has the following format:

`<IP Address>:<port>`

You can enter multiple comma-separated IP address and port combinations. If you have configured high availability on ZooKeeper and one instance of ZooKeeper is down, the EDS Node connects to the next available ZooKeeper server.

**Note:** Do not use the `http` prefix with the IP address and port combination.

`SECURE_MODE`

Indicates if the secure communication, storage and configuration must be enabled for the EDS Node.

If the value is 0, secure mode is not enabled. If the value is 1, secure mode is enabled.

`NETWORK_INTERFACE`

Optional. The network interface if you are installing the components on a multi-homed host.

The interface is of the following format:

`<IP Address>`. For example, `10.65.43.75`

3. Specify the following properties if you want to enable security:

`PC_KERBEROS_ENABLED`

Indicate if you want to enable Kerberos authentication. Specify `true` to enable Kerberos authentication.

`KERBEROS_KEYTAB_LOCATION`

The location to the `eds_node.keytab` file.

`PC_TLS_ENABLED`

Indicate if you want to enable SSL. Specify `true` to enable SSL authentication.

4. Save the properties file.
5. Use a text editor to open the `hostsList` and add the host names or IP addresses of the remote machines, separated by newline characters.

6. To run the remote installation, use the following command:

```
./remote-node.sh install
```

The silent installer runs in the background. The silent installation is complete when the `node-install.out` and `eds-install.out` are created in the `<EDS Node Installation Directory>\node\logs` directory of the remote machine.

The silent installation fails if you incorrectly configure the properties file or if the installation directory is not accessible. View the installation log file in the user home directory of the remote machine. For example, `/home/<username>/silentErrorLog.log`. Correct the errors, delete the files from the directory where the installation failed, and run the silent installation again.

# CHAPTER 4

## Post-Installation Tasks

This chapter includes the following topics:

- [Post-Installation Tasks Overview, 32](#)
- [Start the Administrator Daemon, 32](#)
- [Create Multiple Edge Data Streaming Node Services on Windows, 33](#)
- [Start the Edge Data Streaming Node, 33](#)
- [Start the Informatica Domain, 34](#)
- [Create a Edge Data Streaming Service, 35](#)

### Post-Installation Tasks Overview

After you install the EDS components and Apache ZooKeeper, start the EDS components, optionally add a license, and then create the EDS service.

### Start the Administrator Daemon

After you complete the installations, start the Administrator Daemon on Linux and Windows.

#### Starting or Stopping the Administrator Daemon on Linux

To start the Administrator Daemon, run the `admin.sh` command. The `admin.sh` command also starts or stops the topic resolution daemon (LBMRD), the persistence store (UM Store), and Apache ZooKeeper along with the Administrator Daemon.

To start the Administrator Daemon, LBMRD, the persistence store (UM Store), and ZooKeeper, run the following command from the `<EDS installation directory>/admin/bin` folder:

```
./admin.sh start
```

To start one of the components, run the following command:

```
./admin.sh start <component>
```

Where, `<component>` is `admin`, `lbmrd`, `umestored`, or `zookeeper`.



To stop the Administrator Daemon, run the following command:

```
./admin.sh stop
```

To stop one of the components, run the following command:

```
./admin.sh stop <component>
```

Where, <component> is admind, lbmrd, umestored, or zookeeper.

## Starting or Stopping the Administrator Daemon on Windows

You can start or stop the Administrator Daemon from Windows Administrative Tools.

1. From Windows **Administrative Tools**, select **Services**.
2. Right-click the **Informatica ADMIND Service 240** service.
3. Choose to start or stop the service.

# Create Multiple Edge Data Streaming Node Services on Windows

By default, the EDS Node installation process creates one Windows service. You can create multiple EDS Node services.

To create a EDS Node service run the following command from the <EDS Node installation directory>\node\bin folder:

```
node.bat install <node name>
```

**Note:** Do not include spaces in the node name.

To create multiple services, run the command multiple times with different node names.

## Start the Edge Data Streaming Node

After you complete the installation, start the EDS Node on all hosts you installed them on. The installation process does not automatically start the EDS Node. When you start the EDS Node, it gets the configuration information from Apache ZooKeeper and the plug-ins from the Administrator Daemon.

**Note:** When you start the EDS Nodes, verify that you have a valid license. If you do not have the license, the EDS Nodes start, but do not send or receive information.

## Starting or Stopping the Edge Data Streaming Node on Linux

To start the EDS Node, run the following command from the <EDS Node installation directory>/node/bin folder:

```
./node.sh start <node name>
```

To stop the EDS Node, run the following command:

```
./node.sh stop <node name>
```

To start a EDS Node installed on a remote machine, run the following command:

```
./remote-node.sh start <node name>
```

To stop a EDS Node installed on a remote machine, run the following command:

```
./remote-node.sh stop <node name>
```

**Note:** The node name is optional. If you do not specify it, the command uses the host name.

## Starting or Stopping the Edge Data Streaming Node on Windows

You can start or stop the EDS Node service from Windows Administrative Tools.

1. From Windows **Administrative Tools**, select **Services**.
2. Right-click the **Informatica EDS Node 230 <node name>** service.
3. Choose to start or stop the service.

## Start the Informatica Domain

To start the Informatica domain, use a command line program.

## Starting or Stopping Informatica Domain on Linux

On Linux, run `infaservice.sh` to start or stop the Informatica domain. By default, `infaservice.sh` is located in the following directory:

```
<Informatica Administrator Tool installation directory>/tomcat/bin
```

1. Go to the directory where `infaservice.sh` is located.
2. At the command prompt, enter the following command to start the domain:

```
./infaservice.sh startup
```

To stop the domain, enter the following command:

```
./infaservice.sh shutdown
```

**Note:** If you use a soft link to specify the location of `infaservice.sh`, set the `INFA_HOME` environment variable to the location of the Informatica installation directory.

## Starting or Stopping Informatica Domain on Windows

You can start or stop the EDS Node service from Windows Administrative Tools.

1. From Windows **Administrative Tools**, select **Services**.
2. Right-click the **Informatica10.2.1** service.
3. Choose to start or stop the service.

# Create a Edge Data Streaming Service

Create the Edge Data Streaming service in the Administrator tool to create and monitor EDS data flows.

Optionally, add a EDS license before you create the service.

For more information about EDS data flows, see the *Edge Data Streaming User Guide*.

## Log In to the Administrator Tool

You must have administrator privileges to log in to Administrator tool.

1. Start a web browser.  
Informatica recommends that you use Google Chrome.
2. In the **Address** field, enter the URL for the Administrator tool:  
`http://<host>:<port>/administrator/`
3. On the login page, enter the user name and password.
4. Click **Log In**.

## Adding a License

Add a license key file in the Administrator tool before you create a Edge Data Streaming Service. Place the license key file in a location that is accessible by the machine on which the browser is running. When you update the license, you must specify the location of the license key file.

**Note:** You must remove an existing license before you update it.

1. In the Administrator tool, click the **Manage** tab > **Services and Nodes** view.
2. Right-click **Domain** > **New** > **License**.  
The **Create License** dialog box appears.
3. Enter the following properties:

### Name

Name of the license. The name is not case sensitive and must be unique within the domain. It cannot exceed 128 characters or begin with @. Also, it cannot contain spaces or any of the following special characters:

`` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) [ ]`

### Description

Description of the license. The description cannot exceed 765 characters.

### Path

Path of the domain in which you create the license. Read-only field. Optionally, click **Browse** and select a domain in the **Select Folder** dialog box.

Optionally, click **Create Folder** to create a folder for the domain.

### License file

File containing the original key. Click **Choose Files** to find the file.

4. Click **OK**.

# Creating the Edge Data Streaming Service

Create the EDS Service in the Administrator tool.

Start the Administrator Daemon and Apache ZooKeeper before you create the service.

1. In the Administrator tool, click the **Services and Nodes** tab.
2. Click **Actions > New > Edge Data Streaming Service**.

The **New Edge Data Streaming Service** window appears.

3. Enter the following general properties for the service:

## **Name**

Name of the Edge Data Streaming Service. The name is not case sensitive and must be unique within the Informatica domain. The characters must be compatible with the code page of the associated repository. The name cannot exceed 128 characters or begin with @. It also cannot contain spaces or the following special characters:

```
` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) [ ]
```

## **Description**

Description of the service. The description cannot exceed 765 characters.

## **Location**

Name of the Informatica domain and folder where you want to create the service. Optionally, click **Browse** to select another folder in the Informatica domain.

## **License**

License assigned to the service. Select from the list of EDS licenses available.

## **Assign**

Node on which the service runs. Select **Single Node** to assign the service to a node.

## **Node**

The host name or machine name where the service runs.

4. Click **Next**.
5. Enter the following database properties for the service:

## **Database Type**

The type of database that contains the EDS repository.

You can select one of the following databases:

- DB2
- Oracle
- SQLServer
- Sybase

## **Kerberos Authentication**

Indicate that the database uses Kerberos authentication. This option is supported only for SQLServer.

## **Username**

The database user.

### Password

Database password corresponding to the database user.

### JDBC Connect String

The connection string used to connect to the database.

- **IBM DB2.** `jdbc:informatica:db2://<host name>:<port>;DatabaseName=<database name>`
- **Microsoft SQL Server.** `Server: jdbc:informatica:sqlserver://<host name>:<port>;DatabaseName=<database name>`
- **Kerberos-enabled Microsoft SQL Server.** `jdbc:informatica:sqlserver://<host name>:<port>;DatabaseName=qadb;integratedSecurity=true;authenticationScheme=JavaKerberos;encrypt=false`
- **Oracle.** `jdbc:informatica:oracle://<host name>:<port>;ServiceName=<service name>`
- **Sybase.** `jdbc:informatica:sybase://<host name>:<port>;DatabaseName=<database name>`

### Secure JDBC Parameters

Secure JDBC parameters that you want to append to the database connection URL.

Use this property to specify secure connection parameters such as passwords. The Administrator tool does not display secure parameters or parameter values in the Edge Data Streaming Service properties. Enter the parameters as name=value pairs separated by semicolon characters (;). For example:

```
param1=value1;param2=value2
```

If secure communication is enabled for the database, enter the secure JDBC parameters in this property.

### Database Schema

The schema name for the Microsoft SQL Server database.

### Database Tablespace

Tablespace name for IBM DB2 database. When you specify the tablespace name, the Edge Data Streaming Service creates all repository tables in the same tablespace. You cannot use spaces in the tablespace name.

6. Click **Test Connection** to verify if the connection to the database is successful.
7. Click **Finish**.

## CHAPTER 5

# Uninstallation

This chapter includes the following topics:

- [Uninstallation Overview, 38](#)
- [Before You Uninstall, 38](#)
- [Edge Data Streaming Uninstallation, 38](#)

## Uninstallation Overview

The EDS installation process creates an uninstallation directory for EDS. To completely uninstall EDS, you must uninstall the Administration components, EDS Node, and Apache ZooKeeper. The uninstallation process deletes all files and clears all configurations from a machine.

## Before You Uninstall

Before you uninstall EDS, perform the following tasks:

1. Undeploy all data flows.
2. Delete the Edge Data Streaming Service. The uninstallation process does not remove the Edge Data Streaming Service. If you do not delete the Edge Data Streaming Service before uninstalling EDS, you might see an empty Edge Data Streaming Service when you start the Informatica service.
3. Stop all EDS components. The uninstallation process cannot remove the files that are being used by a component that is running.

## Edge Data Streaming Uninstallation

You can uninstall EDS in graphical mode on Windows and in console mode on Linux.

## Uninstalling Edge Data Streaming on Windows

You can uninstall the EDS in graphical mode on Windows.

1. Go to the following directory:  
`<Informatica installation directory>/Uninstaller_EDS`
2. Run `uninstaller.exe` to uninstall EDS.
3. Click **Uninstall** to continue with the uninstallation.
4. Click **Done** to close the uninstaller.

## Uninstalling Edge Data Streaming in Console Mode

You can uninstall the EDS in console mode on Linux.

1. Go to the following directory:  
`<Informatica installation directory>/Uninstaller_EDS`
2. Run the `./uninstaller` command.
3. Press **Enter**.  
The installer displays a warning messaging to shut down all EDS components.
4. Press **Enter** to continue with the uninstallation.  
The **Post-Uninstallation Summary** page appears.
5. Press **Enter** to exit the uninstallation process.

## Uninstalling the Edge Data Streaming Node in Graphical Mode

You can uninstall the EDS Node in graphical mode on Linux. Before you run the uninstaller, stop the EDS Node.

1. Go to the following directory:  
`<EDS Node installation directory>/Uninstaller_Node`
2. Run `uninstaller.exe` to uninstall the EDS Node.
3. Click **Uninstall** to continue with the uninstallation.
4. Click **Done** to exit the uninstallation process.

## Uninstalling the Edge Data Streaming Node in Console Mode

You can uninstall the EDS Node in console mode on Linux. Before you run the uninstaller, stop the EDS Node.

1. Go to the following directory:  
`<EDS Node installation directory>/Uninstaller_Node`
2. Run the `./uninstaller` command.
3. Press **Enter** to continue with the uninstallation.
4. Click **Enter** to exit the uninstallation process.

## Uninstalling the Remote EDS Node

You can uninstall the EDS Node on a remote machine in console mode on Linux. Before you run the uninstaller, stop the EDS Node.

1. Go to the following directory:

`<EDS Node installation directory>`

Ensure that the `SilentInput.properties` file and the `hostsList` are present in this directory.

2. Run the `./remote-node.sh uninstall` command to uninstall the EDS Node.



## CHAPTER 6

# Troubleshooting the Installation

### When I run the EDS installer, the installer fails to run.

This issue might occur if you do not have permissions for the `/tmp` directory on the hard disk. Ensure that you have permissions for the `/tmp` directory and run the installer again.

### The Administrator Daemon process stops unexpectedly when I try to start the Administrator Daemon.

This error might occur if you change the host name of the machine on which you install the Administrator Daemon. After installation, do not change the host name of the machine on which you install the Administrator Daemon. If you change the host name, you must reinstall the Administrator Daemon.

### The EDS Node does not start after installation.

This error can occur if you have configured the EDS Node incorrectly. Check the `<EDS Installation Directory>/node/logs/<node-name>.out` log file for errors and correct them. Also see the `<EDS Installation Directory>/node/logs/<node name>-node.log` for other errors.

### I am not able to see the contents of the Edge Data Streaming tab after I create the Edge Data Streaming Service.

This issue can occur if the database user does not have sufficient privileges to create tables in the database. Check the Administrator Daemon log files for errors. Perform the following steps to resolve the issue:

1. Ensure that the database user has sufficient permissions to create tables in the database.
2. Delete the Edge Data Streaming Service.
3. Ensure that the Administrator Daemon is restarted.
4. Re-create the Edge Data Streaming Service.

## APPENDIX A

# Configuring Extended JVM Parameters

You can configure the JVM parameter heap size in the Administrator Daemon configuration. The heap size depends on the number of applications in your deployment.

By default the heap size allocated to Administrator Daemon is 2 GB. To change the heap size add the following configuration in the `admin.d.cnf` located in the `<Administrator Daemon Installation Directory>/admin.d/config` directory:

```
jvmOptions="-Xmx4G -Xms4G"
```

where

- `-Xmx4G` is the maximum heap size
- `-Xms4G` is the minimum heap size

# INDEX

## A

Administrator Daemon  
starting [32](#)  
stopping [32](#)  
Administrator tool  
logging in [35](#)

## C

configuration  
Kerberos files [12](#)

## E

Edge Data Streaming Service  
creating [36](#)  
EDS components  
uninstalling [38](#)  
EDS Node  
starting [33](#)  
stopping [33](#)

## H

high availability  
plan [11](#)

## I

Informatica Domain  
starting [34](#)  
starting and stopping on Windows [34](#)  
stopping [34](#)  
Installation  
console mode [20](#)  
EDS Node in console mode [26](#)  
EDS Node in graphical mode [26](#)  
EDS Node in silent mode [28](#)  
EDS Node on Linux [26](#)  
EDS Node on Windows [26](#)  
graphical mode [18](#)  
Linux [20](#)  
overview [18](#)  
Silent mode [22](#)  
Windows [18](#)  
Installation and Configuration  
Overview [7](#)

## K

Kerberos authentication  
configuration files [12](#)

## L

license  
adding [35](#)  
License key [14](#)

## P

post-installation  
overview [32](#)  
pre-installation  
overview [10](#)

## S

security  
pre-installation requirements [11](#)  
Start  
Administrator Daemon [32](#)  
EDS Node [33](#)  
Informatica Domain [34](#)  
Stop  
Administrator Daemon [32](#)  
EDS Node [33](#)  
Informatica Domain [34](#)

## U

Uninstallation  
EDS Node in console mode [39](#)  
EDS Node in graphical mode [39](#)  
EDS Node on Linux [39](#)  
EDS Node on Windows [39](#)  
graphical mode [39](#)  
on Linux [39](#)  
Remote EDS Node in console mode [40](#)  
Remote EDS Node on Linux [40](#)  
Windows [39](#)