

## Contents

Installation and Upgrade.....	1
New Features.....	2
Fixed Limitations.....	2
Known Limitations.....	4
Informatica Global Customer Support.....	8

Use the *B2B Data Exchange Release Notes* to learn about installation and upgrade, new features, fixed limitations, and known limitations for B2B Data Exchange.

## Installation and Upgrade

Before you install or upgrade B2B Data Exchange, verify that your system meets the minimum requirements and follow the pre-installation steps. For information about installing or upgrading B2B Data Exchange, see the *B2B Data Exchange Installation and Configuration Guide*.

### Installation and Upgrade Limitations

The following table describes known installation and upgrade limitations:

Issue	Description
XE-11143	If you install the B2B Data Exchange PowerCenter® server plug-in component by itself, you might receive an error message.
XE-10798	When you install B2B Data Exchange in a Windows operating system, if you clear all the options in the <b>Installation Components</b> page and then navigate to the previous page, <b>Installation Directory</b> , you cannot navigate from the <b>Installation Directory</b> page back to the <b>Installation Components</b> page. Workaround: Verify that at least one component is selected on the <b>Installation Components</b> page before you leave the page.

Issue	Description
XE-10679	<p>When you install B2B Data Exchange with HTTPS ports other than the default ports, then install the Partners Portal with HTTPS ports other than the default ports, both the Operation Console and the Partners Portal are available only through the HTTPS default ports.</p> <p>Workaround: Set the Operation Console port and the Partners Portal port to the same port, even when installed on separate nodes. Set the <b>dx.console.url</b> and <b>dx.portal.url</b> system properties to the same port in the Operation Console.</p>
XE-9809	<p>When you install B2B Data Exchange on a Windows Operating system, if you install the B2B Data Exchange client plugin for PowerCenter component and define a custom ODBC connection string, the string, user name, and password that you define during the installation are not saved to the plugin. When you create custom workflows, event status names are not loaded into PowerCenter Designer.</p> <p>Workaround: Take one of the following steps:</p> <ul style="list-style-type: none"> <li>- Enter the string, user name, and password in the following file:  <code>&lt;DXInstallationDir&gt;/powercenter/pluginVERSION/dxplugin.xml</code></li> <li>- Manually enter event status names in PowerCenter Designer.</li> </ul>

## New Features

For a list of new features and enhancements in B2B Data Exchange, see the *B2B Data Exchange Release Guide*.

## Fixed Limitations

Review the Release Notes of previous releases for information about previous fixed limitations.

The following table describes fixed limitations:

Issue	Description
XE-12674	B2B Data Exchange doesn't recognize a file if the file name contains a closing bracket.
XE-12642	In Managed File Transfer, when you retrieve and send emails through the Retrieve Email and Send Email tasks, and the email has an attachment whose file name has special characters, an error occurs.
XE-12638	In B2B Data Exchange version 10.4.0, the calendar in the Data Exchange console displays incorrect dates.
XE-12632	<p>When you delete a web user in MFT Hosted Endpoint, the Endpoints page behaves in the following manner:</p> <ul style="list-style-type: none"> <li>- The error message "Unexpected JavaScript exception" appears on the last page in pagination.</li> <li>- Incorrect number of endpoints appear when you use the ascending/descending option.</li> <li>- Incorrect number of web users associated with the endpoint appear when you use pagination.</li> </ul> <p>Workaround: Save the web users of the MFT Hosted endpoints before you delete them.</p>
XE-12600	<p>The following error message appears when you access MFT endpoints after upgrading from B2B Data Exchange 10.2.2 HF1 to B2B Data Exchange 10.2.3:</p> <p>"An error occurred. Contact your system administrator."</p>

Issue	Description
XE-12550	When you import an MFT endpoint and choose not to import the system-generated workflows for the endpoint, the import operation succeeds. However, if you import an endpoint with no associated workflows, the import causes inconsistencies in the B2B Data Exchange repository. Workaround: When you import or export an MFT endpoint, verify that the system-generated workflows are also imported or exported.
XE-12588	Unable to sort files in milliseconds using the last modified option in the Create File List task.
XE-12563	A Java Heap space error appears on the Audit event table when you import a partner.
XE-12557	An incorrect aggregated status appears intermittently.
XE-12556	When you use the DX_Add_Document_To_Event transformation to attach text documents to events as <i>Output</i> , the output file intermittently displays an incorrect file size.
XE-12555	B2B Data Exchange does not honor pwc.retry.interval.sec and pwc.retry.max.count system property
MFT-355	In Managed File Transfer, when you test a <b>Network Share</b> resource of the SMB v2 or v3 version and the resource uses an encrypted password, the test fails.
MFT-351	In a Managed File Transfer project with SQL SELECT and Write CSV task, if you run the target table with 0 rows, an error might appear.
MFT-344	A REST API call returns a successful status response even if you provide invalid credentials.
MFT-331	In Managed File Transfer, you cannot set the preserveAttributes attribute to false.
MFT-329	When you test an HTTPS resource after upgrading Managed File Transfer to version 10.2.3, an error along with a stack trace is displayed.
MFT-318	In Managed File Transfer, when you retrieve and send emails through the Retrieve Email and Send Email tasks, the following error message might appear: "ERROR [8098 - prj_slanfe_scania] Unable to load BODYSTRUCTURE"
MFT-317	When an AS2 server receives a message, the server generates a unique Message Disposition Notification(MDN) receipt ID for each file. However, in a two-node cluster, when you upload a large number of messages at the same time, both the nodes generate the same MDN receipt ID for each file.
MFT-313	In Managed File Transfer version 10.4.0, when you add a schedule to the <b>Schedules</b> workflow and the <b>Job Queue</b> option is blank, an error occurs.
MFT-312	In Managed File Transfer version 10.4.0, when you test a <b>Network Share</b> resource with <b>SMB Version</b> as SMB v2 or v3 and the <b>Share Name</b> option is blank, an error occurs.
MFT-280	The Save button is greyed out when you open the MFT projects.
MFT-279	An MFT Project with an SQL Task fails with the following error: [8098 - Check_MFT_Rep] This operation is not supported.
B2BT-1113	In MFT, a user is unable to retain Groups using basic authorization.

Issue	Description
B2BT-1063	In MFT, an authentication error appears when you run a 'call project' task.
B2BT-858	You might experience intermittent failures when you use the Network Share resource in InformaticaMFT and to connect to an SMB Network share.

## Known Limitations

The following table describes known limitations:

CR	Description
MFT-495	If you set a timeout value or set the input and output connection ID value, importing an MLLP project from version 10.5.3 to MFT versions 10.5.0 or 10.4.0 fails. Also, if you set a timeout value for a project, importing the project from version 10.5.3 to version 10.5.0 or 10.4.0 fails. Workaround: Set the <b>Ignore Compile Errors</b> property to <b>true</b> when you import a project.
MFT-490	After you upgrade MFT from version 10.2.2 to any later version, MFT doesn't connect to PowerCenter. Workaround: After Managed File Transfer upgrade from version 10.2.2 to any later version, you must manually place pcsf* files from the following location to MFT\home\server\lib location: <MFT_Installation_Location>\server\powercenter\lib\<pwc_version>
MFT-488	An internal error appears when you provide the category as part of the request body while listing projects using a Project List REST API.
MFT-487	After you upgrade MFT to version 10.5.3, the following log4j files are available in the MFT\server\config location: - log4j.xml - log4j2.xml Workaround: Manually delete the log4j.xml file because they aren't required.
MFT-486	When you run the <b>Notify Consumer Task</b> from Managed File Transfer, the MFT <b>Completed Jobs</b> grid doesn't display the endpoint name.
MFT-485	After you upgrade MFT to version 10.5.3, the OEM projects are added to the following folder: MFT\server\userdata\projects\OEM_MFT_PROJECTS You can ignore these projects because it doesn't cause any functionality loss.
MFT-484	When you run a Password-Protected Excel project in Managed File Transfer, the project might fail. Workaround: Copy the xmlbeans.jar file to the MFT\server\lib location before you run the project in MFT.
MFT-471	When you update the web user password using the update web user REST API, a success message appears. However, the password isn't updated.
MFT-414	Managed File Transfer doesn't log an HTTP request in the debug logs with OKTA login.

CR	Description
XE-12786	<p>B2B Data Exchange displays an internal server error message when you access the Managed File Transfer dashboard from the B2B Data Exchange dashboard and then log out and log in from the same login page.</p> <p>Workaround: Use the same protocol (HTTP or HTTPS) for both Data Exchange and MFT. If you use the https protocol, you must change the MFT URL to https and set the port number to 8002 in the system properties.</p>
XE-12758	<p>B2B Data Exchange displays an error message when you unzip .jar files during startup.</p> <p>You can ignore this issue because it doesn't cause any functionality loss.</p>
XE-12693	<p>In the B2B Data Exchange dashboard, select a partner and an associated account as the filter and apply it as the default setting. If you navigate to other pages and back to the dashboard, the reports don't reflect the default settings.</p> <p>Workaround: Click <b>Apply Filters</b> after navigating back to the dashboard.</p>
XE-12692	<p>In the B2B Data Exchange dashboard, when you click a hyperlink in a panel, the hyperlink works as expected and navigates to the Event List page or the Authorization page. However, when you navigate back to the dashboard, the console does not display the blue color for the hyperlink, but the hyperlink works as expected.</p>
XE-12691	<p>In the B2B Data Exchange console, when you click the <b>Set as default</b> button after selecting the filters, a confirmation message is not displayed and the <b>Set as default</b> button is not disabled.</p>
XE-12690	<p>B2B Data Exchange generates a system error event when you process more than 100 files in a Windows High Availability environment.</p> <p>You can ignore this issue because it doesn't cause any functionality loss.</p>
XE-12689	<p>If you start B2B Data Exchange and Informatica Managed File Transfer using Windows services with TLS version 1.3, the HTTPS pages for B2B Data Exchange and Informatica MFT fail to load. However, the HTTPS pages load when you start B2B Data Exchange and Informatica MFT from a command prompt.</p>
XE-12688	<p>Managed File Transfer doesn't consider the files in the subdirectories and folders for an SCP MGet task even if the <b>Recursive</b> option is set to <code>true</code>.</p>
XE-12687	<p>Users who don't have the View Events privilege can view the total number of events on the report displayed in the dashboard.</p>
XE-12685	<p>When you stop the B2B Data Exchange application on some Linux or AIX environments, the Active MQ service fails to stop and displays an error message.</p>
XE-12634	<p>When you run a scheduled MFT endpoint and import or export schedules simultaneously, Data Exchange fails to respond.</p>
XE-12629	<p>When you place a file which has the Informatica Intelligent Cloud Service profile associated with File receive endpointst, a IICS connection appears. If you replace the file in IICS after moving the docstore, the job fails.</p>
XE-12626	<p>During silent installation or upgrade, if you select to use a new metadata repository, you might receive the following message:</p> <p>"A B2B Data Exchange meta data repository was found in the database account provided."</p> <p>Dismiss the message to continue with the installation.</p>

CR	Description
XE-12587	B2B Data Exchange generates a system error event when you process more than 1000 files in Windows environment. This issue doesn't cause any functionality loss.
XE-12527	For an Informatica Intelligent Cloud Services mapping that is created to integrate with a B2B Data Exchange endpoint, the tab delimiter formatting option does not work.
XE-12526	For an Informatica Intelligent Cloud Services mapping that is created to integrate with a B2B Data Exchange endpoint, the fixed width formatting option does not work.
XE-12525	For an Informatica Intelligent Cloud Services mapping that is created to integrate with a B2B Data Exchange endpoint, the escape character formatting option does not work.
XE-12522	When you try to test an SMTP test connection in B2B Data Exchange, the test fails when the <b>From Name</b> field contains spaces.
XE-12520	If you change the value of the system property <code>dx.iics.runtime.environment</code> during runtime, the change does not apply as B2B Data Exchange creates connection with the previous runtime environment value. Workaround: Manually delete the connections that B2B Data Exchange previously created.
XE-12461	The B2B Data Exchange migration tool cannot retrieve a Local Listener Certificate when the <b>Override Local Listener Certificate</b> property is not configured. Workaround: After the migration tool creates endpoints, manually select a certificate for each relevant endpoint.
XE-12394	For an MFT Receive endpoint with a regular expression pattern, if you select the <b>Regular Expression Partial Match</b> option, clear the regular expression, and then try to save the endpoint, you receive an error message.
XE-12366	When you try to download a large directory (20 GB and up) with the Informatica File Transfer Portal Secure Folder download, it might fail.
XE-12307	You cannot delete an MFT Connection in the B2B Data Exchange Operation Console if you are not assigned the Edit Endpoint privilege.
XE-12300	If you create two portal parameters and one is dependent on the other, both might display as disabled in a profile, rather than just the dependent parameter.
XE-12292	When you open the B2B Data Exchange Operation Console in the Edge browser, you cannot scroll to the last line of the <b>Details</b> section of the <b>Event List</b> page.
XE-11193	When you apply an endpoint file pattern regular expression in Windows with "/" in the file path, files for that endpoint will not be taken. Workaround: Use "\\" instead of "/"
XE-11168	If you create a File Event event type rather than a File Level Event event type, you cannot reprocess the resulting File Event events.
XE-11095	When you create a new portal user and click <b>Save and Send Invitation</b> and then <b>Save</b> , the link in the invitation email displays an error. Workaround: Click <b>Cancel</b> to close the form after <b>Save and Send Invitation</b> .

CR	Description
XE-10881	If you exported all DX entities and then imported them after upgrade to this release, the obsolete SFE scheduler is added and displayed with DX schedules. Workaround: You can manually delete the schedule.
XE-10786	When you delete a partner or account with the B2B Data Exchange Operation Console and then import a partner or account which has same name, the Operational Data Store Event Loader might fail.
XE-10007	When you define an Managed File Transfer endpoint with the B2B Data Exchange Operation Console in a Chrome browser, the Managed File Transfer browser might not work correctly. Workaround: Close the Chrome browser, clear the cache, and reopen the Chrome browser.
XE-7655	The B2B Data Exchange Operation Console lists event-types that are relevant for Data Integration Hub.
XE-7161	When you import a partner to the Operation Console and choose not to import profiles, the import process imports associated schedules for the profiles.
XE-7153	B2B Data Exchange stores operational data store JDBC connection properties in the dx-configuration.properties file in addition to B2B Data Exchange system properties. Workaround: If you change the JDBC connection properties in the dx-configuration.properties file, change the system properties.
XE-7129	You cannot change the category management mode for a partner or a profile with the Web Service API. Workaround: In the Operation Console, manually change the category management mode for the partner or profile.
XE-7048	You cannot use an opening parenthesis character in the file name pattern for Managed File Transfer endpoints.
XE-6695	If you create a delayed processing rule for a profile that contains event properties with incorrect or incomplete default values, B2B Data Exchange might enable the <b>Delay All Events</b> processing rule. Workaround: Discard the event and define correct event attribute values for the profile.
XE-6657	If you use Managed File Transfer and you move the B2B Data Exchange repository to a different machine, Managed File Transfer does not replace the database connection. Workaround: Manually delete the previous database connection in the Databases section of the Managed File Transfer administrator console.
XE-6403	You cannot use the DX_Aggregate transformation in a PowerCenter session with multiple partitions.
XE-5958	When you install B2B Data Exchange with Managed File Transfer on a Linux or UNIX platform and you select HTTPS as the protocol, the Managed File Transfer process does not terminate when the installer terminates. Workaround: Shut down the Managed File Transfer process before you start B2B Data Exchange to register the license.
XE-5909	When the developer uses the Profile Parameters custom transformation to define a workflow parameter that starts with "DX", the output port for this parameter is always null and the transformations fail. Workaround: Do not start parameter names with "DX". This prefix is reserved for internal system use only.

CR	Description
XE-5822	<p>When you install B2B Data Exchange with SQL server and use both the instance name and the port, B2B Data Exchange fails and the following error message appears in the log:</p> <pre>FATAL [com.informatica.b2b.dx.bootstrap.DXRuntimeControlImpl] {main} Fatal error in starting the servicesorg.springframework.beans.factory.BeanInitializationException: DX Repository not found.</pre> <p>Workaround: Enter a connection string without a port number or without the instance name.</p>
XE-5131	In you search for a monitor for a specific partner using the advanced search, in the next search you will not see all the existing partners.
XE-5021	If you attempt to reprocess or resend an empty file, you receive an unclear error message.
XE-5017	If a document is passed by reference to an outbound endpoint, selecting a different file to resend fails.
XE-5000	When you perform an advanced search on an on-boarding checklist, if you select a Status and select OR as the operation, the search does not work.
XE-4820	When configuring the file endpoint to wait for file stabilization, if a file with the same name and size is added with a long time to wait, B2B Data Exchange might not wait for the file to finish.
XE-4805	If a file cannot be read and the option to wait for the file size to stabilize is on, there is no error event.
XE-4035	B2B Data Exchange fails to route files if two endpoints use the same account but only one is enabled.

## Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:

<https://www.informatica.com/services-and-training/customer-success-services/contact-us.html>.

To find online support resources on the Informatica Network, visit <https://network.informatica.com> and select the eSupport option.