



Informatica® PowerCenter
10.2 HotFix 2

How to Install Informatica 10.2 HotFix 2 Using a Docker Utility

Informatica PowerCenter How to Install Informatica 10.2 HotFix 2 Using a Docker Utility
10.2 HotFix 2
May 2019

© Copyright Informatica LLC 2019

Publication Date: 2019-06-11

Table of Contents

Abstract.	iv
Chapter 1: Install docker utility.....	5
Overview.	5
Docker Utility Process.	6
Verify System Requirements.	6
Prerequisites.	6
Install Docker.	7
Set Up a Keystore and Truststore Files.	7
Extract the Installer Files.	8
Verify the License Key.	9
Set Up the Domain Configuration Repository.	9
Build the Informatica Docker Image.	10
Run the Informatica Docker Image.	11
Creating a Domain.	11
Run the Image to Join a Domain.	17
Build the Informatica Docker Image in Silent Mode.	22
Configuring the Properties File.	22
Running the Silent Installer.	23
Run the Docker Image in Silent Mode.	23
Configuring the Properties File.	23
Running the Silent Installer.	30
Post-Install Tasks.	31
Complete the Domain Configuration.	31
Create the Application Services.	31
Install the PowerCenter Client	31
Starting and Stopping the Informatica Services on UNIX.	32
Index.	33

Abstract

Informatica provides the Docker utility to install the Informatica domain quickly. This article describes how to install Informatica using Docker image.

CHAPTER 1

Install docker utility

This chapter includes the following topics:

- [Overview, 5](#)
- [Docker Utility Process, 6](#)
- [Verify System Requirements, 6](#)
- [Prerequisites, 6](#)
- [Build the Informatica Docker Image, 10](#)
- [Run the Informatica Docker Image, 11](#)
- [Build the Informatica Docker Image in Silent Mode, 22](#)
- [Run the Docker Image in Silent Mode, 23](#)
- [Post-Install Tasks, 31](#)
- [Starting and Stopping the Informatica Services on UNIX, 32](#)

Overview

Docker is an open source platform that provides an isolated environment called containers to run the applications. Docker allows independent containers to run within a single Linux instance.

The Informatica Docker utility provides an easy and quick process to install the Informatica domain.

When you run the Informatica Docker utility, you can build the Informatica docker image and run the existing docker image to configure the Informatica domain. When you run the Informatica docker image you are prompted to create a domain or join a domain. You can create the application services in the Administrator tool after the installation is complete.

Docker Utility Process

The installation of the Informatica domain services using Docker utility consists of multiple phases.

Consider the following high-level tasks of the installation process:

1. Before you install the Informatica domain services, perform the following tasks to plan and prepare for the Informatica domain services installation:
 - a. Plan the Informatica domain and prepare the databases for the Informatica domain.
 - b. Set up the machines to meet the Linux requirements to ensure that you can successfully install and run the Informatica domain services.
2. Build the Informatica Docker image. Use the Informatica Docker utility to build the Informatica docker image with base operating system and Informatica binaries.
3. Run the Informatica Docker image. Use the Informatica Docker utility to run the existing docker image to configure the Informatica domain. The first time you run the image, you must create the Informatica domain. During the installation on the additional containers, you create worker nodes that you join to the Informatica domain.
4. After you install the Informatica domain services, perform the following tasks to complete the services installation:
 - a. Complete the domain configuration. Verify code page compatibility, complete tasks required by the type of user authentication used by the domain, and configure environment variables.
 - b. Create the application services in the Administrator tool.
5. Install the PowerCenter client.

Verify System Requirements

Verify that your environment meets the minimum system requirements for the installation process.

The following table describes the system requirements for the installation:

Requirements	Description
Disk space	80 GB
Red Hat Enterprise Linux base operating system image name	Subscribed image name: registry.access.redhat.com/rhel7

For more information about the Informatica product prerequisites, see the *Informatica 10.2 HotFix 2 Installation and Configuration Guide*.

Prerequisites

Ensure that Docker Engine is up and running. For more information about Docker Engine, see the following link:

<https://docs.docker.com/install>

The RHEL operating system that you use must be subscribed.

Before you install the Docker utility, verify that the machine meets the pre-installation requirements for the Informatica product installation.

Install Docker

Before you run the Informatica Docker utility, you must ensure that Docker Engine is up and running. You can use Docker to create, manage, and monitor the containers.

Configure Docker Engine base image size to 40 GB. For instance, to edit Docker Engine base image size from a 10 GB default value to 40 GB, you must update the `/etc/docker/daemon.json` file with the following entries:

```
{
  "storage-driver": "devicemapper",
  "storage-opts": [
    "dm.basesize=40G"
  ]
}
```

Set Up a Keystore and Truststore Files

You can configure security after install.

When you install the Informatica services, you can configure secure communication for the Informatica domain and set up a secure connection to Informatica Administrator (the Administrator tool). To configure the security options, you can use the keystore and truststore packaged with the installer.

Before you install the Informatica services, set up the files for secure communication within the Informatica domain or for a secure connection to the Administrator tool. To create the required files, you can use the following programs:

keytool

You can use keytool to create an SSL certificate or a Certificate Signing Request (CSR) as well as keystores and truststores in JKS format.

OpenSSL

You can use OpenSSL to create an SSL certificate or CSR.

For more information about OpenSSL, see the documentation on the following website:

<https://www.openssl.org/docs/>

For a higher level of security, send your CSR to a Certificate Authority (CA) to get a signed certificate.

The software available for download at the referenced links belongs to a third party or third parties, not Informatica LLC. The download links are subject to the possibility of errors, omissions or change. Informatica assumes no responsibility for such links and/or such software, disclaims all warranties, either express or implied, including but not limited to, implied warranties of merchantability, fitness for a particular purpose, title and non-infringement, and disclaims all liability relating thereto.

Secure Communication Within the Informatica domain

Before you enable secure communication within the Informatica domain, verify that the following requirements are met:

You created a certificate signing request (CSR) and private key.

You can use keytool or OpenSSL to create the CSR and private key.

If you use RSA encryption, you must use more than 512 bits.

You have a signed SSL certificate.

The certificate can be self-signed or CA signed. Informatica recommends a CA signed certificate.

You imported the certificate into keystores.

You must have a keystore in JKS format named `infa_keystore.jks` or a keystore in PEM format named `infa_keystore.pem`.

The keystore files must contain the root and intermediate SSL certificates.

Note: The password for the keystore in JKS format must be the same as the private key pass phrase used to generate the SSL certificate.

You imported the certificate into truststores.

You must have a truststore in JKS format named `infa_truststore.jks` or a truststore in PEM format named `infa_truststore.pem`.

The truststore files must contain the root, intermediate, and end user SSL certificates.

The keystores and truststores are in the correct directory.

The keystore and truststore must be in a directory that is accessible to the installer.

Secure Connection to the Administrator tool

Before you secure the connection to the Administrator tool, verify that the following requirements are met:

You created a certificate signing request (CSR) and private key.

You can use keytool or OpenSSL to create the CSR and private key.

If you use RSA encryption, you must use more than 512 bits.

You have a signed SSL certificate.

The certificate can be self-signed or CA signed. Informatica recommends a CA signed certificate.

You imported the certificate into a keystore in JKS format.

A keystore must contain only one certificate. If you use a unique certificate for each web application service, create a separate keystore for each certificate. Alternatively, you can use a shared certificate and keystore.

If you use the installer-generated SSL certificate for the Administrator tool, you do not need to import the certificate into a keystore in JKS format.

You can import the certificate on the machine where you create the Informatica domain. You can then copy the certificate to each machine where you join the Informatica domain.

The keystore is in the correct directory.

The keystore must be in a directory that is accessible to the installer.

Extract the Installer Files

The Informatica docker utility installer files are compressed and distributed as a zip file.

Download the installer files. Use a zip utility to extract the .zip files to a directory on your machine. You can download the .zip file at the Informatica Marketplace:

https://marketplace.informatica.com/listings/on-premise/solutions/informatica_powercenter_docker_utility.html

The docker utility uses the tar utility to extract the installer server files to a directory on your machine. The user that runs the installer must have read and write permissions on the installer files directory and execute permissions on `install.sh`.

Verify the License Key

Before you install the software, verify that you have the license key available for the Informatica product installer.

PowerCenter is provided as a Bring Your Own License (BYOL). Copy the license key file to a directory accessible to the user account that installs the product. You can use an existing Informatica license agreement or contact Informatica Global Customer Support if you do not have a license key or if you have an incremental license key.

Note: The Informatica docker utility does not require a license to run it.

Set Up the Domain Configuration Repository

Set up a database and user account for the domain configuration repository. The domain configuration repository stores metadata for the Informatica domain. The Informatica domain configuration repository stores metadata for the Informatica domain operations and user authentication. When you install Informatica, you provide the database and user account information for the domain configuration repository. The Informatica installer uses JDBC to communicate with the domain configuration repository.

Use the following rules and guidelines when you set up the domain configuration database and user account:

- The database must be accessible to all nodes in the Informatica domain.
- To prevent database errors in the domain configuration repository from affecting other repositories in the Informatica domain, create the domain configuration repository in a separate database schema with a different database user account.
- If you create more than one Informatica domain, each domain configuration repository must have a separate user account.
- Allow 200 MB of disk space for the database.

For more information about configuring the database, see the documentation for your database system.

Microsoft SQL Server Database Requirements

Use the following guidelines when you set up the repository:

- Set the allow snapshot isolation and read committed isolation level to `ALLOW_SNAPSHOT_ISOLATION` and `READ_COMMITTED_SNAPSHOT` to minimize locking contention.

To set the isolation level for the database, run the following commands:

```
ALTER DATABASE DatabaseName SET ALLOW_SNAPSHOT_ISOLATION ON
```

```
ALTER DATABASE DatabaseName SET READ_COMMITTED_SNAPSHOT ON
```

To verify that the isolation level for the database is correct, run the following commands:

```
SELECT snapshot_isolation_state FROM sys.databases WHERE name=[DatabaseName]
```

```
SELECT is_read_committed_snapshot_on FROM sys.databases WHERE name = DatabaseName
```

- The database user account must have the `CONNECT`, `CREATE TABLE`, and `CREATE VIEW` privileges.

Oracle Database Requirements

Use the following guidelines when you set up the repository on Oracle:

- Set the `open_cursor` parameter to 4000 or higher.
- Set the permissions on the view `$parameter` for the database user.
- Verify that the database user has the following privileges:
 - CREATE SEQUENCE
 - CREATE SESSION
 - CREATE SYNONYM
 - CREATE TABLE
 - CREATE VIEW
- Informatica does not support Oracle public synonyms for repository tables. Verify that public synonyms have not been created for any tables in the database.

Build the Informatica Docker Image

Creates a docker image for Informatica products. After you create the docker image, the docker utility uses the docker image to run on containers. You must build the Informatica docker image to install Informatica products in the docker with the docker utility.

1. Log in to the machine with a system user account. The user must have read, write, and execute permissions. You must have Docker Engine that is up and running.
2. On a shell command line, run the `install.sh` file from the `sudo` directory.
3. On the Welcome screen, press **Enter** to continue the installation.
The **Image Selection** section appears.
4. Press **1** to build the Informatica Docker image.
The **Build Informatica Docker Image** section appears.
5. Enter the information to build the Informatica Docker image.

The following table describes the information to enter to build the Informatica Docker image:

Prompt	Description
Enter the base OS image	Supported Red Hat Enterprise Linux (RHEL) base operating system to create the docker image. Default is <code>registry.access.redhat.com/rhel7</code>
Informatica installer tar file location	Location of the Informatica binaries. For example, enter the tar file in the following format: <code>/root/<user>/tar/informatica_102HF2_server_linux-x64.tar</code>
Informatica Docker base image name	Name of the docker image. Default is <code>informatica1020hf2:1.0</code> , where <code>1.0</code> is the tag name. If you do not specify a tag value, the <code>latest</code> tag is used.

You can view the installation log files to get more information about the tasks performed by the utility.

Run the Informatica Docker Image

After you build the docker image, you can install Informatica products by running the docker image. Run the docker image to create nodes in the Informatica domain. You can run the docker image to create an Informatica domain or join an Informatica domain.

Run the docker utility with the create domain option if it is the first time you install. Run the docker utility with the join domain option if you install on multiple containers and you created a node on another container.

If you install on multiple containers, you can create multiple Informatica domains. When you create an Informatica domain, the node on the container where you install becomes a gateway node in the Informatica domain.

Creating a Domain

Create a domain the first time you run the image.

1. Log in to the machine with a system user account.
2. On a shell command line, run the install.sh file from the sudo directory.
3. On the Welcome screen, press **Enter** to continue the installation.

The **Image selection** section appears.

4. Press **2** to run the Informatica Docker image.

The **Docker Container** section appears.

5. Enter the information to run the Informatica Docker image.

The following table describes the information to enter to run the Informatica Docker image:

Option	Description
Informatica docker image name	Name of the Informatica docker image. A docker image is an executable package that can run an application, a code, run-time files, environment variables, or configuration files.
Informatica container name	Name of the Informatica docker container. A container is a runtime instance of an image.
Informatica host name	Host name of the Informatica domain.
Volume directory	Directory where the Informatica license key and certificates are stored. You must have read, write, and execute permissions on the directory. Enter the existing directory to create tmpfs volume.
Enter the qualified path to license file	Path and file name of the Informatica license key. For example, /root/<username>/License_10.2.HF2.key

6. Specify whether you want to view and expose additional ports in the container other than Informatica ports.
 - Press **1** to expose additional ports in the container. When prompted, enter exposed container ports as comma separated values.
 - Press **2** to hide any additional ports in the container.

Default is 2.

The **Domain selection** section appears.

7. Press **1** to create a domain.

When you create a domain, the node that you create becomes a gateway node in the domain. The gateway node contains a Service Manager that manages all domain operations.

8. To enable secure communication for services in the Informatica domain, press **2**.

To disable secure communication for the Informatica domain, press **1**.

By default, if you enable secure communication for the domain, the installer sets up an HTTPS connection for the Informatica Administrator. You can also create a domain configuration repository on a secure database.

9. Specify the connection details for Informatica Administrator.

- a. If you do not enable secure communication for the domain, you can specify whether to set up a secure HTTPS connection for Informatica Administrator.

The following table describes the options available to enable or disable a secure connection to Informatica Administrator:

Option	Description
Enable HTTPS for Informatica Administrator	Set up a secure connection to Informatica Administrator.
Disable HTTPS	Do not set up a secure connection to Informatica Administrator.

- b. If you enable secure connection for the domain or if you enable HTTPS connection for Informatica Administrator, enter the keystore file and port number for the HTTPS connection to Informatica Administrator.

The following table describes the connection information you must enter if you enable HTTPS:

Option	Description
Port	Port number for the HTTPS connection.
Keystore file	Select whether to use a keystore file generated by the installer or a keystore file you create. You can use a keystore file with a self-signed certificate or a certificate signed by a certification authority. <ul style="list-style-type: none">- Press 1 to use the default keystore generated by the installer. If you select to use a keystore file generated by the installer, the installer creates a self-signed keystore file named Default.keystore in the following location: <Informatica installation directory>/tomcat/conf/- Press 2 to specify the location and password of a custom keystore file.

- c. If you specify the keystore, enter the password and location of the keystore file.
- d. Select if you want to use the container database to configure Informatica domain or not.
- Press **1** to use the container database to configure Informatica domain. When prompted, enter the database container name.
 - Press **2** to not use the container database to configure Informatica domain. When prompted, you can enter domain configuration repository database.

If you enabled secure connection for the domain, the **Domain Security - Secure Communication** section appears. If you did not enable secure connection for the domain, the **Domain Configuration Repository** section appears. Skip to step [11](#) to select the database to use for the domain configuration repository.

10. In the Domain Security - Secure Communication section, specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure domain communication.

- a. Select the type of SSL certificates to use.

The following table describes the options for the SSL certificates that you can use to secure the Informatica domain:

Option	Description
Use the default Informatica SSL certificates	Use the default SSL certificates provided by Informatica. Note: If you do not provide an SSL certificate, Informatica uses the same default private key for all Informatica installations. If you use the default Informatica keystore and truststore files, the security of your domain could be compromised. To ensure a high level of security for the domain, select the option to specify the location of the SSL certificate files.
Specify the location of the custom SSL certificates	Use SSL certificates that you provide. You must specify the location of the keystore and truststore files. You can provide a self-signed certificate or a certificate issued by a certificate authority (CA). You must provide SSL certificates in PEM format and in Java Keystore (JKS) files. Informatica requires specific names for the SSL certificate files for the Informatica domain. You must use the same SSL certificates for all nodes in the domain. Store the truststore and keystore files in a directory accessible to all the nodes in the domain and specify the same keystore file directory and truststore file directory for all nodes in the same domain.

- b. If you provide the SSL certificate, specify the location and passwords of the keystore and truststore files.

The following table describes the parameters that you must enter for the SSL certificate files:

Option	Description
Keystore file directory	Directory that contains the keystore files. The directory must contain a file named infa_keystore.jks or infa_keystore.pem.
Keystore password	Password for the keystore infa_keystore.jks.
Truststore file directory	Directory that contains the truststore files. The directory must contain a file named infa_truststore.jks or infa_truststore.pem.
Truststore password	Password for the infa_truststore.jks file.

The **Domain Configuration Repository** section appears.

11. Select the database to use for the domain configuration repository.

The following table lists the databases you can use for the domain configuration repository:

Option	Description
Database type	Type of database for the domain configuration repository. Choose from the following options: <ul style="list-style-type: none">- Press 1 for Oracle.- Press 2 for Microsoft SQL Server.

12. Enter the properties for the database user account.

The following table lists the properties for the database user account:

Option	Description
Database user ID	Name for the domain configuration database user account.
User password	Password for the domain configuration database user account.

13. Select whether to create a secure domain configuration repository.

You can create a domain configuration repository in a database secured with the SSL protocol.

Press **1** to create a domain configuration repository in a secure database, and skip to the step [15](#) to create a secure domain configuration repository.

Press **2** to create a domain configuration repository in an unsecure database.

14. If you do not create a secure domain configuration repository, enter the parameters for the database.

- a. If you select Microsoft SQL Server, enter the schema name for the database.

The following table describes the properties that you must configure for the Microsoft SQL Server database:

Option	Description
Schema name	Name of the schema that will contain domain configuration tables. If this parameter is blank, the installer creates the tables in the default schema.

- b. To enter the JDBC connection information using the JDBC URL information, press **1**.
To enter the JDBC connection information using a custom JDBC connection string, press **2**.
- c. Enter the JDBC connection information.
- To enter the connection information using the JDBC URL information, specify the JDBC URL properties.

The following table describes the database connection information:

Option	Description
Database address	Host name and port number for the database. Default is <code>host_name:port_no</code>
Database service name	Service or database name : - Oracle: Enter the service name. - Microsoft SQL Server: Enter the database name.
Configure JDBC Parameters	Select whether to add additional JDBC parameters to the connection string: - Press 1 to create additional JDBC parameters to the connection string. You need to enter the parameters or press Enter to accept the default. - Press 2 to not create additional JDBC parameters to the connection string. The installer creates the JDBC connection string without parameters.

- To enter the connection information using a custom JDBC connection string, type the connection string.

You can use the following syntax in the JDBC connection string to connect to a secure database:

Oracle

```
jdbc:Informatica:oracle://
host_name:port_no;ServiceName=service_name;EncryptionMethod=SSL;HostNameInCertificate=DB_host_name;ValidateServerCertificate=true_or_false
```

Microsoft SQL Server

```
jdbc:Informatica:sqlserver://
host_name:port_no;SelectMethod=cursor;DatabaseName=database_name;EncryptionMethod=SSL;HostNameInCertificate=DB_host_name;ValidateServerCertificate=true_or_false
```

- If you create a secure domain configuration repository, enter the parameters for the secure database.

If you create the domain configuration repository on a secure database, you must provide the truststore information for the database. You must also provide a JDBC connection string that includes the security parameters for the database.

The following table describes the options available to create a secure domain configuration repository database:

Option	Description
Database truststore file	Path and file name of the truststore file for the secure database.
Database truststore password	Password for the truststore file.
Custom JDBC Connection String	JDBC connection string to connect to the secure database, including the host name and port number and the security parameters for the database.

You can use the following syntax for the connection strings:

EncryptionMethod

Required. Indicates whether data is encrypted when transmitted over the network. This parameter must be set to `SSL`.

ValidateServerCertificate

Optional. Indicates whether Informatica validates the certificate that the database server sends.

If this parameter is set to True, Informatica validates the certificate that the database server sends. If you specify the HostNameInCertificate parameter, Informatica also validates the host name in the certificate.

If this parameter is set to False, Informatica does not validate the certificate that the database server sends. Informatica ignores any truststore information that you specify

Default is True.

HostNameInCertificate

Optional. Host name of the machine that hosts the secure database. If you specify a host name, Informatica validates the host name included in the connection string against the host name in the SSL certificate.

cryptoProtocolVersion

Required. Specifies the cryptographic protocol to use to connect to a secure database. You can set the parameter to `cryptoProtocolVersion=TLSv1.1` or `cryptoProtocolVersion=TLSv1.2` based on the cryptographic protocol used by the database server.

- **Oracle:** `jdbc:Informatica:oracle://
host_name:port_no;ServiceName=service_name;EncryptionMethod=SSL;HostNameInCertificate=DB_host_name;ValidateServerCertificate=true_or_false`
- **Microsoft SQL Server:** `jdbc:Informatica:sqlserver://
host_name:port_no;SelectMethod=cursor;DatabaseName=database_name;EncryptionMethod=SSL;HostNameInCertificate=DB_host_name;ValidateServerCertificate=true_or_false`

16. In the **Domain Security - Encryption Key** section, enter the keyword and directory for the encryption key for the Informatica domain.

The following table describes the encryption key parameters that you must specify:

Option	Description
Keyword	Keyword to use to create a custom encryption key to secure sensitive data in the domain. The keyword must meet the following criteria: <ul style="list-style-type: none">- From 8 to 20 characters long- Includes at least one uppercase letter- Includes at least one lowercase letter- Includes at least one number- Does not contain spaces The encryption key is created based on the keyword that you provide when you create the Informatica domain.
Encryption key directory	Directory in which to store the encryption key for the Informatica domain. By default, the encryption key is created in the following directory: <code><Informatica installation directory>/isp/config/keys</code> . Note: You cannot specify another location to store the encryption key.

The **Domain and Node Configuration** section appears.

17. Enter the information for the domain and the node that you want to create.

The following table describes the properties that you set for the domain and gateway node:

Option	Description
Domain name	Name of the Informatica domain to create. The default domain name is Domain. The name must not exceed 128 characters and must be 7-bit ASCII only. The name cannot contain a space or any of the following characters: ` % * + ; " ? , < > \ /
Node name	Name of the node to create.
Node host name	Host name or IP address of the machine on which to create the node. The node host name must be same as host name of the Informatica domain.
Node port number	Port number for the node. The default port number for the node is 6005.
Domain user name	User name for the domain administrator. You can use this user name to initially log in to Informatica Administrator. Use the following guidelines: <ul style="list-style-type: none">- The name is not case sensitive and cannot exceed 128 characters.- The name cannot include a tab, newline character, or the following special characters: % * + / ? ; < >- The name can include an ASCII space character except for the first and last character. Other space characters are not allowed.
Domain password	Password for the domain administrator. The password must be more than 2 characters and must not exceed 16 characters. Not available if you configure the Informatica domain to run on a network with Kerberos authentication.
Confirm password	Enter the password again to confirm. Not available if you configure the Informatica domain to run on a network with Kerberos authentication.

The Informatica Docker container starts and after a while, you can view the Post-Installation summary. You can view the installation log files to get more information about the tasks performed by the utility.

Run the Image to Join a Domain

If you want to create other nodes and join the domain, you must run the image to create a container for each node.

1. Log in to the machine with a system user account.
2. Close all other applications.
3. On a shell command line, run the install.sh file from the sudo directory.
4. On the Welcome screen, press **Enter** to continue the installation.
The **Image Selection** section appears.
5. Press **2** to run Informatica image.
The **Docker Container** section appears.
6. Enter the information to run the Informatica Docker image.

The following table describes the information to enter:

Prompt	Description
Informatica docker image name	Name of the Informatica docker image.
Informatica container name	Name of the Informatica docker container.
Informatica host name	Host name of the Informatica domain to join.
Volume directory	Directory where the Informatica license key and certificates are stored. The directory must have read, write, and execute permissions.
Enter the qualified path to license file	Path and file name of the Informatica license key.

7. Specify whether you want to view and expose additional ports in the container other than Informatica ports.
 - Press **1** to expose additional ports in the container. When prompted, enter the exposed container ports as comma separated values.
 - Press **2** to not expose any additional ports in the container.

Default is 2.

The **Domain selection** section appears.

8. Press **2** to join a domain.

The installer creates a node on the container where you install. You can specify the type of node to create and the domain to join.
9. Specify whether the domain you want to join has the secure communication option enabled.
 - Press **1** to join an unsecured domain.
 - Press **2** to join a secure domain.
10. Select the type of node you want to create.
 - Press **1** to configure a gateway node
 - Press **2** to configure a worker node.

If you configure the node as a gateway, you can enable a secure HTTPS connection to the Informatica Administrator.
11. Specify the connection details to Informatica Administrator.
 - a. Specify whether to set up a secure HTTPS connection to Informatica Administrator.
 - Press **1** to enable HTTPS to establish a secure connection for Informatica Administrator
 - Press **2** to disable HTTPS if you do not want to set up a secure connection to Informatica Administrator.

- b. If you enable HTTPS connection for Informatica Administrator, enter the keystore file and port number to use to secure the connection.

Option	Description
Port	Port number for the HTTPS connection.
Keystore file	Select whether to use a keystore file generated by the installer or a keystore file you create. You can use a keystore file with a self-signed certificate or a certificate signed by a certification authority. <ul style="list-style-type: none">- Press 1 to use the default keystore generated by the installer.- Press 2 to specify the location and password of a custom keystore file. If you select to use a keystore file generated by the installer, the installer creates a self-signed keystore file named Default.keystore in the following location: <Informatica installation directory>/tomcat/conf/

- c. If you specify the keystore, enter the password and location of the keystore file.

If you enabled secure communication for the domain, the **Domain Security - Secure Communication** section appears. If you did not enable secure communication for the domain, the **Domain Configuration** section appears.

12. At the prompt, enter the information for the Informatica domain that you want to join.

The following table describes the properties that you specify for the Informatica domain:

Property	Description
Domain name	Name of the domain to join.
Gateway node host	Host name of the container that hosts the gateway node for the domain.
Gateway node port	Port number of the gateway node.
Domain user name	User name of the administrator for the domain you want to join.
Domain password	Password for the domain administrator.
Gateway container name	Container name of the master gateway node.
Join the domain	Specify whether you want to join an Informatica domain created through the container database. <ul style="list-style-type: none">- Press 1 for Yes.- Press 2 for No. Default is 1.
Database Container Name	Enter the database container name.

The Domain Security - Secure Communication section appears.

13. In the Domain Security - Secure Communication section, specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure domain communication.

- a. Select the type of SSL certificates to use.

The following table describes the options for the SSL certificates that you can use to secure the Informatica domain:

Option	Description
Use the default Informatica SSL certificates	Use the default SSL certificates provided by Informatica. Note: If you do not provide an SSL certificate, Informatica uses the same default private key for all Informatica installations. If you use the default Informatica keystore and truststore files, the security of your Informatica domain could be compromised. To ensure a high level of security for the Informatica domain, select the option to specify the location of the SSL certificate files.
Specify the location of the custom SSL certificates	Use SSL certificates that you provide. You must specify the location of the keystore and truststore files. You can provide a self-signed certificate or a certificate issued by a certificate authority (CA). You must provide SSL certificates in PEM format and in Java Keystore (JKS) files. Informatica requires specific names for the SSL certificate files for the Informatica domain. You must use the same SSL certificates for all nodes in the Informatica domain. Store the truststore and keystore files in a directory accessible to all the nodes in the Informatica domain and specify the same keystore file directory and truststore file directory for all nodes in the same Informatica domain.

- b. If you provide the SSL certificate, specify the location and passwords of the keystore and truststore files.

The following table describes the parameters that you must enter for the SSL certificate files:

Option	Description
Keystore file directory	Directory that contains the keystore files. The directory must contain file named infa_keystore.jks or infa_keystore.pem.
Keystore password	Password for the keystore infa_keystore.jks.
Truststore file directory	Directory that contains the truststore files. The directory must contain file named infa_truststore.jks or infa_truststore.pem.
Truststore password	Password for the infa_truststore.jks file.

The **Domain Security - Encryption Key** section appears.

14. Enter the encryption key information for the Informatica domain that you want to join.

If the location of the encryption key in the gateway node is not accessible to the current node, copy the encryption key file to a volume directory.

The following table describes the encryption key parameters that you must specify when you join a domain:

Property	Description
Select the encryption key	Path and file name of the encryption key for the Informatica domain that you want to join. All nodes in the Informatica domain use the same encryption key. You must specify the encryption key file created on the gateway node for the Informatica domain that you want to join. If you copied the encryption key file to the volume directory to make it accessible to the nodes in the Informatica domain, specify the path and file name of the encryption key file in the volume directory.
Encryption key directory	Directory in which to store the encryption key on the node created during this installation. The installer copies the encryption key file for the Informatica domain to the encryption key directory on the new node. By default, the encryption key is created in the following directory: <code></home/Informatica/<version>/isp/config/keys</code> .

15. In the Join Domain Node Configuration section, enter the information for the node you want to create.
The following table describes the properties that you set for the node:

Property	Description
Node host name	Host name or IP address of the machine on which to create the node. The node host name must be same as host name of the Informatica domain.
Node name	Name of the Informatica node to create on this machine. The node name is not the host name for the machine.
Node port number	Port number for the node.
Secure master domain database	Select if you want to secure the domain configuration repository database: - Press 1 for Yes. When prompted, enter the path and password for the database truststore. - Press 2 for No. The post-installation summary section appears.
Database truststore file	Path and file name of the truststore file for the secure database. Select the same database truststore file used by the master gateway node in the Informatica domain. Required if you join a gateway node to a domain that uses a secure domain configuration repository database.
Truststore password	Password for the database truststore file for the secure database. Required if you join a gateway node to a domain that uses a secure domain configuration repository database.

The post-Installation summary section appears.

Build the Informatica Docker Image in Silent Mode

You can build the Docker image in silent mode. Use a properties file to specify the installation options. The installer reads the file to determine the installation options.

To build the Docker image in silent mode, complete the following tasks:

1. Configure the installation properties file and specify the installation options in the properties file.
2. Run the installer with the installation properties file.

Configuring the Properties File

Informatica provides a sample properties file, called `SilentInput_BuildImage.properties`, that includes the parameters that are required by the installer. You can customize the sample properties file to specify the options for your installation. Then run the silent installation.

1. Go to the root of the directory that contains the installation files.
2. Locate the sample `SilentInput_BuildImage.properties` file.
3. Use a text editor to open the file and modify the values of the installation parameters.

The following example shows the contents of the file:

```
# Use the following guidelines when editing this file:
# * Use this file to install without user interaction. Save the file
#   with the following name: SilentInput.properties
# * Any error condition that leads to failure, such as an invalid
#   installation directory, generates a log file in the user home
#   directory. For example: /home/<user name>/silentErrorLog.log

#####
# Informatica Installer Build Details
# Copyright (c) 1993-2019 Informatica LLC
# This software contains confidential and proprietary
# information of Informatica LLC.
# All Rights Reserved.
#####

#####
# Use this file (SilentInput.properties) to install Informatica services without
# user interaction.
# Use this sample properties file to define the parameters for the silent
# installation.
# Use the following guidelines when you edit this file:
#   Back up the file before you modify it.
#   Any error condition that causes the installation to fail, such as an
#   installation directory that is not valid,
#   generates a log file in /home/<user name>. For example: /home/informatica/
#   silentErrorLog.log
#####

IMAGE_NAME=informatica1020hf2:1.0

TAR_FILE_LOC=

OS_NAME=registry.access.redhat.com/rhel7

#####
#
##### DO NOT MODIFY THE FOLLOWING PROPERTIES
```

```
#####
#####
#

INSTALL_TYPE=0
BUILD_IMAGE=1
CONFIGURE_PCRS=0

#####
# After you create the properties file, save the file with the name
# SilentInput.properties and
# run the silent installer to build Docker image.
#####
```

4. Save the properties file with the name `SilentInput.properties`.

Running the Silent Installer

After you configure the properties file, open a command prompt to start the silent installation.

1. Open a command prompt.
2. Go to the root of the directory that contains the installation files.
3. Verify that the directory contains the file `SilentInput.properties` that you edited and resaved.
4. Run the silent installation. On UNIX, run `silentInstall.sh`.

The silent installer runs in the background. The process can take a while. The silent installation is complete when the `Informatica<Version>_Docker_Utility<timestamp>.log` file is created in the directory where you extracted the Docker utility.

Run the Docker Image in Silent Mode

To run the Informatica Docker utility in silent mode, use a properties file to specify the installation options. The installer reads the file to determine the installation options.

To run the Informatica Docker utility in silent mode, complete the following tasks:

1. Configure the installation properties file and specify the installation options in the properties file.
2. Run the installer with the installation properties file.

Configuring the Properties File

Informatica provides a sample properties file, called `SilentInput_RunImage.properties`, that includes the parameters that are required by the installer. You can customize the sample properties file to specify the options for your installation. Then run the silent installation.

1. Go to the root of the directory that contains the installation files.
2. Locate the sample `SilentInput_RunImage.properties` file.
3. Use a text editor to open the file and modify the values of the installation parameters.

The following example shows the contents of the file:

```
# Use the following guidelines when editing the file:
# * Use the file to install without user interaction. Save the file
# with the following name: SilentInput.properties
```

```

# * Any error condition that leads to failure, such as an invalid
#   installation directory, generates a log file in the user home
#   directory. For example: /home/<user name>/silentErrorLog.log

#####
# Informatica Installer Build Details
# Copyright (c) 1993-2019 Informatica LLC
# This software contains confidential and proprietary
# information of Informatica LLC.
# All Rights Reserved.
#####

# Docker Container Details

# IMAGE_NAME represents the Informatica docker image name.
IMAGE_NAME=

# INFA_CONTAINER_NAME represents the name of the Informatica docker container where
# you run Informatica services.
INFA_CONTAINER_NAME=

# INFA_CONTAINER_HOST_NAME represents the host name of the Informatica domain where
# the container resides.
INFA_CONTAINER_HOST_NAME=

# VOLUME_DIRECTORY represents the directory where the Informatica license key and
# certificates are stored. You must have read, write, and execute permissions on the
# directory. Ensure that the volume directory exists in the specified location.
VOLUME_DIRECTORY=

# Set the GATEWAY_CONTAINER_NAME if you want to join a domain.
# GATEWAY_CONTAINER_NAME represents the container name of the master gateway node.
GATEWAY_CONTAINER_NAME=

# USE_DB_CONTAINER represents the option to use the container database to configure
# Informatica domain.
# If you select true, the container database is available to configure the
# Informatica domain.
# If you select false, the container database is unavailable to configure the
# Informatica domain. Select false to use the on-premise database. Default is false.
USE_DB_CONTAINER=false

# DB_CONTAINER_NAME represents the name of the container database.
# Set the DB_CONTAINER_NAME property if USE_DB_CONTAINER=true.
DB_CONTAINER_NAME=

# Set the JOIN_CONTAINER_DB property to true if you want to join an Informatica
# domain created using the container database.
# JOIN_CONTAINER_DB represents the option to join an Informatica domain that has the
# domain configuration repository created on the container database. Set the property
# to true to join the Informatica domain. Set the property to false to create a
# domain. Default is false.
JOIN_CONTAINER_DB=false

# Set the JOIN_DB_CONTAINER_NAME property if JOIN_CONTAINER_DB=true.
# JOIN_DB_CONTAINER_NAME represents the name of the container database that has the
# domain configuration repository that you can use to join the Informatica domain.
JOIN_DB_CONTAINER_NAME=

# Set ENABLE_USAGE_COLLECTION to 1 to accept the product usage toolkit end user
# license agreement.
# You must set the value to 1 to install the Informatica services.
# The product usage toolkit end user license agreement is available at: http://www.informatica.com/us/eula/en-support-eula.aspx.
# As further described in the EULA, your use of the Informatica platform will enable
# the product usage toolkit
# to collect certain product usage and failure information. You may disable this
# feature at any time.

```



```

# For more information on how to disable this feature refer the Informatica
Administrator Guide.

ENABLE_USAGE_COLLECTION=0

# The LICENSE_KEY_LOC property represents the absolute path and file name of the
license key file.
# Set the LICENSE_KEY_LOC property if you are installing Informatica.

LICENSE_KEY_LOC=/home/license.key

#The EXPOSE_USER_DEFINED_PORTS property exposes extra ports from the container to
the guest operating system.
# Set the property to yes to expose extra ports.
# Set the property to no if you do not want to expose the additional ports.

EXPOSE_USER_DEFINED_PORTS=no

# USER_DEFINED_PORTS_LIST represents the list of user defined ports that you can
enter.
# Set the USER_DEFINED_PORTS_LIST only if EXPOSE_USER_DEFINED_PORTS=yes.
# To expose multiple ports, enter comma separated values. You can also enter
multiple port range in the following format: <port_1>-<port_2>. For example,
9000-9010. Or, specify comma-separated values along with port ranges as seen in the
following format: <port_1>,<port_2>-<port_3>. For example, 1000,9000-9010.
# For example, USER_DEFINED_PORTS_LIST=9000,9100

USER_DEFINED_PORTS_LIST=

# The HTTPS_ENABLED property determines whether to secure the connection to
Informatica Administrator.
#Set the HTTPS_ENABLED property to 0 if you want to use an HTTP connection. Set up
an unsecure HTTP connection to Informatica Administrator.
#Set the HTTPS_ENABLED property to 1 if you want to use an HTTPS connection. Set up
a secure HTTPS connection to Informatica Administrator.

HTTPS_ENABLED=0

# The DEFAULT_HTTPS_ENABLED property determines whether the installer creates a
keystore file.
# Set the property if HTTPS_ENABLED=1 (uses HTTPS connection).
#Set the DEFAULT_HTTPS_ENABLED property to 0 if you want to specify a keystore file.
#Set the DEFAULT_HTTPS_ENABLED property to 1 if you want the installer to specify a
keystore file. Set up a secure HTTPS connection to the Informatica Administrator.

DEFAULT_HTTPS_ENABLED=1

# The CUSTOM_HTTPS_ENABLED property determines whether the installer uses an
existing keystore file.
# Set the CUSTOM_HTTPS_ENABLED property to 0 if you want the installer to use an
existing keystore file.
# Set the CUSTOM_HTTPS_ENABLED property to 1 if you want to specify a keystore file
and if DEFAULT_HTTPS_ENABLED=0.

CUSTOM_HTTPS_ENABLED=0

# The KSTORE_PSSWD property represents the password for the keystore file.
# Set the property to the plain text password for the keystore file if
CUSTOM_HTTPS_ENABLED=1.

KSTORE_PSSWD=MyKeystorePassword

# Set the property to the absolute path and file name of the keystore file if
CUSTOM_HTTPS_ENABLED=1.

```

```

KSTORE_FILE_LOCATION=/home/MyKeystoreFile

# The HTTPS_PORT property represents the port number to use for the secure
connection to Informatica Administrator.

HTTPS_PORT=8443

# The CREATE_DOMAIN property determines whether to create an Informatica domain.
#   Value    0    Create a node and join the node to another domain created in a
previous installation. Set the property to 0 if JOIN_DOMAIN=1.
#   Value    1    Create a node and an Informatica domain.

CREATE_DOMAIN=1

#Keyword to use to create an encryption key to secure sensitive data in the domain.
Set the property only when you create a domain.
# The keyword must meet the following criteria:-
# From 8 to 20 characters long-
# Includes at least one uppercase letter-
# Includes at least one lowercase letter-
# Includes at least one number-
# Does not contain spaces

PASS_PHRASE_PASSWD=

# The JOIN_DOMAIN property determines whether to join the node to another domain
created in a previous installation.
#   Value    0    Create a node and an Informatica domain. Set the property to 0
if CREATE_DOMAIN=1.
#   Value    1    Create a node and join the node to another domain created in a
previous installation. Set the property to 1 if CREATE_DOMAIN=0.

JOIN_DOMAIN=0

# The KEY_SRC_LOCATION property represents the directory containing the encryption
key on the master gateway node of the Informatica domain that you want to join.
KEY_SRC_LOCATION=/home/temp/siteKey

# The SSL_ENABLED property enables or disables Transport Layer Security (TLS).
# Set the property to true to enable secure communication between services within
the domain.
# Set the property to true or false if CREATE_DOMAIN=1.
# If SSL_ENABLED=true, then set HTTPS_ENABLED=1 and set HTTPS_PORT.

SSL_ENABLED=false

#####
# The TLS_CUSTOM_SELECTION property represents information about the domain. Set
TLS_CUSTOM_SELECTION to true if you want a TLS option at the domain level.

TLS_CUSTOM_SELECTION=false
#####
#The following fields are only required when you set TLS_CUSTOM_SELECTION=true
NODE_KEYSTORE_DIR=/home/<username>/temp
NODE_KEYSTORE_PASSWD=

```

```

NODE_TRUSTSTORE_DIR=/home/<username>/temp
NODE_TRUSTSTORE_PASSWD=

# The SERVES_AS_GATEWAY property determines whether to create a gateway or worker
node.
# Set the property if JOIN_DOMAIN=1.
# Value 0 The installer configures the node as a worker node.
# Value 1 The installer configures the node as a gateway node.

SERVES_AS_GATEWAY=0

# The DB_TYPE property represents the database type for the domain configuration
database.
# Set the property to one of the following database types (case-sensitive):
Oracle or MSSQLServer

DB_TYPE=Oracle/MSSQLServer

# The DB_UNAME property represents the database user account name for the domain
configuration repository.

DB_UNAME=UserName

# The DB_PASSWD property represents the database password for the database user
account.

DB_PASSWD=UserPassword

# The DB_SSL_ENABLED property indicates whether the database for the domain
# configuration repository is secure. To create the domain configuration repository
# in a secure database, set this parameter to True.
# If the property is set to True, then the DB_CUSTOM_STRING_SELECTION property must
be
# set to 1 to use the custom string option. The DB_CUSTOM_STRING property must
include
# the following secure database parameters:
# EncryptionMethod=SSL;HostNameInCertificate=;ValidateServerCertificate=
# Set the property to 1 to join a domain where the domain configuration repository
database is secured.

DB_SSL_ENABLED=false

# The TRUSTSTORE_DB_FILE indicates the path and file name of the truststore file for
# the secure domain configuration repository database. If the domain that you create
# or join uses a secure domain configuration repository, set this property to the
# truststore file of the repository database.

TRUSTSTORE_DB_FILE=

# TRUSTSTORE_DB_PASSWD to the password for the truststore file for the secure domain
# configuration repository database.

TRUSTSTORE_DB_PASSWD=

# The SQLSERVER_SCHEMA_NAME property represents the name of the schema that will
contain domain configuration tables.
# Set the property if DB_TYPE=MSSQLServer.
# If SQLSERVER_SCHEMA_NAME is empty, the installer creates the tables in the
default schema.

```

```
SQLSERVER_SCHEMA_NAME=
```

```
# The TRUSTED_CONNECTION property determines whether to connect to the Microsoft SQL
Server database through a
# trusted connection using the Windows credentials of the current user account.
# When you create a domain by setting CREATE_DOMAIN=1
# Set TRUSTED_CONNECTION=0 if DB_TYPE is set to another database type or if you are
installing Informatica on Linux.
# If the property is empty, the installer uses Microsoft SQL Server
authentication.
# Value 0 Connect to the Microsoft SQL Server database using a Microsoft
SQL Server user account.
# Value 1 Connect to the Microsoft SQL Server database through a trusted
connection using the Windows credentials of the current user account.
# If TRUSTED_CONNECTION flag is set to 1, ensure that DB_CUSTOM_STRING_SELECTION is
also set to 1 and provide connection details in DB_CUSTOM_STRING_SELECTION.
# Set the TRUSTED_CONNECTION flag only if you opted to join the domain by setting
JOIN_DOMAIN=1.
# Leave the TRUSTED_CONNECTION value as blank for all the remaining installation
cases.
```

```
TRUSTED_CONNECTION=
```

```
# The DB_CUSTOM_STRING_SELECTION property determines whether to use a JDBC URL or a
custom connection string to connect to the domain configuration database.
# Set DB_CUSTOM_STRING_SELECTION=1 if DB_SSL_ENABLED=true. Also provide the
default valid connection string in DB_CUSTOM_STRING.
# Value 0 The installer creates a JDBC URL from the database properties
you provide.
# Value 1 The installer uses the custom connection string you provide.
```

```
DB_CUSTOM_STRING_SELECTION=0
```

```
# The DB_SERVICENAME property represents the service name or database name of the
database.
# Set the property if DB_CUSTOM_STRING_SELECTION=0.
# Set the property to the service name for Oracle database.
# Set the property to the database name for Microsoft SQL Server database.
# Leave the property blank if DB_CUSTOM_STRING_SELECTION=1.
```

```
DB_SERVICENAME=DBServiceName
```

```
# The DB_ADDRESS property represents the host name and port number for the database
instance.
# Set the property if DB_CUSTOM_STRING_SELECTION=0.
# Set the property in the format HostName:PortNumber.
# Leave the property blank if DB_CUSTOM_STRING_SELECTION=1.
```

```
DB_ADDRESS=HostName:PortNumber
```

```
# The ADVANCE_JDBC_PARAM property represents additional parameters in the JDBC URL
connection string.
# If DB_CUSTOM_STRING_SELECTION=0, you can set the property to include optional
parameters in the JDBC URL connection string.
# The parameter string must be valid.
# If the parameter is empty, the installer creates the JDBC URL without
additional parameters.
```

```
ADVANCE_JDBC_PARAM=
```

```

# The DB_CUSTOM_STRING property represents a valid custom JDBC connection string.
#     Set the property if DB_CUSTOM_STRING_SELECTION=1.

DB_CUSTOM_STRING=

# The DOMAIN_NAME property represents the name of the domain to create. The default
domain name is Domain_<MachineName>.
#     Set the property if CREATE_DOMAIN=1.
#     The domain name must not exceed 128 characters and must be 7-bit ASCII only.
#     It cannot contain a space or any of the following characters: ` % * + ; " ? , < > \ /

DOMAIN_NAME=DomainName

# The DOMAIN_HOST_NAME property represents the host name of the machine.
#     * If you create a domain, this is the host name of the machine on which to
create the node.
#         If the machine has a single network name, use the default host name.
#         If the machine has multiple network names, you can modify the default host
name to use an alternate network name. Optionally, you can use the IP address.
#     * If you join a domain, this is the host name of the machine that hosts the
gateway node of the domain you want to join.
#     Do not use localhost. The host name must explicitly identify the machine.
#DOMAIN_HOST_NAME and CONTAINER_HOST_NAME should be same.

DOMAIN_HOST_NAME=HostName

# The NODE_NAME property represents the node to create on the machine. The node name
is not the host name for the machine.

NODE_NAME=NodeName

# The DOMAIN_PORT property represents the port number.
#     * If you create a domain, set the property to the port number for the node to
create.
#         The default port number for the node is 6005.
#         If the default port number is not available on the machine, the installer
displays the next available port number.
#     * If you join a domain, set the property to the port number of the gateway
node of the domain you want to join.

DOMAIN_PORT=

# The DOMAIN_USER property represents the user name for the domain administrator.
#     If you create a domain, you can use this user name to initially log in to the
Informatica Administrator.
#     If you join a domain, enter the following user name to log in to the domain
that you want to join.

DOMAIN_USER=AdminUser

# The DOMAIN_PSSWD property represents the password for the domain administrator.
#     The password must be more than 2 characters but cannot exceed 128 characters.

DOMAIN_PSSWD=

# The DOMAIN_CNFRM_PSSWD property confirms the password you set for the domain
administrator.
#     Set the property to the password you set in the DOMAIN_PSSWD property to
confirm the password.

```

```

DOMAIN_CNFRM_PSSWD=

# The JOIN_NODE_NAME property represents the name of the node to create on the
machine. The node name is not the host name for the machine.
#     Set the property if JOIN_DOMAIN=1.

JOIN_NODE_NAME=NodeName

# The JOIN_HOST_NAME property represents the host name of the machine that hosts the
gateway node of the domain you want to join.
#     Set the property if JOIN_DOMAIN=1.
#JOIN_HOST_NAME and CONTAINER_HOST_NAME should be same.

JOIN_HOST_NAME=DomainHostName

# The JOIN_DOMAIN_PORT property represents the port number of the gateway node of
the domain you want to join.
#     Set the property if JOIN_DOMAIN=1.

JOIN_DOMAIN_PORT=

#####
#
##### DO NOT MODIFY THE FOLLOWING PROPERTIES
#####
#
USER_INSTALL_DIR=/home/Informatica/10.2.0
KEY_DEST_LOCATION=/home/Informatica/10.2.0/isp/config/keys
INSTALL_TYPE=0
RUN_IMAGE=1
ENABLE_KERBEROS=0
ADVANCE_PORT_CONFIG=0
SAML_AUTHENTICATION=false
CREATE_SERVICES=0
CREATE_MONITORING_STATS=0
CLOUD_SUPPORT_ENABLE=0

#####
# After you create the properties file, save the file with the name
SilentInput.properties and
#     run the silent installer to perform the Informatica services installation.
#####

```

4. Save the properties file with the name `SilentInput.properties`.

Running the Silent Installer

After you configure the properties file, open a command prompt to start the silent installation.

1. Open a command prompt.
2. Go to the root of the directory that contains the installation files.
3. Verify that the directory contains the file `SilentInput.properties` that you edited and resaved.
4. Run the silent installation. On UNIX, run `silentInstall.sh`.

The silent installer runs in the background. The process can take a while. The silent installation is complete when the `Informatica<Version>_Docker_Utility<timestamp>.log` file is created in the directory where you extracted the Docker utility.

Post-Install Tasks

After you run the Informatica Docker utility, perform the post-installation tasks.

Complete the Domain Configuration

To complete the domain configuration after you install the Informatica services, perform the following tasks:

Verify local settings and code page compatibility.

The code pages for application services must be compatible with code pages in the domain. Verify and configure the locale settings and code pages:

- Verify that the domain configuration database is compatible with the code pages of the application services that you create in the domain.
- Verify that the locale settings on machines that access the Administrator tool and the Informatica client tools is compatible with the code pages of repositories in the domain.

Configure the environment variables.

Informatica uses environment variables to store configuration information when it runs the application services and connects to the clients.

- Configure the environment variables to meet the Informatica requirements.
- To configure environment variables, log in with the system user account you used to install Informatica.

For more information about configuring the domain, see the chapter "Complete the Domain Configuration" in the *Informatica 10.2.0 HotFix 2 Installation and Configuration Guide*.

Create the Application Services

Before you create the application services, perform the following tasks:

Update the hosts file to access the Administrator tool through the browser.

Enter the following information in the hosts file to access the Administrator tool through the browser:

```
<IP address of the machine> <host name of Informatica domain>.
```

On Windows, the hosts file is located at `\Windows\System32\drivers\etc` directory. On UNIX, the hosts file is located at the `/etc/hosts` directory.

Log in to Informatica Administrator.

You must have a user account to log in to the Informatica Administrator web application.

Create the Application Service.

Use the service creation wizard in the Administrator tool to create the application service, such as the PowerCenter Repository Service and the PowerCenter Integration Service.

For more information about creating the application services, see the chapter "Create the Application Services" in the *Informatica 10.2 HotFix 2 Installation and Configuration Guide*.

Install the PowerCenter Client

You can copy the PowerCenter client install binaries from the Akamai link to your installation directory and install the PowerCenter client.

You can install the client to create data objects, create and run mappings, and create virtual databases. To install the client, perform the following tasks:

Before you install the client.

Before you install the Informatica client, verify that the minimum system and third-party software requirements are met. If the machine where you install the Informatica client is not configured correctly, the installation can fail.

- Verify the disk space for temporary files.
- Verify that the user account that you use to install the Informatica clients has write permission on the installation directory and Windows registry.
- Verify the minimum system requirements to run the Informatica client tools.
- Verify that you installed the third-party software required by the client.

Install the client.

Use the Informatica client installer to install PowerCenter. The PowerCenter Client is a set of tools you can use to manage the PowerCenter repository, mappings, and sessions.

After you install the client.

After you install the client, perform the following tasks:

- Install additional languages on Windows to view languages other than the system locale and to work with repositories that use a UTF-8 code page.
- If you configured secure communication for the domain, configure the Informatica truststore environment variables on the machines that host the Informatica client.

For more information about installing the client, see the *Informatica 10.2 HotFix 2 Installation and Configuration Guide*.

Starting and Stopping the Informatica Services on UNIX

On Linux, run `infaservice.sh` to start and stop the Informatica daemon. By default, `infaservice.sh` is installed in the following directory:

```
<Informatica installation directory>/tomcat/bin
```

1. Go to the directory where `infaservice.sh` is located.
2. At the command prompt, enter the following command to start the daemon:

```
infaservice.sh startup
```

Enter the following command to stop the daemon:

```
infaservice.sh shutdown
```

Note: If you use a softlink to specify the location of `infaservice.sh`, set the `INFA_HOME` environment variable to the location of the Informatica installation directory.

INDEX

D

domain configuration repository
Microsoft SQL Server database requirements [9](#)

M

Microsoft SQL Server database requirements
domain configuration repository [9](#)