



Informatica® PowerExchange for Microsoft
Azure SQL Data Warehouse
10.1.1 Update 2

User Guide

© Copyright Informatica LLC 2016, 2018

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

Informatica, the Informatica logo, and PowerExchange are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jqWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright © MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at <http://www.apache.org/licenses/>. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (<http://www.mozilla.org/>), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at <http://www.gnu.org/licenses/lgpl.html>. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at <http://www.openssl.org> and <http://www.openssl.org/source/license.html>.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://curl.haxx.se/docs/copyright.html>. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.dom4j.org/license.html>.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://dojotoolkit.org/license>.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://source.icu-project.org/repos/icu/icu/trunk/license.html>.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at <http://www.gnu.org/software/kawa/Software-License.html>.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at <http://www.opensource.org/licenses/mit-license.php>.

This product includes software developed by Boost (<http://www.boost.org/>) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http://www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at <http://www.pcre.org/license.txt>.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.eclipse.org/org/documents/epl-v10.php> and at <http://www.eclipse.org/org/documents/edl-v10.php>.

This product includes software licensed under the terms at <http://www.tcl.tk/software/tcltk/license.html>, <http://www.bosrup.com/web/overlib/?License>, <http://www.stlport.org/doc/license.html>, <http://asm.ow2.org/license.html>, <http://www.cryptix.org/LICENSE.TXT>, <http://hsqldb.org/web/hsqLicense.html>, <http://httpunit.sourceforge.net/doc/license.html>, <http://jung.sourceforge.net/license.txt>, http://www.gzip.org/zlib/zlib_license.html, <http://www.openldap.org/software/release/license.html>, <http://www.libssh2.org>, <http://slf4j.org/license.html>, <http://www.sente.ch/software/OpenSourceLicense.html>, <http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3-license-agreement>, <http://antlr.org/license.html>, <http://aopalliance.sourceforge.net/>, <http://www.bouncycastle.org/license.html>, <http://www.jgraph.com/jgraphdownload.html>, <http://www.jcraft.com/jsch/LICENSE.txt>, http://jotm.objectweb.org/bsd_license.html, <http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231>, <http://www.slf4j.org/license.html>, <http://nanoxml.sourceforge.net/orig/copyright.html>, <http://www.json.org/license.html>, <http://forge.ow2.org/projects/javaservice/>, <http://www.postgresql.org/about/licence.html>, <http://www.sqlite.org/copyright.html>, <http://www.tcl.tk/software/tcltk/license.html>, <http://www.jaxen.org/faq.html>, <http://www.jdom.org/docs/faq.html>, <http://www.slf4j.org/license.html>, <http://www.iodbc.org/dataspace/iodbc/wiki/IODBC/License>, <http://www.keplerproject.org/md5/license.html>, <http://www.toedter.com/en/jcalendar/license.html>, <http://www.edankert.com/bounce/index.html>, <http://www.net-snmp.org/about/license.html>, <http://www.openmdx.org/#FAQ>, http://www.php.net/license/3_01.txt, <http://srp.stanford.edu/license.txt>;

<http://www.schneider.com/blowfish.html>; <http://www.jmock.org/license.html>; <http://xsom.java.net>; <http://benalman.com/about/license/>; <https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js>; <http://www.h2database.com/html/license.html#summary>; <http://jsoncpp.sourceforge.net/LICENSE>; <http://jdbc.postgresql.org/license.html>; <http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto>; <https://github.com/rantav/hector/blob/master/LICENSE>; <http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html>; <http://jibx.sourceforge.net/jibx-license.html>; <https://github.com/lyokato/libgeohash/blob/master/LICENSE>; <https://github.com/hjiang/jsonxx/blob/master/LICENSE>; <https://code.google.com/p/lz4/>; <https://github.com/jedisct1/libsodium/blob/master/LICENSE>; <http://one-jar.sourceforge.net/index.php?page=documents&file=license>; <https://github.com/EsotericSoftware/kryo/blob/master/license.txt>; <http://www.scala-lang.org/license.html>; <https://github.com/tinkerpops/blueprints/blob/master/LICENSE.txt>; <http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html>; <https://aws.amazon.com/asl/>; <https://github.com/twbs/bootstrap/blob/master/LICENSE>; <https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt>; <https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE>, and <https://github.com/apache/hbase/blob/master/LICENSE.txt>.

This product includes software licensed under the Academic Free License (<http://www.opensource.org/licenses/afl-3.0.php>), the Common Development and Distribution License (<http://www.opensource.org/licenses/cddl1.php>), the Common Public License (<http://www.opensource.org/licenses/cpl1.0.php>), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (<http://www.opensource.org/licenses/bsd-license.php>), the new BSD License (<http://opensource.org/licenses/BSD-3-Clause>), the MIT License (<http://www.opensource.org/licenses/mit-license.php>), the Artistic License (<http://www.opensource.org/licenses/artistic-license-1.0>) and the Initial Developer's Public License Version 1.0 (<http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/>).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://xstream.codehaus.org/license.html>. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit <http://www.extreme.indiana.edu/>.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at <https://www.informatica.com/legal/patents.html>.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, please report them to us in writing at Informatica LLC 2100 Seaport Blvd. Redwood City, CA 94063.

INFORMATICA LLC PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2018-09-27

Table of Contents

Preface	6
Informatica Resources.	6
Informatica Network.	6
Informatica Knowledge Base.	6
Informatica Documentation.	6
Informatica Product Availability Matrixes.	7
Informatica Velocity.	7
Informatica Marketplace.	7
Informatica Global Customer Support.	7
 Chapter 1: Introduction to PowerExchange for Microsoft Azure SQL Data Warehouse.....	 8
PowerExchange for Microsoft Azure SQL Data Warehouse Overview.	8
Microsoft Azure SQL Data Warehouse.	9
 Chapter 2: Microsoft Azure SQL Data Warehouse Connections.....	 10
Microsoft Azure SQL Data Warehouse Connections Overview.	10
Microsoft Azure SQL Data Warehouse Connection Properties.	11
Creating a Microsoft Azure SQL Data Warehouse Connection.	12
 Chapter 3: PowerExchange for Microsoft Azure SQL Data Warehouse Data Objects.....	 13
Microsoft Azure SQL Data Warehouse Data Object Overview.	13
Microsoft Azure SQL Data Warehouse Data Object Properties.	14
Microsoft Azure SQL Data Warehouse Data Object Read Operation.	14
Microsoft Azure SQL Data Warehouse Data Object Read Operation Properties.	14
Source Properties of the Data Object Read Operation.	15
General Properties - Source.	15
Ports Properties - Source.	15
Advanced Properties - Source.	16
Microsoft Azure SQL Data Warehouse Data Object Write Operation Properties.	16
Input Properties of the Data Object Write Operation.	16
Ports Properties - Input Write.	17
Run-time Properties.	17
Advanced Properties - Target.	18
Importing a Microsoft Azure SQL Data Warehouse Data Object.	18
Creating a Microsoft Azure SQL Data Warehouse Data Object Read or Write Operation.	19
 Chapter 4: Microsoft Azure SQL Data Warehouse Mappings.....	 20
Microsoft Azure SQL Data Warehouse Mapping Overview.	20

Mapping Validation and Run-time Environments.	20
Microsoft Azure SQL Data Warehouse Mapping Example.	21
Appendix A: Microsoft Azure SQL Data Warehouse Datatype Reference.	22
Datatype Reference Overview.	22
Microsoft Azure SQL Data Warehouse and Transformation Datatypes.	23
Index.	25

Preface

The *Informatica PowerExchange® for Microsoft Azure SQL Data Warehouse User Guide* provides information about reading data from and writing data to Microsoft Azure SQL Data Warehouse. It is written for administrators and developers who create mappings to read from or write data to a Microsoft Azure SQL Data Warehouse resource.

This guide assumes that you have knowledge of Microsoft Azure SQL Data Warehouse and Informatica.

Informatica Resources

Informatica Network

Informatica Network hosts Informatica Global Customer Support, the Informatica Knowledge Base, and other product resources. To access Informatica Network, visit <https://network.informatica.com>.

As a member, you can:

- Access all of your Informatica resources in one place.
- Search the Knowledge Base for product resources, including documentation, FAQs, and best practices.
- View product availability information.
- Review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to search Informatica Network for product resources such as documentation, how-to articles, best practices, and PAMs.

To access the Knowledge Base, visit <https://kb.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

To get the latest documentation for your product, browse the Informatica Knowledge Base at https://kb.informatica.com/_layouts/ProductDocumentation/Page/ProductDocumentSearch.aspx.

If you have questions, comments, or ideas about this documentation, contact the Informatica Documentation team through email at infa_documentation@informatica.com.

Informatica Product Availability Matrixes

Product Availability Matrixes (PAMs) indicate the versions of operating systems, databases, and other types of data sources and targets that a product release supports. If you are an Informatica Network member, you can access PAMs at

<https://network.informatica.com/community/informatica-network/product-availability-matrices>.

Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services. Developed from the real-world experience of hundreds of data management projects, Informatica Velocity represents the collective knowledge of our consultants who have worked with organizations from around the world to plan, develop, deploy, and maintain successful data management solutions.

If you are an Informatica Network member, you can access Informatica Velocity resources at <http://velocity.informatica.com>.

If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at ips@informatica.com.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that augment, extend, or enhance your Informatica implementations. By leveraging any of the hundreds of solutions from Informatica developers and partners, you can improve your productivity and speed up time to implementation on your projects. You can access Informatica Marketplace at <https://marketplace.informatica.com>.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through Online Support on Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:

<http://www.informatica.com/us/services-and-training/support-services/global-support-centers>.

If you are an Informatica Network member, you can use Online Support at <http://network.informatica.com>.

CHAPTER 1

Introduction to PowerExchange for Microsoft Azure SQL Data Warehouse

This chapter includes the following topics:

- [PowerExchange for Microsoft Azure SQL Data Warehouse Overview, 8](#)
- [Microsoft Azure SQL Data Warehouse, 9](#)

PowerExchange for Microsoft Azure SQL Data Warehouse Overview

Use PowerExchange for Microsoft Azure SQL Data Warehouse to read data from and write data to Microsoft Azure SQL Data Warehouse. You can also use PowerExchange for Microsoft Azure SQL Data Warehouse to collate and organize the details from multiple input sources and write the data to Microsoft Azure SQL Data Warehouse.

You can use Microsoft Azure SQL Data Warehouse objects as sources and targets in mappings. When you use Microsoft Azure SQL Data Warehouse objects in mappings, you must configure properties specific to Microsoft Azure SQL Data Warehouse. You can validate and run mappings in native or Hadoop environments.

PowerExchange for Microsoft Azure SQL Data Warehouse is optimized for large data sets and can perform better than traditional data integration methods, such as ODBC or JDBC. When you read data from or write data to a Microsoft Azure SQL Data Warehouse, PowerExchange for Microsoft Azure SQL Data Warehouse stages data files to Microsoft Azure Storage and uses T-SQL commands with Microsoft Polybase to load relational and non-relational data in parallel. PowerExchange for Microsoft Azure SQL Data Warehouse supports Azure tables. PowerExchange for Microsoft Azure SQL Data Warehouse does not support Azure views and synonyms.

Example

You work in sales operations and you frequently need to analyze a high volume of data to improve operational intelligence. You design a mapping to read data from Salesforce and other transactional systems and aggregate the data. You create a summary table in Microsoft Azure SQL Data Warehouse that you can query against to assess your sales organization's performance.

You use PowerExchange for Microsoft Azure SQL Data Warehouse to write aggregated data to Microsoft Azure SQL Data Warehouse.

Microsoft Azure SQL Data Warehouse

Azure SQL Data Warehouse is a cloud-based, scalable database that can process massive volumes of relational and non-relational data. Microsoft Azure SQL Data Warehouse is built on a massively parallel processing (MPP) architecture to handle the enterprise workload.

CHAPTER 2

Microsoft Azure SQL Data Warehouse Connections

This chapter includes the following topics:

- [Microsoft Azure SQL Data Warehouse Connections Overview, 10](#)
- [Microsoft Azure SQL Data Warehouse Connection Properties, 11](#)
- [Creating a Microsoft Azure SQL Data Warehouse Connection, 12](#)

Microsoft Azure SQL Data Warehouse Connections Overview

Microsoft Azure SQL Data Warehouse connection enables you to read data from or write data to Microsoft Azure SQL Data Warehouse.

You can use Microsoft Azure SQL Data Warehouse connections to create data objects and run mappings. The Developer tool uses the connection when you create a data object. The Data Integration Service uses the connection when you run mappings.

You can create a Microsoft Azure SQL Data Warehouse connection from the Developer tool or the Administrator tool. The Developer tool stores connections in the domain configuration repository. Create and manage connections in the Preferences dialog box or the Connection Explorer view.

Microsoft Azure SQL Data Warehouse Connection Properties

When you set up a Microsoft Azure SQL Data Warehouse connection, you must configure the connection properties.

The following table describes the Microsoft Azure SQL Data Warehouse connection properties:

Property	Description
Name	The name of the connection. The name is not case sensitive and must be unique within the domain. You can change this property after you create the connection. The name cannot exceed 128 characters, contain spaces, or contain the following special characters: ~ ` ! \$ % ^ & * () - + = { [] \ : ; " ' < , > . ? /
ID	String that the Data Integration Service uses to identify the connection. The ID is not case sensitive. It must be 255 characters or less and must be unique in the domain. You cannot change this property after you create the connection. Default value is the connection name.
Description	The description of the connection. The description cannot exceed 4,000 characters.
Location	The domain where you want to create the connection.
Type	The connection type. Select Microsoft Azure SQL Data Warehouse.

The following table describes the properties for metadata access:

Property	Description
Azure DW JDBC URL	Microsoft Azure Data Warehouse JDBC connection string. For example, you can enter the following connection string: jdbc:sqlserver:// <Server>.database.windows.net:1433;database=<Database>. The Administrator can download the URL from Microsoft Azure portal.
Azure DW JDBC Username	User name to connect to the Microsoft Azure SQL Data Warehouse account. You must have permission to read, write, and truncate data in Microsoft Azure SQL Data Warehouse.
Azure DW JDBC Password	Password to connect to the Microsoft Azure SQL Data Warehouse account.
Azure DW Schema Name	Name of the schema in Microsoft Azure SQL Data Warehouse.
Azure Blob Account Name	Name of the Microsoft Azure Storage account to stage the files.
Azure Blob Account Key	The key that authenticates the access to the Blob storage account.

Creating a Microsoft Azure SQL Data Warehouse Connection

Create a Microsoft Azure SQL Data Warehouse connection before you create a Microsoft Azure SQL Data Warehouse data object.

1. In the Developer tool, click **Window > Preferences**.
2. Select **Informatica > Connections**.
3. Expand the domain in the **Available Connections**.
4. Select the connection type **Database > AzureDW**, and click **Add**.
5. Enter a connection name and an optional description.
6. Select Microsoft Azure SQL Data Warehouse as the connection type.
7. Click **Next**.
8. Configure the connection properties.
9. Click **Test Connection** to verify the connection to Microsoft Azure SQL Data Warehouse.
10. Click **Finish**.

CHAPTER 3

PowerExchange for Microsoft Azure SQL Data Warehouse Data Objects

This chapter includes the following topics:

- [Microsoft Azure SQL Data Warehouse Data Object Overview, 13](#)
- [Microsoft Azure SQL Data Warehouse Data Object Properties, 14](#)
- [Microsoft Azure SQL Data Warehouse Data Object Read Operation, 14](#)
- [Microsoft Azure SQL Data Warehouse Data Object Write Operation Properties, 16](#)
- [Importing a Microsoft Azure SQL Data Warehouse Data Object, 18](#)
- [Creating a Microsoft Azure SQL Data Warehouse Data Object Read or Write Operation, 19](#)

Microsoft Azure SQL Data Warehouse Data Object Overview

A Microsoft Azure SQL Data Warehouse data object is a physical data object that represents Microsoft Azure SQL Data Warehouse table as a source or target. A Microsoft Azure SQL Data Warehouse data object is the representation of data that is based on a Microsoft Azure SQL Data Warehouse object. You can configure the data object read and write operation properties that determine how data can be read from Microsoft Azure SQL Data Warehouse or loaded to Microsoft Azure SQL Data Warehouse.

To read data from the Microsoft Azure SQL Data Warehouse, create a data object read operation based on the Microsoft Azure SQL Data Warehouse data object. Configure the read operation properties to determine how the Data Integration Service must read data from the Microsoft Azure SQL Data Warehouse table. Add the read operation as a source in a mapping.

To write data to the Microsoft Azure SQL Data Warehouse, create a data object write operation based on the Microsoft Azure SQL Data Warehouse data object. Configure the write operation properties to determine how the Data Integration Service must write data to the Microsoft Azure SQL Data Warehouse. Add the write operation as a Write transformation in a mapping.

Microsoft Azure SQL Data Warehouse Data Object Properties

The Microsoft Azure SQL Data Warehouse Overview view displays general information about the Microsoft Azure SQL Data Warehouse data object and the object properties that apply to the Microsoft Azure SQL Data Warehouse table you import.

General Properties

You can configure the following properties for a Microsoft Azure SQL Data Warehouse data object:

- Name. Name of the Microsoft Azure SQL Data Warehouse data object.
- Description. Description of the Microsoft Azure SQL Data Warehouse data object.
- Connection. Name of the Microsoft Azure SQL Data Warehouse connection.

Microsoft Azure SQL Data Warehouse Data Object Read Operation

The Data Integration Service reads data from a Microsoft Azure SQL Data Warehouse table based on the data object read operation properties that you specify.

When you create a data object read operation, the Developer tool creates a Source transformation and an Output transformation.

The Source transformation represents the data that the Data Integration Service reads from the Microsoft Azure SQL Data Warehouse table.

The Output transformation represents the data that the Data Integration Service passes into the mapping pipeline. Select the Output transformation to edit the ports, sources, query, run-time, and advanced properties.

You can specify the location of the staging directory, and securely write the results to Microsoft Azure SQL Data Warehouse.

Microsoft Azure SQL Data Warehouse Data Object Read Operation Properties

The Data Integration Service reads data from a Microsoft Azure SQL Data Warehouse object based on the data object read operation. The Developer tool displays the data object read operation properties of the Microsoft Azure SQL Data Warehouse data object in the Data Object Operation view.

You can view or configure the data object read operation from the source and output properties.

Source properties

Represents data that the Data Integration Service reads from the Microsoft Azure SQL Data Warehouse object. Select the source properties to view data, such as the name and description of the Microsoft Azure SQL Data Warehouse object, the ports, and advanced properties.

Output properties

Represents data that the Data Integration Service passes into the mapping pipeline. Select the output properties to edit the port properties of the data object read operation. You can also set advanced properties, such as Azure Blob Container Name, Field Delimiter, and Number of Concurrent Connections to Blob Store.

Source Properties of the Data Object Read Operation

When you create a data object, the source properties populate based on the Microsoft Azure SQL Data Warehouse object that you add. The source properties of the data object read operation include general, column, and advanced properties that apply to the Microsoft Azure SQL Data Warehouse object.

You can view the source properties of the data object read operation from the **General**, **Column**, and **Advanced** tabs.

General Properties - Source

The following table describes the source general properties of the data object read operation:

Property	Description
Name	Name of the Microsoft Azure SQL Data Warehouse source object.
Description	Description of the data object read operation.

Ports Properties - Source

The column properties display the data types, precision, and scale of the source property in the data object read operation.

The following table describes the source column properties of the data object read operation:

Property	Description
Name	Name of the column.
Type	Native data type of the column.
Precision	Maximum number of significant digits for numeric data types, or maximum number of characters for string data types. For numeric data types, precision includes scale.
Scale	Maximum number of digits after the decimal point for numeric values.
Description	Description of the column.

Advanced Properties - Source

The advanced properties display the physical name of the Microsoft Azure SQL Data Warehouse object.

The following table describes the source column properties of the data object read operation:

Property	Description
Azure Blob Container Name	Microsoft Azure Storage container name. You must mention the Microsoft Azure Storage Container name to successfully run the mapping. When you mention the container name that does not exist, the data preview fails but the Data Integration Service creates a container with the specified name and successfully runs the mapping.
Field Delimiter	Character used to separate fields in the file. Default is a comma (.). The mapping fails when you parameterize a multiple delimiter. You can use single delimiter when you parameterize a delimiter. Ensure that the source or target data does not contain the delimiter character, new line character, or double quotes.
Number of Concurrent Connections to Blob Store	Number of concurrent connections to extract data from the Microsoft Azure Blob Storage. Default is 4.

Microsoft Azure SQL Data Warehouse Data Object Write Operation Properties

The Data Integration Service writes data to a Microsoft Azure SQL Data Warehouse object based on the data object write operation. The Developer tool displays the data object write operation properties for the Microsoft Azure SQL Data Warehouse data object in the Data Object Operation section.

You can view the data object write operation from the Input and Target properties.

Input properties

Represent data that the Data Integration Service reads from a Microsoft Azure SQL Data Warehouse directory server. Select the input properties to edit the port properties and specify the advanced properties of the data object write operation.

Target properties

Represent data that the Data Integration Service writes to Microsoft Azure SQL Data Warehouse. Select the target properties to view data, such as the name and description of the Microsoft Azure SQL Data Warehouse object.

Input Properties of the Data Object Write Operation

Input properties represent data that the Data Integration Service writes to a Microsoft Azure SQL Data Warehouse directory server. Select the input properties to edit the port properties of the data object write operation. You can also specify advanced data object write operation properties to write data to Microsoft Azure SQL Data Warehouse objects.

The input properties of the data object write operation include general properties that apply to the data object write operation. Input properties also include port, source, and advanced properties that apply to the data object write operation.

You can view and change the input properties of the data object write operation from the **General**, **Ports**, **Targets**, **run-time**, and **Advanced** tabs.

Ports Properties - Input Write

The input ports properties list the data types, precision, and scale of the data object write operation.

The following table describes the input ports properties that you must configure in the data object write operation:

Property	Description
Name	Name of the port.
Type	Data type of the port.
Precision	Maximum number of significant digits for numeric data types, or maximum number of characters for string data types. For numeric data types, precision includes scale.
Scale	Maximum number of digits after the decimal point for numeric values.
Description	Description of the port.

Run-time Properties

The run-time properties displays the name of the connection used for write transformation.

The following table describes the run-time properties that you configure for a Microsoft Azure SQL Data Warehouse write operation:

Property	Description
Connection	Name of the Microsoft Azure SQL Data Warehouse connection.

Note: You must mention the default partition type as **Partition is not supported**.

Advanced Properties - Target

The advanced properties allow you to specify data object write operation properties to write data to a Microsoft Azure SQL Data Warehouse server

The following table describes the advanced properties that you configure for a Microsoft Azure SQL Data Warehouse write operation:

Property	Description
Azure Blob Container Name	Microsoft Azure Storage container name. You must mention the Microsoft Azure Storage Container name to successfully run the mapping. When you mention a container name that does not exist, Data Integration Service creates a container with the specified name and successfully runs the mapping.
Field Delimiter	Character used to separate fields in the file. Default is a comma (.). The mapping fails when you parameterize a multiple delimiter. You can use single delimiter when you parameterize a delimiter. Ensure that the source or target data does not contain the delimiter character, new line character, or double quotes.
Number of Concurrent Connections to Blob Storage	Number of threads to use to move data to the staging area in Microsoft Azure Blob Storage. Default is 4.
Truncate Table	Specify the truncate table property when you use insert operations. Truncates the target before inserting data to the target.

Importing a Microsoft Azure SQL Data Warehouse Data Object

Import a Microsoft Azure SQL Data Warehouse data object to add to a mapping.

1. Select a project or folder in the **Object Explorer** view.
2. Click **File > New > Data Object**.
3. Select **AzureDW Data Object** and click **Next**.
The **AzureDW Data Object** dialog box appears.
4. Enter a name for the data object.
5. Click **Browse** next to the **Location** option and select the target project or folder.
6. Click **Browse** next to the **Connection** option and select the Microsoft Azure SQL Data Warehouse connection from which you want to import the Microsoft Azure SQL Data Warehouse resource metadata.
7. To add a resource, click **Add** next to the **Selected Resources** option.
The **Add Resource** dialog box appears.
8. From the Package Explorer, select a naming context from which you want to import the schema.
9. You can Perform one of the following tasks to import an Microsoft Azure SQL Data Warehouse table, and then click **OK**:
 - Navigate to the Microsoft Azure SQL Data Warehouse table that you want to import.

- Search for the Microsoft Azure SQL Data Warehouse table, enter the name of the Microsoft Azure SQL Data Warehouse table entity that you want to add and click **OK**.
10. Click **Finish**.
The data object appears under Data Objects in the project or folder in the **Object Explorer** view.

Creating a Microsoft Azure SQL Data Warehouse Data Object Read or Write Operation

You can add a Microsoft Azure SQL Data Warehouse data object read or write operation to a mapping or mapplet as a source. You can create the data object read or write operation for one or more Microsoft Azure SQL Data Warehouse data objects.

Before you create a Microsoft Azure SQL Data Warehouse data object read or write operation, you must create at least one Microsoft Azure SQL Data Warehouse data object.

1. Select the data object in the Object Explorer view.
2. Right-click and select **New > Data Object Operation**.
The **Data Object Operation** dialog box appears.
3. Enter a name for the data object read or write operation.
4. Select **Read** or **Write** as the type of data object operation.
5. Click **Add**.
The **Select Resources** dialog box appears.
6. Select the Microsoft Azure SQL Data Warehouse object for which you want to create the data object read or write operation and click **OK**.
7. Click **Finish**.

The Developer tool creates the data object read or write operation for the selected data object.

CHAPTER 4

Microsoft Azure SQL Data Warehouse Mappings

This chapter includes the following topics:

- [Microsoft Azure SQL Data Warehouse Mapping Overview, 20](#)
- [Mapping Validation and Run-time Environments, 20](#)
- [Microsoft Azure SQL Data Warehouse Mapping Example, 21](#)

Microsoft Azure SQL Data Warehouse Mapping Overview

After you create the Microsoft Azure SQL Data Warehouse data object with a Microsoft Azure SQL Data Warehouse connection, you can develop a mapping. You can define the following types of objects in the mapping:

- A Read transformation of the Microsoft Azure SQL Data Warehouse data object to read data from Microsoft Azure SQL Data Warehouse in native or Hadoop run-time environment.
- A Write transformation of the Microsoft Azure SQL Data Warehouse data object to write data to Microsoft Azure SQL Data Warehouse in native or Hadoop run-time environment..

Validate and run the mapping. You can deploy the mapping and run it or add the mapping to a Mapping task in a workflow.

Mapping Validation and Run-time Environments

You can validate and run mappings in the native environment or a Hadoop environment.

You can validate a mapping in the native environment, Hadoop environment, or both. The Data Integration Service validates whether the mapping can run in the selected environment. You must validate the mapping for an environment before you run the mapping in that environment.

When you run a mapping in the native environment, the Data Integration Service runs the mapping.

When you run a mapping in a Hadoop environment, the Data Integration Service converts the task into HiveQL queries to enable the Hadoop cluster to process the data. The Hadoop environment supports Hive mode.

Note: PowerExchange for Microsoft Azure SQL Data Warehouse supports HortonWorks, HDInsight and MapR Hadoop distributions.

Microsoft Azure SQL Data Warehouse Mapping Example

Sales department of your organization has a large amount of customer details for all regions in flat files. The sales analyst needs to analyze the customer data in a given region in a short span of time. Create a mapping that reads all the customer records and write the records to Microsoft Azure SQL Data Warehouse table.

You can use the following objects in a Microsoft Azure SQL Data Warehouse mapping:

Flat file input

The input file is a flat file that contains the customer names and other details about customers.

Create a flat file data object. Configure the flat file connection and specify the flat file that contains the customer data as a resource for the data object. Drag the data object into a mapping as a read data object.

Transformations


Add Filter transformation to get customer data in a particular region.

The Filter transformation filters the source data based on the value you specify for the region ID column. The Data Integration Service returns the rows that meet the filter condition.

Microsoft Azure SQL Data Warehouse output

Create a Microsoft Azure SQL Data Warehouse data object write operation. Configure the Microsoft Azure SQL Data Warehouse connection and specify the Microsoft Azure SQL Data Warehouse object as a target for the data object. Drag the data object into a mapping as a target data object.

The following image shows the Microsoft Azure SQL Data Warehouse mapping example:



When you run the mapping, the customer records are read from the flat file and written to the Microsoft Azure SQL Data Warehouse table.

APPENDIX A

Microsoft Azure SQL Data Warehouse Datatype Reference

This appendix includes the following topics:

- [Datatype Reference Overview, 22](#)
- [Microsoft Azure SQL Data Warehouse and Transformation Datatypes, 23](#)

Datatype Reference Overview

Informatica Developer uses the following data types in Microsoft Azure SQL Data Warehouse mappings:

- Microsoft Azure SQL Data Warehouse native data types. Microsoft Azure SQL Data Warehouse data types appear in the physical data object column properties.
- Transformation data types. Set of data types that appear in the transformations. They are internal data types based on ANSI SQL-92 generic data types, which the Data Integration Service uses to move data across platforms. Transformation data types appear in all transformations in a mapping.

When PowerExchange for Microsoft Azure SQL Data Warehouse reads source data, it converts the native data types to the comparable transformation data types before transforming the data. When PowerExchange for Microsoft Azure SQL Data Warehouse writes to a target, it converts the transformation data types to the comparable native data types.

Microsoft Azure SQL Data Warehouse and Transformation Datatypes

The following table lists the Microsoft Azure SQL Data Warehouse data types that the Data Integration Service supports and the corresponding transformation data types:

Microsoft Azure SQL Data Warehouse Native Data Type	Transformation Data Type	Range
bigint	bigint	-9,223,372,036,854,770,000 to 9,223,372,036,854,770,000
binary	binary	1 to 8000 bytes
bit	integer	0,1,NULL
char	string	1 to 8000 characters
date	date/time	January 1, 1753 00:00:00 to 12/31/9999
datetime	date/time	January 1, 1753 00:00:00 to December 31, 9999 23:59:59.997
datetime2	date/time	January 1, 1753 00:00:00 to a 9999-12-31 23:59:59.999
decimal	decimal	Precision 28, scale 0 to 5 Note: Data corruption is possible when the table has a defined decimal column with precision more than 28, but the table contains data less than 28.
float	decimal	Precision 28, scale 0 to 5
int	integer	-2,147,483,648 to 2,147,483,647
money	decimal	-922,337,203,685,477.0000 to 922,337,203,685,477.0000
nchar	string	1 to 4000 characters
nvarchar	string	1 to 4,000 characters
real	decimal	Precision 28, scale 0 to 5
smalldatetime	date/time	1/1/1900 0:00 to 6/6/2079 23:59
smallint	integer	-32,768 to 32,767
smallmoney	decimal	-214,748.3648 to 214,748.3647
time	string	00:00:00.0000000 to 23:59:59.9999999
tinyint	integer	0 to 255

Microsoft Azure SQL Data Warehouse Native Data Type	Transformation Data Type	Range
varbinary	binary	1 to 8000 bytes
varchar	string	1 to 8000 characters

Note: Binary, Varbinary, Date and Smalldatetime data types are not supported in Hadoop environment.

INDEX

A

advanced properties
 Azure Blob Container Name [16](#)
 Field Delimiter [16](#)

C

create
 Microsoft Azure SQL Data Warehouse connection [12](#)
creating
 Microsoft Azure SQL Data Warehouse data object read operation [19](#)

D

data object read operation
 creating [19](#)

G

General properties [15](#)

I

importing
 Microsoft Azure SQL Data Warehouse data object [18](#)
input properties [16](#)

M

mapping example
 Microsoft Azure SQL Data Warehouse [21](#)
Microsoft Azure SQL Data Warehouse
 create [12](#)
 importing a data object [18](#)
 massively parallel processing [9](#)
Microsoft Azure SQL Data Warehouse connection
 overview [10](#)

Microsoft Azure SQL Data Warehouse connection (*continued*)
 properties [11](#)
Microsoft Azure SQL Data Warehouse data object
 overview [13](#)
Microsoft Azure SQL Data Warehouse data object read operation
 creating [19](#)
Microsoft Azure SQL Data Warehouse data types
 comparing with transformation data types [23](#)
 overview [22](#)
Microsoft Azure SQL Data Warehouse mappings
 overview [20](#)
Microsoft Azure SQL Data Warehouse run-time environment
 description [20](#)
Microsoft Azure SQL Data Warehouse validation environment
 description [20](#)
Microsoft Azure SQL Data Warehouse write operation
 properties [16](#)

O

Output properties [14](#)
overview
 Microsoft Azure SQL Data Warehouse connection [10](#)

P

Ports properties [15](#)
PowerExchange for Microsoft Azure SQL Data Warehouse
 data integration methods [8](#)
 mappings in native or Hadoop environments [8](#)
 overview [8](#)

S

source properties [15](#)