



Informatica® PowerExchange for Salesforce
Analytics

10.1.1 Update1

User Guide for PowerCenter

© Copyright Informatica LLC 2006, 2018

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

Informatica, the Informatica logo, PowerCenter, and PowerExchange are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at <http://www.apache.org/licenses/>. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (<http://www.mozilla.org/>), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at <http://www.gnu.org/licenses/lgpl.html>. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at <http://www.openssl.org> and <http://www.openssl.org/source/license.html>.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://curl.haxx.se/docs/copyright.html>. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.dom4j.org/license.html>.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://dojotoolkit.org/license>.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://source.icu-project.org/repos/icu/icu/trunk/license.html>.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at <http://www.gnu.org/software/kawa/Software-License.html>.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at <http://www.opensource.org/licenses/mit-license.php>.

This product includes software developed by Boost (<http://www.boost.org/>) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http://www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at <http://www.pcre.org/license.txt>.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.eclipse.org/org/documents/epl-v10.php> and at <http://www.eclipse.org/org/documents/edl-v10.php>.

This product includes software licensed under the terms at <http://www.tcl.tk/software/tcltk/license.html>, <http://www.bosrup.com/web/overlib/?License>, <http://www.stlport.org/doc/license.html>, <http://asm.ow2.org/license.html>, <http://www.cryptix.org/LICENSE.TXT>, <http://hsqldb.org/web/hsqldbLicense.html>, <http://httpunit.sourceforge.net/doc/license.html>, <http://jung.sourceforge.net/license.txt>, http://www.gzip.org/zlib/zlib_license.html, <http://www.openldap.org/software/release/license.html>, <http://www.libssh2.org>, <http://slf4j.org/license.html>, <http://www.sente.ch/software/OpenSourceLicense.html>, <http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3-license-agreement>, <http://antlr.org/license.html>, <http://aopalliance.sourceforge.net/>, <http://www.bouncycastle.org/license.html>, <http://www.jgraph.com/jgraphdownload.html>, <http://www.jcraft.com/jsch/LICENSE.txt>, http://jotm.objectweb.org/bsd_license.html, <http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231>, <http://www.slf4j.org/license.html>, <http://nanoxml.sourceforge.net/orig/copyright.html>, <http://www.json.org/license.html>, <http://forge.ow2.org/projects/jasaservice/>, <http://www.postgresql.org/about/licence.html>, <http://www.sqlite.org/copyright.html>, <http://www.tcl.tk/software/tcltk/license.html>, <http://www.jaxen.org/faq.html>, <http://www.jdom.org/docs/faq.html>, <http://www.slf4j.org/license.html>, <http://www.iodbc.org/dataspace/iodbc/wiki/IODBC/License>, <http://www.keplerproject.org/md5/license.html>, <http://www.toedter.com/en/jcalendar/license.html>, <http://www.edankert.com/bounce/index.html>, <http://www.net-snmp.org/about/license.html>, <http://www.openmdx.org/#FAQ>, http://www.php.net/license/3_01.txt, <http://srp.stanford.edu/license.txt>, <http://www.schneider.com/blowfish.html>, <http://www.jmock.org/license.html>, <http://xsom.java.net>, <http://benalman.com/about/license/>, <https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js>, <http://www.h2database.com/html/license.html#summary>, <http://jsoncpp.sourceforge.net/LICENSE>, <http://jdbc.postgresql.org/license.html>, <http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto>, <https://github.com/rantav/hector/blob/master/LICENSE>, <http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html>, <http://jibx.sourceforge.net/jibx-license.html>, <https://github.com/lyokato/libgeohash/blob/master/LICENSE>, <https://github.com/hjiang/jsonxx/blob/master/LICENSE>, <https://code.google.com/p/lz4/>, <https://github.com/jedisct1/libsodium/blob/master/LICENSE>, <http://one-jar.sourceforge.net/index.php?page=documents&file=license>, <https://github.com/EsotericSoftware/kryo/blob/master/license.txt>, <http://www.scala-lang.org/license.html>, <https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt>, and <http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html>.

This product includes software licensed under the Academic Free License (<http://www.opensource.org/licenses/afl-3.0.php>), the Common Development and Distribution License (<http://www.opensource.org/licenses/cddl1.php>) the Common Public License (<http://www.opensource.org/licenses/cpl1.0.php>), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (<http://www.opensource.org/licenses/bsd-license.php>), the new BSD License (<http://opensource.org/licenses/BSD-3-Clause>), the MIT License (<http://www.opensource.org/licenses/mit-license.php>), the Artistic License (<http://www.opensource.org/licenses/artistic-license-1.0>) and the Initial Developer's Public License Version 1.0 (<http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/>).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://xstream.codehaus.org/license.html>. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit <http://www.extreme.indiana.edu/>.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at <https://www.informatica.com/legal/patents.html>.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, please report them to us in writing at Informatica LLC 2100 Seaport Blvd. Redwood City, CA 94063.

INFORMATICA LLC PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2018-09-28

Table of Contents

Preface	6
Informatica Resources.	6
Informatica My Support Portal.	6
Informatica Documentation.	6
Informatica Product Availability Matrixes.	6
Informatica Web Site.	7
Informatica How-To Library.	7
Informatica Knowledge Base.	7
Informatica Support YouTube Channel.	7
Informatica Marketplace.	7
Informatica Velocity.	7
Informatica Global Customer Support.	7
 Chapter 1: Introduction to PowerExchange for Salesforce Analytics.....	 9
PowerExchange for Salesforce Analytics Overview.	9
Introduction to Salesforce Analytics.	9
 Chapter 2: Installation and Configuration.....	 10
Prerequisites.	10
Installing and Configuring PowerExchange for Salesforce Analytics.	10
Installing PowerExchange for Salesforce Analytics.	11
Installing the Client Component.	11
Installing the Server Component.	11
Plug-in Registration.	12
 Chapter 3: Salesforce Analytics Targets.....	 13
Salesforce Analytics Targets Overview.	13
Generating a JSON File.	13
Manually Creating a JSON File.	13
Importing a Salesforce Analytics Target Definition.	14
 Chapter 4: Salesforce Analytics Mappings.....	 15
Salesforce Analytics Mappings Overview.	16
Salesforce Analytics Mapping Example.	16
 Chapter 5: Salesforce Analytics Sessions.....	 18
Salesforce Analytics Sessions Overview.	18
Salesforce Analytics Connections.	18
Configuring a Salesforce Analytics Connection.	18
Session Configuration for Salesforce Analytics Targets.	19

Success and Error Logs.	20
Appendix A: Data Type Reference.....	21
Data Type Reference Overview.	21
Salesforce Analytics and Transformation Data Types.	21
Index.....	23

Preface

The *PowerExchange® for Salesforce Analytics User Guide for PowerCenter®* provides information to build Salesforce Analytics mappings and load data into Salesforce Analytics objects. It is written for developers who are responsible for loading data into Salesforce Analytics objects.

This book assumes that you have knowledge of web services concepts, relational database concepts, PowerCenter, Salesforce, and Salesforce Analytics. You must also be familiar with the interface requirements for other supporting applications.

Informatica Resources

Informatica My Support Portal

As an Informatica customer, you can access the Informatica My Support Portal at <http://mysupport.informatica.com>.

The site contains product information, user group information, newsletters, access to the Informatica customer support case management system (ATLAS), the Informatica How-To Library, the Informatica Knowledge Base, Informatica Product Documentation, and access to the Informatica user community.

The site contains product information, user group information, newsletters, access to the Informatica How-To Library, the Informatica Knowledge Base, Informatica Product Documentation, and access to the Informatica user community.

Informatica Documentation

The Informatica Documentation team makes every effort to create accurate, usable documentation. If you have questions, comments, or ideas about this documentation, contact the Informatica Documentation team through email at infa_documentation@informatica.com. We will use your feedback to improve our documentation. Let us know if we can contact you regarding your comments.

The Documentation team updates documentation as needed. To get the latest documentation for your product, navigate to Product Documentation from <http://mysupport.informatica.com>.

Informatica Product Availability Matrixes

Product Availability Matrixes (PAMs) indicate the versions of operating systems, databases, and other types of data sources and targets that a product release supports. You can access the PAMs on the Informatica My Support Portal at <https://mysupport.informatica.com/community/my-support/product-availability-matrixes>.

Informatica Web Site

You can access the Informatica corporate web site at <http://www.informatica.com>. The site contains information about Informatica, its background, upcoming events, and sales offices. You will also find product and partner information. The services area of the site includes important information about technical support, training and education, and implementation services.

Informatica How-To Library

As an Informatica customer, you can access the Informatica How-To Library at <http://mysupport.informatica.com>. The How-To Library is a collection of resources to help you learn more about Informatica products and features. It includes articles and interactive demonstrations that provide solutions to common problems, compare features and behaviors, and guide you through performing specific real-world tasks.

Informatica Knowledge Base

As an Informatica customer, you can access the Informatica Knowledge Base at <http://mysupport.informatica.com>. Use the Knowledge Base to search for documented solutions to known technical issues about Informatica products. You can also find answers to frequently asked questions, technical white papers, and technical tips. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team through email at KB_Feedback@informatica.com.

Informatica Support YouTube Channel

You can access the Informatica Support YouTube channel at <http://www.youtube.com/user/INFASupport>. The Informatica Support YouTube channel includes videos about solutions that guide you through performing specific tasks. If you have questions, comments, or ideas about the Informatica Support YouTube channel, contact the Support YouTube team through email at supportvideos@informatica.com or send a tweet to @INFASupport.

Informatica Marketplace

The Informatica Marketplace is a forum where developers and partners can share solutions that augment, extend, or enhance data integration implementations. By leveraging any of the hundreds of solutions available on the Marketplace, you can improve your productivity and speed up time to implementation on your projects. You can access Informatica Marketplace at <http://www.informaticamarketplace.com>.

Informatica Velocity

You can access Informatica Velocity at <http://mysupport.informatica.com>. Developed from the real-world experience of hundreds of data management projects, Informatica Velocity represents the collective knowledge of our consultants who have worked with organizations from around the world to plan, develop, deploy, and maintain successful data management solutions. If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at ips@informatica.com.

Informatica Global Customer Support

You can contact a Customer Support Center by telephone or through the Online Support.

Online Support requires a user name and password. You can request a user name and password at <http://mysupport.informatica.com>.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at <http://www.informatica.com/us/services-and-training/support-services/global-support-centers/>.

CHAPTER 1

Introduction to PowerExchange for Salesforce Analytics

This chapter includes the following topics:

- [PowerExchange for Salesforce Analytics Overview, 9](#)
- [Introduction to Salesforce Analytics, 9](#)

PowerExchange for Salesforce Analytics Overview

PowerExchange for Salesforce Analytics provides connectivity between PowerCenter and Salesforce Analytics. You can use PowerExchange for Salesforce Analytics to write data to Salesforce Analytics. You can then run queries on the Salesforce Analytics database to analyze the data.

Salesforce Analytics target represent objects in the Salesforce Analytics object model. Salesforce Analytics objects are tables that correspond to tabs and other user interface elements on the Salesforce Analytics web site.

Example

You work for a social media organization that tracks users website activity. You use Salesforce Analytics to store the users online activity. You can then analyze the activity through Salesforce Analytics to identify trends such as the top users for a period.

Introduction to Salesforce Analytics

Salesforce Analytics is a cloud-based platform that connects data from multiple sources, creates interactive views of that data, and displays those views in dashboards. Business users can use Salesforce Analytics reports to understand and act on real-time information.

You can use Salesforce Analytics to get instant access to analytics data and explore data of any data source.

CHAPTER 2

Installation and Configuration

This chapter includes the following topics:

- [Prerequisites, 10](#)
- [Installing and Configuring PowerExchange for Salesforce Analytics, 10](#)

Prerequisites

Before you upgrade or install PowerExchange for Salesforce Analytics, perform the following tasks:

- Install or upgrade PowerCenter.
- Verify that you have read and write permissions on the following directories on each machine that runs the PowerCenter Integration Service and PowerCenter Repository Service:

```
<Informatica Installation Directory>\server\bin\plugin  
<Informatica Installation Directory>\server\bin\native  
<Informatica Installation Directory>\server\bin\javalib
```

The installer must be able to add and overwrite files in these directories.

- Verify that you have read and write permissions on the following directories of each PowerCenter Client machine:

```
<Informatica Installation Directory>\clients\PowerCenterClient\client\bin  
<Informatica Installation Directory>\clients\PowerCenterClient\client\bin\Help  
<Informatica Installation Directory>\clients\PowerCenterClient\client\bin\Help  
  \<language>  
<Informatica Installation Directory>\clients\PowerCenterClient\client\bin\javalib
```

The installer must be able to add and overwrite files in these directories.

Installing and Configuring PowerExchange for Salesforce Analytics

To install and configure PowerExchange for Salesforce Analytics, perform the following tasks:

1. Verify the prerequisites.
2. Install PowerExchange for Salesforce Analytics.
3. Register the plug-in.

4. Create connections.

After you install and configure PowerExchange for Salesforce Analytics, you can create connections to access Salesforce Analytics. Create connection objects in the Workflow Manager so the PowerCenter Integration Service can connect to Salesforce Analytics at run time.

Installing PowerExchange for Salesforce Analytics

If you are installing or upgrading PowerExchange for Salesforce Analytics, you must run the product installer. When you install PowerExchange for Salesforce Analytics, you install the following components that allow PowerCenter to access Salesforce Analytics:

- Client component. Use the PowerCenter Client to import definitions, create mappings, and create connection objects.
- Server component. Use the PowerCenter Repository Service to store and access the Salesforce Analytics metadata in the repository and the PowerCenter Integration Service to run sessions.

Installing the Client Component

Install the Client component on each PowerCenter Client machine where you want to access Salesforce Analytics metadata and create targets using the Salesforce Analytics metadata.

1. Run install.bat from the installation package.
2. Click **Next**.
3. Select the Informatica installation directory.

By default, the client is installed in the following location:

```
<Informatica installation directory>\clients\PowerCenterClient\client\bin
```

4. Click **Next**.
5. Click **Install** to begin the installation.
6. Click **Done** when the installation is complete.

The client component is installed.

Installing the Server Component

The PowerExchange for Salesforce Analytics server component installs the PowerCenter Integration Service and PowerCenter Repository Service components.

If the PowerCenter Integration Service or PowerCenter Repository Service is configured to run on primary and backup nodes, install the PowerExchange for Salesforce Analytics server component on each node configured to run the PowerCenter Integration Service or PowerCenter Repository Service.

If the PowerCenter Integration Service is configured to run on a grid, install the PowerExchange for Salesforce Analytics server component on each node configured to run on the grid. If you cannot install the PowerExchange for Salesforce Analytics server component on each node in the grid, create a resource in the domain and assign it to each node where you installed the PowerExchange for Salesforce Analytics server component. When you create a session, configure the session to use the resource.

For example, create a custom resource called Salesforce Analytics. When you create a session, assign the resource as a required resource. The Load Balancer dispatches the Session task to a node that has the resource.

Installing the Server Component on UNIX

Install the PowerExchange for Salesforce Analytics server component on UNIX when the PowerCenter Integration Service or PowerCenter Repository Service runs on UNIX.

To install the PowerExchange for Salesforce Analytics server component on the UNIX platforms that support graphical user interface, perform the same steps that you use to install the server components on Windows.

To install the PowerExchange for Salesforce Analytics server component on the UNIX platforms that use the command line interface, perform the following steps:

1. Enter `sh install.sh` at the prompt.
2. Enter the path to the Informatica installation directory.

By default, the server components are installed in the following location:

```
<User Home Directory>/Informatica/<version folder>
```

The PowerCenter Integration Service and PowerCenter Repository Service components are installed.

Installing the Server Component on Windows

Install the PowerExchange for Salesforce Analytics server component on Windows when the PowerCenter Integration Service or PowerCenter Repository Service runs on Windows.

1. Run `install.bat` from the installation package.
2. Click **Next**.
3. Select the Informatica installation directory.

By default, the server components are installed in the following location:

```
C:\Informatica installation directory\<version folder>
```

4. Click **Next**.
5. Click **Install** to begin the installation.
6. Click **Done** when the installation is complete.

The PowerCenter Integration Service and PowerCenter Repository Service components are installed.

Plug-in Registration

After you install PowerExchange for Salesforce Analytics, register the plug-in with the repository. If you are upgrading from a previous version, update the plug-in registration when you register the plug-in.

A plug-in is an XML file that defines the functionality of PowerExchange for Salesforce Analytics. To register the plug-in, the repository must be running in exclusive mode. Use the Informatica Administrator or the *pmrep* RegisterPlugin command to register the plug-in.

The plug-in file for PowerExchange for Salesforce Analytics is `pmsfdc.xml`. When you install the Repository component, the installer copies `AnalyticsPlugin.xml` to the following directory:

```
<PowerCenter Installation Directory>/server/bin/plugin
```

Note: If you do not have the correct privileges to register the plug-in, contact the user who manages the PowerCenter Repository Service.

CHAPTER 3

Salesforce Analytics Targets

This chapter includes the following topics:

- [Salesforce Analytics Targets Overview, 13](#)
- [Generating a JSON File, 13](#)
- [Importing a Salesforce Analytics Target Definition, 14](#)

Salesforce Analytics Targets Overview

Use the Designer to import Salesforce Analytics target definitions into the PowerCenter repository.

Salesforce Analytics does not contain predefined metadata. Salesforce Analytics uses the JSON file format to describe the metadata. You must create a JSON file that contains metadata in the Salesforce Analytics schema format.

To create a JSON file, create a .csv file that contains the data that you want to load into Salesforce Analytics. Use the Salesforce `datasetloader.jar` file to convert the .csv file into a JSON file.

You can also manually create the JSON file based on the Salesforce Analytics schema format.

Generating a JSON File

You must create a JSON file before you can import the file into the Designer.

Before you create a JSON file, you must download the `datasetloader.jar` from the following location:

https://marketplace.informatica.com/solutions/salesforce_analytics_schema_creator

1. Create a .csv file with the supported data types and data.
2. From the command prompt, run the command: `java -jar datasetloader.jar <filename>.csv`.
A JSON file is created in the Salesforce Analytics schema format.

Manually Creating a JSON File

1. Open a text editor and enter the data in the following Salesforce Analytics schema format:

```
{
```

```

    "name" : "AmountWithoutOwnerAdjustment",
    "type" : "Numeric",
    "precision" : 18,
    "scale" : 0
  },
  {
    "name" : "CurrencyIsoCode",
    "type" : "Text"
  }
}

```

If the type is not text, specify the data type and precision details in the field name.

2. Save the JSON file with a file name that ends with `_schema` and close the file. For example, `MyDataset_schema.json`.

Importing a Salesforce Analytics Target Definition

1. In the Target Designer, click **Targets > Import from SFDC Analytics**.
2. In the Import Tables from Salesforce Analytics dialog box, enter the following information:

Import Attribute	Description
User Name	Salesforce Analytics user name.
Password	Password for the Salesforce Analytics user name. The password is case sensitive.
Service URL	URL of the Salesforce Analytics service that you want to access. In a test or development environment, you might want to access the Salesforce Analytics Sandbox testing environment. For more information about the Salesforce Analytics Sandbox, see the Salesforce documentation.
Security Token	The token used to log in to Salesforce Analytics from an untrusted network.
Temp Folder Name	The directory where the JSON files are stored.
Default Date Format	The date format to read date columns in the JSON file.

3. Click **Connect**.
4. Click **Next**.
The Designer displays a list of JSON metadata files to import.
5. Select the files that you want to import, and click **Finish**.

CHAPTER 4

Salesforce Analytics Mappings

This chapter includes the following topics:

- [Salesforce Analytics Mappings Overview, 16](#)
- [Salesforce Analytics Mapping Example, 16](#)


Salesforce Analytics Mappings Overview

After you import a Salesforce Analytics target definition into the PowerCenter repository, create a mapping to write data to the Salesforce Analytics target.

Salesforce Analytics Mapping Example

You work for an organization that sells electronic products through multiple websites and warehouses. You want to determine the sales details for a particular warehouse and write the sales information to Salesforce Analytics.

The following image shows the Salesforce Analytics mapping example:



The Salesforce Analytics mapping contains the following objects:

Sources

The mapping contains the following flat file sources:

- Contains details of the sales placed through websites and warehouses.
- Contains details of the warehouses from where the products are shipped.
- Contains details of the websites through which customers can place orders for products.

Transformations

The websales_join Joiner transformation joins the sales details with the website details. The sales record contains the website key. The transformation uses the website key to retrieve web site details from the web_site source.

The websales_warehouse_join_website Joiner transformation joins the output of the websales_join Joiner transformation with the warehouse details.

Target

The target named `SFDC` is a Salesforce Analytics target.

When you run the session, the PowerCenter Integration Service writes the sales information of the specified warehouse to Salesforce Analytics. You can then run queries on Salesforce Analytics to analyze the data.

CHAPTER 5

Salesforce Analytics Sessions

This chapter includes the following topics:

- [Salesforce Analytics Sessions Overview, 18](#)
- [Salesforce Analytics Connections, 18](#)
- [Session Configuration for Salesforce Analytics Targets, 19](#)

Salesforce Analytics Sessions Overview

After you create mappings, you can create a session and use the session in a workflow to load data. Create sessions and workflows in the Workflow Manager.

When you configure a Salesforce Analytics session, you create connections to write data to Salesforce Analytics. You can also define properties in a session to determine how the PowerCenter Integration Service writes data to a Salesforce Analytics target.

Salesforce Analytics Connections

Before the PowerCenter Integration Service can connect to Salesforce Analytics, you must configure a Salesforce Analytics application connection in the Workflow Manager.

When you configure a Salesforce Analytics application connection, you specify connection attributes the PowerCenter Integration Service uses to connect to Salesforce Analytics. A connection object stores the Salesforce Analytics user ID, password, and the service URL information for the run-time connection.

Configuring a Salesforce Analytics Connection

1. In the Workflow Manager, connect to a PowerCenter repository.
2. Click **Connections > Application**.
The Application Connection Browser dialog box appears.
3. From Select Type, select **Analytics**.
4. Click **New**.

5. In the **Connection Object Definition** dialog box, enter the following information:

Attribute Name	Description
Username	Salesforce Analytics user name for the application connection.
Password	Password for the Salesforce Analytics user name. The password is case sensitive.
Security Token	The token used to login to Salesforce Analytics from an untrusted network.
Service URL	URL of the Salesforce Analytics service that you want to access. In a test or development environment, you might want to access the Salesforce Analytics Sandbox testing environment. For more information about the Salesforce Analytics Sandbox, see the Salesforce documentation.
Temp Folder Name	The directory where the JSON files are stored.
Default Date Format	The date format to read date columns in the JSON file.

6. Click **OK**.

The application connection appears in the Application Object Browser.

Session Configuration for Salesforce Analytics Targets

You can configure the session properties for a Salesforce Analytics target on the Mapping tab. Define the properties for each target instance in the session.

The following table describes the session properties that you can configure for a Salesforce Analytics target:

Target Load Type

You can choose Normal mode or Bulk mode.

Default is Normal mode.

INSERT

Inserts a row to the Salesforce Analytics database.

DELETE

Deletes a row from the Salesforce Analytics database.

When you enable **DELETE**, the PowerCenter Integration Service deletes all rows flagged for delete and rejects all rows flagged when you disable **DELETE**.

UPSERT

When you enable **UPSERT**, the PowerCenter Integration Service upserts records, links the external ID to the external ID field from the source through the transformations in the target definition. Salesforce uses **UPSERT** to identify the records that must be upserted.

Success File Directory

Path to the success log files that the PowerCenter Integration Service generates.

Error File Directory

Path to the error log files that the PowerCenter Integration Service generates.

For a Salesforce Analytics target, you cannot configure the UPDATE operation.

Success and Error Logs

The PowerCenter Integration Service can generate record-level logs for each session that writes data to a Salesforce Analytics target.

The PowerExchange for Salesforce Analytics success and error logs are different from the PowerCenter session logs. The PowerExchange for Salesforce Analytics success and error logs contain record-level details that are specific to sessions with Salesforce Analytics targets.

The PowerCenter Integration Service can generate the following types of Salesforce Analytics logs:

Success log

The success log contains an entry for each record that successfully loads data into the Salesforce Analytics. Each entry contains the values loaded for all fields of the record. Use this file to understand what data is loaded into the Salesforce Analytics target. The naming convention for the success log is: <session name><timestamp>_success.csv.

Error log

The error log contains an entry for each data error. Each log entry contains the values for all fields of the record and the error message. The error log displays error messages from Salesforce Analytics and PowerCenter. Use this file to understand why records did not load data into Salesforce Analytics. The naming convention for the error log is: <session name><timestamp>_error.csv.

To configure the PowerCenter Integration Service to generate success and error logs for a session that writes data into Salesforce Analytics, configure the Success File and Error File Directory session properties.

APPENDIX A

Data Type Reference

This appendix includes the following topics:

- [Data Type Reference Overview, 21](#)
- [Salesforce Analytics and Transformation Data Types, 21](#)

Data Type Reference Overview

When the PowerCenter Integration Service loads data into a Salesforce Analytics object, it converts each PowerCenter transformation data type to a compatible Salesforce Analytics data type.

PowerExchange for Salesforce Analytics uses the following data types:

Salesforce Analytics data types

Salesforce Analytics data types appear in Salesforce Analytics definitions in a mapping.

Transformation data types

Set of data types that appear in the transformations. They are internal data types based on ANSI SQL-92 generic data types, which the PowerCenter Integration Service uses to move data across platforms. They appear in all transformations in a mapping.

Salesforce Analytics and Transformation Data Types

When the PowerCenter Integration Service writes data to a Salesforce Analytics target, it converts the data based on the native data types in the target.

The following table shows the conversion between Salesforce Analytics data types and transformation data types:

Salesforce Analytics Data Type	Transformation Data Type	Range and Description
DateTime	Date/Time	Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (precision to nanosecond)
Int	Integer	Precision 10, scale 0
String	String	1 to 104,857,600 characters

INDEX

D

- data type reference
 - overview [18, 21](#)
- data types
 - salesforce analytics and transformation data types [21](#)

I

- installing
 - PowerExchange for Salesforce Analytics [9–11](#)
- installing and configuring
 - PowerExchange for Salesforce Analytics [9–11](#)
- installing salesforce analytics
 - installing the server [11](#)

O

- overview
 - PowerExchange for Salesforce Analytics [9–11](#)

P

- PowerExchange for Salesforce Analytics
 - salesforce analytics introduction [9](#)

- PowerExchange for Salesforce Analytics (*continued*)
 - targets overview [13](#)

S

- Salesforce Analytics Installation
 - installing the client [11](#)
 - installing the server on UNIX [12](#)
 - plug-in registration [12](#)
 - prerequisites [10](#)
- Salesforce Analytics Mapping
 - mapping example [16](#)
- Salesforce Analytics Mappings
 - mappings overview [16](#)
- salesforce analytics sessions
 - overview [18, 21](#)
- Salesforce Analytics Sessions
 - logging session details [20](#)
 - session configuration for targets [19](#)
- Salesforce Analytics Targets
 - creating a metadata file [13](#)
 - importing a target definition [14](#)
- Salesforce Sessions
 - configuring a connection [18](#)