



Informatica® PowerExchange for HANA
10.5

User Guide for PowerCenter

© Copyright Informatica LLC 2020, 2021

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

Informatica, the Informatica logo, PowerCenter, and PowerExchange are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright © MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at <http://www.apache.org/licenses/>. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (<http://www.mozilla.org/>), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at <http://www.gnu.org/licenses/lgpl.html>. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at <http://www.openssl.org> and <http://www.openssl.org/source/license.html>.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://curl.haxx.se/docs/copyright.html>. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.dom4j.org/license.html>.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://dojotoolkit.org/license>.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://source.icu-project.org/repos/icu/icu/trunk/license.html>.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at <http://www.gnu.org/software/kawa/Software-License.html>.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at <http://www.opensource.org/licenses/mit-license.php>.

This product includes software developed by Boost (<http://www.boost.org/>) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http://www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at <http://www.pcre.org/license.txt>.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.eclipse.org/org/documents/epl-v10.php> and at <http://www.eclipse.org/org/documents/edl-v10.php>.

This product includes software licensed under the terms at <http://www.tcl.tk/software/tcltk/license.html>, <http://www.bosrup.com/web/overlib/?License>, <http://www.stlport.org/doc/license.html>, <http://asm.ow2.org/license.html>, <http://www.cryptix.org/LICENSE.TXT>, <http://hsqldb.org/web/hsqldbLicense.html>, <http://httpunit.sourceforge.net/doc/license.html>, <http://jung.sourceforge.net/license.txt>, http://www.gzip.org/zlib/zlib_license.html, <http://www.openldap.org/software/release/license.html>, <http://www.libssh2.org>, <http://slf4j.org/license.html>, <http://www.sente.ch/software/OpenSourceLicense.html>, <http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3-license-agreement>, <http://antlr.org/license.html>, <http://aopalliance.sourceforge.net/>, <http://www.bouncycastle.org/licence.html>, <http://www.jgraph.com/jgraphdownload.html>, <http://www.jcraft.com/jsch/LICENSE.txt>, http://jotm.objectweb.org/bsd_license.html, <http://www.w3.org/>

Consortium/Legal/2002/copyright-software-20021231; <http://www.slf4j.org/license.html>; <http://nanoxml.sourceforge.net/orig/copyright.html>; <http://www.json.org/license.html>; <http://forge.ow2.org/projects/javaservice/>; <http://www.postgresql.org/about/license.html>; <http://www.sqlite.org/copyright.html>; <http://www.tcl.tk/software/tcltk/license.html>; <http://www.jaxen.org/faq.html>; <http://www.jdom.org/docs/faq.html>; <http://www.slf4j.org/license.html>; <http://www.iodbc.org/dataspace/iodbc/wiki/IODBC/License>; <http://www.keplerproject.org/md5/license.html>; <http://www.toedter.com/en/jcalendar/license.html>; <http://www.edankert.com/bounce/index.html>; <http://www.net-snmp.org/about/license.html>; <http://www.openmdx.org/#FAQ>; http://www.php.net/license/3_01.txt; <http://srp.stanford.edu/license.txt>; <http://www.schneider.com/blowfish.html>; <http://www.jmock.org/license.html>; <http://xsom.java.net>; <http://benalman.com/about/license/>; <https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js>; <http://www.h2database.com/html/license.html#summary>; <http://jsoncpp.sourceforge.net/LICENSE>; <http://jdbc.postgresql.org/license.html>; <http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto>; <https://github.com/rantav/hector/blob/master/LICENSE>; <http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html>; <http://jibx.sourceforge.net/jibx-license.html>; <https://github.com/lyokato/libgeohash/blob/master/LICENSE>; <https://github.com/hjiang/jsonxx/blob/master/LICENSE>; <https://code.google.com/p/lz4/>; <https://github.com/jedisct1/libsodium/blob/master/LICENSE>; <http://one-jar.sourceforge.net/index.php?page=documents&file=license>; <https://github.com/EsotericSoftware/kryo/blob/master/license.txt>; <http://www.scala-lang.org/license.html>; <https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt>; <http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html>; <https://aws.amazon.com/asl/>; <https://github.com/twbs/bootstrap/blob/master/LICENSE>; <https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt>; <https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE>, and <https://github.com/apache/hbase/blob/master/LICENSE.txt>.

This product includes software licensed under the Academic Free License (<http://www.opensource.org/licenses/afl-3.0.php>), the Common Development and Distribution License (<http://www.opensource.org/licenses/cddl1.php>), the Common Public License (<http://www.opensource.org/licenses/cpl1.0.php>), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (<http://www.opensource.org/licenses/bsd-license.php>), the new BSD License (<http://opensource.org/licenses/BSD-3-Clause>), the MIT License (<http://www.opensource.org/licenses/mit-license.php>), the Artistic License (<http://www.opensource.org/licenses/artistic-license-1.0>) and the Initial Developer's Public License Version 1.0 (<http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/>).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://xstream.codehaus.org/license.html>. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit <http://www.extreme.indiana.edu/>.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at <https://www.informatica.com/legal/patents.html>.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2021-03-17

Table of Contents

| | |
|---|-----------|
| Preface | 6 |
| Informatica Resources. | 6 |
| Informatica Network. | 6 |
| Informatica Knowledge Base. | 6 |
| Informatica Documentation. | 6 |
| Informatica Product Availability Matrices. | 7 |
| Informatica Velocity. | 7 |
| Informatica Marketplace. | 7 |
| Informatica Global Customer Support. | 7 |
| Chapter 1: Introduction to PowerExchange for HANA..... | 8 |
| PowerExchange for HANA Overview. | 8 |
| Introduction to SAP HANA. | 8 |
| Chapter 2: PowerExchange for HANA Configuration..... | 9 |
| PowerExchange for HANA Configuration Overview. | 9 |
| Prerequisites. | 9 |
| Configuring the HANA ODBC Data Sources. | 10 |
| Chapter 3: HANA Sources and Targets..... | 13 |
| HANA Sources and Targets Overview. | 13 |
| HANA Data Modelling Views. | 13 |
| Input Types for Data Modelling Views. | 13 |
| Importing HANA Source or Target Definitions | 14 |
| Rules and Guidelines for HANA Modelling Views. | 16 |
| Chapter 4: HANA Mappings..... | 17 |
| HANA Mappings Overview. | 17 |
| Creating a HANA Mapping. | 17 |
| Chapter 5: HANA Sessions..... | 20 |
| HANA Sessions Overview. | 20 |
| PowerExchange for HANA Connections. | 20 |
| Configuring a HANA ODBC Connection. | 21 |
| Creating a HANA Session. | 22 |
| Enabling Array Upsert for PowerExchange for HANA | 24 |
| Chapter 6: HANA Pushdown Optimization..... | 27 |
| Pushdown Optimization Overview. | 27 |
| Pushdown Optimization Functions. | 27 |

Pushdown Optimization Transformations, Operators, and Variables. 29

Appendix A: HANA Datatype Reference..... 30

HANA Data Type Reference Overview. 30

SAP HANA and Transformation Datatypes. 30

Index..... 33

Preface

Use the *Informatica® PowerExchange® for HANA User Guide for PowerCenter®* to learn how to read from or write to SAP HANA by using PowerCenter Client. Learn to create a HANA ODBC connection, develop mappings, and run sessions in an Informatica domain.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit <https://network.informatica.com>.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit <https://search.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit <https://docs.informatica.com>.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at <https://network.informatica.com/community/informatica-network/product-availability-matrices>.

Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services and based on real-world experiences from hundreds of data management projects. Informatica Velocity represents the collective knowledge of Informatica consultants who work with organizations around the world to plan, develop, deploy, and maintain successful data management solutions.

You can find Informatica Velocity resources at <http://velocity.informatica.com>. If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at ips@informatica.com.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at <https://marketplace.informatica.com>.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:

<https://www.informatica.com/services-and-training/customer-success-services/contact-us.html>.

To find online support resources on the Informatica Network, visit <https://network.informatica.com> and select the eSupport option.

CHAPTER 1

Introduction to PowerExchange for HANA

This chapter includes the following topics:

- [PowerExchange for HANA Overview, 8](#)
- [Introduction to SAP HANA, 8](#)

PowerExchange for HANA Overview

PowerExchange for HANA provides connectivity between PowerCenter and SAP HANA. You can use PowerExchange for HANA to read from or write to SAP HANA database tables and views. You can also read data from SAP HANA modelling views, such as attribute views, analytical views, and calculation views.

PowerExchange for HANA uses the HANA ODBC driver to connect to SAP HANA. You must select the ODBC subtype as SAP HANA in the ODBC connection properties. When you run a session, the PowerCenter Integration Service uses the configured HANA ODBC data source name to read from or write to SAP HANA.

Introduction to SAP HANA

SAP High Performance Analytical Application (SAP HANA) is a secure modern data platform that simplifies operations, leverages advanced data processing engines for business, and processes data in-memory. It is a single platform for trans-analytic applications, with built-in advanced analytics and multi-model data processing engines that you can leverage to develop next-generation applications for the intelligent enterprise.

CHAPTER 2

PowerExchange for HANA Configuration

This chapter includes the following topic:

- [PowerExchange for HANA Configuration Overview, 9](#)

PowerExchange for HANA Configuration Overview

PowerExchange for HANA installs with PowerCenter. You can use PowerExchange for HANA on Windows or UNIX.

You must also configure the HANA ODBC driver and create the HANA ODBC data source names to connect to the SAP HANA database.

Prerequisites

You must complete the prerequisites before you can use PowerExchange for HANA.

Note: Ensure that you have the PowerExchange for HANA license.

1. Install PowerCenter.
2. On Windows, download and install the Microsoft Visual C++ 2010 Redistributable Package in server and client machines from the Microsoft website. For example, download the `vc_redist_x86.exe` file.
3. Verify that you have read, write, and execute permissions on the following directories:
 - `<PowerCenter Installation Directory>/server/bin`
 - `<PowerCenter Installation Directory>/server/bin/Plugin`
4. Configure the HANA ODBC driver on the machines where you install the Informatica services and clients.
 - a. Configure the HANA ODBC 32-bit driver on the Informatica client machine.
 - b. Configure the HANA ODBC 64-bit driver on the machine where PowerCenter Integration Service runs.

For more information about product requirements and supported platforms, see the Product Availability Matrix on Informatica Network:

<https://network.informatica.com/community/informatica-network/product-availability-matrices>

Configuring the HANA ODBC Data Sources

Create the HANA ODBC data source name in the HANA ODBC driver properties to connect to the SAP HANA database. The data source contains the connection credentials that you need to access the database, such as the SAP HANA database name, user name, and password.

You must configure both the HANA ODBC 32-bit and 64-bit drivers. The PowerCenter Designer uses the HANA ODBC 32-bit driver to import HANA tables and views as source or target definitions. The PowerCenter Integration Service uses the HANA ODBC 64-bit driver to extract data from or load data to SAP HANA.

The ODBC driver also varies based on the operating system.

The following table lists the SAP HANA ODBC driver that you must configure for different platforms:

| Platform | SAP HANA ODBC Driver |
|----------------|--|
| 32-bit Windows | HDBODBC32 |
| 64-bit Windows | HDBODBC |
| 64-bit UNIX | libodbcHDB Note: The file extension varies based on the UNIX platform. |

Download and Install the HANA ODBC Drivers

SAP HANA ODBC drivers are packaged with the SAP HANA client software.

1. Download and install the SAP HANA client software version 2.0 or later from the SAP Software Download Center.
You must have an account with SAP to download the software.
2. Create the HANA ODBC 32-bit data source on the machine that contains the Informatica client software installation.
3. Create the HANA ODBC 64-bit data source on the machine that runs the PowerCenter Integration Service.


Creating a HANA ODBC Data Source on Windows

On Windows, use the ODBC Data Source Administrator to create an ODBC data source.


To open the ODBC administrator, perform the following tasks:

1. Select **Start > Administrative Tools > Data Source (ODBC)**.
The ODBC Data Source Administrator dialog box appears.
2. Click the **System DSN** tab, and then click **Add**.
The Create New Data Source dialog box appears.

3. Select the HANA ODBC driver HDBODBC for 64-bit Windows or driver HDBCODBC32 for 32-bit Windows to set up the SAP HANA data source.



4. Click **Finish**.
The SAP HDB dialog box opens.
5. Enter the data source name, description, and server and port fields required to access SAP HANA.
Additionally, click the **Connect** button to verify that a successful ODBC connection can be established with the server.



6. Click **OK** to complete the driver configuration.

Create a HANA ODBC Data Source on UNIX

On UNIX, set the ODBC_HOME, ODBCINI, and shared library environment variables. Add the data source entries to the `odbc.ini` file in the system `$ODBC_HOME` directory.

Set the following environment variables:

ODBC_HOME

Set the variable to the ODBC installation directory.

For example, `setenv ODBC_HOME /export/home/qamercury/Informatica/10.4.1/ODBC7.0`

ODBCINI

Set the variable to point to the directory that contains the `odbc.ini` file.

For example, `setenv ODBCINI /export/home/qamercury/MBUGB_ODBCINI/10.4.1/odbc.ini`

LD_LIBRARY_PATH, LIBPATH, or SHLIB_PATH

Set the shared library environment variable to the directory where the SAP HANA ODBC driver is installed.

For example, `setenv LD_LIBRARY_PATH ".:${PM_HOME}:${JAVA_HOME}/lib:${ORACLE_HOME}/lib:/usr/sap/hdbclient:"`

After you set environment variables, add data source entries to the `odbc.ini` file found in the system `$ODBC_HOME` directory.

For SAP HANA, add the following entry to the `odbc.ini` file:

```
[SAP HANA source]
Driver=/usr/sap/hdbclient/libodbcHDB.so
DriverUnicodeType=1
ServerNode=<server_node>:<port>
```

Note: The operating system user that runs Informatica processes must have read and execute permissions on the HANA ODBC driver file.

CHAPTER 3

HANA Sources and Targets

This chapter includes the following topics:

- [HANA Sources and Targets Overview, 13](#)
- [Importing HANA Source or Target Definitions , 14](#)
- [Rules and Guidelines for HANA Modelling Views, 16](#)

HANA Sources and Targets Overview

You can import HANA tables, views, or modelling views as an ODBC source definition in the Designer. You can configure advanced read options in the ODBC driver configuration before you import the data.

HANA Data Modelling Views

When you use PowerExchange for HANA, you can read from the following HANA data modelling views:

Attribute views

Attribute views are built on top of dimension tables. You can use attribute views to define joins between tables and to select a subset of columns and rows from a table.

Analytic views

Analytic views are optimized for aggregating mass data. You can use analytical views if you need aggregated data from the underlying table.

Calculation views

Calculation views are layered on top of one or more analytic or attribute views and allow you to perform calculations after grouping at the attribute level and after aggregation at the analytic level.

Input Types for Data Modelling Views

You can use the following input types when you read data from SAP HANA modelling views:

Variables

A variable is a filter. A variable is associated with an attribute column, for example, company name, of the view. However, a variable does not appear in the source metadata in the PowerCenter Designer.

Provide the variable value in the attribute column that you specified in SAP HANA.

Parameters

An input parameter is a placeholder to the query. You can use parameters to insert values for analytical views and calculation views. The data type for an input parameter in PowerCenter is `char`.

Specify the data for input parameters in the format that you defined in SAP HANA.

Input Parameter Types

When you select a HANA modelling view, Informatica adds a prefix to the parameter name. The prefix is used to indicate the parameter type.

You can use the following types of parameters:

- **Mandatory Parameter.** A parameter for which you are required to specify a value. For example, in the field `PARAM_M_ip_param_4_empID1`, `PARAM_M` is the prefix for a mandatory parameter that Informatica adds. `ip_param_4_empID1` is the parameter name that is a part of HANA modelling views.
- **Optional Parameter.** A parameter for which you do not need to provide a value. For example, in the field `PARAM_O_par_4_sal_hike`, `PARAM_O` is the prefix for an optional parameter that Informatica adds. `par_4_sal_hike` is the parameter name that is a part of HANA modelling views.

Importing HANA Source or Target Definitions


Before you import HANA source or target definitions, ensure that you have installed the 32-bit HANA ODBC driver. Use the 32-bit ODBC data source to import HANA tables, views, or HANA modelling views.



For example, perform the following tasks to import HANA modelling views into the Designer.

1. Click **Sources > Import from Database**.
2. Select the 32-bit ODBC data source.
3. Enter the username and password.
4. Click **Connect**.
The **Select tables** list appears.
5. From the **Select tables** list, select **_SYS_BIC**.


Note: The modelling views are listed under the `_SYS_BIC` schema and not under the user schema.

The following image shows the _SYS_BIC schema under the **Select tables** list:



6. Click the  icon next to the _SYS_BIC schema.
7. Click the  icon next to **Views** to select the column view name in the table list.
8. Select a basic view that you have created in SAP HANA. Do not select a view name that has a hierarchy.

The following image shows the ANLV_PURCHASE_ORDER_USING_PARAM_00 view selected from the list of views:



9. Click **OK** to import the source definition for the modelling view.

Rules and Guidelines for HANA Modelling Views

Consider the following rules and guidelines when you read data from SAP HANA modelling views:

- You cannot use parameters with lookups.
- SAP HANA adds a `row.count` field when you import a view in the calculated column. If you do not create a calculated column for a view, the `row.count` field does not appear in the source metadata.

CHAPTER 4

HANA Mappings

This chapter includes the following topics:

- [HANA Mappings Overview, 17](#)
- [Creating a HANA Mapping, 17](#)

HANA Mappings Overview

After you import a HANA source or target definition into the PowerCenter repository, create a HANA mapping.

In a mapping, you can join multiple HANA tables by specifying a join condition. You can also enter a filter condition to reduce the number of source rows the PowerCenter Integration Service returns from HANA sources. You can enter a single filter condition or a series of conditions.


Configure the source filter and join in the Application Source Qualifier.

Creating a HANA Mapping


After you import the HANA table, view, or modelling view, create a mapping.

To read from modelling views in SAP HANA, you must select a source filter that you configured in HANA and specify the variables or parameters in the source qualifier.

Perform the following tasks to create a mapping to read from HANA modelling views:


1. Create a mapping.
Note: If you use input parameters, do not connect the input parameters in the Source Qualifier to the output fields. Otherwise, the mapping fails.
2. To edit the Source Qualifier, click the **Properties** tab in the **Edit Transformations** window.
3. Click the  icon next to the **Source Filter** field.
The **SQL Editor** page appears.
4. Select the column view in which you want to apply a filter from the list of column views on the left pane.
5. Specify the variable name or input parameter name in double quotes. Specify the variable value or input parameter value in single quotes. When you want to specify more than one variable or parameter, separate the variables or parameters using commas.

The following image shows a source filter for a variable value:



In the above figure, the view ANLV_PURCHASE_ORDER_USING_VAR_01 has a variable COMPANY with a value of 1000.

The following image shows a source filter for parameter values:



In the above figure, the view `ANLV_PURCHASE_ORDER_USING_PARAM_00_1` has a parameter `PARAM_O_ip_param_4_category` with a value of `MM`. The view also has a parameter `PARAM_O_ip_param_4_comp` with a value of `1000`.

6. Click **OK**.
 7. Click **Apply**.
- The fields are mapped.

CHAPTER 5

HANA Sessions

This chapter includes the following topics:

- [HANA Sessions Overview, 20](#)
- [PowerExchange for HANA Connections, 20](#)
- [Creating a HANA Session, 22](#)
- [Enabling Array Upsert for PowerExchange for HANA , 24](#)

HANA Sessions Overview

After you create mappings, you can create a session to read from or write to SAP HANA.

You must configure a HANA connection in the **Workflow Manager** and then define the properties in a session to determine how the PowerCenter Integration Service must extract from or load data to the HANA source.

PowerExchange for HANA Connections

You must configure a HANA ODBC data source before you can import HANA sources.

The following table describes the HANA ODBC connection properties:

| Property | Decription |
|-----------|---|
| Name | Name you want to use for this connection. The connection name cannot contain spaces or other special characters, except for the underscore. |
| Type | Read-only. Type of database. For SAP HANA, this property is set to ODBC. |
| User Name | Database user name with the appropriate read and write database permissions to access the database. To define the user name in the parameter file, enter session parameter \$ParamName as the user name, and define the value in the session or workflow parameter file. The Integration Service interprets user names that start with \$Param as session parameters. |

| Property | Decription |
|-----------------------------|---|
| Use Parameter in Password | Indicates that the password for the database user name is a session parameter, \$ParamName. Define the password in the workflow or session parameter file, and encrypt it by using the pmpasswd CRYPT_DATA option. Default is disabled. |
| Password | Password for the database user name. Must be in 7-bit ASCII. |
| Connect String | Connect string used to communicate with the SAP HANA database. |
| Code Page | Code page the Integration Service uses to read from a source database or write to a target database. |
| Connection Environment SQL | Runs an SQL command with each database connection. Default is disabled. |
| Transaction Environment SQL | Runs an SQL command before the initiation of each transaction. Default is disabled. |
| Connection Retry Period | Number of seconds the Integration Service attempts to reconnect to the database if the connection fails. If the Integration Service cannot connect to the database in the retry period, the session fails. Default value is 0. |
| ODBC Subtype | Type of database to which ODBC connects. Select SAP HANA . |

Configuring a HANA ODBC Connection

Configure a HANA ODBC connection in the Workflow Manager. When you create a connection object, choose the connection type in the Connection Browser. An ODBC connection includes the connection subtypes. For SAP HANA, create a relational connection with subtype ODBC. In the ODBC connection properties, select SAP HANA as the ODBC subtype.

Install the 64-bit HANA ODBC driver and use the 64-bit ODBC data source in the ODBC connection.

1. In the Workflow Manager, connect to a repository.
2. Click **Connections > Relational**.
The **Relational Connection Browser** dialog box appears.
3. Click **New**.
The **Select Subtype** dialog box appears.
4. Select **ODBC** from the **Select Subtype** list.
5. Click **OK**.
The **Connection Object Definition** dialog box appears.
6. Enter the connection details.
7. Click **OK**.
The database connection appears in the **Connection Browser** list.

Creating a HANA Session


You must use the HANA ODBC connection with the SAP HANA ODBC subtype to run a session that reads from or writes to SAP HANA.

1. In the PowerCenter Workflow Manager, click **Tools > Task Developer**.
2. Click **Tasks > Create**.
3. Select **Session** as the task type to create.
4. Enter the session name and click **Create**.
The **Mappings** dialog box appears.
5. Select the required mapping and click **OK**.
6. Click **Done** in the **Create Task** dialog box.
7. In the workspace, double-click the session you created.
8. On the **Mappings** tab, select **Sources** in the Transformations pane on the left.
9. Select the source as **Relational Reader**.
10. To select the source connection name in the **Connections** pane, click **Edit**.
The **Connection Object Definition** page appears.
11. Enter the source connection name.
12. Enter the username and password.
13. In the **Connect String** field, specify the 64-bit ODBC data source.
Note: You must install the 64-bit HANA ODBC driver to use the 64-bit ODBC data source.
14. Select the ODBC subtype as **SAP HANA**.

Note: If you do not select the ODBC subtype as SAP HANA, the session fails.

The following image shows the ODBC subtype selected for the connection:

Connection Object Definition

 Relational Connection Editor

Name:

Type:

User Name:

☐ Use Parameter In Password

Password:


Connect String:

Code Page:

Attributes:

| Attribute | Value |
|----------------------------|----------|
| Connection Environment ... | |
| Transaction Environment... | |
| Connection Retry Period | 0 |
| ODBC Subtype | SAP HANA |

15. Click **OK**.
16. In the **Properties** pane for the source connection, specify the **Owner Name** as **_SYS_BIC**.
The following image shows the owner name for the source connection in the **Properties** pane:



17. Select a target.
18. Click **OK** to save and close the session properties.
19. Create a workflow.
20. Run the workflow.

Enabling Array Upsert for PowerExchange for HANA

You can configure an upsert operation to upsert data in bulk and improve the session performance

Before you upsert data into SAP HANA targets, configure the following properties:

EnableArrayUpsert=Yes

Add the EnableArrayUpsert custom property and set the value to yes for the PowerCenter Integration Service in the Administrator tool.

If you want to set the custom property in the HANA session properties, click the **Properties** tab in the HANA session properties.

In the advanced section, in the **Custom Properties** field, add the attribute **EnableArrayUpsert** and set the value to **yes**.

Edit Tasks

General

Properties

Config Object

Mapping

Components

Metadata Extensions

Select task:

s_test_reader

Task type:

Session

Config Name:

default_session_config

| Attribute | Value | UnOverride |
|--|-------------------------------------|------------|
| Advanced | | |
| Constraint based load ordering | <input type="checkbox"/> | |
| Cache LOOKUP() function | <input checked="" type="checkbox"/> | |
| Default buffer block size | Auto | |
| Line Sequential buffer length | 1024 | |
| Maximum Memory Allowed For Auto Me... | 512MB | |
| Maximum Percentage of Total Memory ... | 5 | |
| Additional Concurrent Pipelines for Loo... | Auto | |
| Custom Properties | EnableArrayUpsert=yes; | Revert |
| Pre-build lookup cache | Auto | |
| Date/Time Format String | MM/DD/YYYY HH24:MI:SS.US | |
| Pre 85 Timestamp Compatibility | <input type="checkbox"/> | |
| Log Options | | |
| Save session log by | Session runs | |
| Save session log for these runs | 0 | |
| Session Log File Max Size | 0 | |
| Session Log File Max Time Period | 0 | |
| Maximum Partial Session Log Files | 1 | |
| Writer Commit Statistics Log Frequency | 1 | |
| Writer Commit Statistics Log Interval | 0 | |

Custom Properties

Custom properties at session level. These custom properties would override the DI service level properties.

OK

Cancel

Apply

Help

Treat Source Rows As

In the General options section, enter **Update** as the **Treat Source Rows As** property.

General

Properties

Config Object

Mapping

Components

Metadata Extensions

Select task:

s_m_hana_writer_tp_old_method

Task type:

Session

| Attribute | Value |
|--|-------------------------------------|
| General Options | |
| Write Backward Compatible Session Log File | <input checked="" type="checkbox"/> |
| Session Log File Name | s_m_hana_writer_tp_old_method.log |
| Session Log File directory | \$PMSessionLogDir\ |
| Parameter Filename | |
| Enable Test Load | <input type="checkbox"/> |
| Number of rows to test | 1 |
| \$Source connection value | |
| \$Target connection value | |
| Treat source rows as | Update |
| Commit Type | Target |
| Commit Interval | 10000 |
| Commit On End Of File | <input checked="" type="checkbox"/> |
| Rollback Transactions on Errors | <input type="checkbox"/> |
| Recovery Strategy | Fail task and continue workflow |
| Java Classpath | |
| Performance | |
| DTM buffer size | Auto |
| Collect performance data | <input type="checkbox"/> |

Update Else Insert

On the **Mapping** tab, select the target and then enable the **Update Else Insert** property.

The screenshot displays the SAP HANA Studio Mapping tab for the task 's_m_hana_writer_ip_upsert'. The left sidebar shows the project structure with 'Targets' expanded, highlighting 'LINEITEM'. The main area is divided into three sections: Writers, Connections, and Properties.

Writers

| Instance | Writers |
|----------|-------------------|
| LINEITEM | Relational Writer |

Connections

| Type | Value | Connections |
|------------|-----------|---------------|
| Relational | HANA_ODBC | DB Connection |

Properties

| Attribute | Value |
|------------------------------|-------------------------------------|
| LINEITEM - Relational Writer | |
| Insert | <input type="checkbox"/> |
| Update as Update | <input type="checkbox"/> |
| Update as Insert | <input type="checkbox"/> |
| Update else Insert | <input checked="" type="checkbox"/> |
| Delete | <input type="checkbox"/> |
| Truncate target table option | <input type="checkbox"/> |

CHAPTER 6

HANA Pushdown Optimization

This chapter includes the following topics:

- [Pushdown Optimization Overview, 27](#)
- [Pushdown Optimization Functions, 27](#)
- [Pushdown Optimization Transformations, Operators, and Variables, 29](#)

Pushdown Optimization Overview

To optimize the performance of a HANA session in PowerCenter, you can push the transformation logic to an SAP HANA source or target database. You can use source, target, or full pushdown optimization for the HANA session that uses the ODBC connection with the ODBC subtype SAP HANA.

Pushdown Optimization Functions

When you use pushdown optimization, the PowerCenter Integration Service converts the expression in the transformation or workflow link by determining equivalent operators and functions in the database.

PowerExchange for HANA supports the following pushdown functions in a SAP HANA database:

| Function | Pushdown | Function | Pushdown | Function | Pushdown |
|---------------|----------|-------------|----------|---------------|----------|
| ABORT() | - | INITCAP() | - | REG_MATCH() | - |
| ABS() | X | INSTR() | - | REG_REPLACE | - |
| ADD_TO_DATE() | - | IS_DATE() | - | REPLACECHR() | - |
| AES_DECRYPT() | - | IS_NUMBER() | - | REPLACESTR() | - |
| AES_ENCRYPT() | - | IS_SPACES() | - | REVERSE() | - |
| ASCII() | - | ISNULL() | X | ROUND(DATE) | - |
| AVG() | X | LAST() | - | ROUND(NUMBER) | - |

| Function | Pushdown | Function | Pushdown | Function | Pushdown |
|-----------------|----------|------------------|----------|-----------------|----------|
| CEIL() | X | LAST_DAY() | - | RPAD() | - |
| CHOOSE() | - | LEAST() | - | RTRIM() | - |
| CHR() | - | LENGTH() | - | SET_DATE_PART() | - |
| CHRCODE() | - | LN() | - | SIGN() | - |
| COMPRESS() | - | LOG() | - | SIN() | X |
| CONCAT() | - | LOOKUP | X | SINH() | - |
| COS() | X | LOWER() | X | SOUNDEX() | - |
| COSH() | - | LPAD() | - | SQRT() | X |
| COUNT() | X | LTRIM() | - | STDDEV() | - |
| CRC32() | - | MAKE_DATE_TIME() | - | SUBSTR() | - |
| CUME() | - | MAX() | X | SUM() | X |
| DATE_COMPARE() | X | MD5() | - | SYSDATE() | - |
| DATE_DIFF() | X | MEDIAN() | - | SYSTIMESTAMP() | X |
| DECODE() | X | METAPHONE() | - | TAN() | X |
| DECODE_BASE64() | - | MIN() | X | TANH() | - |
| DECOMPRESS() | - | MOD() | - | TO_BIGINT | - |
| ENCODE_BASE64() | - | MOVINGAVG() | - | TO_CHAR(DATE) | - |
| EXP() | X | MOVINGSUM() | - | TO_CHAR(NUMBER) | - |
| FIRST() | - | NPER() | - | TO_DATE() | - |
| FLOOR() | - | PERCENTILE() | - | TO_DECIMAL() | - |
| FV() | - | PMT() | - | TO_FLOAT() | - |
| GET_DATE_PART() | - | POWER() | X | TO_INTEGER() | - |
| GREATEST() | - | PV() | - | TRUNC(DATE) | - |
| IIF() | X | RAND() | - | TRUNC(NUMBER) | - |
| IN() | X | RATE() | - | UPPER() | X |
| INDEXOF() | - | REG_EXTRACT() | - | VARIANCE() | - |

Note: Columns marked with an X indicate that the PowerCenter Integration Service can push the function to the SAP HANA database by using source-side, target-side, or full pushdown optimization. Columns marked

with a dash (-) symbol indicate that the PowerCenter Integration Service cannot push the function to the database.

Pushdown Optimization Transformations, Operators, and Variables

When you use pushdown optimization, the PowerCenter Integration Service converts the expression in the transformation or workflow link by determining equivalent operators, functions, and variables in the database.

PowerExchange for HANA supports the following transformations for pushdown optimization:

| Transformations Supported | Pushdown Type |
|---------------------------|----------------------|
| Aggregator | Source, Target, Full |
| Expression | Source, Target, Full |
| Filter | Source, Target, Full |
| Joiner | Source, Target, Full |
| Lookup | Source, Target, Full |
| Sorter | - |
| Union | Source, Target, Full |
| Router | Source, Target, Full |
| Update Strategy | Source, Target, Full |
| Source Qualifier | |

The PowerCenter Integration Service can push the following arithmetic, comparison, and logical pushdown operators to an SAP HANA database by using source-side, target-side, or full pushdown optimization:

+, -, *, /, %, ||, >, =, >=, <=, !=, AND, OR, NOT, ^=.

The PowerCenter Integration Service can push the following variables to an SAP HANA database by using source-side, target-side, or full pushdown optimization:

- SESSSTARTTIME
- SYSDATE

APPENDIX A

HANA Datatype Reference

This appendix includes the following topics:

- [HANA Data Type Reference Overview, 30](#)
- [SAP HANA and Transformation Datatypes, 30](#)

HANA Data Type Reference Overview

PowerCenter uses the following data types in HANA mappings:

- HANA native data types. SAP HANA data types appear in HANA definitions in a mapping.
- Transformation data types. Set of data types that appear in the transformations. They are internal data types based on ANSI SQL-92 generic data types, which the PowerCenter Integration Service uses to move data across platforms. They appear in all transformations in a mapping.

When the PowerCenter Integration Service reads source data, it converts the native data types to the comparable transformation data types before transforming the data. When the PowerCenter Integration Service writes to a target, it converts the transformation data types to the comparable native data types.

SAP HANA and Transformation Datatypes

The following table compares SAP HANA datatypes and transformation datatypes:

| SAP HANA Datatype | Range | Transformation Datatype | Range |
|-------------------|---|-------------------------|--|
| Alphanum | Precision 1 to 127 | Nstring | 1 to 104,857,600 characters |
| Bigint | -9,223,372,036,854,775,808 to 9,223,372,036,854,775,807 | Bigint | -9,223,372,036,854,775,808 to 9,223,372,036,854,775,807 Precision 19, scale 0 |
| Bintext | - | String | Precision 32000 |
| Binary | Used to store bytes of binary data | Binary | 1 to 104,857,600 bytes |
| Blob | Up to 2 GB | Binary | 1 to 104,857,600 bytes |

| SAP HANA Datatype | Range | Transformation Datatype | Range |
|--|---|--------------------------------|--|
| Boolean | True/False | Integer | Boolean (True/False) values, precision 10 |
| Clob | Up to 2 GB | Text | 1 to 104,857,600 characters |
| Date | Jan 1, 0001 A.D. to Dec 31, 9999 A.D. Precision 10, scale 0 | Date/Time | Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (precision to the nanosecond) |
| Decimal (precision, scale) or Dec (p, s) | Precision 1 to 34 | Decimal | Precision 1 to 28, scale 0 to 28 |
| Double | Specifies a single-precision 64-bit floating-point number | Double | Precision 15 |
| Float | Precision 1 to 53 | Double | Precision 15 |
| Integer | -2,147,483,648 to 2,147,483,647 | Integer | -2,147,483,648 to 2,147,483,647 Precision 10, scale 0 |
| NClob | Up to 2 GB | Ntext | 1 to 104,857,600 characters |
| Nvarchar | Precision 1 to 5000 | Nstring | 1 to 104,857,600 characters |
| Real | Specifies a single-precision 32-bit floating-point number | Real | Precision 7, scale 0 |
| Seconddate | 0001-01-01 00:00:01 to 9999-12-31 24:00:00 | Date/Time | Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (precision to the nanosecond) |
| Shorttext | Specifies a variable-length character string, which supports text search and string search features | Nstring | 1 to 104,857,600 characters |
| Smalldecimal | Precision 1 to 16 | Decimal | Precision 1 to 28, scale 0 to 28 |
| Smallint | -32,768 to 32,767 | Small Integer | Precision 5, scale 0 |
| Text | Specifies a variable-length character string, which supports text search features | Text | 1 to 104,857,600 characters |
| Time | 24-hour time period | Date/Time | Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (precision to the nanosecond) |
| Timestamp | 0001-01-01 00:00:00.0000000 to 9999-12-31 23:59:59.9999999 | Date/Time | Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (precision to the nanosecond) |
| Tinyint | 0 to 255 | Small Integer | Precision 5, scale 0 |

| SAP HANA Datatype | Range | Transformation Datatype | Range |
|--------------------------|---------------------|--------------------------------|-----------------------------|
| Varchar | Precision 1 to 5000 | String | 1 to 104,857,600 characters |
| Varbinary | 1 to 5000 bytes | Binary | 1 to 104,857,600 bytes |

INDEX

C

configuring
 connection [21](#)
connection
 configuring [21](#)

F

filter [17](#)

H

HANA
 mappings [17](#)

I

Introduction
 HANA [8](#)

M

mapping
 filter [17](#)
 source [17](#)
 target [17](#)

P

PowerExchange for HANA
 configuring [9](#)

S

session
 overview [20](#)