



Informatica® Metadata Command Center  
November 2025

# SAP Datasphere Sources

© Copyright Informatica LLC 2023, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, Informatica Cloud, Informatica Intelligent Cloud Services, PowerCenter, PowerExchange, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2025-11-20

# Table of Contents

Preface . . . . .	4
<b>Chapter 1: Introduction to SAP Datasphere catalog sources.....</b>	<b>5</b>
Extraction and view process. . . . .	6
About the SAP Datasphere catalog source. . . . .	7
Extracted metadata. . . . .	7
Data profiling for SAP Datasphere objects. . . . .	7
Compatible connectors. . . . .	8
<b>Chapter 2: Before you begin.....</b>	<b>9</b>
Verify permissions. . . . .	9
Permissions for metadata extraction. . . . .	9
Permissions to run data profiles. . . . .	9
Permissions to run data classification. . . . .	9
Permissions to run glossary association. . . . .	9
Create a connection . . . . .	10
Create endpoint catalog sources for connection assignment. . . . .	11
Install SAP Datasphere Command Line Interface. . . . .	11
<b>Chapter 3: Create catalog sources in Metadata Command Center.....</b>	<b>13</b>
Step 1. Register a catalog source. . . . .	13
Step 2. Configure capabilities. . . . .	15
Configure metadata extraction. . . . .	15
Configure lineage discovery. . . . .	16
Configure data profiling and quality. . . . .	17
Configure data classification. . . . .	19
Configure glossary association. . . . .	20
Step 3. Associate stakeholders and asset groups. . . . .	21
Step 4. Run or schedule the job. . . . .	23
Step 5. Assign reference catalog source connections to endpoint catalog source objects. . . . .	24
<b>Chapter 4: View results in Data Governance and Catalog.....</b>	<b>26</b>
View metadata extraction results. . . . .	26
View data lineage. . . . .	28
View lineage at the catalog source level. . . . .	28
View lineage at the data set level. . . . .	28
View lineage at the data element level. . . . .	29
View data profiling results . . . . .	30
View classified data. . . . .	31
View glossary associations. . . . .	31

# Preface

Read *SAP Datasphere Sources* to learn how to register and configure SAP Datasphere sources in Metadata Command Center as catalog sources. After you configure a catalog source, you extract metadata and then view the results in Data Governance and Catalog.

## CHAPTER 1

# Introduction to SAP Datasphere catalog sources

You can use Metadata Command Center to extract metadata from a source system.

A source system is any system that contains data or metadata. For example, SAP Datasphere is a source system from which you can extract metadata through an SAP Datasphere catalog source with Metadata Command Center. A catalog source is an object that represents and contains metadata from the source system.

Before you extract metadata from a source system, you first create and register a catalog source that represents the source system. Then you configure capabilities for the catalog source. A capability is a task that Metadata Command Center can perform, such as metadata extraction, lineage discovery, data profiling, data classification, or glossary association.

When Metadata Command Center extracts metadata, Data Governance and Catalog displays the extracted metadata and its attributes as technical assets. You can then perform tasks such as analyzing the assets, viewing lineage, and creating links between those assets and their business context.

The following table describes the capabilities of the catalog source:

Capability	Description
Lineage Discovery	Builds the complete lineage of a catalog source by recommending endpoint catalog source objects to assign to reference catalog source connections. When you run the catalog source job, Metadata Command Center assigns the reference catalog source connections to CLAIRE recommended endpoint catalog source objects. You can then view the list of CLAIRE recommendations and accept or reject them.
Data Profiling and Quality	<ul style="list-style-type: none"><li>- <b>Data Profiling.</b> Assesses source metadata and analyzes the collected statistics to discover content and structure, such as value distribution, patterns, and data types.</li><li>- <b>Data Quality.</b> Measures the reliability of the data and enables data usage.</li></ul>
Data Classification	Data classification is the process of identifying and organizing data into relevant categories based on the functional meaning of the data. Classifying data can help your organization manage risks, compliance, and data security.
Glossary Association	You can associate terms that are in the glossary with technical assets to provide user-friendly business names to technical assets. Glossary Association automatically associates glossary terms with technical assets or recommends glossary terms that you can manually associate with technical assets in Data Governance and Catalog.


**Preview Notice:** Effective in the November 2024 release, the SAP Datasphere catalog source is available for preview. Preview functionality is supported for evaluation purposes but is unwarranted and is not supported in production environments or any environment that you plan to push to production. Informatica intends to

include the preview functionality in an upcoming release for production use, but might choose not to in accordance with changing market or technical circumstances. For more information, contact Informatica Global Customer Support.

## Extraction and view process

To extract metadata from a source system, configure the catalog source and run the extraction job in Metadata Command Center. Then view the results in Data Governance and Catalog.

The following image shows the process to extract metadata from SAP Datasphere:



After you verify prerequisites, perform the following tasks to extract metadata from SAP Datasphere:

1. Register a catalog source. Create a catalog source object, select SAP Datasphere, and then select and test the connection.
2. Configure the catalog source. Specify the runtime environment and configure parameters for metadata extraction. Optionally, add filters to include or exclude source system assets from metadata extraction. You can also configure other capabilities such as data profiling and quality, data classification, or glossary association.
3. Optionally, associate stakeholders. Associate users with technical assets, giving the users permission to perform actions determined by their roles.
4. Run or schedule the catalog source job.
5. Optionally, if the catalog source job generates referenced asset objects, you can assign a connection to referenced source system assets. You can view the lineage with object references without performing connection assignment. After connection assignment, you can view the objects.

After you run the catalog source job, you view the results in Data Governance and Catalog.

# About the SAP Datasphere catalog source

You can use the SAP Datasphere catalog source to extract metadata from an SAP Datasphere source system.

SAP Datasphere is a public cloud software as a service data warehouse that includes services for data modeling, data integration, cataloging, and data warehousing across SAP and non-SAP data.

## Extracted metadata

You can use the SAP Datasphere catalog source to extract metadata from an SAP Datasphere source system. The metadata extracted differs based on the extraction method that you configure.

Metadata Command Center extracts the following metadata from an SAP Datasphere source system:

Metadata Extraction Method	Metadata extracted
API	<ul style="list-style-type: none"><li>- Space</li><li>- Table</li><li>- Table Column</li><li>- View</li><li>- View Column</li><li>- Analytic Model</li><li>- Analytic Model Column</li></ul>
CLI	<ul style="list-style-type: none"><li>- Table</li><li>- Table Column</li><li>- View</li><li>- View Column</li><li>- Analytic Model</li><li>- Analytic Model Column</li><li>- Business Entity</li><li>- Business Entity Column</li><li>- Consumption Model</li><li>- Consumption Model Column</li><li>- Fact Model</li><li>- Fact Model Column</li><li>- Perspective</li><li>- Perspective Column</li></ul>

## Data profiling for SAP Datasphere objects

Configure data profiling to run profiles on the metadata extracted from an SAP Datasphere source system. You can view the profiling statistics in Data Governance and Catalog.

You can run data profiles on the following objects:

- Analytic Model
- View

For information about the data types on which data profiling tasks run, see *SAP OData V4 Connector* in Data Integration Connectors.

## Compatible connectors

Before you configure a catalog source, you must connect to the SAP Datasphere source system.

Use the SAP OData V4 connector to connect to the SAP Datasphere source system.

For information about configuring a connection, see *Connections* in the Administrator service.



## CHAPTER 2

# Before you begin

Before you create a catalog source, ensure that you have the information required to connect to the source system.

Perform the following tasks:

- Assign the required permissions.
- Create a connection to the SAP Datasphere source system in Administrator.
- Create endpoint catalog sources for connection assignment.
- To run jobs with the CLI metadata extraction method, install SAP Datasphere CLI.

## Verify permissions

To extract metadata and to configure other capabilities that a catalog source might include, you need account access and permissions on the source system. The permissions required might vary depending on the capability.

### Permissions for metadata extraction

To extract SAP Datasphere metadata, you need the DW Administrator role to generate the access token.

### Permissions to run data profiles

You can run profiles with the permissions required to perform metadata extraction.

### Permissions to run data classification

You can perform data classification with the permissions required to perform metadata extraction.

### Permissions to run glossary association

You can perform glossary association with the permissions required to perform metadata extraction.

# Create a connection

Create an SAP Datasphere connection object in Administrator with the connection details of the SAP Datasphere source system.

1. In Administrator, select **Connections**.
2. Click **New Connection**.
3. Enter the following connection details:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.
Runtime Environment	The name of the runtime environment where you want to run tasks. Select a Secure Agent or elastic runtime environment. For more information about how to configure and use the runtime environments, see <i>Runtime Environments</i> in the Administrator help.
Service Type	The service type of the SAP OData V4 service endpoint to which you want to connect. Select one of the following service types from the list: <ul style="list-style-type: none"><li>- Default. Connects to a specific SAP service.</li><li>- SAP Gateway Catalog. Connects to the SAP catalog service that provides a list of all available services on SAP Gateway.</li></ul> Default is Default.
Service URL	The service URL for the selected application type and service type. Enter the service URL in the following format depending on the selected application type and service type: <ul style="list-style-type: none"><li>- For the <b>SAP Datasphere</b> application type and the <b>Default</b> service type: <code>https://&lt;Host name of the SAP server&gt;/api/v1/dwc/consumption/relational/&lt;Space name of SAP Datasphere&gt;/&lt;Asset name of SAP Datasphere&gt;/</code></li><li>- For the <b>SAP Datasphere</b> application type and the <b>SAP Gateway Catalog</b> service type: <code>https://&lt;Host name of the SAP server&gt;/api/v1/dwc/&lt;Catalog service name in SAP Datasphere&gt;/</code></li><li>- For the <b>SAP S/4Hana</b> application type and the <b>Default</b> service type: <code>http://&lt;Host name of the SAP server&gt;:&lt;Port number&gt;/sap/opu/odata4/sap/&lt;Service name&gt;/&lt;Path of the service&gt;/&lt;version number&gt;/</code></li><li>- For the <b>SAP S/4Hana</b> application type and the <b>SAP Gateway Catalog</b> service type: <code>http://&lt;Host name of the SAP server&gt;:&lt;Port number&gt;/sap/opu/odata4/iwfnd/config/default/iwfnd/&lt;Catalog service name in SAP S/4HANA&gt;/&lt;version number&gt;/</code></li></ul>
Authentication Type	The authentication type to connect to the SAP OData V4 service. You can use the OAuth 2.0 authorization code authentication method to connect to SAP Datasphere.

Property	Description
Authorization Token URL	<p>The SAP OAuth 2.0 authorization server that is used to authorize the user request.</p> <p>Enter the authorization token URL in the following format:</p> <pre>https://&lt;Host name of the server&gt;/oauth/authorize</pre> <p>For example, If the host name is example.authentication.us01.hana.ondemand.com, enter the following authorization token URL:</p> <pre>https://example.authentication.us01.hana.ondemand.com/oauth/authorize</pre>
Access Token URL	<p>The SAP OAuth 2.0 authorization server that is used to exchange the authorization code to get an access token.</p> <p>Enter the access token URL in the following format:</p> <pre>https://&lt;Host name of the server&gt;/oauth/token</pre> <p>For example, If the host name is example.authentication.us01.hana.ondemand.com, enter the following access token URL:</p> <pre>https://example.authentication.us01.hana.ondemand.com/oauth/token</pre>
Client ID	The client identifier of your application generated when you configure the application for OAuth.
Client Secret	The client secret generated for the client ID.
Access Token	<p>The access token granted by the authorization server to access the SAP data.</p> <p>Enter the populated access token value that you get from the OAuth endpoint, or click <b>Generate Access Token</b> to populate the access token value.</p>

For more information about configuring a connection in Administrator, see *SAP OData V4 connection properties* in the Administrator help.

4. Click **Test Connection**.

## Create endpoint catalog sources for connection assignment

An endpoint catalog source represents a source system that the catalog source references. Before you perform connection assignment, create endpoint catalog sources and run the catalog source jobs.

You can then perform connection assignment to reference source systems to view complete lineage with source system objects.

## Install SAP Datasphere Command Line Interface

To run metadata extraction jobs via the SAP Datasphere CLI, install the SAP Datasphere Command Line Interface. You can install the CLI on both Linux and Windows machines.

Perform the following steps to install SAP Datasphere Command Line Interface:

On Linux, run the following installation commands on the Secure Agent machine:

1. `curl -fsSL https://rpm.nodesource.com/setup_22x | sudo bash -`
2. `sudo yum install -y nodejs`
3. `npm install -g @sap/datasphere-cli`

When the installation completes, run the following commands to confirm that the installation is successful:

- `node -v`
- `npm -v`
- `datasphere-version`

On Windows, install the following tools on the Secure Agent machine:

1. Node.js version  $\geq 20$  and  $\leq 22$
2. npm version  $\geq 8$  and  $\leq 10$

When the installation completes, run the following commands to confirm that the installation is successful:

- `node -v`
- `npm -v`
- `npm install -g @sap/datasphere-cli`

For more information about how to install or update the SAP Datasphere Command Line Interface, see the corresponding third-party vendor documentation.

## CHAPTER 3

# Create catalog sources in Metadata Command Center

Use Metadata Command Center to configure a catalog source for SAP Datasphere and extract metadata.

When you configure a catalog source, you define the source system that you want to extract metadata from. Configure filters to include source system metadata before you run the job. Optionally, configure other capabilities, such as lineage discovery, data profiling and quality, data classification, relationship discovery, and glossary association.

To provide stakeholders access to technical assets, you can assign access through stakeholder roles. You can also associate technical assets extracted from the catalog source to asset groups. If your catalog source references other source systems, you can create a connection assignment to the endpoint catalog source to view complete lineage.

## Step 1. Register a catalog source


When you register a catalog source, provide general information and connection values.

1. Log in to Informatica Intelligent Cloud Services.

The **My Services** page appears.

2. Click **Metadata Command Center**.


The following image shows the Metadata Command Center box on the **My Services** page:



The Metadata Command Center home page appears.

3. Click **New**.
4. Select **Catalog Source** from the list of asset types.
5. Select SAP Datasphere from the list of catalog source types.

The following image shows the SAP Datasphere catalog source type:



6. Click **Create**.
- The **New Catalog Source** page opens.
7. In the **General Information** section, enter a name and an optional description for the catalog source.  
**Note:** You can rename a catalog source after you create it, but to apply the change to all associated objects you must rerun the metadata extraction job.  
 After you save the catalog source, you can update the description in Metadata Command Center and Data Governance and Catalog. The update appears only in the service in which you update it.
  8. In the **Connection Information** area, select the connection that you created in Administrator.

**Note:** To create or edit a catalog source, you need permissions on the connection to the source system. Select a connection that you have access to, or ask the administrator to grant the necessary permissions to the connection that you want to use.

9. Click **Connection Properties** to expand and view the connection properties for the selected connection.
10. Click **Test Connection** to test your connection to the source system.
11. Click **Next**.

The **Configuration** page appears.

## Step 2. Configure capabilities

When you configure the SAP Datasphere catalog source, you define the settings for the metadata extraction capability and other optional capabilities.

The metadata extraction capability extracts source metadata from external source systems. You can also configure other capabilities that the catalog source includes.

You can save the catalog source configuration at any point after you enter the connection information. After you save the catalog source, you can choose to run the catalog source job. To run the job once, click **Run**. To run metadata extraction and other capabilities on a recurring schedule, configure schedules on the **Schedule** tab.

### Configure metadata extraction

When you configure the SAP Datasphere catalog source, you choose a runtime environment, define filters, and enter configuration parameters for metadata extraction.

1. In the **Connection and Runtime** area, choose a serverless runtime environment or the Secure Agent group where you want to run catalog source jobs.

**Note:** Serverless runtime environment options are available if the catalog source works with a serverless runtime environment.

2. Choose to retain, delete, or deprecate objects that are deleted from the source system in the catalog with the **Metadata Change Option**.
  - **Retain.** Retains objects that are deleted from the source system in the catalog. If you update or add a filter, the catalog retains objects extracted from the previous job and extracts additional objects that match the current filter. Objects deleted from the source system are not deleted from the catalog. Enrichments added on deleted objects and relationships are retained.
  - **Delete.** Deletes metadata from the catalog based on objects deleted from the source system and changes you make to the filter. Enrichments added on deleted objects and relationships are also permanently lost. Objects renamed in the source system are removed and recreated in the catalog.
  - **Deprecate.** The lifecycle of objects imported into the catalog moves to Obsolete based on objects deleted from the source system and changes you make to the filter. This does not impact enrichments added on deprecated objects and relationships. Objects renamed in the source system are removed and recreated in the catalog. When you run the catalog source job again for other capabilities such as data classification, relationship discovery, or glossary association, the job doesn't consider obsolete objects. Obsolete objects remain in the catalog until they are purged when you run a **Purge Obsolete Objects** job on the **Explore** page.

**Note:** You can also change the configured metadata change option when you run a catalog source.

3. In the **Filters** area, define one or more filter conditions to apply for metadata extraction:
  - a. Select **Yes** to view filter options.
  - b. From the **Include metadata** metadata list, choose to include metadata based on the filter parameters.
  - c. From the Object type list, select **Space**.
  - d. Enter the filter values.  
 You can't use wildcards. To include metadata from a space, specify only the space name. Don't include separators.

The following image shows the filter condition options:

The screenshot shows the 'Filters' section with the following elements:

- Specify metadata filters:** A toggle switch with 'No' and 'Yes' options. 'Yes' is selected.
- [Show supported wildcards and examples](#)
- Include Metadata:** A dropdown menu with 'Include Metadata' selected.
- Space:** A dropdown menu with 'Space' selected.
- Enter a value to specify the object location:** A text input field.
- +** and **🗑️** icons for adding and removing filters.

- e. To define an additional filter with an OR condition, click the **Add** icon.

The following image shows a sample filter added:

The screenshot shows the 'Filters' section with the following elements:

- Specify metadata filters:** A toggle switch with 'No' and 'Yes' options. 'Yes' is selected.
- [Show supported wildcards and examples](#)
- Include Metadata:** A dropdown menu with 'Include Metadata' selected.
- Space:** A dropdown menu with 'Space' selected.
- INFA\_DEV:** A text input field containing the value 'INFA\_DEV'.
- +** and **🗑️** icons for adding and removing filters.

4. In the **Catalog Source Configuration Options** section, select one of the following extraction methods:
  - API
  - CLI
5. In the **Additional Settings** section, enter additional settings.

**Note:** The **Additional Settings** section appears when you click **Show Advanced**.

The following table describes the property that you enter for advanced settings:

Property	Description
Expert Parameters	<p>Enter additional configuration options to be passed at runtime. Required if you need to troubleshoot the catalog source job.</p> <p><b>Caution:</b> Use expert parameters when it is recommended by Informatica Global Customer Support.</p>

6. Configure additional capabilities for the catalog source by clicking on the tabs.

## Configure lineage discovery

Enable the lineage discovery capability and use CLAIRE to build complete lineage by recommending endpoint catalog source objects to assign to reference catalog source connections.

1. Click the **Lineage Discovery** tab.
2. Select **Enable Lineage Discovery**.
3. In the **Filters** area, define one or more filter conditions to apply for lineage discovery.



To define filters, you can choose to select catalog source types, asset groups, or enter a catalog source name or search from a list of catalog sources.

- a. Select **Yes** to view filter options.
- b. From the Include/Exclude list, choose to include or exclude catalog sources for lineage discovery based on the filter parameters.
- c. From the filter type list, select catalog source type, catalog source name, or asset group.
- d. In the filter value field, select the required catalog source types, or click the Search button and select catalog sources or asset groups.

Filters can contain the asterisk wildcard to represent multiple characters or empty text.

The following image shows the filter condition options:

Enable Lineage Discovery: ☒

Filters

Specify lineage discovery filters: ☐ No ☒ Yes

[Show supported wildcards and examples](#)

Include	Catalog Source Type	Select Catalog Source Types	+	🗑️
Exclude	Catalog Source Name	Select Catalog Sources	+	🗑️
Exclude	Asset Group	Select Asset Groups	+	🗑️

Examples:

- To include or exclude all Oracle catalog sources, select **Catalog Source Type** as the filter type and select `Oracle` in the filter value field.
- To include or exclude the 'Oracle\_Retail' catalog source, select **Catalog Source Name** as the filter type and search for the catalog source or enter `Oracle_Retail` in the filter value field.
- To include or exclude all catalog sources with names that start with 'Oracle', select **Catalog Source Name** as the filter type and search for the catalog source or enter `Oracle*` in the filter value field.
- To include or exclude all catalog sources with names that end with 'Retail', select **Catalog Source Name** as the filter type and search for the catalog source or enter `*Retail` in the filter value field.
- To include or exclude all catalog sources with names that contain 'Ret', select **Catalog Source Name** as the filter type and search for the catalog source or enter `*Ret*` in the filter value field.
- To include or exclude all catalog sources that are part of the 'Financial Group' asset group, select **Asset Group** as the filter type and search `Financial Group` in the filter value field.

**Note:** You can't add more than one include or exclude filter for the same filter type.

- e. Optionally, to define an additional filter with an AND condition, click the **Add** icon.

For more information about lineage discovery, see *Lineage discovery* in the *Administration* help.

## Configure data profiling and quality

Enable the data profiling capability to evaluate the quality of metadata extracted from the SAP Datasphere source system.

1. Click the **Data Profiling and Quality** tab.
2. Expand **Data Profiling** and select **Enable Data Profiling**.

**Note:** Ensure that you have permissions on all the staging connections that you use in your data profiling configuration. You can't run the job if you don't have permissions on the connections that you use. Select

connections that you have access to, or ask the administrator to grant the necessary permissions on the connections that you want to use.

3. In the **Connection and Runtime** area, choose the Secure Agent group where you want to run catalog source jobs.
4. Optionally, specify data profiling filters to run the profile on a subset of the metadata that you extract.
  - a. Select **Yes** to view filter options.
  - b. From the Include Metadata list, choose to include metadata based on the filter parameters.
  - c. From the Object type list, select Space.
  - d. Enter a value to specify the object location.

Example:

You extracted metadata from all spaces, and now you want to run a profile on all assets in the 'MARKETING' space. Select 'Spaces' from the Object type option and then enter 'MARKETING' in the input field.

To include or exclude multiple objects, click the **Add** icon to add filters with the OR condition.

5. In the **Parameters** area, configure the following parameters:

Parameter	Description
Modes of Run	Determines the type of data that you want the data profiling task to collect. Choose one of the following options: <ul style="list-style-type: none"><li>• Keep signatures only. Collects only aggregate information such as data types, average, standard deviation, and patterns.</li><li>• Keep signatures and values. Collects both signatures and data values.</li></ul>
Profiling Scope	Determines whether you want to run data profiling only on the changes made to the source system or on the entire source system. Choose one of the following options: <ul style="list-style-type: none"><li>• Incremental. Includes only source metadata that is changed or updated since the last profile run.</li><li>• Full. Includes the entire metadata that is extracted based on the filters applied for extraction.</li></ul>
Sampling Type	Determines the sample rows on which you want to run the data profiling task. Choose any of the following options: <ul style="list-style-type: none"><li>• All Rows. Runs data profiling on all rows in the metadata.</li><li>• Limit N Rows. Runs data profiling on a limited number of rows.</li></ul>
No of rows to limit	Required if you select Limit N Rows in Sampling Type. Specify the number of rows that you want to run the profile on. Default is 1000.
Maximum Precision of String Fields	The maximum precision value to be used for profiling fields that include the string data type. You can set a maximum precision value of 255 characters. Default is 50.
Text Qualifier	The character that defines string boundaries. If you select a quote character, profiling ignores delimiters within the quotes. Select a qualifier from the list. Default is Double Quote.

6. Expand **Data Quality** and select **Enable Data Quality**.

**Note:** You can click **Use Data Profiling Parameters** to use the same parameters as in the **Data Profiling** section.

**Note:** Ensure that you have permissions on all the staging and flat file connections that you use in your data quality configuration. You can't run the job if you don't have permissions on the connections that you use. Select connections that you have access to, or ask the administrator to grant the necessary permissions on the connections that you want to use.

7. In the **Connection and Runtime** area, choose the Secure Agent group where you want to run catalog source jobs.
8. In the **Parameters** area, configure the following parameters based on your requirements:


Parameter	Description
Data Quality Rule Automation	Enable the option to automatically create or update rule occurrences for data elements in the catalog source. Choose one of the following options: <ul style="list-style-type: none"><li>• Apply on Data Elements linked with Business Dataset. Creates rule occurrences for all data elements that are linked with business data sets in the catalog source.</li><li>• Apply on all Data Elements. Creates rule occurrences for all data elements in the catalog source.</li></ul>
Cache Result	Enable the option to generate a cache file in the runtime environment and preview the cached results faster in subsequent data preview runs. Choose one of the following options: <ul style="list-style-type: none"><li>• Agent Cache. Stores the results in the runtime environment cache for seven days by default after the first run.</li><li>• No Cache. Doesn't store the preview results in the cache. You can only view live results.</li></ul>
Run Rule Occurrence Frequency	Specify whether you want to run data quality rules based on the frequency defined for the rule occurrence in Data Governance and Catalog.
Sampling Type	Determines the sample rows on which you want to run the data quality task. Choose one of the following options: <ul style="list-style-type: none"><li>• All Rows. Runs data quality on all rows in the metadata.</li><li>• Limit N Rows. Runs data quality on a limited number of rows.</li></ul>
No of rows to limit	Required if you select Limit N Rows in Sampling Type. Specify the number of rows that you want to run the data quality task on. Default is 1000.
Maximum Precision of String Fields	The maximum precision value to be used for fields that include the string data type. Default is 50.
Text Qualifier	The character that defines string boundaries. If you select a quote character, the data quality task ignores delimiters within the quotes. Select a qualifier from the list. Default is Double Quote.

## Configure data classification

Enable the data classification capability to identify and organize data into relevant categories based on the functional meaning of the data.

1. Click the **Data Classification** tab.

2. Select **Enable Data Classification**.
3. Choose one or both of the following options:
  - **Generated Data Classifications**. CLAIRE automatically generates data classifications for the data elements.
  - **Data Classification Rules**. Choose from predefined or custom data classifications.
    1. Click **Add Data Classification**. The following image shows the **Select Data Classifications** dialog box:



2. Select the data classifications that you want to use.
3. Click **OK**.

## Configure glossary association

Enable the glossary association capability to associate glossary terms with technical assets, or to get recommendations for glossary terms that you can manually associate with technical assets in Data Governance and Catalog.

Metadata Command Center considers all published business terms in the glossary while making recommendations to associate your technical assets.

1. Click the **Glossary Association** tab.
2. Select **Enable Glossary Association**.
3. Select **Enable auto-acceptance** to automatically accept glossary association recommendations.
4. Specify the **Confidence Score Threshold for Auto-Acceptance** to set a threshold limit based on which the glossary association capability automatically accepts the recommended glossary terms.
 

**Note:** Specify a percentage from 80 to 100. If the score is higher than the specified limit, the glossary association capability automatically assigns a matching glossary term to the data element.
5. Select **Enable Below-threshold Recommendations** to receive glossary association recommendations below the auto-acceptance threshold. If you enable auto-acceptance, you can enable below-threshold recommendations to receive glossary recommendations below the auto-acceptance threshold.
6. Specify the **Confidence Score Threshold for Recommendations** to set a threshold based on which the glossary association capability makes recommendations

If you enable auto-acceptance, specify a percentage from 80 to the selected auto-acceptance threshold. You can accept or reject the recommended glossary terms that fall within this range in Data Governance and Catalog.

If you disable auto-acceptance, specify a percentage from 80 to 100 inclusive.

7. Choose to automatically assign business names and descriptions to technical assets. You can then choose to retain existing assignments and only assign business names and descriptions to assets that don't have assignments, or allow overwrite of existing assignments.

By default, existing assignments are retained.

8. Optional. Choose to ignore specific parts of data elements when making recommendations. Select **Yes** and enter prefix and suffix keyword values as needed.

Click **Select** to enter a keyword. You can enter multiple unique prefix and suffix keywords. Keyword values are case insensitive.

9. Optional. Choose specific top-level business glossary assets to associate with technical assets. Selecting a top-level asset selects its child assets as well. Select **Top-level Glossary Assets** and specify the assets on the **Select Assets** page.

10. Optional. Choose to use abbreviations and synonym definitions from lookup tables for accurate glossary association. Select **Yes** to enable, and then click **Select** to upload a lookup table.

11. Click **Next**.

The **Associations** page appears.

## Step 3. Associate stakeholders and asset groups

Associate users or user groups within a stakeholder role as stakeholders for technical assets in Data Governance and Catalog. Also, you can choose to assign technical assets extracted from the catalog source to asset groups. You can then use access policies to control permissions on assets that are assigned to asset groups.

Verify that the administrator assigned users and user groups to the stakeholder role that you want to associate with technical assets.

1. To associate users or user groups as stakeholders with technical assets extracted from the catalog source, perform the following steps:
  - a. On the **Associations** page, click **Stakeholders**.
  - b. Select **Assign Stakeholders**.
  - c. Select a stakeholder role.
  - d. Click **Select** to add users and user groups from the stakeholder role as stakeholders for the technical assets.

The **Add Users & User Groups** dialog box displays a list of users and user groups assigned to the selected stakeholder role.

Add Users & User Groups

Users

User Groups

All Users (1)

Find

↕


<input type="checkbox"/>	Full Name	Email	User Name ↑	Status
<input type="checkbox"/>	gov owner_09			Active

?

OK

Cancel

- e. Select one or more users or user groups to assign as stakeholders for the technical assets, and click **OK**.  
Only the selected users and user groups belonging to the specified stakeholder role are granted the permissions to technical assets.
  - f. To assign users or user groups from another stakeholder role, click **Add** and then repeat the steps.
2. To assign asset groups to technical assets extracted from the catalog source, perform the following steps:
  - a. On the **Associations** page, click **Asset Groups**.
  - b. Select **Assign Asset Groups**.
  - c. Click **Select**.  
The **Select Asset Groups** dialog box displays the list of asset groups.  
If you enabled an access policy that includes an asset group, you can only view assets that belong to that asset group.
3. Select the asset groups to which you want to assign technical assets extracted from the catalog source, and click **OK**.



4. Choose to save and run the job or to schedule a recurring job.
  - To save and run the job, click **Save** and then **Run**.
  - To schedule a recurring job, click **Next** to open the **Schedule** page.

## Step 4. Run or schedule the job

Choose to run a catalog source job manually, or configure it to run on schedule.

**Note:** You can't run multiple jobs simultaneously.

You can choose to perform a full or an incremental metadata extraction. A full metadata extraction extracts all objects from the source to the catalog. An incremental metadata extraction extracts only the changed and new objects since the last successful catalog source job run. Incremental metadata extraction doesn't remove deleted objects from the catalog and doesn't extract metadata of code-based objects if applicable.

When you run an incremental metadata extraction job with a filter to include metadata from objects, the job extracts only the objects that have the latest timestamp since the last successful job.

**Note:** The incremental extraction option appears if it is available for the catalog source.

### Run the job manually

Click **Save** to save the catalog source and click **Run**. On the **Run Catalog Source Job** window, click **Run** to run the job.

You can override the capabilities that you selected while configuring your catalog source on the **Configuration** page. The first time you run the catalog source job, the metadata extraction capability is mandatory. From the second run onwards, you can choose to override the configured metadata change option. You can retain, delete, or deprecate objects that are deleted from the source in the catalog. For subsequent runs of the catalog source job, the metadata extraction capability is optional.

**Note:** You can choose incremental metadata extraction for subsequent runs only after one full metadata extraction job completes successfully. Incremental metadata extraction jobs run with the **Retain** metadata change option even if you set the option to **Delete** or **Deprecate** in the catalog source.

**Note:** To run a catalog source job, you need permissions on the connection to the source system. To run a catalog source job for catalog sources that reference other source systems, you need permissions on the connections for all the reference source systems.

### Run the job on a schedule

You can choose to run metadata extraction and other capabilities on a recurring schedule. You can't choose incremental metadata extraction and full metadata extraction in the same schedule. To create a schedule for incremental metadata extraction, you must have completed at least one full metadata extraction job successfully. If not, first create a schedule for a full metadata extraction.

If an incremental metadata extraction is scheduled to run when the last run details aren't available, the job first performs a full metadata extraction, followed by incremental metadata extraction on subsequent runs.

For example, this can happen in the following scenarios:

- You create schedules for both incremental metadata extraction and full metadata extraction, but schedule the incremental extraction to run before the first full metadata extraction job.
- You create schedules for both incremental metadata extraction and full metadata extraction, but delete the full metadata extraction schedule before its first run.

1. On the **Schedule** tab, select **Run on Schedule**.  
The **Schedule** configuration page opens.
2. Click the checkbox corresponding to each capability that you want to include in the schedule.
3. Enter the start date, time zone, and the interval at which you want to run the job.
4. You can manage additional schedules using the following options:
  - To create a new schedule, click the **Add** button.
  - To delete a schedule, click the **Delete** button.
  - To enable or disable a schedule, click the **Enable Schedule** toggle button.

**Note:** You can create a maximum of one schedule per capability that you enable. If you purged a catalog source or did not run the metadata extraction job, the catalog source job runs metadata extraction before running other scheduled capabilities.

**Note:** To create a schedule, you need permissions on the connection to the source system. If you lose permissions on the connection after you create a schedule, the scheduled jobs continue to run.

5. Click **Save** to save the schedule.

### Monitor job status

After the job runs, you can monitor the status of the job on the **Overview** page of the job.

For more information about job monitoring, see *Administration*.

## Step 5. Assign reference catalog source connections to endpoint catalog source objects

When you run the catalog source job, if the catalog source references another source system, a reference catalog source and connection get created that point to the reference source system. To view the complete lineage for your catalog source, you can perform connection assignment from the reference catalog source connection to the objects in the reference source system. A reference source system might be a data



warehouse, such as SAP HANA Database. You must first create and run an endpoint catalog source that connects to the reference source system.

Before you assign a connection, ensure that you have created and run an endpoint catalog source for each reference source system.

**Note:** If the source schema contains case-sensitive tables or if the reference objects contain multiple objects with the same name in different cases, perform case-sensitive connection assignment to get correct lineage.

If you enabled the lineage discovery capability for your catalog source, you can either curate the CLAIRE recommended endpoint objects on the **Related Catalog Sources** tab or assign connections manually.

For more information about related catalog sources and lineage discovery, see *Lineage discovery* in the *Administration* help.

1. On the **Configure** page, select the **Lineage** tab, and then select the **Lineage Discovery** tab. On the **Catalog Sources** panel, select the required catalog source and click the **Assign Connections** tab.

The **Assign Connections** tab displays a list of assigned and unassigned connections along with details for each connection. Use filters to view the connections based on the connection names. Click the **Add Filter** menu to add filters.

2. Select the connection to the reference source system and click **Assign**.

The connection name appears prefixed to the reference catalog source name on the **Hierarchy** tab of your catalog source in Data Governance and Catalog.

The **Assign Connection** dialog box appears with a list of recommended objects from the endpoint catalog sources. Click **All** to view all endpoint catalog source objects.

3. In the **Assign Connection** dialog box, select one or more objects from the endpoint catalog sources and click **Assign**.

You can filter the list in the **Assign Connection** dialog box by name, type, or endpoint.

You can connect to the following reference source systems:

Source system	Object class type
SAP HANA Database	Database
SAP ERP	Database
SAP HANA	Database
SAP Analytics Cloud	Database
SAP Business Warehouse (SAP BW)	Database
SAP BW/4HANA	Database
SAP S/4HANA	Database

When you click **Assign**, Metadata Command Center creates links between matching objects in the connected catalog sources, and it calculates the percentage of matched and unmatched objects. The higher the percentage of matched objects, the more accurate the lineage that you view in Data Governance and Catalog.

## CHAPTER 4

# View results in Data Governance and Catalog

After Metadata Command Center runs a job, you can view the results in Data Governance and Catalog where the catalog source and its elements are called technical assets. You can view a catalog source as a hierarchy. Expand each technical asset to see its components.

When referenced source systems are connected to a catalog source, you can expand the hierarchy to see details about the technical asset's component elements.

You can view the data lineage of an asset contained within a catalog source to see individual elements such as data sources, calculations, and filters. When you view data lineage, you can see the individual upstream elements that contribute data or expressions to each component of a data flow or catalog source.

## View metadata extraction results


After a job runs in Metadata Command Center, view the results in Data Governance and Catalog. You can view details about source system contents in a hierarchical structure and trace data lineage.

1. Log in to Informatica Intelligent Cloud Services.


The **My Services** page appears.

2. Click Data Governance and Catalog.

The following image shows the Data Governance and Catalog box on the **My Services** page:



3. On the Data Governance and Catalog home page, click the number in the **Technical Assets** panel. The **Technical Assets** page opens.
4. Select **Catalog Source** in the **Filter** list. The list of catalog sources opens.
5. Search for the catalog source from which you extracted metadata, and click the name. The **Overview** tab of the asset opens. The following image shows a sample asset page:



6. View the asset from different perspectives by clicking on the tabs. For more information about working with assets, see *Working with Assets in Data Governance and Catalog* help.

# View data lineage

Data lineage is a visual representation of the flow of data across the systems in your organization. Lineage depicts how the data flows from the system of its origin to the system of its destination.

Data lineage views are available for technical assets in the catalog source. You can view lineage at the catalog source, data set, or data element level.

The lineage at the catalog source level shows how data flows from one catalog source to another. The lineage at the data set and the data element levels show how other technical assets such as files or tables contribute to the selected asset.

If linking catalog sources is available for your catalog source, you can use Metadata Command Center to generate data lineage based on rules or by generating automated lineage with CLAIRE. You can choose source and target catalog sources and objects to link and generate lineage.

To determine whether linking catalog sources is available for your catalog source, navigate to the **Configuration** tab of the **Link Catalog Sources** page. The catalog source must appear in the list of source and target catalog sources.

For information about linking catalog sources, see *Link catalog sources* in the Administration help.

## View lineage at the catalog source level

The catalog source level shows how data flows from one catalog source to another with the lineage aggregating data from the data set and data element levels.


To view data lineage at the catalog source level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Catalog Source Level**.

## View lineage at the data set level


The data set level displays individual sets of data in the data flow.

To view lineage at the data set level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Set Level**.

The following image shows how the sap\_cpms4h\_avrCV\_MSTRPROJACTCOST SAP Datasphere table gets data from the CV\_MSTRPROJACTCOST source reference data set before connection assignment:



The following image shows how the sap\_cpms4h\_avrCV\_MSTRPROJACTCOST target table gets data from the CV\_MSTRPROJACTCOST source calculation view after connection assignment:




After connection assignment, the referenced object icons change to specific object icons.

## View lineage at the data element level

The data element level displays details of the data set level. At the data element level, you can see the input sources for expressions or commands and calculations or transformations on the data.


To view data lineage at the data element level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Element Level**.

The following image shows how the ACCOUNTINGDOCUMENT SAP Datasphere table column of the sap\_cpms4h\_avrCV\_MSTRPROJACTCOST SAP Datasphere table gets data from the ACCOUNTINGDOCUMENT reference data element of the CV\_MSTRPROJACTCOST reference data set before connection assignment:



The following image shows how the ACCOUNTINGDOCUMENT SAP Datasphere table column of the sap\_cpms4h\_avrCV\_MSTRPROJACTCOST SAP Datasphere table gets data from the ACCOUNTINGDOCUMENT attribute of the CV\_MSTRPROJACTCOST calculation view after connection

assignment: :




After connection assignment, the referenced object icons change to specific object icons.

## View data profiling results

When you enable the data profiling task for a catalog source in Metadata Command Center, the system runs a profile to evaluate the quality of the metadata extracted from the source system. The profiling statistics appear in Data Governance and Catalog when you open the technical assets.

The scope of profiling statistics that Data Governance and Catalog displays depends on the data profiling configuration parameters that you set when you configured the catalog source in Metadata Command Center.

The following image shows the data profiling statistics that appear on a column asset page in Data Governance and Catalog:




For more information about data profiling results, see *Asset Details* in the Data Governance and Catalog help.

## View classified data

When you add data classification rules to a catalog source in Metadata Command Center, the system identifies the columns and tables that match the rules and displays one or more matched data classifications on the column or table asset pages in Data Governance and Catalog.

The following image shows a column asset page with the inferred data element classifications that match the column data and metadata:



For more information about data classification assets, see *Asset Details* in the Data Governance and Catalog help.

## View glossary associations

When you enable the glossary association capability for a catalog source in Metadata Command Center, you can view the accepted glossary assets in Data Governance and Catalog.

The **Overview** tab for a technical asset in the catalog source displays glossary assets in the Accepted and CLAIRE Recommendations sections.

The **Glossaries** panel shows the automatically accepted and CLAIRE® recommended terms.

The following image shows a sample asset page:

