



Informatica® Dynamic Data Masking  
9.8.4

# Release Guide

© Copyright Informatica LLC 1993, 2018

This software and documentation contain proprietary information of Informatica LLC and are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright law. Reverse engineering of the software is prohibited. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. This Software may be protected by U.S. and/or international Patents and other Patents Pending.

Use, duplication, or disclosure of the Software by the U.S. Government is subject to the restrictions set forth in the applicable software license agreement and as provided in DFARS 227.7202-1(a) and 227.7702-3(a) (1995), DFARS 252.227-7013(1)(ii) (OCT 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14 (ALT III), as applicable.

The information in this product or documentation is subject to change without notice. If you find any problems in this product or documentation, please report them to us in writing.

Informatica, Informatica Platform, Informatica Data Services, PowerCenter, PowerCenterRT, PowerCenter Connect, PowerCenter Data Analyzer, PowerExchange, PowerMart, Metadata Manager, Informatica Data Quality, Informatica Data Explorer, Informatica B2B Data Transformation, Informatica B2B Data Exchange Informatica On Demand, Informatica Identity Resolution, Informatica Application Information Lifecycle Management, Informatica Complex Event Processing, Ultra Messaging, Informatica Master Data Management, and Live Data Map are trademarks or registered trademarks of Informatica LLC in the United States and in jurisdictions throughout the world. All other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jqWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright © MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at <http://www.apache.org/licenses/>. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (<http://www.mozilla.org/>), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at <http://www.gnu.org/licenses/lgpl.html>. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at <http://www.openssl.org> and <http://www.openssl.org/source/license.html>.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://curl.haxx.se/docs/copyright.html>. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.dom4j.org/license.html>.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://dojotoolkit.org/license>.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://source.icu-project.org/repos/icu/icu/trunk/license.html>.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at <http://www.gnu.org/software/kawa/Software-License.html>.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at <http://www.opensource.org/licenses/mit-license.php>.

This product includes software developed by Boost (<http://www.boost.org/>) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at [http://www.boost.org/LICENSE\\_1\\_0.txt](http://www.boost.org/LICENSE_1_0.txt).

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at <http://www.pcre.org/license.txt>.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at <http://www.eclipse.org/org/documents/epl-v10.php> and at <http://www.eclipse.org/org/documents/edl-v10.php>.

This product includes software licensed under the terms at <http://www.tcl.tk/software/tcltk/license.html>, <http://www.bosrup.com/web/overlib/?License>, <http://www.stlport.org/doc/license.html>, <http://asm.ow2.org/license.html>, <http://www.cryptix.org/LICENSE.TXT>, <http://hsqldb.org/web/hsqldbLicense.html>, <http://httpunit.sourceforge.net/doc/license.html>, <http://jung.sourceforge.net/license.txt>, [http://www.gzip.org/zlib/zlib\\_license.html](http://www.gzip.org/zlib/zlib_license.html), <http://www.openldap.org/software/release/license.html>, <http://www.libssh2.org>, <http://slf4j.org/license.html>, <http://www.sente.ch/software/OpenSourceLicense.html>, <http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3-license-agreement>, <http://antlr.org/license.html>, <http://aopalliance.sourceforge.net/>, <http://www.bouncycastle.org/licence.html>, <http://www.jgraph.com/jgraphdownload.html>, <http://www.jcraft.com/jsch/LICENSE.txt>, [http://jotm.objectweb.org/bsd\\_license.html](http://jotm.objectweb.org/bsd_license.html), <http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231>, <http://www.slf4j.org/license.html>, <http://nanoxml.sourceforge.net/orig/copyright.html>, <http://www.json.org/license.html>, <http://forge.ow2.org/projects/javaservice/>, <http://www.postgresql.org/about/licence.html>, <http://www.sqlite.org/copyright.html>, <http://www.tcl.tk/software/tcltk/license.html>, <http://www.jaxen.org/faq.html>, <http://www.jdom.org/docs/faq.html>, <http://www.slf4j.org/license.html>, <http://www.iodbc.org/dataspace/iodbc/wiki/IODBC/License>, <http://www.keplerproject.org/md5/license.html>, <http://www.toedter.com/en/jcalendar/license.html>, <http://www.edankert.com/bounce/index.html>, <http://www.net-snmp.org/about/license.html>, <http://www.openmdx.org/#FAQ>, [http://www.php.net/license/3\\_01.txt](http://www.php.net/license/3_01.txt), <http://srp.stanford.edu/license.txt>, <http://www.schneider.com/blowfish.html>, <http://www.jmock.org/license.html>, <http://xsom.java.net>, <http://benalman.com/about/license/>, <https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js>, <http://www.h2database.com/html/license.html#summary>, <http://jsoncpp.sourceforge.net/LICENSE>, <http://jdbc.postgresql.org/license.html>, <http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto>, <https://github.com/rantav/hector/blob/master/LICENSE>, <http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html>, <http://jibx.sourceforge.net/jibx-license.html>, <https://github.com/lyokato/libgeohash/blob/master/LICENSE>, <https://github.com/hjiang/jsonxx/blob/master/LICENSE>, <https://code.google.com/p/lz4/>, <https://github.com/jedisct1/libsodium/blob/master/LICENSE>, <http://one-jar.sourceforge.net/index.php?page=documents&file=license>, <https://github.com/EsotericSoftware/kryo/blob/master/license.txt>, <http://www.scala-lang.org/license.html>, <https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt>, <http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html>, <https://aws.amazon.com/ssl/>, <https://github.com/twbs/bootstrap/blob/master/LICENSE>, <https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt>, <https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE>, and <https://github.com/apache/hbase/blob/master/LICENSE.txt>.

This product includes software licensed under the Academic Free License (<http://www.opensource.org/licenses/afl-3.0.php>), the Common Development and Distribution License (<http://www.opensource.org/licenses/cddl1.php>), the Common Public License (<http://www.opensource.org/licenses/cpl1.0.php>), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (<http://www.opensource.org/licenses/bsd-license.php>), the new BSD License (<http://opensource.org/licenses/BSD-3-Clause>), the MIT License (<http://www.opensource.org/licenses/mit-license.php>), the Artistic License (<http://www.opensource.org/licenses/artistic-license-1.0>) and the Initial Developer's Public License Version 1.0 (<http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/>).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at <http://xstream.codehaus.org/license.html>. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit <http://www.extreme.indiana.edu/>.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at <https://www.informatica.com/legal/patents.html>.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

## NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

Revision: 1

Publication Date: 2018-07-20

# Table of Contents

<b>Preface .....</b>	<b>7</b>
Informatica Resources. ....	7
Informatica Network. ....	7
Informatica Knowledge Base. ....	7
Informatica Documentation. ....	7
Informatica Product Availability Matrixes. ....	8
Informatica Velocity. ....	8
Informatica Marketplace. ....	8
Informatica Global Customer Support. ....	8
 <b>Part I: Dynamic Data Masking Version 9.8.4.....</b>	 <b>9</b>
 <b>Chapter 1: New Features and Enhancements (9.8.4).....</b>	 <b>10</b>
New Features and Enhancements for Version 9.8.4. ....	10
Dynamic Data Masking Server New Features and Enhancements. ....	10
 <b>Chapter 2: Updates and Changed Behavior (9.8.4).....</b>	 <b>13</b>
Updates and Changed Behavior for Version 9.8.4. ....	13
 <b>Part II: Dynamic Data Masking Version 9.8.3.....</b>	 <b>14</b>
 <b>Chapter 3: New Features and Enhancements (9.8.3).....</b>	 <b>15</b>
New Features and Enhancements for Version 9.8.3. ....	15
Dynamic Data Masking Server New Features and Enhancements. ....	15
 <b>Part III: Dynamic Data Masking Verison 9.8.2.....</b>	 <b>18</b>
 <b>Chapter 4: New Features and Enhancements (9.8.2).....</b>	 <b>19</b>
New Features and Enhancements for Version 9.8.2. ....	19
Dynamic Data Masking Server New Features and Enhancements. ....	19
 <b>Part IV: Dynamic Data Masking Version 9.8.1.....</b>	 <b>20</b>
 <b>Chapter 5: New Features and Enhancements (9.8.1).....</b>	 <b>21</b>
New Features and Enhancements for Version 9.8.1. ....	21
Dynamic Data Masking Server New Features and Enhancements. ....	21
Generic JDBC and ODBC Wrapper New Features and Enhancements. ....	22
Management Console New Features and Enhancements. ....	23
Accelerator New Features and Enhancements. ....	23

<b>Part V: Dynamic Data Masking Version 9.8.0.....</b>	<b>24</b>
<b>Chapter 6: New Features and Enhancements (9.8.0).....</b>	<b>25</b>
New Features and Enhancements for Version 9.8.0. ....	25
Accelerator New Features and Enhancements. ....	25
Dynamic Data Masking Server New Features and Enhancements. ....	25
<b>Chapter 7: Updates and Changed Behavior (9.8.0).....</b>	<b>27</b>
Updates and Changed Behavior for Version 9.8.0. ....	27
Installation Updates and Changed Behavior. ....	27
Accelerator Updates and Changed Behavior. ....	28
<b>Part VI: Dynamic Data Masking Version 9.7.0.....</b>	<b>29</b>
<b>Chapter 8: New Features and Enhancements (9.7.0).....</b>	<b>30</b>
New Features and Enhancements for Version 9.7.0. ....	30
Accelerator New Features and Enhancements. ....	30
<b>Part VII: Dynamic Data Masking Version 9.6.2.....</b>	<b>31</b>
<b>Chapter 9: New Features and Enhancements (9.6.2).....</b>	<b>32</b>
New Features and Enhancements for Version 9.6.2. ....	32
Dynamic Data Masking Server New Features and Enhancements. ....	32
Accelerator New Features and Enhancements. ....	33
<b>Part VIII: Dynamic Data Masking Version 9.6.1.....</b>	<b>34</b>
<b>Chapter 10: New Features and Enhancements (9.6.1).....</b>	<b>35</b>
New Features and Enhancements for Version 9.6.1. ....	35
Dynamic Data Masking Server New Features and Enhancements. ....	35
Management Console New Features and Enhancements. ....	36
Accelerator New Features and Enhancements. ....	36
<b>Chapter 11: Updates and Changed Behavior (9.6.1).....</b>	<b>37</b>
Updates and Changed Behavior for Version 9.6.1. ....	37
Accelerator Updates and Changed Behavior. ....	37
<b>Part IX: Dynamic Data Masking Version 9.6.0.....</b>	<b>38</b>
<b>Chapter 12: New Features and Enhancements (9.6.0).....</b>	<b>39</b>
New Features and Enhancements for Version 9.6.0. ....	39
Dynamic Data Masking Server New Features and Enhancements. ....	39
Accelerator New Features and Enhancements. ....	40

<b>Part X: Dynamic Data Masking Version 9.5.3.....</b>	<b>41</b>
<b>Chapter 13: New Features and Enhancements (9.5.3).....</b>	<b>42</b>
New Features and Enhancements for Version 9.5.3. . . . .	42
Dynamic Data Masking Server New Features and Enhancements. . . . .	42
Management Console New Features and Enhancements. . . . .	42
<b>Part XI: Dynamic Data Masking Version 9.5.2.....</b>	<b>43</b>
<b>Chapter 14: New Features and Enhancements (9.5.2).....</b>	<b>44</b>
New Features and Enhancements for Version 9.5.2. . . . .	44
Dynamic Data Masking Server New Features and Enhancements. . . . .	44
Management Console New Features and Enhancements. . . . .	44
Installation New Features and Enhancements. . . . .	45
Accelerator New Features and Enhancements. . . . .	45
<b>Chapter 15: Updates and Changed Behavior (9.5.2).....</b>	<b>46</b>
Updates and Changed Behavior for Version 9.5.2. . . . .	46
Management Console Updates and Changed Behavior. . . . .	46
<b>Part XII: Dynamic Data Masking Version 9.5.1.....</b>	<b>47</b>
<b>Chapter 16: New Features and Enhancements (9.5.1).....</b>	<b>48</b>
New Features and Enhancements for Version 9.5.1. . . . .	48
Installation New Features and Enhancements. . . . .	48
Dynamic Data Masking Server New Features and Enhancements. . . . .	48
Management Console New Features and Enhancements. . . . .	48
Accelerators New Features and Enhancements. . . . .	49
Log Loader New Features and Enhancements. . . . .	49
<b>Part XIII: Dynamic Data Masking Version 9.5.0.....</b>	<b>50</b>
<b>Chapter 17: New Features and Enhancements (9.5.0).....</b>	<b>51</b>
New Features and Enhancements for Version 9.5.0. . . . .	51
Dynamic Data Masking Server New Features and Enhancements. . . . .	51
Management Console New Features and Enhancements. . . . .	51
<b>Chapter 18: Updates and Changed Behavior (9.5.0).....</b>	<b>53</b>
Updates and Changed Behavior for Version 9.5.0. . . . .	53
Management Console Updates and Changed Behavior. . . . .	53
Installation Updates and Changed Behavior. . . . .	53

# Preface

The *Informatica Dynamic Data Masking Release Guide* is written for system administrators who are responsible for the configuration of Dynamic Data Masking. This guide assumes that you have knowledge of your operating systems, relational database concepts, and the database engines in your environment. The *Informatica Dynamic Data Masking Release Guide* lists new features and enhancements and behavior changes between versions.

## Informatica Resources

### Informatica Network

Informatica Network hosts Informatica Global Customer Support, the Informatica Knowledge Base, and other product resources. To access Informatica Network, visit <https://network.informatica.com>.

As a member, you can:

- Access all of your Informatica resources in one place.
- Search the Knowledge Base for product resources, including documentation, FAQs, and best practices.
- View product availability information.
- Review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

### Informatica Knowledge Base

Use the Informatica Knowledge Base to search Informatica Network for product resources such as documentation, how-to articles, best practices, and PAMs.

To access the Knowledge Base, visit <https://kb.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at [KB\\_Feedback@informatica.com](mailto:KB_Feedback@informatica.com).

### Informatica Documentation

To get the latest documentation for your product, browse the Informatica Knowledge Base at [https://kb.informatica.com/\\_layouts/ProductDocumentation/Page/ProductDocumentSearch.aspx](https://kb.informatica.com/_layouts/ProductDocumentation/Page/ProductDocumentSearch.aspx).

If you have questions, comments, or ideas about this documentation, contact the Informatica Documentation team through email at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

## Informatica Product Availability Matrixes

Product Availability Matrixes (PAMs) indicate the versions of operating systems, databases, and other types of data sources and targets that a product release supports. If you are an Informatica Network member, you can access PAMs at

<https://network.informatica.com/community/informatica-network/product-availability-matrices>.

## Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services. Developed from the real-world experience of hundreds of data management projects, Informatica Velocity represents the collective knowledge of our consultants who have worked with organizations from around the world to plan, develop, deploy, and maintain successful data management solutions.

If you are an Informatica Network member, you can access Informatica Velocity resources at <http://velocity.informatica.com>.

If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at [ips@informatica.com](mailto:ips@informatica.com).

## Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that augment, extend, or enhance your Informatica implementations. By leveraging any of the hundreds of solutions from Informatica developers and partners, you can improve your productivity and speed up time to implementation on your projects. You can access Informatica Marketplace at <https://marketplace.informatica.com>.

## Informatica Global Customer Support

You can contact a Global Support Center by telephone or through Online Support on Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:

<http://www.informatica.com/us/services-and-training/support-services/global-support-centers>.

If you are an Informatica Network member, you can use Online Support at <http://network.informatica.com>.



# Part I: Dynamic Data Masking

## Version 9.8.4

This part contains the following chapters:

- [New Features and Enhancements \(9.8.4\), 10](#)
- [Updates and Changed Behavior \(9.8.4\), 13](#)

# CHAPTER 1

## New Features and Enhancements (9.8.4)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.8.4, 10](#)

## New Features and Enhancements for Version 9.8.4

This section describes the new features and enhancements for version 9.8.4.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.8.4.

#### SSL Communication

SSL communication in Dynamic Data Masking is enhanced to support multiple keystores within the Dynamic Data Masking Server. The Dynamic Data Masking Server can load multiple existing keystores that can contain multiple certificates. Previously, the Dynamic Data Masking Server could load one keystore, the Dynamic Data Masking keystore. The Dynamic Data Masking keystore, previously used for the connection between the database client and the Dynamic Data Masking Server, is no longer required.

The Dynamic Data Masking Server can also load multiple truststores that can contain multiple certificates. Previously, the Dynamic Data Masking Server could load one truststore and you were required to import all public database certificates to the Dynamic Data Masking truststore.

Dynamic Data Masking 9.8.4 now supports SSL communication between the Management Console and Server Control, to the Dynamic Data Masking Server.

You can configure SSL communication in Dynamic Data Masking to use various network protocols and cipher suites available in the Java Virtual Machine that Dynamic Data Masking runs on.

SSL communication in Dynamic Data Masking is available for Oracle, Microsoft SQL Server, and IBM DB2 databases.

For more information, see the *Dynamic Data Masking Administrator Guide*.

## Secure@Source Integration

You can use Dynamic Data Masking to mask columns or block requests to a table that Informatica Secure@Source has identified as sensitive. From Secure@Source, you can export a CSV file that contains information about a particular data store. When you import the CSV file in Dynamic Data Masking, Dynamic Data Masking identifies which columns in the data store tables are protected by a security rule in Dynamic Data Masking. If a column is not protected by any security rule, you can apply a security rule at the column level or block requests to the table at the table level.

For more information, see the *Dynamic Data Masking User Guide*.

## Kerberos Support for Impala and Hive Databases

The Dynamic Data Masking services for Hive and Impala databases support the Kerberos protocol of authentication and encryption. In a Kerberos implementation for Hive or Impala, Dynamic Data Masking gets the client user context and forwards it to the Hive or Impala server. Dynamic Data Masking uses database user context delegation to maintain the client user context on a Hive or Impala database.

Dynamic Data Masking uses the Simple Authentication and Security Layer (SASL) framework for Kerberos context establishment between the database client and the Dynamic Data Masking Server, and the Dynamic Data Masking Server and the Hive or Impala database.

For more information, see the *Dynamic Data Masking Administrator Guide*.

## Teradata COP Support

Dynamic Data Masking supports Teradata COP discovery. Dynamic Data Masking performs COP discovery once for all Teradata databases when the Dynamic Data Masking Server starts. Dynamic Data Masking uses the same naming convention as the Teradata JDBC driver to find COP hosts. COP functionality in Dynamic Data Masking discovers COP host names, not IP addresses as with the Teradata JDBC driver.

For more information, see the *Dynamic Data Masking High Availability Guide*.

## Result Set Masking for Microsoft SQL Server

Dynamic Data Masking can mask a result set returned by a Microsoft SQL Server stored procedure call. The result set masking functionality does not require creation of temporary tables in the database. Result set masking is available for numeric, string, date, and XML data types.

The following new matchers are available for Microsoft SQL Server result set masking:

- Procedure Call matcher
- Metadata matcher

The following new actions are available for Microsoft SQL Server result set masking:

- Process Result action
- Content Masking action
- Masking action
- Custom Transformer action
- Apply Masking action

For more information, see the *Dynamic Data Masking User Guide*.

## Session Changing Commands

You can use session changing commands in Microsoft SQL Server and Sybase target databases. For more information see the *Dynamic Data Masking Administrator Guide*.

## Native Protocol Deployment with Hive and Impala Databases

Dynamic Data Masking supports Hive2 and Impala native protocols. The service DDM for Impala is available for use.

## CHAPTER 2

# Updates and Changed Behavior (9.8.4)

This chapter includes the following topic:

- [Updates and Changed Behavior for Version 9.8.4, 13](#)

## Updates and Changed Behavior for Version 9.8.4

This section describes the updates and changed behavior for version 9.8.4.

### Masking Functionality

By default, version 9.8.4 uses an enhanced masking functionality that might modify certain types of SQL statements differently than previous versions.

If you want to use the previous masking functionality, you can set the property in `jvm.params`.

# Part II: Dynamic Data Masking

## Version 9.8.3

This part contains the following chapter:

- [New Features and Enhancements \(9.8.3\), 15](#)

## CHAPTER 3

# New Features and Enhancements (9.8.3)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.8.3, 15](#)

## New Features and Enhancements for Version 9.8.3

This section describes the new features and enhancements for version 9.8.3.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.8.3.

#### SSL Communication

You can enable the Dynamic Data Masking Server to operate in SSL mode between a database server and database client. SSL functionality is available for Oracle, Microsoft SQL Server, and Informatica Data Vault 6.4.3 databases.

For more information about SSL communication in Dynamic Data Masking, see the *Dynamic Data Masking 9.8.3 Administrator Guide*.

#### Dynamic Data Masking Service Configuration

When you create or edit a service node for an Oracle database or Informatica Data Vault version 6.4.3, you can configure the "Security" parameter to enable SSL communication.

With the "Address" parameter, you can also provide an IP address for a specific Dynamic Data Masking listener port. The address parameter ensures that the Dynamic Data Masking service listens on the specified port only at the given address. The address parameter is optional and is available for Oracle, Informatica Data Vault, Microsoft SQL Server, IBM DB2, Informix, Teradata, Sybase, and Generic JDBC and ODBC databases.

For more information about Dynamic Data Masking service configuration, see the *Dynamic Data Masking 9.8.3 Administrator Guide*.

## IP Address Binding

You can use the `setAddress` command to enable IP address binding if you want multiple Dynamic Data Masking Servers to run on the same machine and use the same listener port. You can also use the same listener port for multiple Dynamic Data Masking services when the same service is defined on different Dynamic Data Masking Servers.

For more information about IP address binding in Dynamic Data Masking, see the *Dynamic Data Masking 9.8.3 Administrator Guide*.

## Credentials Management

You can use a key store to protect target database credentials and a security provider to access the key store. When you configure a target database connection, choose either the default key store and security provider, or a custom key store and security provider. The default key store and security provider are pre-configured for use with Dynamic Data Masking. You must configure custom key store and security providers for use with Dynamic Data Masking.

For more information about credentials management, see the *Dynamic Data Masking 9.8.3 Administrator Guide*.

## Server Control

You can use the following Server Control commands:

### **server config setKeyStore**

Sets the type of key store, either default or custom, used for a particular target database.

### **server setAddress**

Sets the network address of the Dynamic Data Masking Server to enable IP address binding.

### **server removeAddress**

Removes the Dynamic Data Masking Server network address that you added with the `setAddress` Server Control command.

### **server displayAddress**

Displays the Dynamic Data Masking Server network address that you added with the `setAddress` Server Control command.

For more information about Server Control commands, see the *Dynamic Data Masking 9.8.3 Administrator Guide*.

## Connection Rules

Dynamic Data Masking version 9.8.3 contains the following connection rule matchers:

### **Incoming DDM Listener Address Matcher**

The Incoming DDM Listener Address matcher searches for the Dynamic Data Masking listener address in the incoming connection.

For more information about the connection rule matchers, see the *Dynamic Data Masking 9.8.3 User Guide*.

## Database Parsers

Specific parsers are available for the following databases:

- IBM DB2
- Teradata
- Sybase
- Hive and Impala



- Microsoft SQL Server 2016

# Part III: Dynamic Data Masking

## Verison 9.8.2

This part contains the following chapter:

- [New Features and Enhancements \(9.8.2\), 19](#)

## CHAPTER 4

# New Features and Enhancements (9.8.2)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.8.2, 19](#)

## New Features and Enhancements for Version 9.8.2

This section describes the new features and enhancements for version 9.8.2.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.8.2.

#### SSL Communication

The Dynamic Data Masking Server uses SSL communication. You can enable SSL communication between the Dynamic Data Masking Server and the Data Vault, and between the Dynamic Data Masking Server and the Data Vault client. When you enable SSL communication in the Data Vault, SSL communication is automatically enabled in the Dynamic Data Masking Server.

For more information about SSL communication in Dynamic Data Masking, see the *Dynamic Data Masking 9.8.2 Administrator Guide*.

#### Security Rule Parser Matcher

The Parser matcher identifies requests that Dynamic Data Masking is unable to parse. You can use the Parser matcher with security rule actions to change the request. For example, you can use the Block Statement rule action to block requests that Dynamic Data Masking cannot parse.

For more information about the Parser matcher, see the *Dynamic Data Masking 9.8.2 User Guide*.

# Part IV: Dynamic Data Masking

## Version 9.8.1

This part contains the following chapter:

- [New Features and Enhancements \(9.8.1\), 21](#)

## CHAPTER 5

# New Features and Enhancements (9.8.1)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.8.1, 21](#)

## New Features and Enhancements for Version 9.8.1

This section describes the new features and enhancements for version 9.8.1.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.8.1.

#### Generic Database Node

Dynamic Data Masking impersonates the user context for a generic database node.

You can enter a sanity check script in the Management Console to verify that the connection to the database is valid.

For more information about the generic database node, see the *Dynamic Data Masking 9.8.1 Administrator Guide*.

#### Predefined Security Rule Sets

The Dynamic Data Masking installation contains predefined security rule sets that you can use with a generic database node if you want to run commands that alter the user context. The rule set captures the commands and updates the Dynamic Data Masking symbols for the session.

You can use predefined rule sets for the following databases:

- Greenplum
- MySQL
- Netezza

For more information about the predefined security rule sets, see the *Dynamic Data Masking 9.8.1 Administrator Guide*.

## Server Control

You can use the following Server Control commands:

### **server support**

Creates a .zip archive of Dynamic Data Masking logs. You can send the encrypted log archive to Informatica Global Customer Support to troubleshoot issues with Dynamic Data Masking.

### **server encrypt**

Encrypts a file that contains sensitive information so that you can send the file to Informatica Global Customer Support. Informatica Global Customer Support can decrypt files that you encrypt with the `encrypt` command.

For more information about Server Control commands, see the *Dynamic Data Masking 9.8.1 Administrator Guide*.

## Mask Rule Action

The security rule Mask action contains a **Keep original number of rows** checkbox that you can use to preserve the original number of rows in the masked output when the query contains the DISTINCT operator or a GROUP BY, HAVING, or ORDER BY clause. The default value is unchecked. The unchecked value is backward compatible with previous versions of Dynamic Data Masking.

You can mask SQL batch in Sybase and Microsoft SQL Server databases.

For more information about the Mask action, see the *Dynamic Data Masking 9.8.1 User Guide*.

## Troubleshooting

You can create an encrypted log archive .zip file that you can send to Informatica Global Customer Support to troubleshoot issues with Dynamic Data Masking. You can create the file in the Management Console or with the Server Control `server support` command.

For information about how to create the file, see the *Dynamic Data Masking 9.8.1 Administrator Guide*.

# Generic JDBC and ODBC Wrapper New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking generic JDBC and ODBC wrappers for version 9.8.1.

## JDBC Wrapper Logging

The Dynamic Data Masking installation contains a template configuration file for JDBC logging. If you use the DDM for JDBC service, you can configure logging on the client machine to debug the JDBC wrapper.

For information about configuring JDBC logging, see the *Dynamic Data Masking 9.8.1 Administrator Guide*.

## ODBC Wrapper Logging

The Dynamic Data Masking installation contains a template configuration file for ODBC logging. If you use the DDM for ODBC service, you can configure logging on the client machine to debug the Driver Manager proxy.

For information about configuring ODBC logging, see the *Dynamic Data Masking 9.8.1 Administrator Guide*.

## Management Console New Features and Enhancements

This section describes the new features and enhancements for the Management Console for version 9.8.1.

### Menu

The Tree menu contains a **Support** option that you can use to create an encrypted .zip archive of Dynamic Data Masking logs. You can send the log archive to Informatica Global Customer Support to troubleshoot issues with Dynamic Data Masking.

For more information about the Management Console, see the *Dynamic Data Masking 9.8.1 User Guide*.

## Accelerator New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.8.1.

### Stored Procedure Accelerator for DB2

When you set up the stored procedure accelerator for DB2, you can create the CLEANUP\_TEMP\_OBJECTS procedure and schedule the procedure job to drop the temporary tables and stored procedures that the accelerator creates in the DB2 TempDB schema as part of the masking process.

For more information about the stored procedure accelerator for DB2, see the *Dynamic Data Masking 9.8.1 Stored Procedure Accelerator Guide for DB2*.

### Stored Procedure Accelerator for Microsoft SQL Server

When you set up the stored procedure for Microsoft SQL Server, you can create the CLEANUP\_TEMP\_OBJECTS procedure and schedule the procedure job to drop the temporary tables that the accelerator creates in the TempDB database as part of the masking process.

For more information about the stored procedure accelerator for Microsoft SQL Server, see the *Dynamic Data Masking 9.8.1 Stored Procedure Accelerator Guide for Microsoft SQL Server*.

### Stored Procedure Accelerator for Sybase

When you set up the stored procedure accelerator for Sybase, you can create a cleanup task on Windows or a cleanup job on Linux to drop the temporary tables and stored procedures that the accelerator creates in the temporary database as part of the masking process.

For more information about the stored procedure accelerator for Sybase, see the *Dynamic Data Masking 9.8.1 Stored Procedure Accelerator Guide for Sybase*.

# Part V: Dynamic Data Masking

## Version 9.8.0

This part contains the following chapters:

- [New Features and Enhancements \(9.8.0\), 25](#)
- [Updates and Changed Behavior \(9.8.0\), 27](#)



## CHAPTER 6

# New Features and Enhancements (9.8.0)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.8.0, 25](#)

## New Features and Enhancements for Version 9.8.0

This section describes the new features and enhancements for version 9.8.0.

### Accelerator New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.8.0.

#### Stored Procedure Accelerator for Oracle

The Stored Procedure Accelerator for Oracle supports prepared statement caching.

Optionally, you can use the `MATCH_FUNCTION` and `MATCH_FUNCTION_PARAMS` symbols and a user-defined function to determine whether to mask a stored procedure. You define the symbols in the `DefMaskRSSym` rule and specify the number of arguments that you want to pass to the function.

For more information, see the *Dynamic Data Masking 9.8.0 Stored Procedure Accelerator Guide for Oracle*.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.8.0.

#### Connection Rules

Dynamic Data Masking version 9.8.0 contains the following connection rule matchers:

##### **Check Database DSN Matcher**

The Check Database DSN matcher identifies a request based on the data source name of the database. The Check Database DSN matcher is available for the DDM for ODBC service.

### **Check Database URL Matcher**

The Check Database URL matcher identifies a request based on the URL that the client application gives for the driver. The Check Database URL matcher is available for the DDM for JDBC service.

### **Check Property Matcher**

The Check Property Matcher identifies a request based on a property provided by the ODBC or JDBC driver. The Check Property matcher is available for the DDM for ODBC and DDM for JDBC services.

For more information about the connection rule matchers, see the *Dynamic Data Masking 9.8.0 User Guide*.

### **Generic Database Node**

Create a Generic Database connection node to mask data for a database that uses JDBC or ODBC connectivity. Dynamic Data Masking retrieves metadata from the database to mask the SQL request and sends the altered request back to the client. The client then sends the masked request to the database and the database returns masked data.

For more information about the Generic Database node, see the *Dynamic Data Masking 9.8.0 Administrator Guide*.

### **Services**

The Dynamic Data Masking Server contains services for JDBC and ODBC connectivity. Use the DDM for JDBC service to mask data for a database that uses JDBC connectivity. Use the DDM for ODBC service to mask data for a database that uses ODBC connectivity.

For more information about the DDM for JDBC and DDM for ODBC services, see the *Dynamic Data Masking 9.8.0 Administrator Guide*.

## CHAPTER 7

# Updates and Changed Behavior (9.8.0)

This chapter includes the following topic:

- [Updates and Changed Behavior for Version 9.8.0, 27](#)

## Updates and Changed Behavior for Version 9.8.0

This section describes the updates and changed behavior for version 9.8.0.

### Installation Updates and Changed Behavior

This section describes the updates and changed behavior for installation for version 9.8.0.

#### Dynamic Data Masking Server

On Windows, the Dynamic Data Masking Server installation updates the system path to include the Dynamic Data Masking installation `jre\bin` directory.

Previously, the Dynamic Data Masking Server installation required the Java DLL files to be in the Windows system directory.

For more information, see the *Dynamic Data Masking 9.8.0 Installation and Upgrade Guide*.

#### Java Version

On Windows and Linux, Java SE 7 is installed with the Dynamic Data Masking Server. On UNIX, the machine where you install the Dynamic Data Masking Server must have Java SE 7 installed.

Previously, the installer installed Java SE 6 on Windows and Linux, and the UNIX machine had to have Java SE 6 installed.

For more information, see the *Dynamic Data Masking 9.8.0 Installation and Upgrade Guide*.

## Accelerator Updates and Changed Behavior

This section describes the updates and changed behavior for Dynamic Data Masking accelerators for version 9.8.0.

### Stored Procedure Accelerator for Oracle

Effective version 9.8.0, you must compile the DDM\_SP\_MASKING PL/SQL package before you set up the accelerator. Previously, you did not have to compile a package.

For more information, see the *Dynamic Data Masking 9.8.0 Stored Procedure Accelerator Guide for Oracle*.

# Part VI: Dynamic Data Masking

## Version 9.7.0

This part contains the following chapter:

- [New Features and Enhancements \(9.7.0\), 30](#)

## CHAPTER 8

# New Features and Enhancements (9.7.0)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.7.0, 30](#)

## New Features and Enhancements for Version 9.7.0

This section describes the new features and enhancements for version 9.7.0.

### Accelerator New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.7.0.

#### Stored Procedure Accelerator for Oracle

The Stored Procedure Accelerator for Oracle masks stored procedures and user-defined functions in an Oracle database.

For more information, see the *Dynamic Data Masking 9.7.0 Stored Procedure Accelerator for Oracle*.

# Part VII: Dynamic Data Masking

## Version 9.6.2

This part contains the following chapter:

- [New Features and Enhancements \(9.6.2\), 32](#)

## CHAPTER 9

# New Features and Enhancements (9.6.2)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.6.2, 32](#)

## New Features and Enhancements for Version 9.6.2

This section describes the new features and enhancements for version 9.6.2.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.6.2.

#### Check Server Name Matcher

You can use the Check Server Name connection rule matcher to apply the connection rule action based on the name of the Dynamic Data Masking Server that receives the request.

For more information about the Check Server Name connection rule matcher, see the *Dynamic Data Masking 9.6.2 User Guide*.

#### Microsoft SQL Server Database Connection

You can use the Server Instance Name parameter to connect to a Microsoft SQL Server database that is configured to use dynamic port allocation.

For more information about the Server Instance Name parameter, see the *Dynamic Data Masking 9.6.2 Administrator Guide*.

#### Server Control

You can use the following Server Control commands:

##### **config export**

Exports a Dynamic Data Masking database or security rule set from the Dynamic Data Masking Server.

##### **config import**

Imports a Dynamic Data Masking database or security rule set into one or more Dynamic Data Masking Servers.



**config setDBPassword**

Sets the password for the Dynamic Data Masking databases in one or more Dynamic Data Masking Servers.

**config sync**

Synchronizes the Dynamic Data Masking configuration between one source Dynamic Data Masking Server and one or more target Dynamic Data Masking Servers.

**service export**

Exports a Dynamic Data Masking service from the Dynamic Data Masking Server.

**service import**

Imports a Dynamic Data Masking service into one or more Dynamic Data Masking Servers.

For more information about Server Control commands, see the *Dynamic Data Masking 9.6.2 Administrator Guide*.

## Accelerator New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.6.2.

### [Stored Procedure Accelerator for DB2](#)

The Stored Procedure Accelerator for DB2 masks stored procedures that use the OUT CURSOR parameter.

For more information, see the *Dynamic Data Masking 9.6.2 Stored Procedure Accelerator for DB2*.

### [Stored Procedure Accelerator for Sybase](#)

You can use the Stored Procedure Accelerator for Sybase to mask Sybase ASE stored procedures in Dynamic Data Masking. The accelerator contains two .jar files that Dynamic Data Masking uses to alter the stored procedures and example security rules.

For more information, see the *Dynamic Data Masking 9.6.2 Stored Procedure Accelerator for Sybase*.

# Part VIII: Dynamic Data Masking

## Version 9.6.1

This part contains the following chapters:

- [New Features and Enhancements \(9.6.1\), 35](#)
- [Updates and Changed Behavior \(9.6.1\), 37](#)

## CHAPTER 10

# New Features and Enhancements (9.6.1)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.6.1, 35](#)

## New Features and Enhancements for Version 9.6.1

This section describes the new features and enhancements for version 9.6.1.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.6.1.

#### Check Database Connection Matcher

You can use the connection rule Check Database Connection matcher to direct requests based on the availability of the database connection.

For more information about the Check Database Connection matcher, see the *Dynamic Data Masking 9.6.1 User Guide*.

#### Load Control Rule Action

You can use the Load Control connection rule action to configure high availability for the Dynamic Data Masking Server for DB2 databases.

For more information about the Load Control action, see the *Dynamic Data Masking 9.6.1 User Guide*.

#### PL/SQL Function Rule Action

You can use the PL/SQL Function security rule action to replace an incoming request with a valid query that Dynamic Data Masking sends to the database for execution.

For more information about the PL/SQL Function security rule action, see the *Dynamic Data Masking 9.6.1 User Guide*.

#### Server Control

You can use the log Server Control command to set and display the Dynamic Data Masking Server log level.

You can use the `setDBPassword` Server Control command to change the password that Dynamic Data Masking uses to connect to the database.

You can use the `sync` Server Control command to sync the Management Console tree of a local Dynamic Data Masking Server with the Management Console tree of a remote Dynamic Data Masking Server.

For more information about Server Control commands, see the *Dynamic Data Masking 9.6.1 Administrator Guide*.

## Management Console New Features and Enhancements

This section describes the new features and enhancements for the Management Console for version 9.6.1.

### Security Rule Simulator

You can simulate security rules, security rule folders, and security rule sets with the Security Rule Simulator. Use the Security Rule Simulator to verify that you created the security rules correctly.

For more information, see the *Dynamic Data Masking 9.6.1 User Guide*.

## Accelerator New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.6.1.

### Stored Procedure Accelerator for DB2

You can use the Stored Procedure Accelerator for DB2 to mask IBM DB2 stored procedures and stored functions in Dynamic Data Masking. The accelerator contains two .jar files that Dynamic Data Masking uses to alter the stored procedures and example security rules.

For more information, see the *Dynamic Data Masking 9.6.1 Stored Procedure Accelerator for DB2*.

## CHAPTER 11

# Updates and Changed Behavior (9.6.1)

This chapter includes the following topic:

- [Updates and Changed Behavior for Version 9.6.1, 37](#)

## Updates and Changed Behavior for Version 9.6.1

This section describes the updates and changed behavior for version 9.6.1.

### Accelerator Updates and Changed Behavior

This section describes the updates and changed behavior for Dynamic Data Masking accelerators for version 9.6.1.

#### Stored Procedure Accelerator for Microsoft SQL Server

Effective version 9.6.1, the Stored Procedure Accelerator for Microsoft SQL Server contains .xml files with the following names:

- SQLServer\_HRStoredProcMasksRS.xml
- SQLServer\_HRStoredProcRS.xml
- SQLServer\_StoredProcMasksRSTmpl.xml
- SQLServer\_StoredProcRSTmpl.xml

Previously, the files had the following names:

- HRStoredProcMasksRS.xml
- HRStoredProcRS.xml
- StoredProcMasksRSTmpl.xml
- StoredProcRSTmpl.xml

# Part IX: Dynamic Data Masking

## Version 9.6.0

This part contains the following chapter:

- [New Features and Enhancements \(9.6.0\), 39](#)

## CHAPTER 12

# New Features and Enhancements (9.6.0)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.6.0, 39](#)

## New Features and Enhancements for Version 9.6.0

This section describes the new features and enhancements for version 9.6.0.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.6.0.

#### Define Symbol Rule Action

You can define multiple symbols with the Define Symbol security rule action. You can specify whether you want the symbol to exist for the client session or the SQL request.

For more information, see the *Dynamic Data Masking 9.6.0 User Guide*.

#### Loggers

The Management Console contains logger and appender nodes that you create to log security rule events. Use the loggers in security rules with the Log Message rule action to define the events that you want to log. Appenders define the format of the log information.

For more information, see the *Dynamic Data Masking 9.6.0 Administrator Guide*.

#### Replace Table Rule Action

The Replace Table security rule action replaces the FROM clause of an SQL request to remove rows that contain sensitive data from the result set.

For more information, see the *Dynamic Data Masking 9.6.0 User Guide*.

## Accelerator New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.6.0.

### Data Archive Accelerator

You can use the Data Archive accelerator to implement Dynamic Data Masking for Data Vault. The Data Archive accelerator contains a .jar file that Dynamic Data Masking uses to extract user and user role information from the SQL request. The accelerator contains an example set of security rules that mask sensitive data in the Loyalty demo database.

For more information, see the *Dynamic Data Masking 9.6.0 Data Archive Accelerator Guide*.

### Stored Procedure Accelerator

You can use the Stored Procedure accelerator to mask Microsoft SQL Server stored procedures and stored functions in Dynamic Data Masking. The stored procedure accelerator contains two .jar files that Dynamic Data Masking uses to alter the stored routines and example security rule sets.

For more information, see the *Dynamic Data Masking 9.6.0 Stored Procedure Accelerator Guide*.



# Part X: Dynamic Data Masking

## Version 9.5.3

This part contains the following chapter:

- [New Features and Enhancements \(9.5.3\), 42](#)

## CHAPTER 13

# New Features and Enhancements (9.5.3)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.5.3, 42](#)

## New Features and Enhancements for Version 9.5.3

This section describes the new features and enhancements for version 9.5.3.

### Dynamic Data Masking Server New Features and Enhancements

The Dynamic Data Masking Server contains services for Hive and File Archive Service. The Dynamic Data Masking for Hive service routes requests to Hive databases. The Dynamic Data Masking for File Archive Service service routes requests to File Archive Service databases.

You can use Dynamic Data Masking Transparent Archive to redirect an SQL request sent to a Microsoft SQL Server database. Dynamic Data Masking redirects the request to a File Archive Service database.

You can use Dynamic Data Masking to access a Netezza database with a server link between a Microsoft SQL Server database and the Netezza database.

### Management Console New Features and Enhancements

Connection rules contain a Transparent Archive rule action that you use to configure Transparent Archive.

# Part XI: Dynamic Data Masking

## Version 9.5.2

This part contains the following chapters:

- [New Features and Enhancements \(9.5.2\), 44](#)
- [Updates and Changed Behavior \(9.5.2\), 46](#)

## CHAPTER 14

# New Features and Enhancements (9.5.2)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.5.2, 44](#)

## New Features and Enhancements for Version 9.5.2

This section describes the new features and enhancements for version 9.5.2.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.5.2.

#### Configuration

The configuration file, config.cfg, and the public key file, config.pbk, have a digital signature that updates when a user performs an operation on the Dynamic Data Masking Server through the Management Console. The Dynamic Data Masking Server does not start if it cannot verify the public key against the configuration file.

#### Dynamic Data Masking Services

The Dynamic Data Masking Server contains services for Informix native protocol, Teradata, and Sybase. The Dynamic Data Masking for Informix native protocol routes requests to Informix databases using the native Informix protocol. The Dynamic Data Masking for Teradata service routes requests to Teradata databases. The Dynamic Data Masking for Sybase service routes requests to Sybase databases.

The Dynamic Data Masking for Microsoft SQL Server service is available for Linux 32 bit, Linux 64 bit, and UNIX.

### Management Console New Features and Enhancements

This section describes the new features and enhancements for the Management Console for version 9.5.2.

#### Access Control

You can manage users and user groups with the authorizations option in the Management Console. You can define the Management Console tree nodes that an LDAP user or an LDAP user group can edit.

### Detailed Audit Trail

The detailed audit trail file contains comprehensive audit information about changes made within the Management Console.

## Installation New Features and Enhancements

This section describes the new features and enhancements for installation for version 9.5.2.

### Silent Installation

You can use silent installation to install and upgrade the Dynamic Data Masking Server and Management Console without user interaction.

### Upgrade

You can manually upgrade the Dynamic Data Masking for Microsoft SQL Server service.

## Accelerator New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.5.2.

### Active Directory Accelerator

The Active Directory accelerator contains predefined rules that allow you to mask data based on the LDAP user or LDAP group that accesses the database. You can define LDAP attributes and LDAP attribute values to define the data you want to mask.

## CHAPTER 15

# Updates and Changed Behavior (9.5.2)

This chapter includes the following topic:

- [Updates and Changed Behavior for Version 9.5.2, 46](#)

## Updates and Changed Behavior for Version 9.5.2

This section describes the updates and changed behavior for version 9.5.2.

### Management Console Updates and Changed Behavior

This section describes the updates and changed behavior for the Management Console for version 9.5.2.

#### Security Rule Sets

Effective version 9.5.2, you add a security rule set to a domain node in the Management Console tree.

Previously, you added a security rule set to the Dynamic Data Masking Server node.

# Part XII: Dynamic Data Masking

## Version 9.5.1

This part contains the following chapter:

- [New Features and Enhancements \(9.5.1\), 48](#)

## CHAPTER 16

# New Features and Enhancements (9.5.1)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.5.1, 48](#)

## New Features and Enhancements for Version 9.5.1

This section describes the new features and enhancements for version 9.5.1.

### Installation New Features and Enhancements

This section describes the new features and enhancements for installation for version 9.5.1.

#### Upgrade

You can upgrade Dynamic Data Masking.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.5.1.

#### Dynamic Data Masking Services

The Dynamic Data Masking Server contains a service for Informix Distributed Relational Database Architecture (DRDA). The DDM for Informix DRDA service routes requests to Informix DRDA databases.

### Management Console New Features and Enhancements

This section describes the new features and enhancements for the Management Console for version 9.5.1.

#### Cut, Copy, and Paste

You can cut, copy, and paste rules, rule folders, database nodes, and domain nodes.



## Accelerators New Features and Enhancements

This section describes the new features and enhancements for the accelerators for version 9.5.1.

### SAP Accelerator

The SAP accelerator configures Dynamic Data Masking to work with SAP. Dynamic Data Masking performs data masking with the SAP cache.

### Siebel Accelerator

The Siebel accelerator package contains predefined security rules. You can import the rules into the Dynamic Data Masking Management Console to facilitate Dynamic Data Masking implementation. The accelerator package contains rules mask data for unauthorized Siebel users and users that belong to unauthorized Siebel positions.

### Active Directory Accelerator

The Active Directory accelerator authorizes access to the database based on user credentials. The accelerator contains sample security rules and connection parameters for an LDAP directory.

## Log Loader New Features and Enhancements

This section describes the new features and enhancements for the Log Loader for version 9.5.1.

### Log Loader

The Log Loader is a program that reads the rule.log file and loads the log information into database tables. You use the database tables to read and sort rule log information. The Log Loader is a separate program from Dynamic Data Masking.

### Reports

Dynamic Data Masking Reports is a program that reads the database tables that the Log Loader creates. The Reports program creates PDF and HTML files of the log information.

# Part XIII: Dynamic Data Masking

## Version 9.5.0

This part contains the following chapters:

- [New Features and Enhancements \(9.5.0\), 51](#)
- [Updates and Changed Behavior \(9.5.0\), 53](#)

## CHAPTER 17

# New Features and Enhancements (9.5.0)

This chapter includes the following topic:

- [New Features and Enhancements for Version 9.5.0, 51](#)

## New Features and Enhancements for Version 9.5.0

This section describes the new features and enhancements for version 9.5.0.

### Dynamic Data Masking Server New Features and Enhancements

This section describes the new features and enhancements for the Dynamic Data Masking Server for version 9.5.0.

#### Server Control

The Server Control program is a command line interface that you use to manage and configure the Dynamic Data Masking Server and start and stop the Dynamic Data Masking services.

#### Dynamic Data Masking Services

The Dynamic Data Masking Server contains services for DB2 and Microsoft SQL Server. The Dynamic Data Masking for DB2 service routes requests to DB2 databases. The Dynamic Data Masking for Microsoft SQL Server service routes requests to Microsoft SQL Server databases.

### Management Console New Features and Enhancements

This section describes the new features and enhancements for the Management Console for version 9.5.0.

#### Domain Node

You use a domain node to group other nodes. You can use domains to create a visual representation of the structure of the databases within an organization.

#### Service Node

Dynamic Data Masking service nodes can now route queries to DB2 and Microsoft SQL Server databases.

## Server Node

The Dynamic Data Masking Server manages databases located under a parent domain or all sub domains of the Server node in the tree. You can move the Server node within the Management Console tree.

## auditTrail.log

The auditTrail.log file logs changes made within the Management Console.

## CHAPTER 18

# Updates and Changed Behavior (9.5.0)

This chapter includes the following topic:

- [Updates and Changed Behavior for Version 9.5.0, 53](#)

## Updates and Changed Behavior for Version 9.5.0

This section describes the updates and changed behavior for version 9.5.0.

### Management Console Updates and Changed Behavior

This section describes the updates and changed behavior for the Management Console for version 9.5.0.

#### Services Editor

You define the listener ports that the Dynamic Data Masking service uses to monitor incoming connection requests in the Services Editor in the Management Console. You can define listener ports for Oracle, DB2, and Microsoft SQL Server databases.

Previously, you defined listener ports in the DNR Manager for Oracle databases.

#### Connection Rules

You use a connection rule to define the criteria that the Rule Engine uses to identify a connection and the target database.

Previously, the name for connection rule was switching rule.

### Installation Updates and Changed Behavior

This section describes the updates and changed behavior for installation for version 9.5.0.

#### Server Start

When you install Dynamic Data Masking, the Dynamic Data Masking Server starts automatically.

Previously, you started the Dynamic Data Masking server manually after installation.