Informatica

Informatica® Dynamic Data Masking
9.9

Release Notes

Informatica Dynamic Data Masking Release Notes
9.9
February 2019

© Copyright Informatica LLC 1993, 2019

Revision: 1
Publication Date: 2019-02-21

Table of Contents

Abstract. iv

Chapter 1: Emergency Bug Fixes (9.9). 5

Chapter 2: Fixed Limitations (9.9). 7

Chapter 3: Known Limitations (9.9). 8

Chapter 4: Informatica Global Customer Support. 9

Abstract

This document contains important information about installation, fixed limitations, and known limitations for Dynamic Data Masking.

CHAPTER 1

Emergency Bug Fixes (9.9)

Dynamic Data Masking 9.9 includes the following emergency bug fixes:

EBF	Reference Number	Description
EBF-14036	DDM-3303	The Masking function cannot mask more than four characters in the value on Microsoft SQL Server databases.
EBF-13720	DDM-3255	Enable the Insert and Select statements for Teradata databases.
EBF-13269	DDM-3188	When you use the Easy Connect Naming method with the SQL*Plus client, Dynamic Data Masking cannot connect to Oracle.
EBF-13136	DDM-3169	When the client machine is enabled for Reverse HostName Lookup, Microsoft SQL Server Management Studio does not connect to the Microsoft SQL Server database immediately.
EBF-12854	DDM-3127	Dynamic Data Masking uses the `jackson-databind-2.8.1` JAR which, according to the National Vulnerability Database, has critical vulnerable exceptions.
EBF-12710	DDM-3095 DDM-3096	You cannot mask data during the creation process of volatile tables in Teradata. The Date-Time expression does not work in Teradata if it does not include the keyword: `extract`
EBF-12203	DDM-3028	When the database is Informix, the Dynamic Data Masking server is unresponsive to clients in a multi-threaded environment.
EBF-11869	- DDM-3000 - DDM-3008 - DDM-2997 - DDM-2960 - DDM-3001	- On machines with Red Hat Linux v7.3, when the Dynamic Data Masking server is repeatedly stoped and started, the server fails to restart. - When OS authentication is enabled for Oracle databases, the Dynamic Data Masking symbols cannot be retrieved. - When Dynamic Data Masking processes split packets of a result set, the CPU usage rises to 99%. - When the database is Microsoft SQL Server or Oracle, the Dynamic Data Masking server cannot parse SQL statements that use identifiers such as TEXT, CONTENT, and LOGIN for column names. - Unable to mask data from Oracle Apps when an SQL statement is sent in multiple packets.
EBF-11764	DDM-2860	The same masking rule is applied to tables with the same name and columns in all schemas even if the masking rule was specified for one schema.

EBF	Reference Number	Description
EBF-11595	DDM-2962	Dynamic Data Masking displays unmasked data on the Oracle Enterprise Resource Planning client.
EBF-11166	DDM-2137	Provide impersonation support for the Informatica Data Vault.

CHAPTER 2

Fixed Limitations (9.9)

Review the Release Notes of previous releases for information about previous fixed limitations.

The following table describes the fixed limitations:

Reference Number	Description
DDM-3027	Unable to mask data in Hive when then syntax contains: `INSERT TABLE...SELECT`
DDM-2941	Unable to import sensitive columns if an existing security rule uses the Any matcher.

CHAPTER 3

Known Limitations (9.9)

The following table describes the known limitations:

Reference Number	Description
DDM-3284	On Teradata databases, Dynamic Data Masking cannot parse the query if the COALESCE function contains the default value.
DDM-3281	On Microsoft SQL Server databases, Dynamic Data Masking cannot bind NULL or empty values in the Stored Procedure Accelerator.
DDM-3233	When a Hive query contains the `insert into...select` syntax, the **From clause** matcher does not function.
DDM-3230	When the Hive node URL in Apache ZooKeeper contains the default Namespace `hiveserver2`, Dynamic Data Masking cannot resolve the _HOST issue.
DDM-3224	On PostgreSQL databases, duplicate columns appear in the result sets for join queries.
DDM-3189	If the Hive database name does not match the client connection URL and the Dynamic Data Masking database node, Dynamic Data Masking cannot mask data.
DDM-3186	When the service is Hive or Hive/HTTP, the **Client/Application Information** matcher does not function.
DDM-3172	When the database is Microsoft Azure SQL Database, the **Client/Application Information** matcher does not function.
DDM-3167	Dynamic Data Masking does not support XML functions in PostgreSQL databases.
DDM-3148	When the database is PostgreSQL and the query contains WITH RECURSIVE, the Parser fails.
DDM-3125	When the database is Microsoft SQL Server and the query contains the relative path in object names, the Parser fails. For example, the Parser fails if the query is: `Select * from ...employee`

CHAPTER 4

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the eSupport option.