



Informatica® Cloud Data Integration

# Advanced FTP V2 Connector

© Copyright Informatica LLC 2019, 2023

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at <https://www.informatica.com/legal/patents.html>.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

#### NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2023-11-29

# Table of Contents

- Preface ..... 4**
  - Informatica Resources. .... 4
    - Informatica Documentation. .... 4
    - Informatica Intelligent Cloud Services web site. .... 4
    - Informatica Intelligent Cloud Services Communities. .... 4
    - Informatica Intelligent Cloud Services Marketplace. .... 5
    - Data Integration connector documentation. .... 5
    - Informatica Knowledge Base. .... 5
    - Informatica Intelligent Cloud Services Trust Center. .... 5
    - Informatica Global Customer Support. .... 5
- Chapter 1: Introduction to Advanced FTP V2 Connector..... 6**
  - Advanced FTP V2 Connector overview. .... 6
  - Advanced FTP V2 supported task types and asset types. .... 7
- Chapter 2: Advanced FTP V2 Connections..... 8**
  - Advanced FTP V2 connections overview. .... 8
  - Advanced FTP V2 connection properties. .... 8
- Chapter 3: File transfer..... 11**
  - sendfiles. .... 11
  - receivefiles. .... 13
  - job. .... 15
- Index..... 16**

# Preface

Use the Advanced FTP V2 Connector to learn how to read files from and to write files to an FTP server. Learn how to create a connection and how to use connections in file ingestion tasks and in B2B Gateway.

## Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

### Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit <https://docs.informatica.com>.

Informatica maintains documentation for many products on the Informatica Knowledge Base in addition to the Documentation Portal. If you cannot find documentation for your product or product version on the Documentation Portal, search the Knowledge Base at <https://search.informatica.com>.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

### Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at <http://www.informatica.com/cloud>. This site contains information about Data Integration editions and applications as well as information about other Informatica Cloud integration services.

### Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

<https://network.informatica.com/community/informatica-network/products/cloud-integration>

To find resources on using Application Integration (the Informatica Cloud Real Time service), access the community at:

<https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-application-integration/content>

Developers can learn more and share tips at the Cloud Developer community:

<https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers>

## Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and maplets:

[https://marketplace.informatica.com/community/collections/cloud\\_integration](https://marketplace.informatica.com/community/collections/cloud_integration)

## Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Informatica Cloud Community:

<https://network.informatica.com/cloud/index.htm>

## Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit <https://search.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at [KB\\_Feedback@informatica.com](mailto:KB_Feedback@informatica.com).

## Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at <https://www.informatica.com/trust-center.html>.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The [Informatica Intelligent Cloud Services Status](#) page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, go to the [Informatica Intelligent Cloud Services Status](#) page and click **SUBSCRIBE TO UPDATES**. You can then choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

## Informatica Global Customer Support

You can contact a Customer Support Center by telephone or online.

For online support, click **Submit Support Request** in Informatica Intelligent Cloud Services. You can also use Online Support to log a case. Online Support requires a login. You can request a login at <https://network.informatica.com/welcome>.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at <https://www.informatica.com/services-and-training/support-services/contact-us.html>.

# CHAPTER 1

## Introduction to Advanced FTP V2 Connector

This chapter includes the following topics:

- [Advanced FTP V2 Connector overview, 6](#)
- [Advanced FTP V2 supported task types and asset types, 7](#)

### Advanced FTP V2 Connector overview

Advanced FTP V2 Connector enables you to securely transfer to and from FTP servers.

When you transfer files to and from an FTP server, you can specify the Secure Agent. When you use FTP objects in file ingestion tasks, you configure properties specific to FTP.

Create an Advanced FTP V2 connection and use the connection as a source or as a target in file ingestion tasks and B2B Gateway partner flows.

When you create an Advanced FTP V2 connection, you specify the runtime environment that contains the Secure Agent. Create an Advanced FTP V2 connection to specify the location of FTP sources or targets that you want to include in a file ingestion task and B2B Gateway partner flows.

When you run a file ingestion task, the Secure Agent transfers files to or from an FTP server, based on the task and the Advanced FTP V2 connection configuration. The Secure Agent connects and reads files from and writes files to the FTP server through a TCP/IP network.

When you use an Advanced FTP V2 source in a file ingestion task, you can schedule the task to receive notifications from a file listener.

#### Example

You work for an organization that stores audit trail logs in an on-premises FTP server. You need to move data from the on-premises FTP site to an affordable cloud-based environment. Create a file ingestion task to read all the audit trail logs from the FTP server and write them to an Amazon S3 target.

# Advanced FTP V2 supported task types and asset types

The following table lists the tasks and asset types that the Advanced FTP V2 Connector supports:

Task Type	Source	Target
File Ingestion	Yes	Yes

## CHAPTER 2

# Advanced FTP V2 Connections

This chapter includes the following topics:

- [Advanced FTP V2 connections overview, 8](#)
- [Advanced FTP V2 connection properties, 8](#)

## Advanced FTP V2 connections overview

An Advanced FTP V2 connection enables you to read data from and write data to FTP servers. You can use an Advanced FTP V2 connection to specify sources and targets in file ingestion tasks.

Create an Advanced FTP V2 connection on the **Connections** page and associate it with a file ingestion task. Define the source properties to read from an FTP server or define the target properties to write to an FTP server.

## Advanced FTP V2 connection properties

When you set up an Advanced FTP V2 connection, you must configure the connection properties.

The following table describes the Advanced FTP V2 connection properties:

Connection property	Description
Connection Name	The name of the connection. The name is not case sensitive and must be unique within the domain. You can change this property after you create the connection. The name cannot exceed 128 characters, contain spaces, or contain the following special characters:~`!\$%^&*() - + = {[]}  \ : ; " ' < , > . ? /
Description	Optional. The description of the connection. The description cannot exceed 4,000 characters.
Type	Select the <b>Advanced FTP V2</b> connection type.
Runtime Environment	The name of the runtime environment where you want to run the tasks. Specify a Secure Agent.
Host	The host name or IP address of the FTP server.



Connection property	Description
Port	The port number to use for connecting to the FTP server. If left blank, the default port number 21 is used.
Username	User name to connect to the FTP server.
Password	Password to connect to the FTP server.
Folder Path	The directory to use after connecting to the FTP server.
Use passive mode	<p>Indicates whether the connection uses <b>Passive</b> or <b>Active</b> mode. Specify <b>Yes</b> to use <b>Passive</b> mode. Specify <b>No</b> to use <b>Active</b> mode.</p> <p>The default value is <b>Yes</b>.</p> <p>In Passive mode, the server does not need to connect back to a port on the connection client, which is a firewall-friendly mode. If you have problems with connecting to the server, you might want to change the mode to Passive by selecting <b>Yes</b> for this option. In Passive mode, depending on the FTP server, the connection may require high port range based on the port availability to transfer data.</p> <p>In Active mode, the server attempts to connect back to a port on the connection client to perform the data transfer.</p>
Data Connection Start Port	The starting port number to use for the data connection.
Data Connection End Port	The ending port number to use for the data connection.
Timeout	The number of seconds to wait when attempting to connect to the server. A timeout occurs if the connection cannot be established in the specified amount of time. If left blank, the default value of 120 seconds is used.
Connection Retry Attempts	The number of times to connect to retry the FTP connection if a connection cannot be established. This setting is used for both the initial connection and any reconnect attempts due to lost connections. If left blank, no retries will be attempted.
Connection Retry Interval	<p>The number of seconds to wait between each connection retry attempt.</p> <p><b>Note:</b> For instance, if you want to retry to connect up to 10 times with a five second delay between retries, then specify <b>10</b> for the <b>Connection Retry Attempts</b> and <b>5</b> for the <b>Connection Retry Interval</b>.</p>
Control Encoding	If left blank, the connection uses the ISO standard ISO-8859-1. If supported by the server, other encodings such as UTF-8 can be specified to support international characters.
List Parser	The list parser to use for the server connection. If the field is left blank, the Advanced FTP V2 Connector attempts to use the MLSD parser. If the MLSD parser is not supported by the server, the UNIX parser is used. If you experience problems listing directories, select a different list parser.

Connection property	Description
Date Format	This date format is applied if the server returns a date that is different from the selected list parser default. If your location requires a different date format (for example, d MMM yyyy), specify the date format in this field. Not all list parsers support the date format setting. List parsers that do not support the date format setting ignores any user specified value.
Recent Date Format	Specify the date format to use when parsing the recent last modified date for each file. The recent date format applies in UNIX-based systems and appears on entries less than a year old. If your location requires a specific date format (for example, d MMM HH:mm), specify that pattern in this field. Not all list parsers support the recent date format setting. List parsers that do not support the recent date format setting ignores any user-specified value.

## CHAPTER 3

# File transfer

You can send files to a remote server or receive files from a remote server, and get the job status through the REST API.

Use the following resources for file transfer:

- `sendfiles`. Use to send files to a remote server.
- `receivefiles`. Use to receive files from a remote server.
- `job`. Use to get the status of the supported file transfer jobs that are initiated using the `sendfiles` or `receivefiles` resource.

When you use these resources, note the following rules:

- Use JSON format.
- Use the following base URL:  
`<serverUrl>/mftsaas/api/v1/<API name>`
- Use the following request header format:  
`<METHOD> <serverUrl>/<URI> HTTP/<HTTP version>`  
`Content-Type: application/json`  
`Accept: application/json`  
`IDS-SESSION-ID: <SessionId>`

**Note:** You must have the appropriate connector license to send and receive files.

## sendfiles

Use the `sendfiles` resource to transfer files to a remote server.

The following connection types use the `sendfiles` resource to transfer files to the remote server:

- AS2
- Advanced FTP V2
- Advanced FTPS V2
- Advanced SFTP V2

Before you construct a `sendfiles` request to transfer files, obtain the identifier of the connection that provides access to the server. To get the connection ID, you can send a GET request using the connection resource. The connection resource can return information for each of your organization's connections.

## POST Request

To transfer files, include the connection ID in the following URI.

```
mftsaas/api/v1/sendfiles/<connection ID>
```

Include the following information in the request:

Field	Type	Required	Description
targetConnectionType	String	Yes	Connection type. The supported connection types are: <ul style="list-style-type: none"><li>- Advanced FTP V2</li><li>- Advanced FTPS V2</li><li>- Advanced SFTP V2</li><li>- AS2</li></ul>
srcDirectoryPath	String	Yes	Directory path from where files are transferred.
tgtDirectoryPath	String	-	Directory path to where files are transferred. This option is available only for Advanced FTP V2, Advanced FTPS V2, and Advanced SFTP V2 connection types. Default is '/'.
srcFilePattern	String	Yes	Source file name pattern. Specify a file name pattern to identify which files to send. You can use the regular expression type.
deleteSourceFiles	String	-	Whether to delete source files after a successful POST request. Use one of the following values: <ul style="list-style-type: none"><li>- true. Delete source files.</li><li>- false. Save source files.</li></ul> Default is true.

For example, to transfer the files that begin with "file\_" that are located in the workspace directory, you might use the following request:

```
POST <serverUrl>/mftsaas/api/v1/sendfiles/<connection ID>
Accept:application/json
IDS-SESSION-ID: <icSessionId or INFA-SESSION-ID>
{
  "targetConnectionType": "as2",
  "srcDirectoryPath": "C:\\server\\userdata\\workspace",
  "srcFilePattern": "file_*"
}
```

For example, to transfer the files with ".txt" pattern, you might use the following request:

```
POST <serverUrl>/mftsaas/api/v1/sendfiles/<connection ID>
Accept:application/json
IDS-SESSION-ID: <icSessionId or INFA-SESSION-ID>
{
  "targetConnectionType": "Advanced SFTP V2",
  "srcDirectoryPath": "C:\\docstoreLocal2",
  "tgtDirectoryPath": "C:\\server\\userdata\\workspace",
  "srcFilePattern": ".*txt"
}
```

## POST Response

If successful, Informatica Intelligent Cloud Services returns the run ID for the job. Use the run ID to monitor the job status.

The following example shows a successful response:

```
{
  "projectId": 0,
  "timeTaken": 0,
  "queuePriority": 0,
  "runPriority": 0,
  "runMode": "UNKNOWN",
  "submitSourceId": -1,
  "correlationId": "OWMxOTc2YjktNzI4YS00Mm",
  "runModeInteractive": false,
  "runModeBatch": false,
  "runModeDebug": false,
  "runModeUnknown": true,
  "formattedTimeTaken": "0.00",
  "id": 1000000000384,
  "runId": 385
}
```

If unsuccessful, the response includes a reason for the failure.

## receivefiles

Use the receivefiles resource to get files from a remote server.

The following connection types use the receivefiles resource to transfer files to the remote server:

- Advanced FTP V2
- Advanced FTPS V2
- Advanced SFTP V2

Before you construct a receivefiles request to receive files, obtain the identifier of the connection that provides access to the server. To get the connection ID, you can send a GET request using the connection resource. The connection resource can return information for each of your organization's connections.

### POST Request

To receive files, include the connection ID in the following URI.

```
mftsaas/api/v1/receivefiles/<connection ID>
```

Include the following information in the request:

Field	Type	Required	Description
sourceConnectionType	String	Yes	Connection type. The supported source connection types are: <ul style="list-style-type: none"><li>- Advanced FTP V2</li><li>- Advanced FTPS V2</li><li>- Advanced SFTP V2</li></ul>
tgtDirectoryPath	String	Yes	Directory path to where files are transferred.
srcDirectoryPath	String	-	Directory path from where files are transferred. Default is '/'.
srcFilePattern	String	Yes	Source file name pattern. Specify a file name pattern to identify which files to send. You can use the regular expression type.

Field	Type	Required	Description
processFilesRecursively	String	-	Whether to process files from all sub-folders within the base directory. Default is false.
afterFilePickupAction	String	-	Determines what to do with source files after the files transfer. The following options are available: <ul style="list-style-type: none"> <li>- Keep the files in the source directory.</li> <li>- Delete the files from the source directory.</li> <li>- Rename the files in the source directory. You must specify a file name suffix that adds to the file name when renaming the files.</li> <li>- Archive the files to a different location. You must specify an archive directory.</li> </ul> Default is KEEP.
skipDuplicateFiles	String	-	Do not transfer duplicate files. If files with the same name and creation date were transferred, the task does not transfer them again, and the files are marked as duplicate in the job log. If this option is not selected the task transfers all files. Default is false.
whenFileExists	String	-	Determines what to do with a file if a flat file with the same name exists in the target directory. The following options are available: <ul style="list-style-type: none"> <li>- rename</li> <li>- overwrite</li> <li>- skip</li> <li>- stop</li> <li>- error</li> </ul> Default is rename.

For example, to transfer the files with ".txt" pattern, and rename the file if a flat file with same name exists in the target directory, you might use the following request:

```
POST <serverUrl>/mftsaas/api/v1/sendfiles/<connection ID>
Accept:application/json
IDS-SESSION-ID: <icSessionId or INFA-SESSION-ID>
{
  "sourceConnectionType": "Advanced SFTP V2",
  "tgtDirectoryPath": "C:\\docstoreLocal2",
  "srcDirectoryPath": "C:\\server\\userdata\\workspace",
  "srcFilePattern": ".*txt",
  "processFilesRecursively": false,
  "afterFilePickupAction": "KEEP",
  "skipDuplicateFiles": false,
  "whenFileExists": "rename",
}
```

## POST Response

If successful, Informatica Intelligent Cloud Services returns the run ID for the job. Use the run ID to monitor the job status.

The following example shows a successful response:

```
{
  "projectId": 0,
  "timeTaken": 0,
  "queuePriority": 0,
  "runPriority": 0,
  "runMode": "UNKNOWN",
  "submitSourceId": -1,
  "correlationId": "OWMxOTc2YjktNzI4YS00Mm",
  "runModeInteractive": false,
```

```

    "runModeBatch": false,
    "runModeDebug": false,
    "runModeUnknown": true,
    "formattedTimeTaken": "0.00",
    "id": 1000000000384,
    "runId": 385
  }

```

If unsuccessful, the response includes a reason for the failure.

## job

When you use the REST API to send or receive files, use the REST API version 1 job resource to get the status of the file transfer.

Do not use the platform REST API version 2 job resource to get the status of an file transfer job.

### Get Request

When you send the request for status of an file transfer job, include the run ID returned in the sendfiles POST response. Use the following URI:

```
mftsaas/api/v1/job/<runID>/status
```

### Get Response

If successful, Data Integration returns the job status.

If unsuccessful, the response includes a reason for the failure.

### Get Response Example

If the request is successful, you might receive a response similar to the following example:

```

{
  "jobStatus": "SUCCESS"
}

```

# INDEX

## A

Advanced FTP V2 connections  
  properties [8](#)  
AS2 server  
  sendfiles resource [11](#)

## C

Cloud Application Integration community  
  URL [4](#)  
Cloud Developer community  
  URL [4](#)

## D

Data Integration community  
  URL [4](#)

## F

file transfer  
  monitoring using REST API [15](#)

## I

Informatica Global Customer Support  
  contact information [5](#)  
Informatica Intelligent Cloud Services  
  web site [4](#)

## M

maintenance outages [5](#)

## R

receivefiles  
  REST API resource [13](#)  
REST API  
  receivefiles resource [13](#)  
  sendfiles resource [11](#)

## S

sendfiles  
  REST API resource [11](#)  
status  
  Informatica Intelligent Cloud Services [5](#)  
system status [5](#)

## T

trust site  
  description [5](#)

## U

upgrade notifications [5](#)

## W

web site [4](#)