



Informatica® Data Integration - Free & PayGo
April 2023

Function Reference

© Copyright Informatica LLC 2022, 2023

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, Informatica Cloud, Informatica Intelligent Cloud Services, PowerCenter, PowerExchange, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2023-04-03

Table of Contents

Preface	8
Informatica Resources.	8
Informatica Documentation.	8
Informatica Intelligent Cloud Services web site.	8
Informatica Intelligent Cloud Services Communities.	8
Informatica Intelligent Cloud Services Marketplace.	8
Data Integration connector documentation.	9
Informatica Knowledge Base.	9
Informatica Intelligent Cloud Services Trust Center.	9
Informatica Global Customer Support.	9
 Chapter 1: Function reference.....	 10
Function components.	10
 Chapter 2: Constants.....	 11
FALSE.	11
Example.	11
NULL.	11
Working with null values in Boolean expressions.	12
Null values in filter conditions.	12
Nulls with operators.	12
TRUE.	12
Example.	12
 Chapter 3: Operators.....	 13
Operator precedence.	13
Arithmetic operators.	14
String operators.	15
Nulls.	15
Example of string operators.	15
Comparison operators.	16
Comparing hierarchies.	16
Logical operators.	17
Nulls.	17
 Chapter 4: Dates.....	 18
Dates overview.	18
Date/Time datatype.	18
Julian Day, Modified Julian Day, and the Gregorian calendar.	19
Supported dates.	19

Dates in databases.	21
Dates in flat files.	21
Default date format.	21
Date Format Strings.	22
TO_CHAR format strings.	23
Examples.	25
TO_DATE and IS_DATE format strings.	26
Requirements.	28
Example.	28
Understanding date arithmetic.	29

Chapter 5: Functions..... 31

Function overview.	31
Aggregate functions.	31
Conversion functions.	33
Data cleansing functions.	33
Date functions.	34
Encoding functions.	35
Financial functions.	35
Horizontal expansion functions.	35
Numeric functions.	36
Scientific functions.	36
Special functions.	36
String functions.	37
Test functions.	37
Function quick reference.	38
%OPR_CONCAT%.	49
%OPR_CONCATDELIM%.	50
%OPR_IIF%.	51
%OPR_SUM%.	52
ABORT.	53
ABS.	53
ADD_TO_DATE.	54
AES_DECRYPT.	57
AES_ENCRYPT.	58
AES_GCM_DECRYPT.	59
AES_GCM_ENCRYPT.	60
ASCII.	61
AVG.	62
CEIL.	63
CHOOSE.	64
CHR.	65
CHRCODE.	66

COMPRESS.	67
CONCAT.	67
CONVERT_BASE.	69
COS.	69
COSH.	70
COUNT.	71
CRC32.	73
CUME.	74
DATE_COMPARE.	75
DATE_DIFF.	76
DEC_BASE64.	78
DECODE.	79
DECOMPRESS.	81
ENC_BASE64.	82
ERROR.	82
EXP.	83
FIRST.	84
FLOOR.	85
FV.	86
GET_DATE_PART.	87
GREATEST.	89
IIF.	90
IN.	92
INDEXOF.	92
INITCAP.	93
INSTR.	95
IS_DATE.	97
IS_NUMBER.	99
IS_SPACES.	101
ISNULL.	102
LAST.	103
LAST_DAY.	104
LEAST.	105
LENGTH.	106
LN.	107
LOG.	107
LOWER.	109
LPAD.	110
LTRIM.	111
MAKE_DATE_TIME.	112
MAX (Dates).	113
MAX (Numbers).	114

MAX (String).	116
MD5.	117
MEDIAN.	118
METAPHONE.	119
MIN (Dates).	123
MIN (Numbers).	124
MIN (String).	125
MOD.	127
MOVINGAVG.	128
MOVINGSUM.	129
NPER.	130
PERCENTILE.	131
PMT.	133
POWER.	134
PV.	135
RAND.	136
RATE.	136
REG_EXTRACT.	137
REG_MATCH.	139
REG_REPLACE.	141
REPLACECHR.	142
REPLACESTR.	145
REVERSE.	147
ROUND (Dates).	148
ROUND (Numbers).	151
RPAD.	153
RTRIM.	154
SET_DATE_PART.	155
SETCOUNTVARIABLE.	158
SETMAXVARIABLE.	158
SETMINVARIABLE.	159
SETVARIABLE.	160
SIGN.	161
SIN.	162
SINH.	163
SOUNDEX.	164
SQRT.	166
STDDEV.	166
SUBSTR.	168
SUM.	170
SYSTIMESTAMP.	171
TAN.	172

TANH.	173
TO_BIGINT.	174
TO_CHAR (Dates).	176
TO_CHAR (Numbers).	180
TO_DATE.	181
TO_DECIMAL.	184
TO_FLOAT.	184
TO_INTEGER.	185
TRUNC (Dates).	187
TRUNC (Numbers).	189
UPPER.	191
VARIANCE.	191
Chapter 6: System variables.	194
CurrentMappingName.	194
CurrentRunId.	194
CurrentTaskName.	194
SESSSTARTTIME.	194
SYSDATE.	195
Chapter 7: Datatype reference.	196
Datatype reference overview.	196
Rules and guidelines for datatypes.	197
Transformation datatypes.	197
Integer datatypes.	198
Binary datatype.	200
Date/Time data type.	200
Decimal and double data types.	201
String datatypes.	202
Index.	203

Preface

Refer to the *Function Reference* for information about the transformation language used to write functions to transform data with Data Integration. Learn how to use functions, operators, and constants to write simple or complex transformation expressions.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit <https://docs.informatica.com>.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at <http://www.informatica.com/cloud>. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

<https://network.informatica.com/community/informatica-network/products/cloud-integration>

Developers can learn more and share tips at the Cloud Developer community:

<https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers>

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

<https://marketplace.informatica.com/>

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit <https://docs.informatica.com>.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit <https://search.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at <https://www.informatica.com/trust-center.html>.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The [Informatica Intelligent Cloud Services Status](#) page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, go to <https://status.informatica.com/> and click **SUBSCRIBE TO UPDATES**. You can then choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Customer Support Center by telephone or online.

For online support, click **Submit Support Request** in Informatica Intelligent Cloud Services. You can also use Online Support to log a case. Online Support requires a login. You can request a login at <https://network.informatica.com/welcome>.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at <https://www.informatica.com/services-and-training/support-services/contact-us.html>.

CHAPTER 1

Function reference

Informatica provides a transformation language that includes SQL-like functions to transform source data. Use these functions to write expressions and create user-defined functions.

Expressions modify data or test whether data matches conditions. For example, you can use the AVG function to calculate the average salary of all the employees or the SUM function to calculate the total sales for a specific branch. You can create a simple expression that only contains a single function, such as AVG. You can also write complex expressions by nesting functions within functions.

User-defined functions use expression logic to build complex expressions. You can include them in other user-defined functions or in expressions. For more information about user-defined functions, see *Components*.

Function components

The transformation language includes the following components to create simple or complex transformation expressions:

- **Functions.** Over 100 SQL-like functions allow you to change data in a mapping.
- **Operators.** Use transformation operators to create transformation expressions to perform mathematical computations, combine data, or compare data.
- **Constants.** Use built-in constants to reference values that remain constant, such as TRUE.
- **System Variables.** Use variables to return system values that change, such as the current task name and run ID.

CHAPTER 2

Constants

This chapter includes the following topics:

- [FALSE, 11](#)
- [NULL, 11](#)
- [TRUE, 12](#)

FALSE

Clarifies a conditional expression. FALSE is equivalent to the integer 0.

Example

The following example uses FALSE in a DECODE expression to verify that values are between 25 and 30. This is useful if you want to perform multiple searches based on a single search value:

```
DECODE (FALSE,  
Var1 >= 25, 'Var1 not in desired range.',  
Var1 <= 30, 'Var1 not in desired range.',  
 'Var1 in desired range.')
```

NULL

Indicates that a value is either unknown or undefined. NULL is not equivalent to a blank or empty string (for character columns) or 0 (for numerical columns).

Although you can write expressions that return nulls, any column that has the NOT NULL or PRIMARY KEY constraint will not accept nulls. Therefore, if Data Integration tries to write a null value to a column with one of these constraints, the database will reject the row and Data Integration will write it to the reject file. Be sure to consider nulls when you create transformations.

Functions can handle nulls differently. If you pass a null value to a function, it might return 0 or NULL, or it might ignore null values.

Working with null values in Boolean expressions

Expressions that combine a null value with a Boolean expression produces results that are ANSI compliant. For example:

- NULL AND TRUE = NULL
- NULL AND FALSE = FALSE

Null values in filter conditions

If a filter condition evaluates to NULL, the function does not select the record.

Nulls with operators

Any expression that uses operators (except the string operator ||) and contains a null value always evaluates to NULL. For example, the following expression evaluates to NULL:

```
8 * 10 - NULL
```

To test for nulls, use the ISNULL function.

TRUE

Returns a value based on the result of a comparison. TRUE is equivalent to the integer 1.

Example

The following example uses TRUE in a DECODE expression to return values based on the results of a comparison. This is useful if you want to perform multiple searches based on a single search value:

```
DECODE( TRUE,  
Var1 = 22, 'Variable 1 was 22!',  
Var2 = 49, 'Variable 2 was 49!',  
Var1 < 23, 'Variable 1 was less than 23.',  
Var2 > 30, 'Variable 2 was more than 30.',  
'Variables were out of desired ranges.')
```

CHAPTER 3

Operators

This chapter includes the following topics:

- [Operator precedence, 13](#)
- [Arithmetic operators, 14](#)
- [String operators, 15](#)
- [Comparison operators, 16](#)
- [Logical operators, 17](#)

Operator precedence

When you create an expression, you can use multiple operators and use operators within nested expressions.

If you write an expression that includes multiple operators, Data Integration evaluates the expression in the following order:

1. Complex operators
2. Arithmetic operators
3. String operators
4. Comparison operators
5. Logical operators

Data Integration evaluates operators in the order they appear in the following table. It evaluates operators in an expression with equal precedence to all operators from left to right.

The following table lists the precedence for all transformation language operators:

Operator	Meaning
[], .	Subscript, dot.
()	Parentheses.
+, -, NOT	Unary plus and minus and the logical NOT operator.
*, /, %	Multiplication, division, modulus.
+, -	Addition, subtraction.

Operator	Meaning
	Concatenate.
<, <=, >, >=	Less than, less than or equal to, greater than, greater than or equal to.
=, <>, !=, ^=	Equal to, not equal to, not equal to, not equal to.
AND	Logical AND operator, used when specifying conditions.
OR	Logical OR operator, used when specifying conditions.

You can use operators within nested expressions. When expressions contain parentheses, Data Integration evaluates operations inside parentheses before operations outside parentheses. Operations in the innermost parentheses are evaluated first.

For example, depending on how you nest the operations, the equation $8 + 5 - 2 * 8$ returns different values:

Equation	Return value
$8 + 5 - 2 * 8$	-3
$8 + (5 - 2) * 8$	32

Arithmetic operators

Use arithmetic operators to perform mathematical calculations on numeric data.

The following table lists the transformation language arithmetic operators in order of precedence:

Operator	Meaning
+, -	Unary plus and minus. Unary plus indicates a positive value. Unary minus indicates a negative value.
*, /, %	Multiplication, division, modulus. A modulus is the remainder after dividing two integers. For example, $13 \% 2 = 1$ because 13 divided by 2 equals 6 with a remainder of 1.
+, -	Addition, subtraction. The addition operator (+) does not concatenate strings. To concatenate strings, use the string operator . To perform arithmetic on date values, use the date functions.

If you perform arithmetic on a null value, the function returns NULL.

When you use arithmetic operators in an expression, all of the operands in the expression must be numeric. For example, the expression $1 + '1'$ is not valid because it adds an integer to a string. The expression $1.23 + 4 / 2$ is valid because all of the operands are numeric.

String operators

Use the || string operator to concatenate two strings. The || operator converts operands of any datatype (except Binary) to String datatypes before concatenation:

Input value	Return value
'alpha' 'betical'	alphabetical
'alpha' 2	alpha2
'alpha' NULL	alpha

The || operator includes leading and trailing spaces. Use the LTRIM and RTRIM functions to trim leading and trailing spaces before concatenating two strings.

Nulls

The || operator ignores null values. However, if both values are NULL, the || operator returns NULL.

Example of string operators

The following example shows an expression that concatenates employee first names and employee last names from two columns. This expression removes the spaces from the end of the first name and the beginning of the last name, concatenates a space to the end of each first name, then concatenates the last name:

```
LTRIM( RTRIM( EMP_FIRST ) || ' ' || LTRIM( EMP_LAST ) )
```

EMP_FIRST	EMP_LAST	RETURN VALUE
' Alfred'	' Rice '	Alfred Rice
' Bernice'	' Kersins'	Bernice Kersins
NULL	' Proud'	Proud
' Curt'	NULL	Curt
NULL	NULL	NULL

Note: You can also use the CONCAT function to concatenate two string values. The || operator, however, produces the same results in less time.

Comparison operators

Use comparison operators to compare string or numeric strings, manipulate data, and return a TRUE (1) or FALSE (0) value.

The following table lists the transformation language comparison operators:

Operator	Meaning
=	Equal to.
>	Greater than.
<	Less than.
>=	Greater than or equal to.
<=	Less than or equal to.
<>	Not equal to.
!=	Not equal to.
^=	Not equal to.

Use the greater than (>) and less than (<) operators to compare numeric values or return a range of rows based on the sort order for a primary key in a particular field

When you use comparison operators in an expression, the operands must be the same datatype. For example, the expression `123.4 > '123'` is not valid because the expression compares a decimal with a string. The expressions `123.4 > 123` and `'a' != 'b'` are valid because the operands are the same datatype.

If you compare a value to a null value, the result is NULL.

If a filter condition evaluates to NULL, Data Integration returns NULL.

Comparing hierarchies

You can use the equal to (=) and not equal to (!=) operators to compare two arrays or two structs.

Comparing arrays

Two arrays are equivalent if the following conditions are true:

- The array elements are the same data type.
- The arrays are the same size.
- The element at each index is the same.

For example, you have the following arrays:

```
A = [1, 2, 3]
B = [1, 2, 3]
```

You can make the following comparison:

```
A = B
```


Both arrays contain integers, the arrays are the same size, and the element at each index is the same such that `A[0]=B[0]`, `A[1]=B[1]`, and `A[2]=B[2]`. The return value is `TRUE (1)`.

Comparing structs

Two structs are equivalent if the following conditions are true for the corresponding struct elements:

- The elements are the same data type.
- The elements hold the same data.

Note: Two structs are equivalent even if the elements have different names.

For example, you have the following structs:

```
struct1 {  
    name:'Paul'  
    zip:10004  
}  
  
struct2 {  
    firstname:'Paul'  
    zip1:10004  
}
```

You can make the following comparison:

```
struct1 = struct2
```

The corresponding elements are the same data type and hold the same data, so the return value is `TRUE (1)`.

Logical operators

Use logical operators to manipulate numeric data. Expressions that return a numeric value evaluate to `TRUE` for values other than 0, `FALSE` for 0, and `NULL` for `NULL`.

The following table lists the transformation language logical operators:

Operator	Meaning
NOT	Negates result of an expression. For example, if an expression evaluates to <code>TRUE</code> , the operator <code>NOT</code> returns <code>FALSE</code> . If an expression evaluates to <code>FALSE</code> , <code>NOT</code> returns <code>TRUE</code> .
AND	Joins two conditions and returns <code>TRUE</code> if both conditions evaluate to <code>TRUE</code> . Returns <code>FALSE</code> if one condition is not true.
OR	Connects two conditions and returns <code>TRUE</code> if any condition evaluates to <code>TRUE</code> . Returns <code>FALSE</code> if both conditions are not true.

Nulls

Expressions that combine a null value with a Boolean expression produce results that are ANSI compliant.

For example, Data Integration produces the following results:

- `NULL AND TRUE = NULL`
- `NULL AND FALSE = FALSE`

CHAPTER 4

Dates

This chapter includes the following topics:

- [Dates overview, 18](#)
- [Date Format Strings, 22](#)
- [TO_CHAR format strings, 23](#)
- [TO_DATE and IS_DATE format strings, 26](#)
- [Understanding date arithmetic, 29](#)

Dates overview

With the date functions, you can round, truncate, or compare dates, extract one part of a date, or perform arithmetic on a date. You can pass any value with a date datatype to a date function.

Use date variables to capture the current date or session start time on the machine that hosts Data Integration.

The transformation language also provides the following sets of format strings:

Date format strings

Use with date functions to specify the parts of a date.

TO_CHAR format strings

Use to specify the format of the return string.

TO_DATE and IS_DATE format strings

Use to specify the format of a string you want to convert to a date or test.

Date/Time datatype

The transformation language provides a set of generic datatypes to transform data from different sources. These transformation datatypes include a Date/Time datatype. Data Integration stores dates internally in binary format.

Date functions accept datetime values only. To pass a string to a date function, first use TO_DATE to convert it to a datetime value. For example, the following expression converts a string field to datetime values and then adds one month to each date:

```
ADD_TO_DATE( TO_DATE( STRING_PORT, 'MM/DD/RR'), 'MM', 1 )
```

Note: Data Integration supports dates between 1753 A.D. and 9999 A.D.

Milliseconds

Data Integration supports datetime values up to the second.

If you import a datetime value that includes milliseconds, Data Integration truncates to seconds. If you write a datetime value to a target column that supports milliseconds, Data Integration inserts zeros for the millisecond portion of the date.

Julian Day, Modified Julian Day, and the Gregorian calendar

Data Integration supports dates in the Gregorian calendar system only. Dates expressed in a different calendar system are not supported.

Note: Dates in the Julian calendar are called Julian *dates* and are not supported in Data Integration. This term should not be confused with Julian *Day* or with Modified Julian Day.

The transformation language provides the ability to manipulate Modified Julian Day (MJD) formats using the J format string.

The MJD for a given date is the number of days to that date since Jan 1 4713 BC 00:00:00 (midnight). By definition, MJD includes a time component expressed as a decimal, which represents some fraction of 24 hours. The J format string does not convert this time component.

For example, the following TO_DATE expression converts strings in the SHIP_DATE_MJD_STRING field to date values in the default date format:

```
TO_DATE (SHIP_DATE_MJD_STR, 'J')
```

SHIP_DATE_MJD_STR	RETURN_VALUE
2451544	Dec 31 1999 00:00:00
2415021	Jan 1 1900 00:00:00

Because the J format string does not include the time portion of a date, the return values have the time set to 00:00:00.

You can also use the J format string in TO_CHAR expressions. For example, use the J format string in a TO_CHAR expression to convert date values to MJD values expressed as strings. For example:

```
TO_CHAR(SHIP_DATE, 'J')
```

SHIP_DATE	RETURN_VALUE
Dec 31 1999 23:59:59	2451544
Jan 1 1900 01:02:03	2415021

Note: Data Integration ignores the time portion of the date in a TO_CHAR expression.

Supported dates

Data Integration supports dates between 1753 A.D. and 9999 A.D.

RR format string

The transformation language provides the RR format string to convert strings with two-digit years to dates. Using TO_DATE and the RR format string, you can convert a string in the format MM/DD/RR to a date. The RR format string converts data differently depending on the current year.

Current Year Between 0 and 49

If the current year is between 0 and 49 (such as 2003) and the source string year is between 0 and 49, Data Integration returns the current century plus the two-digit year from the source string. If the source string year is between 50 and 99, Data Integration returns the previous century plus the two-digit year from the source string.

Current Year Between 50 and 99

If the current year is between 50 and 99 (such as 1998) and the source string year is between 0 and 49, Data Integration returns the next century plus the two-digit year from the source string. If the source string year is between 50 and 99, Data Integration returns the current century plus the specified two-digit year.

The following table summarizes how the RR format string converts to dates:

Current year	Source year	RR format string returns
0-49	0-49	Current century
0-49	50-99	Previous century
50-99	0-49	Next century
50-99	50-99	Current century

Example of RR

The following expression produces the same return values for any current year between 1950 and 2049:

```
TO_DATE( ORDER_DATE, 'MM/DD/RR' )
```

ORDER_DATE	RETURN_VALUE
'04/12/98'	04/12/1998 00:00:00
'11/09/01'	11/09/2001 00:00:00

Difference between the YY and RR format strings

The transformation language also provides a YY format string. Both the RR and YY format strings specify two-digit years. The YY and RR format strings produce identical results when used with all date functions except TO_DATE.

In TO_DATE expressions, RR and YY produce different results.

The following table shows the different results each format string returns:

String	Current year	TO_DATE(String, 'MM/DD/RR')	TO_DATE(String, 'MM/DD/YY')
04/12/98	1998	04/12/1998 00:00:00	04/12/1998 00:00:00
11/09/01	1998	11/09/2001 00:00:00	11/09/1901 00:00:00
04/12/98	2003	04/12/1998 00:00:00	04/12/2098 00:00:00
11/09/01	2003	11/09/2001 00:00:00	11/09/2001 00:00:00

For dates in the year 2000 and beyond, the YY format string produces less meaningful results than the RR format string. Use the RR format string for dates in the twenty-first century.

Dates in databases

Although date formats vary from database to database, and even between applications, Data Integration can read any date with a date datatype.

In general, dates stored in databases contain a date and time value. The date includes the month, day, and year, while the time might include the hours, minutes, and seconds. You can pass datetime data to any of the date functions.

Dates in flat files

The transformation language provides the TO_DATE function to convert strings to datetime values. You can also use IS_DATE to check if a string is a valid date before converting it with TO_DATE.

Note: Transformation language date functions accept date values only. If you want to pass a string to a date function, you must first use the TO_DATE function to convert it to a transformation Date/Time datatype.

Default date format

The application uses a default date format to store and manipulate strings that represent dates. Because Data Integration stores dates in binary format, Data Integration only uses the default date format in certain circumstances.

Data Integration only uses the default date format when you perform the following actions:

Convert a date to a string by connecting a date/time field to a string field.

The application converts the date to a string in the default date format, MM/DD/YYYY HH24:MI:SS.

Convert a string to a date by connecting a string field to a date/time field.

The application expects the string values to be in the default date format, MM/DD/YYYY HH24:MI:SS. If an input value does not match this format, or it is an invalid date, Data Integration skips the row. If the string is in the default date format, Data Integration converts the string to a date value.

Use TO_CHAR(date, [format_string]) to convert dates to strings.

If you omit the format string, Data Integration returns the string in the default date format, MM/DD/YYYY HH24:MI:SS. If you specify a format string, Data Integration returns a string in the specified format.

Use **TO_DATE(date, [format_string])** to convert strings to dates.

If you omit the format string, Data Integration expects the string in the default date format, MM/DD/YYYY HH24:MI:SS. If you specify a format string, Data Integration expects a string in the specified format.

The default date format of MM/DD/YYYY HH24:MI:SS consists of:

- Month (January = 01, September = 09)
- Day (of the month)
- Year (expressed in four digits, such as 1998)
- Hour (in 24-hour format, for example, 12:00:00AM = 0, 1:00:00AM = 1, 12:00:00PM = 12, 11:00:00PM = 23)
- Minutes
- Seconds

Date Format Strings

You can evaluate input dates using a combination of format strings and date functions. Date format strings are not internationalized and must be entered in predefined formats as listed in the following table.

The following table summarizes the format strings to specify a part of a date:

Format String	Description
D, DD, DDD, DAY, DY, J	Days (01-31). Use any of these format strings to specify the entire day portion of a date. For example, if you pass 12-APR-1997 to a date function, use any of these format strings specify 12.
HH, HH12, HH24	Hour of day (0-23), where 0 is 12 AM (midnight). Use any of these formats to specify the entire hour portion of a date. For example, if you pass the date 12-APR-1997 2:01:32 PM, use HH, HH12, or HH24 to specify the hour portion of the date.
MI	Minutes (0-59).
MM, MON, MONTH	Month (01-12). Use any of these format strings to specify the entire month portion of a date. For example, if you pass 12-APR-1997 to a date function, use MM, MON, or MONTH to specify APR.
MS	Milliseconds (0-999).
NS	Nanoseconds (0-999999999).
SS, SSSS	Seconds (0-59).
US	Microseconds (0-999999).
Y, YY, YYYY, YYYY, RR	Year portion of date (1753 to 9999). Use any of these format strings to specify the entire year portion of a date. For example, if you pass 12-APR-1997 to a date function, use Y, YY, YYYY, or YYYY to specify 1997.

Note: The format string is not case sensitive. It must always be enclosed within single quotation marks.

The following table describes date functions that use date format strings to evaluate input dates:

Function	Description
ADD_TO_DATE	The part of the date you want to change.
DATE_DIFF	The part of the date to use to calculate the difference between two dates.
GET_DATE_PART	The part of the date you want to return. This function returns an integer value based on the default date format.
IS_DATE	The date you want to check.
ROUND (Dates)	The part of the date you want to round.
SET_DATE_PART	The part of the date you want to change.
SYSTIMESTAMP	The timestamp precision.
TO_CHAR (Dates)	The character string.
TO_DATE	The character string.
TRUNC (Dates)	The part of the date you want to truncate.

TO_CHAR format strings

The TO_CHAR function converts a Date/Time datatype to a string with the format you specify. You can convert the entire date or a part of the date to a string. You might use TO_CHAR to convert dates to string, changing the format for reporting purposes.

TO_CHAR is generally used when the target is a database that does not support a Date/Time datatype.

The following table summarizes the format strings for dates in the function TO_CHAR:

Format string	Description
AM, A.M., PM, P.M.	Meridian indicator. Use any of these format strings to specify AM and PM hours. AM and PM return the same values as A.M. and P.M.
D	Day of week (1-7), where Sunday equals 1.
DD	Day of month (01-31).
DDD	Day of year (001-366, including leap years).
DAY	Name of day, including up to nine characters (for example, Wednesday).
DY	Abbreviated three-character name for a day (for example, Wed).
HH, HH12	Hour of day (01-12).

Format string	Description
HH24	Hour of day (00-23), where 00 is 12AM (midnight).
J	Modified Julian Day. Converts the calendar date to a string equivalent to its Modified Julian Day value, calculated from Jan 1, 4713 00:00:00 BC. It ignores the time component of the date. For example, the expression TO_CHAR(SHIP_DATE, 'J') converts Dec 31 1999 23:59:59 to the string 2451544.
MI	Minutes (00-59).
MM	Month (01-12).
MONTH	Name of month, including up to nine characters (for example, January).
MON	Abbreviated three-character name for a month (for example, Jan).
Q	Quarter of year (1-4), where January to March equals 1.
RR	Last two digits of a year. The function removes the leading digits. For example, if you use 'RR' and pass the year 1997, TO_CHAR returns 97. When used with TO_CHAR, 'RR' produces the same results as, and is interchangeable with, 'YY.' However, when used with TO_DATE, 'RR' calculates the closest appropriate century and supplies the first two digits of the year.
SS	Seconds (00-59).
SSSSS	Seconds since midnight (00000 - 86399). When you use SSSSS in a TO_CHAR expression, Data Integration only evaluates the time portion of a date. For example, the expression TO_CHAR(SHIP_DATE, 'MM/DD/YYYY SSSSS') converts 12/31/1999 01:02:03 to 12/31/1999 03783.
Y	Last digit of a year. The function removes the leading digits. For example, if you use 'Y' and pass the year 1997, TO_CHAR returns 7.
YY	Last two digits of a year. The function removes the leading digits. For example, if you use 'YY' and pass the year 1997, TO_CHAR returns 97.
YYY	Last three digits of a year. The function removes the leading digits. For example, if you use 'YYY' and pass the year 1997, TO_CHAR returns 997.
YYYY	Entire year portion of date. For example, if you use 'YYYY' and pass the year 1997, TO_CHAR returns 1997.
W	Week of month (1-5), where week 1 starts on the first day of the month and ends on the seventh, week 2 starts on the eighth day and ends on the fourteenth day. For example, Feb 1 designates the first week of February.
WW	Week of year (01-53), where week 01 starts on Jan 1 and ends on Jan 7, week 2 starts on Jan 8 and ends on Jan 14, and so on.
- / . ; :	Punctuation that displays in the output. You might use these symbols to separate date parts. For example, you might create the following expression to separate date parts with a period: TO_CHAR(DATES, 'MM.DD.YYYY').

Format string	Description
"text"	Text that displays in the output. For example, if you have the expression: TO_CHAR(DATES, 'MM/DD/YYYY "Sales Were Up"') and pass the date Apr 1 1997, the function returns the string '04/01/1997 Sales Were Up'. You can enter multibyte characters that are valid in the repository code page.
" "	Use double quotation marks to separate ambiguous format strings, for example D"D"DDD. The empty quotation marks do not appear in the output.

Note: The format string is not case sensitive. It must always be enclosed within single quotation marks.

Examples

The following examples illustrate the J, SSSSS, RR, and YY format strings. See the individual functions for more examples.

Note: The application ignores the time portion of the date in a TO_CHAR expression.

J format string

Use the J format string in a TO_CHAR expression to convert date values to MJD values expressed as strings. For example:

```
TO_CHAR(SHIP_DATE, 'J')
```

SHIP_DATE	RETURN_VALUE
Dec 31 1999 23:59:59	2451544
Jan 1 1900 01:02:03	2415021

SSSSS format string

You can also use the format string SSSSS in a TO_CHAR expression. For example, the following expression converts the dates in the SHIP_DATE port to strings representing the total seconds since midnight:

```
TO_CHAR( SHIP_DATE, 'SSSSS')
```

SHIP_DATE	RETURN_VALUE
12/31/1999 01:02:03	3783
09/15/1996 23:59:59	86399

RR format string

The following expression converts dates to strings in the format MM/DD/YY:

```
TO_CHAR( SHIP_DATE, 'MM/DD/RR')
```

SHIP_DATE	RETURN_VALUE
12/31/1999 01:02:03	12/31/99
09/15/1996 23:59:59	09/15/96

SHIP_DATE	RETURN_VALUE
05/17/2003 12:13:14	05/17/03

YY format string

In TO_CHAR expressions, the YY format string produces the same results as the RR format string. The following expression converts dates to strings in the format MM/DD/YY:

```
TO_CHAR( SHIP_DATE, 'MM/DD/YY')
```

SHIP_DATE	RETURN_VALUE
12/31/1999 01:02:03	12/31/99
09/15/1996 23:59:59	09/15/96
05/17/2003 12:13:14	05/17/03

TO_DATE and IS_DATE format strings

The TO_DATE function converts a string with the format you specify to a datetime value. TO_DATE is generally used to convert strings from flat files to datetime values. TO_DATE format strings are not internationalized and must be entered in predefined formats as listed in the table below.

Note: TO_DATE and IS_DATE use the same set of format strings.

When you create a TO_DATE expression, use a format string for each part of the date in the source string. The source string format and the format string must match, including any date separators. If any parts do not match, Data Integration does not convert the string and skips the row. If you omit the format string, the source string must be in the default date format MM/DD/YYYY HH24:MI:SS.

IS_DATE tells you if a value is a valid date. A valid date is any string representing a valid date in the default date format of MM/DD/YYYY HH24:MI:SS. If the strings you want to test are not in the default date format, use the format strings listed in the following table to specify the date format. If a string does not match the specified format string or is not a valid date, the function returns FALSE (0). If the string matches the format string and is a valid date, the function returns TRUE (1). IS_DATE format strings are not internationalized and must be entered in predefined formats as listed in the following table.

The following table summarizes the format strings for the functions TO_DATE and IS_DATE:

Format string	Description
AM, a.m., PM, p.m.	Meridian indicator. Use any of these format strings to specify AM and PM hours. AM and PM return the same values as do a.m. and p.m.
DAY	Name of day, including up to nine characters (for example, Wednesday). The DAY format string is not case sensitive.
DD	Day of month (1-31).
DDD	Day of year (001-366, including leap years).

Format string	Description
DY	Abbreviated three-character name for a day (for example, Wed). The DY format string is not case sensitive.
HH, HH12	Hour of day (1-12).
HH24	Hour of day (0-23), where 0 is 12AM (midnight).
J	Modified Julian Day. Convert strings in MJD format to date values. It ignores the time component of the source string, assigning all dates the time of 00:00:00. For example, the expression TO_DATE('2451544', 'J') converts 2451544 to Dec 31 1999 00:00:00.
MI	Minutes (0-59).
MM	Month (1-12).
MONTH	Name of month, including up to nine characters (for example, August). Case does not matter.
MON	Abbreviated three-character name for a month (for example, Aug). Case does not matter.
MS	Milliseconds (0-999).
NS	Nanoseconds. TO_DATE and IS_DATE can support sub-seconds by using the format token 'NS.' The unit is nanosecond. If the sub-second portion is in milliseconds, you can still use it by appending three zeroes as shown in the following examples: TO_DATE('2005-05-02 09:23:34 123000', 'YYYY-MM-DD HH24:MI:SS NS') TO_DATE('2005-05-02 09:23:34.123' '000', 'YYYY-MM-DD HH24:MI:SS.NS') TO_DATE('2005-05-02 09:23:34123000', 'YYYY-MM-DD HH24:MI:SSNS')
RR	Four-digit year (for example, 1998, 2034). Use when source strings include two-digit years. Use with TO_DATE to convert two-digit years to four-digit years. <ul style="list-style-type: none"> - Current Year Between 50 and 99. If the current year is between 50 and 99 (such as 1998) and the year value of the source string is between 0 and 49, Data Integration returns the next century plus the two-digit year from the source string. If the year value of the source string is between 50 and 99, Data Integration returns the current century plus the specified two-digit year. - Current Year Between 0 and 49. If the current year is between 0 and 49 (such as 2003) and the source string year is between 0 and 49, Data Integration returns the current century plus the two-digit year from the source string. If the source string year is between 50 and 99, Data Integration returns the previous century plus the two-digit year from the source string.
SS	Seconds (0-59).
SSSSS	Seconds since midnight. When you use SSSSS in a TO_DATE expression, Data Integration only evaluates the time portion of a date. For example, the expression TO_DATE(DATE_STR, 'MM/DD/YYYY SSSSS') converts 12/31/1999 3783 to 12/31/1999 01:02:03.
US	Microseconds (0-999999).
Y	The current year on the machine running the Secure Agent with the last digit of the year replaced with the string value.
YY	The current year on the machine running the Secure Agent with the last two digits of the year replaced with the string value.

Format string	Description
YYY	The current year on the machine running the Secure Agent with the last three digits of the year replaced with the string value.
YYYY	Four digits of a year. Do not use this format string if you are passing two-digit years. Use the RR or YY format string instead.

Requirements

Data Integration expects the format of the TO_DATE string to meet the following conditions:

- The format of the TO_DATE string must match the format string including any date separators. If it does not, Data Integration might return inaccurate values or skip the row. For example, if you pass the string '20200512', representing May 12, 2020, to TO_DATE, you must include the format string YYYYMMDD. If you do not include a format string, Data Integration expects the string in the default date format MM/DD/YYYY HH24:MI:SS. Likewise, if you pass a string that does not match the format string, Data Integration returns an error and skips the row. For example, if you pass the string 2020120 to TO_DATE and include the format string YYYYMMDD, Data Integration returns an error and skips the row because the string does not match the format string.
- The format string must always be enclosed within single quotation marks.

Tip: By default, Data Integration uses the format string MM/DD/YYYY HH24:MI:SS. The format string is not case sensitive.

Example

The following examples illustrate the J, RR, and SSSSS format strings. See the individual functions for more examples.

J format string

The following expression converts strings in the SHIP_DATE_MJD_STRING field to date values in the default date format:

```
TO_DATE (SHIP_DATE_MJD_STR, 'J')
```

SHIP_DATE_MJD_STR	RETURN_VALUE
2451544	Dec 31 1999 00:00:00
2415021	Jan 1 1900 00:00:00

Because the J format string does not include the time portion of a date, the return values have the time set to 00:00:00.

RR format string

The following expression converts a string to a four-digit year format. The current year is 1998:

```
TO_DATE( DATE_STR, 'MM/DD/RR')
```

DATE_STR	RETURN VALUE
04/01/98	04/01/1998 00:00:00
08/17/05	08/17/2005 00:00:00

YY format string

The following expression converts a string to a four-digit year format. The current year is 1998:

```
TO_DATE( DATE_STR, 'MM/DD/YY')
```

DATE_STR	RETURN VALUE
04/01/98	04/01/1998 00:00:00
08/17/05	08/17/1905 00:00:00

Note: For the second row, RR returns the year 2005, but YY returns the year 1905.

SSSSS format string

The following expression converts strings that include the seconds since midnight to date values:

```
TO_DATE( DATE_STR, 'MM/DD/YYYY SSSSS')
```

DATE_STR	RETURN_VALUE
12/31/1999 3783	12/31/1999 01:02:03
09/15/1996 86399	09/15/1996 23:59:59

Understanding date arithmetic

The transformation language provides built-in date functions so you can perform arithmetic on datetime values as follows:

ADD_TO_DATE

Add or subtract a specific portion of a date.

DATE_DIFF

Subtract two dates.

SET_DATE_PART

Change one part of a date.

You cannot use numeric arithmetic operators (such as + or -) to add or subtract dates.

Data Integration recognizes leap years and accepts dates between Jan. 1, 1753 00:00:00 AD and Dec. 31, 9999 23:59:59 AD.

Note: Data Integration uses the Date/Time datatype to specify date values. You can only use the date functions on datetime values.

CHAPTER 5

Functions

This chapter describes the functions in the transformation language in alphabetical order. Each function description includes:

- Syntax
- Return value
- Example

Function overview

The transformation language provides the following function categories:

- Aggregate
- Conversion
- Data Cleansing
- Date
- Encoding
- Financial
- Horizontal Expansion
- Numerical
- Scientific
- Special
- String
- Test
- Window

Aggregate functions

Aggregate functions return summary values for non-null values in selected fields.

With aggregate functions you can complete the following tasks:

- Calculate a single value for all rows in a group.
- Return a single value for each group in an Aggregator object.
- Apply filters to calculate values for specific rows in the selected fields.

- Use operators to perform arithmetic within the function.
- Calculate two or more aggregate values derived from the same source columns in a single pass.

Use aggregate functions in mapping tasks only.

The transformation language includes the following aggregate functions:

- AVG
- COUNT
- FIRST
- LAST
- MAX (Date)
- MAX (Number)
- MAX (String)
- MEDIAN
- MIN (Date)
- MIN (Number)
- MIN (String)
- PERCENTILE
- STDDEV
- SUM
- VARIANCE

Use aggregate functions in Aggregator objects only. You can nest only one aggregate function within another aggregate function. Data Integration evaluates the innermost aggregate function expression and uses the result to evaluate the outer aggregate function expression.

You can set up an Aggregator object that groups by ID and nests two aggregate functions as follows:

```
SUM( AVG( earnings ) )
```

where the dataset contains the following values:

ID	EARNINGS
1	32
1	45
1	100
2	65
2	75
2	76
3	21
3	45
3	99

The return value is 186. Data Integration groups by ID, evaluates the AVG expression, and returns three values. Then it adds the values with the SUM function to get the result.

Filter conditions

Use a filter condition to limit the rows returned in a search.

A filter limits the rows returned in a search. You can apply a filter condition to all aggregate functions and to CUME, MOVINGAVG, and MOVINGSUM. The filter condition must evaluate to TRUE, FALSE, or NULL. If the filter condition evaluates to NULL or FALSE, Data Integration does not select the row.

You can enter any valid transformation expression. For example, the following expression calculates the median salary for all employees who make more than \$50,000:

```
MEDIAN( SALARY, SALARY > 50000 )
```

You can also use other numeric values as the filter condition. For example, you can enter the following as the complete syntax for the MEDIAN function, including a numeric field:

```
MEDIAN( PRICE, QUANTITY > 0 )
```

In all cases, Data Integration rounds a decimal value to an integer (for example, 1.5 to 2, 1.2 to 1, 0.35 to 0) for the filter condition. If the value rounds to 0, the filter condition returns FALSE. If you do not want to round up a value, use the TRUNC function to truncate the value to an integer:

```
MEDIAN( PRICE, TRUNC( QUANTITY ) > 0 )
```

If you omit the filter condition, the function selects all rows in the field.

Conversion functions

The transformation language provides the following conversion functions:

- TO_BIGINT
- TO_CHAR(Date)
- TO_CHAR(Number)
- TO_DATE
- TO_DECIMAL
- TO_FLOAT
- TO_INTEGER

Data cleansing functions

The transformation language provides a group of functions to eliminate data errors. You can complete the following tasks with data cleansing functions:

- Test source values.
- Convert the datatype of an source value.
- Trim string values.
- Replace characters in a string.
- Encode strings.
- Match patterns in regular expressions.

The transformation language provides the following data cleansing functions:

- BETWEEN

- GREATEST
- IN
- INSTR
- IS_DATE
- IS_NUMBER
- IS_SPACES
- ISNULL
- LEAST
- LTRIM
- METAPHONE
- REG_EXTRACT
- REG_MATCH
- REG_REPLACE
- REPLACECHR
- REPLACESTR
- RTRIM
- SOUNDEX
- SUBSTR
- TO_BIGINT
- TO_CHAR
- TO_DATE
- TO_DECIMAL
- TO_FLOAT
- TO_INTEGER

Date functions

The transformation language provides a group of date functions to round, truncate, or compare dates, extract one part of a date, or perform arithmetic on a date.

You can pass any value with a date datatype to any of the date functions. However, if you want to pass a string to a date function, you must first use the TO_DATE function to convert it to a transformation Date/Time datatype.

The transformation language provides the following date functions:

- ADD_TO_DATE
- DATE_COMPARE
- DATE_DIFF
- GET_DATE_PART
- LAST_DAY
- MAKE_DATE_TIME
- ROUND
- SET_DATE_PART

- SYSTIMESTAMP
- TRUNC

Several of the date functions include a *format* argument. You must specify one of the transformation language format strings for this argument. Date format strings are not internationalized.

The Date/Time transformation datatype does not support milliseconds. Therefore, if you pass a date with milliseconds, Data Integration truncates the millisecond portion of the date.

Encoding functions

The transformation language provides the following functions for data encoding, encryption, compression, and checksum:

- AES_DECRYPT
- AES_ENCRYPT
- AES_GCM_DECRYPT
- AES_GCM_ENCRYPT
- COMPRESS
- CRC32
- DEC_BASE64
- DECOMPRESS
- ENC_BASE64
- MD5

Financial functions

The transformation language provides the following financial functions:

- FV
- NPER
- PMT
- PV
- RATE

Horizontal expansion functions

Use a horizontal expansion function to create a horizontal macro expression.

Horizontal expansion functions use the following naming convention: %OPR_<function_type>%.

Horizontal expansion functions use square brackets (`[]`) instead of parentheses.

The transformation language provides the following horizontal expansion functions:

- %OPR_CONCAT%
- %OPR_CONCATDELIM%
- %OPR_IIF%
- %OPR_SUM%

Numeric functions

The transformation language provides the following numeric functions:

- ABS
- CEIL
- CONV
- CUME
- EXP
- FLOOR
- LN
- LOG
- MOD
- MOVINGAVG
- MOVINGSUM
- POWER
- RAND
- ROUND
- SIGN
- SQRT
- TRUNC

Scientific functions

The transformation language provides the following scientific functions:

- COS
- COSH
- SIN
- SINH
- TAN
- TANH

Special functions

The transformation language provides the following special functions:

- ABORT
- DECODE
- ERROR
- IIF
- SETCOUNTVARIABLE
- SETMAXVARIABLE
- SETMINVARIABLE

- SETVARIABLE

You can nest other functions within special functions.

String functions

The transformation language provides the following string functions:

- ASCII
- CHOOSE
- CHR
- CHRCODE
- CONCAT
- INDEXOF
- INITCAP
- INSTR
- LENGTH
- LOWER
- LPAD
- LTRIM
- REPLACECHR
- REPLACESTR
- REVERSE
- RPAD
- RTRIM
- SUBSTR
- UPPER

To evaluate character data, the string functions LOWER, UPPER, and INITCAP use the code page of the Secure Agent that runs the task.

Test functions

The transformation language provides the following test functions:

- ISNULL
- IS_DATE
- IS_NUMBER
- IS_SPACES

Function quick reference

The following table contains the syntax and a brief description of the functions that can be used in field expressions:

Function	Function type	Syntax	Description
%OPR_CONCAT%	Horizontal Expansion	%OPR_CONCAT[<i>macro_input_field</i>]%	Uses the CONCAT function and expands an expression in an expression macro to concatenate multiple fields. For more information, see "%OPR_CONCAT%" on page 49
%OPR_CONCATDELIM%	Horizontal Expansion	%OPR_CONCATDELIM[<i>macro_input_field</i>]%	Uses the CONCAT function and expands an expression in an expression macro to concatenate multiple fields, and adds a comma delimiter. For more information, see "%OPR_CONCATDELIM%" on page 50
%OPR_IIF%	Horizontal Expansion	%OPR_IIF[<i>condition</i> , <i>macro_input_field</i> [, <i>value</i>]]%	Uses the IIF function and expands an expression in an expression macro to evaluate a set of IIF statements. For more information, see "%OPR_IIF%" on page 51
%OPR_SUM%	Horizontal Expansion	%OPR_SUM[<i>macro_input_field</i> [, <i>filter_condition</i>]]%	Uses the SUM function and expands an expression in an expression macro to return the sum of all fields. For more information, see "%OPR_SUM%" on page 52
ABORT	Special	ABORT(<i>string</i>)	Stops the session and issues a specified error message. For more information, see "ABORT" on page 53 .
ABS	Numeric	ABS(<i>numeric_value</i>)	Returns the absolute value of a numeric value. For more information, see "ABS" on page 53 .
ADD_TO_DATE	Data Cleansing, Date	ADD_TO_DATE(<i>date</i> , <i>format</i> , <i>amount</i>)	Adds a specified amount to one part of a date/time value, and returns a date in the same format as the specified date. If you do not specify the year as YYYY, Data Integration assumes the date is in the current century. For more information, see "ADD_TO_DATE" on page 54 .
AES_DECRYPT	Encoding	AES_DECRYPT (<i>value</i> , <i>key</i>)	Returns the decrypted value in string format, after performing AES-ECB decryption on the input value. For more information, see "AES_DECRYPT" on page 57 .

Function	Function type	Syntax	Description
AES_ENCRYPT	Encoding	AES_ENCRYPT (<i>value</i> , <i>key</i>)	Returns binary data in encrypted format, after performing AES-ECB encryption on the input value. For more information, see "AES_ENCRYPT" on page 58 .
AES_GCM_DECRYPT	Encoding	AES_GCM_DECRYPT (<i>value</i> , <i>init_vector</i> , <i>key</i> [, <i>keysize</i>])	Returns plaintext, a decrypted value as a string, after performing AES-GCM decryption on an input value with the given initialization vector and key. For more information, see "AES_GCM_DECRYPT" on page 59 .
AES_GCM_ENCRYPT	Encoding	AES_GCM_ENCRYPT (<i>value</i> , <i>init_vector</i> , <i>key</i> [, <i>keysize</i>])	Returns ciphertext as a binary value after performing AES-GCM encryption on an input value with the given initialization vector and key. The ciphertext is encrypted plaintext. For more information, see "AES_GCM_ENCRYPT" on page 60 .
ASCII	String	ASCII (<i>string</i>)	Returns the numeric ASCII value of the first character of the string passed to the function. This function is identical in behavior to the CHRCODE function. If you use the ASCII function in existing expressions, it will still work correctly. However, when you create new expressions, use the CHRCODE function instead of the ASCII function. For more information, see "ASCII" on page 61 .
AVG	Aggregate	AVG (<i>numeric_value</i> [, <i>filter_condition</i>])	Returns the average of all values in a group of rows. For more information, see "AVG" on page 62 .
CEIL	Numeric	CEIL (<i>numeric_value</i>)	Returns the smallest integer greater than or equal to the specified numeric value. For more information, see "CEIL" on page 63 .
CHOOSE	String	CHOOSE(<i>index</i> , <i>string1</i> , [<i>string2</i> , ..., <i>stringN</i>])	Chooses a string from a list of strings based on a given position. For more information, see "CHOOSE" on page 64 .
CHR	String	CHR(<i>numeric_value</i>)	Returns the ASCII character corresponding to the specified numeric value. For more information, see "CHR" on page 65 .

Function	Function type	Syntax	Description
CHRCODE	String	CHRCODE(<i>string</i>)	Returns the numeric ASCII value of the first character of the string passed to the function. This function is identical in behavior to the ASCII function. For more information, see “CHRCODE” on page 66 .
COMPRESS	Encoding	COMPRESS(<i>value</i>)	Compresses data using the zlib compression algorithm. For more information, see “COMPRESS” on page 67 .
CONCAT	String	CONCAT(<i>first_string</i> , <i>second_string</i>)	Concatenates two strings. For more information, see “CONCAT” on page 67 .
CONVERT_BASE	Numeric	CONVERT_BASE(<i>value</i> , <i>source_base</i> , <i>dest_base</i>)	Converts a number from one base value to another base value. For more information, see “CONVERT_BASE” on page 69 .
COS	Scientific	COS(<i>numeric_value</i>)	Returns the cosine of a numeric value (expressed in radians). For more information, see “COS” on page 69 .
COSH	Scientific	COSH(<i>numeric_value</i>)	Returns the hyperbolic cosine of a numeric value (expressed in radians). For more information, see “COSH” on page 70 .
COUNT	Aggregate	COUNT(<i>value</i> [, <i>filter_condition</i>]) or COUNT(* [, <i>filter_condition</i>])	Returns the number of rows that have non-null values in a group. For more information, see “COUNT” on page 71 .
CRC32	Encoding	CRC32(<i>value</i>)	Returns a 32-bit Cyclic Redundancy Check (CRC32) value. For more information, see “CRC32” on page 73 .
CUME	Numeric	CUME(<i>numeric_value</i> [, <i>filter_condition</i>])	Returns a running total. For more information, see “CUME” on page 74 .
DATE_COMPARE	Data Cleansing, Date	DATE_COMPARE(<i>date1</i> , <i>date2</i>)	Returns a value indicating the earlier of two dates. For more information, see “DATE_COMPARE” on page 75 .

Function	Function type	Syntax	Description
DATE_DIFF	Data Cleansing, Date	DATE_DIFF(<i>date1</i> , <i>date2</i> , <i>format</i>)	Returns the length of time between two dates, measured in the specified increment (years, months, days, hours, minutes, or seconds). For more information, see "DATE_DIFF" on page 76 .
DEC_BASE64	Encoding	DEC_BASE64(<i>value</i>)	Decodes the value and returns a string with the binary data representation of the data. For more information, see "DEC_BASE64" on page 78 .
DECODE	Special	DECODE(<i>value</i> , <i>first_search</i> , <i>first_result</i> [, <i>second_search</i> , <i>second_result</i>]...[, <i>default</i>])	Searches a column for the specified value. For more information, see "DECODE" on page 79 .
DECOMPRESS	Encoding	DECOMPRESS(<i>value</i> , <i>precision</i>)	Decompresses data using the zlib compression algorithm. For more information, see "DECOMPRESS" on page 81 .
ENC_BASE64	Encoding	ENC_BASE64(<i>value</i>)	Encodes data by converting binary data to string data using Multipurpose Internet Mail Extensions (MIME) encoding. For more information, see "ENC_BASE64" on page 82 .
ERROR	Special	ERROR(<i>string</i>)	Causes the Data Integration to skip a row. It writes the row into the error rows file with the specified error message. For more information, see "ERROR" on page 82 .
EXP	Numeric	EXP(<i>exponent</i>)	Returns e raised to the specified power (exponent), where e=2.71828183. For more information, see "EXP" on page 83 .
FIRST	Aggregate	FIRST(<i>value</i> [, <i>filter_condition</i>])	Returns the first value found within a field or group. For more information, see "FIRST" on page 84 .
FLOOR	Numeric	FLOOR(<i>numeric_value</i>)	Returns the largest integer less than or equal to the specified numeric value. For more information, see "FLOOR" on page 85 .
FV	Financial	FV(<i>rate</i> , <i>terms</i> , <i>payment</i> [, <i>present value</i> , <i>type</i>])	Returns the future value of an investment, where you make periodic, constant payments and the investment earns a constant interest rate. For more information, see "FV" on page 86 .

Function	Function type	Syntax	Description
GET_DATE_PART	Date, Data Cleansing	GET_DATE_PART(<i>date</i> , <i>format</i>)	Returns the specified part of a date as an integer value, based on the default date format of MM/DD/YYYY HH24:MI:SS. For more information, see “GET_DATE_PART” on page 87 .
GREATEST	Data Cleansing	GREATEST(<i>value1</i> , [<i>value2</i> , ..., <i>valueN</i>], <i>CaseFlag</i>)	Returns the greatest value from a list of input values. For more information, see “GREATEST” on page 89 .
IIF	Special	IIF(<i>condition</i> , <i>value2</i> [, <i>value2</i>])	Returns one of two values you specify, based on the results of a condition. For more information, see “IIF” on page 90 .
IN	Data Cleansing	IN(<i>valueToSearch</i> , <i>value1</i> , [<i>value2</i> , ..., <i>valueN</i>], <i>CaseFlag</i>)	Matches input data to a list of values. For more information, see “IN ” on page 92 .
INDEXOF	String	INDEXOF(<i>valueToSearch</i> , <i>string1</i> , [<i>string2</i> , ..., <i>stringN</i>], <i>CaseFlag</i>)	Finds the index of a string among a list of strings. For more information, see “INDEXOF” on page 92 .
INITCAP	String	INITCAP(<i>string</i>)	Capitalizes the first letter in each word of a string and converts all other letters to lowercase. For more information, see “INITCAP” on page 93 .
INSTR	String, Data Cleansing	INSTR(<i>string</i> , <i>search_value</i> [, <i>start</i> [, <i>occurrence</i>]])	Returns the position of a character set in a string, counting from left to right. For more information, see “INSTR” on page 95 .
IS_DATE	Data Cleansing, Test	IS_DATE(<i>value</i>)	Returns whether a value is a valid date. For more information, see “IS_DATE” on page 97 .
IS_NUMBER	Data Cleansing, Test	IS_NUMBER(<i>value</i>)	Returns whether a string is a valid number. For more information, see “IS_NUMBER” on page 99 .
IS_SPACES	Data Cleansing, Test	IS_SPACES(<i>value</i>)	Returns whether a value consists entirely of spaces. For more information, see “IS_SPACES” on page 101 .
ISNULL	Data Cleansing, Test	ISNULL(<i>value</i>)	Returns whether a value is NULL. For more information, see “ISNULL” on page 102 .

Function	Function type	Syntax	Description
LAST	Aggregate	LAST(<i>value</i> [, <i>filter_condition</i>])	Returns the last row in the selected field. For more information, see "LAST" on page 103 .
LAST_DAY	Data Cleansing, Date	LAST_DAY(<i>date</i>)	Returns the date of the last day of the month for each date in a column. For more information, see "LAST_DAY" on page 104 .
LEAST	Data Cleansing	LEAST(<i>value1</i> , [<i>value2</i> , ..., <i>valueN</i>], <i>CaseFlag</i>)	Returns the smallest value from a list of input values. For more information, see "LEAST" on page 105 .
LENGTH	String	LENGTH(<i>string</i>)	Returns the number of characters in a string, including trailing blanks. For more information, see "LENGTH" on page 106 .
LN	Numeric	LN(<i>numeric_value</i>)	Returns the natural logarithm of a numeric value. For more information, see "LN" on page 107 .
LOG	Numeric	LOG(<i>base</i> , <i>exponent</i>)	Returns the logarithm of a numeric value. For more information, see "LOG" on page 107 .
LOWER	String	LOWER(<i>string</i>)	Converts uppercase string characters to lowercase. For more information, see "LOWER" on page 109 .
LPAD	String	LPAD(<i>first_string</i> , <i>length</i> [, <i>second_string</i>])	Adds a set of blanks or characters to the beginning of a string to set a string to a specified length. For more information, see "LPAD" on page 110 .
LTRIM	String, Data Cleansing	LTRIM(<i>string</i> [, <i>trim_set</i>])	Removes blanks or characters from the beginning of a string. For more information, see "LTRIM" on page 111 .
MAKE_DATE_TIME	Data Cleansing, Date	MAKE_DATE_TIME(<i>year</i> , <i>month</i> , <i>day</i> , <i>hour</i> , <i>minute</i> , <i>second</i>)	Returns the date and time based on the input values. For more information, see "MAKE_DATE_TIME" on page 112 .
MAX (Dates)	Aggregate	MAX(<i>date</i> [, <i>filter_condition</i>])	Returns the latest date found within a field or group. For more information, see "MAX (Dates)" on page 113 .

Function	Function type	Syntax	Description
MAX (Numbers)	Aggregate	MAX(<i>numeric_value</i> [, <i>filter_condition</i>])	Returns the maximum numeric value found within a field or group. For more information, see "MAX (Numbers)" on page 114 .
MAX (String)	Aggregate	MAX(<i>string</i> [, <i>filter_condition</i>])	Returns the highest string value found within a field or group. For more information, see "MAX (String)" on page 116 .
MD5	Encoding	MD5(<i>value</i>)	Calculates the checksum of the input value. The function uses Message-Digest algorithm 5 (MD5). For more information, see "MD5" on page 117 .
MEDIAN	Aggregate	MEDIAN(<i>numeric_value</i> [, <i>filter_condition</i>])	Returns the median of all values in a selected field. For more information, see "MEDIAN" on page 118 .
METAPHONE	Data Cleansing	METAPHONE(<i>string</i> [, <i>length</i>])	Encodes characters of the English language alphabet (A-Z). For more information, see "METAPHONE" on page 119 .
MIN (Dates)	Aggregate	MIN(<i>date</i> [, <i>filter_condition</i>])	Returns the earliest date found in a field or group. For more information, see "MIN (Dates)" on page 123 .
MIN (Numbers)	Aggregate	MIN(<i>date</i> [, <i>filter_condition</i>])	Returns the smallest numeric value found in a field or group. For more information, see "MIN (Numbers)" on page 124 .
MIN (String)	Aggregate	MIN(<i>string</i> [, <i>filter_condition</i>])	Returns the lowest string value found in a field or group. For more information, see "MIN (String)" on page 125 .
MOD	Numeric	MOD(<i>numeric_value</i> , <i>divisor</i>)	Returns the remainder of a division calculation. For more information, see "MOD" on page 127 .
MOVINGAVG	Numeric	MOVINGAVG(<i>numeric_value</i> , <i>rowset</i> [, <i>filter_condition</i>])	Returns the average (row-by-row) of a specified set of rows. For more information, see "MOVINGAVG" on page 128 .
MOVINGSUM	Numeric	MOVINGSUM(<i>numeric_value</i> , <i>rowset</i> [, <i>filter_condition</i>])	Returns the sum (row-by-row) of a specified set of rows. For more information, see "MOVINGSUM" on page 129 .

Function	Function type	Syntax	Description
NPER	Financial	NPER(<i>rate</i> , <i>present value</i> , <i>payment</i> [, <i>future value</i> , <i>type</i>])	Returns the number of periods for an investment based on a constant interest rate and periodic, constant payments. For more information, see "NPER" on page 130 .
PERCENTILE	Aggregate	PERCENTILE(<i>numeric_value</i> , <i>percentile</i> [, <i>filter_condition</i>])	Calculates the value that falls at a given percentile in a group of numbers. For more information, see "PERCENTILE" on page 131 .
PMT	Financial	PMT(<i>Rate</i> , <i>terms</i> , <i>present value</i> [, <i>future value</i> , <i>type</i>])	Returns the payment for a loan based on constant payments and a constant interest rate. For more information, see "PMT" on page 133 .
POWER	Numeric	POWER(<i>base</i> , <i>exponent</i>)	Returns a value raised to the specified exponent. For more information, see "POWER" on page 134 .
PV	Financial	PV(<i>Rate</i> , <i>terms</i> , <i>payment</i> [, <i>future value</i> , <i>type</i>])	Returns the present value of an investment. For more information, see "PV" on page 135 .
RAND	Numeric	RAND(<i>seed</i>)	Returns a random number between 0 and 1. For more information, see "RAND" on page 136 .
RATE	Financial	RATE(<i>terms</i> , <i>payment</i> , <i>present value</i> [, <i>future value</i> , <i>type</i>])	Returns the interest rate earned per period by a security. For more information, see "RATE" on page 136 .
REG_EXTRACT	Data Cleansing	REG_EXTRACT(<i>subject</i> , <i>pattern</i> , <i>subPatternNum</i>)	Extracts subpatterns of a regular expression within an input value. For more information, see "REG_EXTRACT" on page 137 .
REG_MATCH	Data Cleansing	REG_MATCH(<i>subject</i> , <i>pattern</i>)	Returns whether a value matches a regular expression pattern. For more information, see "REG_MATCH" on page 139 .
REG_REPLACE	Data Cleansing	REG_REPLACE(<i>subject</i> , <i>pattern</i> , <i>replace</i> , <i>numReplacements</i>)	Replaces characters in a string with a another character pattern. For more information, see "REG_REPLACE" on page 141 .
REPLACECHR	String, Data Cleansing	REPLACECHR(<i>CaseFlag</i> , <i>InputString</i> , <i>OldCharSet</i> , <i>NewChar</i>)	Replaces characters in a string with a single character or no character. For more information, see "REPLACECHR" on page 142 .

Function	Function type	Syntax	Description
REPLACESTR	String, Data Cleansing	REPLACESTR (<i>InputString</i> , <i>OldString1</i> , [<i>OldString2</i> , ... <i>OldStringN</i> ,] <i>NewString</i>)	Replaces characters in a string with a single character, multiple characters, or no character. For more information, see "REPLACESTR" on page 145 .
REVERSE	String	REVERSE(<i>string</i>)	Reverses the input string. For more information, see "REVERSE" on page 147 .
ROUND	Data Cleansing, Date, Numeric	ROUND(<i>date</i> [, <i>format</i>]) or ROUND(<i>numeric_value</i> [, <i>precision</i>])	For data cleansing, rounds one part of a date. For numeric values, rounds numbers to a specified digit. For more information, see "ROUND (Dates)" on page 148 or "ROUND (Numbers)" on page 151 .
RPAD	String	RPAD(<i>first_string</i> , <i>length</i> [, <i>second_string</i>])	Converts a string to a specified length by adding blanks or characters to the end of the string. For more information, see "RPAD" on page 153 .
RTRIM	String, Data Cleansing	RTRIM(<i>string</i> [, <i>trim_set</i>])	Removes blanks or characters from the end of a string. For more information, see "RTRIM" on page 154 .
SET_DATE_PART	Data Cleansing, Date	SET_DATE_PART(<i>date</i> , <i>format</i> , <i>value</i>)	Sets one part of a date/time value to a specified value. For more information, see "SET_DATE_PART" on page 155 .
SETCOUNTVARIABLE	Special	SETCOUNTVARIABLE(\$ <i>\$Variable</i>)	Counts the rows evaluated by the function and increments the current value of an in-out parameter based on the count. For more information, see "SETCOUNTVARIABLE" on page 158 .
SETMAXVARIABLE	Special	SETMAXVARIABLE(\$ <i>\$Variable</i> , <i>value</i>)	Sets the current value of an in-out parameter to the higher of two values: the current value of the parameter or the value you specify. For more information, see "SETMAXVARIABLE" on page 158 .
SETMINVARIABLE	Special	SETMINVARIABLE(\$ <i>\$Variable</i> , <i>value</i>)	Sets the current value of an in-out parameter to the lower of two values: the current value of the parameter or the value you specify. For more information, see "SETMINVARIABLE" on page 159 .

Function	Function type	Syntax	Description
SETVARIABLE	Special	SETVARIABLE(<i>\$\$Variable, value</i>)	Sets the current value of an in-out parameter to a value you specify. For more information, see “SETVARIABLE” on page 160 .
SIGN	Numeric	SIGN(<i>numeric_value</i>)	Indicates whether a numeric value is positive, negative, or 0. For more information, see “SIGN” on page 161 .
SIN	Scientific	SIN(<i>numeric_value</i>)	Returns the sin of a numeric value expressed in radians. For more information, see “SIN” on page 162 .
SINH	Scientific	SINH(<i>numeric_value</i>)	Returns the hyperbolic sin of a numeric value expressed in radians. For more information, see “SINH” on page 163 .
SOUNDEX	Data Cleansing	SOUNDEX(<i>string</i>)	Encodes a string value into a four-character string. For more information, see “SOUNDEX” on page 164 .
SQRT	Numeric	SQRT(<i>numeric_value</i>)	Returns the square root of a positive numeric value. For more information, see “SQRT” on page 166 .
STDDEV	Aggregate	STDDEV(<i>numeric_value</i> [, <i>filter_condition</i>])	Returns the standard deviation of the numeric values you pass to this function. For more information, see “STDDEV” on page 166 .
SUBSTR	String, Data Cleansing	SUBSTR(<i>string, start</i> [, <i>length</i>])	Returns a portion of a string. For more information, see “SUBSTR” on page 168 .
SUM	Aggregate	SUM(<i>numeric_value</i> [, <i>filter_condition</i>])	Returns the sum of all values in the selected field. For more information, see “SUM” on page 170 .
SYSTIMESTAMP	Date	SYSTIMESTAMP([<i>format</i>])	Returns the current date and time with precision to the nanosecond of the system that hosts the Secure Agent that starts the task. For more information, see “SYSTIMESTAMP” on page 171 .
TAN	Scientific	TAN(<i>numeric_value</i>)	Returns the tangent of a numeric value expressed in radians. For more information, see “TAN” on page 172 .

Function	Function type	Syntax	Description
TANH	Scientific	TANH(<i>numeric_value</i>)	Returns the hyperbolic tangent of a numeric value expressed in radians. For more information, see "TANH" on page 173 .
TO_BIGINT	Conversion, Data Cleansing	TO_BIGINT(<i>value</i> [, <i>flag</i>])	Converts a string or numeric value to a bigint value. For more information, see "TO_BIGINT" on page 174 .
TO_CHAR	Conversion, Data Cleansing	TO_CHAR(<i>date</i> [, <i>format</i>]) or TO_CHAR(<i>numeric_value</i>)	Converts dates or numeric values to text strings. For more information, see "TO_CHAR (Dates)" on page 176 or "TO_CHAR (Numbers)" on page 180 .
TO_DATE	Conversion, Data Cleansing	TO_DATE(<i>string</i> [, <i>format</i>])	Converts a character string to a date datatype in the same format as the character string. For conversion, you must specify the date format if the string is not in the mm/dd/yyyy hh:mi:ss format. For more information, see "TO_DATE" on page 181 . For more information about date formats, see Chapter 4, "Dates" on page 18 .
TO_DECIMAL	Conversion, Data Cleansing	TO_DECIMAL(<i>value</i> [, <i>scale</i>])	Converts any value (except binary) to a decimal. For more information, see "TO_DECIMAL" on page 184 .
TO_FLOAT	Conversion, Data Cleansing	TO_FLOAT(<i>value</i>)	Converts any value (except binary) to a double-precision floating point number (the Double datatype). For more information, see "TO_FLOAT" on page 184 .
TO_INTEGER	Conversion, Data Cleansing	TO_INTEGER(<i>value</i>)	Converts any value (except binary) to an integer by rounding the decimal portion of a value. For more information, see "TO_INTEGER" on page 185 .
TRUNC	Data Cleansing, Date, Numeric	TRUNC(<i>date</i> [, <i>format</i>]) or TRUNC(<i>numeric_value</i> [, <i>precision</i>])	Truncates dates to a specific year, month, day, hour, or minute. Truncates numeric values to a specific digit. For more information, see "TRUNC (Dates)" on page 187 or "TRUNC (Numbers)" on page 189 .

Function	Function type	Syntax	Description
UPPER	String	UPPER(<i>string</i>)	Converts lowercase string characters to uppercase. For more information, see "UPPER" on page 191 .
VARIANCE	Aggregate	VARIANCE(<i>numeric_value</i> [, <i>filter_condition</i>])	Returns the variance of a value you pass to it. For more information, see "VARIANCE" on page 191 .

%OPR_CONCAT%

Uses the CONCAT function and expands an expression in an expression macro to concatenate multiple fields. %OPR_CONCAT% converts all data to text, and then concatenates the fields.

Syntax

```
%OPR_CONCAT[ macro_input_field ]%
```

The following table describes the argument for this function:

Argument	Required/Optional	Description
<i>macro_input_field</i>	Required	Any datatype except Binary. You can use a set of incoming fields or a set of constants. You can enter a macro input field or an expression that includes at least one macro input field.

Return Value

String.

NULL if all strings in the set of fields are NULL.

Returns NULL if all strings are null. Otherwise, ignores the null values and concatenates the strings that are not null.

Example

You have two legacy systems that have merged into one system. You need to concatenate the identification numbers from both systems into another system. The macro input field %ClientID% contains the following fields:

```
ID1, ID2
```

The following expression concatenates the fields in %ClientID%:

```
%OPR_CONCAT[ %ClientID% ]%
```

%OPR_CONCAT% concatenates the following IDs into one return value:

ID1	ID2	RETURN VALUE
A6JU4199	7021	A6JU41997021
NULL	7022	7022
T7QX9018	7023	T7QX90187023

ID1	ID2	RETURN VALUE
C2CL5421	7024	C2CL54217024
NULL	NULL	NULL

%OPR_CONCATDELIM%

Uses the CONCAT function and expands an expression in an expression macro to concatenate multiple fields, and adds a comma delimiter. %OPR_CONCATDELIM% converts all data to text, and then concatenates the fields.

Syntax

```
%OPR_CONCATDELIM[ macro_input_field ]%
```

The following table describes the argument for this function:

Argument	Required/Optional	Description
<i>macro_input_field</i>	Required	Any datatype except Binary. You can use a set of incoming fields or a set of constants. You can enter a macro input field or an expression that includes at least one macro input field.

Return Value

String.

Returns NULL if all strings are null. Otherwise, ignores the null values and concatenates the strings that are not null.

If all strings in the set are NULL, %OPR_CONCATDELIM% returns NULL.

Example

The macro input field %Address% contains the following fields:

```
City, State, Zip
```

The following expression concatenates the fields in %Address% and adds a comma between fields:

```
%OPR_CONCATDELIM[ %Address% ]%
```

%OPR_CONCAT_DELIM% concatenates the following address fields into one return value:

CITY	STATE	ZIP	RETURN VALUE
Reston	VA	20190	Reston,VA,20190
Maywood	IL	NULL	Maywood,IL
Eagle River	AK	99577	Eagle River,AK,99577
St. Louis	MO	63110	St. Louis,MO,63110
NULL	NULL	NULL	NULL

%OPR_IIF%

Uses the IIF function and expands an expression in an expression macro to evaluate a set of IIF statements.

Syntax

```
%OPR_IIF[ condition, macro_input_field [, value ] ]%
```

The following table describes the arguments for this function:

Argument	Required/ Optional	Description
<i>condition</i>	Required	The condition you want to evaluate. You can enter any valid expression that evaluates to TRUE or FALSE. You can enter a macro input field or an expression that includes at least one macro input field.
<i>macro_input_field</i>	Required	The values you want to return if the condition is TRUE. Any data type except Binary. The return value is the data type specified by this argument. You can enter a macro input field or an expression that includes at least one macro input field.
<i>value</i>	Optional	The value you want to return if the condition is FALSE. Any data type except Binary. In a horizontal or vertical macro, you can enter any valid expression. In a hybrid macro, enter the input macro field that is used to define the output macro field.

Unlike conditional functions in some systems, the FALSE (*value*) condition in the %OPR_IIF% function is not required. If you omit *value*, the function returns the following values when the condition is FALSE:

- Zero if *macro_input_field* is a Numeric data type.
- Empty string if *macro_input_field* is a String data type.
- NULL if *macro_input_field* is a Date/Time data type.

Return Value

macro_input_field if the condition is TRUE.

value if the condition is FALSE.

If the data contains multibyte characters and the condition argument compares string data, the return value depends on the code page of the Secure Agent that runs the task.

%OPR_IIF% and Data types

When you use %OPR_IIF%, the data type of the return value is the same as the data type of the result with the greatest precision.

When at least one result is Double, the data type of the return value is Double.

Example

The following macro input fields %tmin% and %tmax% create ranges that correspond to the following %type% macro input field:

%tmin%	%tmax%	%type%
0	30	very cold
31	60	cold
61	90	warm
91	100	hot
101	150	very hot

The following expression assigns a type based on the temperature data:

```
%OPR_IIF [ (TEMP >= %tmin%) AND (TEMP <= %tmax%), '%type%', 'out of range' ]%
```

%OPR_IIF% evaluates the following temperatures and returns a type:

TEMP	RETURN VALUE
79	warm
21	very cold
170	out of range
99	hot
90	warm

%OPR_SUM%

Uses the SUM function and expands an expression in an expression macro to return the sum of all fields. Optionally, you can apply a filter to limit the rows you read to calculate the total. You can use only one other aggregate function within SUM, and the nested function must return a numeric datatype.

Syntax

```
%OPR_SUM[ macro_input_field [, filter_condition ] ]%
```

The following table describes the arguments for this function:

Argument	Required/Optional	Description
<i>macro_input_field</i>	Required	Numeric datatype. Passes the values you want to add. You can enter a macro input field or an expression that includes at least one macro input field.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all fields passed to the function are NULL or if no rows are selected. For example, if a filter condition evaluates to FALSE or NULL for all rows, %OPR_SUM% returns NULL .

If a single value is NULL, %OPR_SUM% ignores it. If all values are NULL, %OPR_SUM% returns NULL.

Group By

%OPR_SUM% groups values based on group by fields that you define in the transformation, and returns one result for each group.

If there is no group by field, %OPR_SUM% treats all rows as one group, returning one value.

Example

The %Sales% macro input field represents the following fields:

Q1, Q2, Q3, Q4

The following expression returns the sum of the fields that %Sales% represents:

```
%OPR_SUM[ %Sales% ]%
```

%OPR_SUM% adds the following sales figures from each quarter to return one value:

Q1	Q2	Q3	Q4	RETURN VALUE
50	200	50	100	400
100	NULL	100	250	450
500	200	200	200	1100
NULL	NULL	NULL	NULL	NULL
400	NULL	NULL	400	800

ABORT

Stops the task and issues an error message in the job details. When Data Integration encounters an ABORT function, it stops transforming data at that row.

Use ABORT to validate data. Generally, you use ABORT within an IIF or DECODE function to set rules for aborting a task. You might use ABORT to avoid writing null values to the target.

Syntax

```
ABORT( string )
```

Argument	Required/Optional	Description
string	Required	String. The message you want to display in the job details when the session stops. The string can be any length. You can enter any valid expression.

Return Value

NULL.

ABS

Returns the absolute value of a numeric value.

Syntax

```
ABS( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. Returns the absolute value of a number. You can enter any valid expression.

Return Value

Positive numeric value. ABS returns the same datatype as the numeric value passed as an argument. If you pass a Double, it returns a Double. Likewise, if you pass an Integer, it returns an Integer.

NULL if you pass a null value to the function.

Example

The following expression returns the difference between two numbers as a positive value, regardless of which number is larger:

```
ABS( PRICE - COST )
```

PRICE	COST	RETURN VALUE
250	150	100
52	48	4
169.95	69.95	100
59.95	NULL	NULL
70	30	40
430	330	100
100	200	100

ADD_TO_DATE

Adds a specified amount to one part of a datetime value, and returns a date in the same format as the date you pass to the function.

ADD_TO_DATE accepts positive and negative integer values. Use ADD_TO_DATE to change the following parts of a date:

Year

Enter a positive or negative integer in the *amount* argument. Use any of the year format strings: Y, YY, YYYY, or YYYY. For example, the expression `ADD_TO_DATE (SHIP_DATE, 'YY', 10)` adds 10 years to all dates in the SHIP_DATE column.

Month

Enter a positive or negative integer in the *amount* argument. Use any of the month format strings: MM, MON, MONTH. For example, the expression `ADD_TO_DATE(SHIP_DATE, 'MONTH', -10)` subtracts 10 months from each date in the SHIP_DATE column.

Day

Enter a positive or negative integer in the *amount* argument. Use any of the day format strings: D, DD, DDD, DY, and DAY. For example, the expression `ADD_TO_DATE(SHIP_DATE, 'DD', 10)` adds 10 days to each date in the SHIP_DATE column.

Hour

Enter a positive or negative integer in the *amount* argument. Use any of the hour format strings: HH, HH12, HH24. For example, the expression `ADD_TO_DATE(SHIP_DATE, 'HH', 14)` adds 14 hours to each date in the SHIP_DATE column.

Minute

Enter a positive or negative integer in the *amount* argument. Use the MI format string to set the minute. For example, the expression `ADD_TO_DATE(SHIP_DATE, 'MI', 25)` adds 25 minutes to each date in the SHIP_DATE column.

Seconds

Enter a positive or negative integer in the *amount* argument. Use the SS format string to set the second. For example, the following expression adds 59 seconds to each date in the SHIP_DATE column:

```
ADD_TO_DATE( SHIP_DATE, 'SS', 59 )
```

Syntax

```
ADD_TO_DATE( date, format, amount )
```

Argument	Required/Optional	Description
<i>date</i>	Required	Date/Time datatype. Passes the values you want to change. You can enter any valid expression.
<i>format</i>	Required	A format string specifying the portion of the date value you want to change. Enclose the format string within single quotation marks, for example, 'mm'. The format string is not case sensitive.
<i>amount</i>	Required	An integer value specifying the amount of years, months, days, hours, and so on by which you want to change the date value. You can enter any valid expression that evaluates to an integer.

Return Value

Date in the same format as the date you pass to this function.

NULL if a null value is passed as an argument to the function.

Example

The following expressions all add one month to each date in the DATE_SHIPPED column. If you pass a value that creates a day that does not exist in a particular month, Data Integration returns the last day of the month. For example, if you add one month to Jan 31 1998, Data Integration returns Feb 28 1998.

ADD_TO_DATE recognizes leap years and adds one month to Jan 29 2000:

```
ADD_TO_DATE( DATE_SHIPPED, 'MM', 1 )
ADD_TO_DATE( DATE_SHIPPED, 'MON', 1 )
ADD_TO_DATE( DATE_SHIPPED, 'MONTH', 1 )
```

DATE_SHIPPED	RETURN VALUE
Jan 12 1998 12:00:30AM	Feb 12 1998 12:00:30AM
Jan 31 1998 6:24:45PM	Feb 28 1998 6:24:45PM
Jan 29 2000 5:32:12AM	Feb 29 2000 5:32:12AM (<i>Leap Year</i>)
Oct 9 1998 2:30:12PM	Nov 9 1998 2:30:12PM
NULL	NULL

The following expressions subtract 10 days from each date in the DATE_SHIPPED column:

```
ADD_TO_DATE( DATE_SHIPPED, 'D', -10 )
ADD_TO_DATE( DATE_SHIPPED, 'DD', -10 )
ADD_TO_DATE( DATE_SHIPPED, 'DDD', -10 )
ADD_TO_DATE( DATE_SHIPPED, 'DY', -10 )
ADD_TO_DATE( DATE_SHIPPED, 'DAY', -10 )
```

DATE_SHIPPED	RETURN VALUE
Jan 1 1997 12:00:30AM	Dec 22 1996 12:00AM
Jan 31 1997 6:24:45PM	Jan 21 1997 6:24:45PM
Mar 9 1996 5:32:12AM	Feb 29 1996 5:32:12AM (<i>Leap Year</i>)
Oct 9 1997 2:30:12PM	Sep 30 1997 2:30:12PM
Mar 3 1996 5:12:20AM	Feb 22 1996 5:12:20AM
NULL	NULL

The following expressions subtract 15 hours from each date in the DATE_SHIPPED column:

```
ADD_TO_DATE( DATE_SHIPPED, 'HH', -15 )
ADD_TO_DATE( DATE_SHIPPED, 'HH12', -15 )
ADD_TO_DATE( DATE_SHIPPED, 'HH24', -15 )
```

DATE_SHIPPED	RETURN VALUE
Jan 1 1997 12:00:30AM	Dec 31 1996 9:00:30AM
Jan 31 1997 6:24:45PM	Jan 31 1997 3:24:45AM
Oct 9 1997 2:30:12PM	Oct 8 1997 11:30:12PM
Mar 3 1996 5:12:20AM	Mar 2 1996 2:12:20PM
Mar 1 1996 5:32:12AM	Feb 29 1996 2:32:12PM (<i>Leap Year</i>)
NULL	NULL

Working with Dates

Use the following tips when working with ADD_TO_DATE:

- You can add or subtract any part of the date by specifying a format string and making the *amount* argument a positive or negative integer.
- If you pass a value that creates a day that does not exist in a particular month, Data Integration returns the last day of the month. For example, if you add one month to Jan 31 1998, Data Integration returns Feb 28 1998.
- You can nest TRUNC and ROUND to manipulate dates.
- You can nest TO_DATE to convert strings to dates.
- ADD_TO_DATE changes only one portion of the date, which you specify. If you modify a date so that it changes from standard to daylight savings time, you need to change the hour portion of the date.

AES_DECRYPT

Returns the decrypted value in string format. Data Integration uses the Advanced Encryption Standard (AES) algorithm with the Electronic Codebook (ECB) mode of operation. The AES algorithm is a FIPS-approved cryptographic algorithm that uses 128-bit encryption.

Syntax

```
AES_DECRYPT ( value, key )
```

Argument	Required/Optional	Description
value	Required	Binary datatype. Value you want to decrypt.
key	Required	String datatype. Precision of 16 characters or fewer. Use the same key to decrypt a value that you used to encrypt it.

Return Value

Decrypted string value.

NULL if the input value is a null value.

Example

The following example returns decrypted Social Security numbers. In this example, Data Integration derives the key from the first three numbers of the Social Security number using the SUBSTR function:

```
AES_DECRYPT( SSN_ENCRYPT, SUBSTR( SSN,1,3 ) )
```

SSN_ENCRYPT	DECRYPTED VALUE
07FB945926849D2B1641E708C85E4390	832-17-1672
9153ACAB89D65A4B81AD2ABF151B099D	832-92-4731
AF6B5E4E39F974B3F3FB0F22320CC60B	832-46-7552
992D6A5D91E7F59D03B940A4B1CBBCBE	832-53-6194

SSN_ENCRYPT

992D6A5D91E7F59D03B940A4B1CBBCBE

DECRYPTED VALUE

832-81-9528

AES_ENCRYPT

Returns binary data in encrypted format. Data Integration uses the Advanced Encryption Standard (AES) algorithm with the Electronic Codebook (ECB) mode of operation. The AES algorithm is a FIPS-approved cryptographic algorithm that uses 128-bit encryption.

Use this function to prevent sensitive data from being visible to everyone. For example, to store Social Security numbers in a database, use the AES_ENCRYPT function to encrypt the Social Security numbers to maintain confidentiality.

Syntax

```
AES_ENCRYPT ( value, key )
```

Argument	Required/ Optional	Description
value	Required	String datatype. Value you want to encrypt.
key	Required	String datatype. Precision of 16 characters or fewer.

Return Value

Encrypted binary value.

NULL if the input is a null value.

Example

The following example returns encrypted values for Social Security numbers. In this example, Data Integration derives the key from the first three numbers of the Social Security number using the SUBSTR function:

```
AES_ENCRYPT( SSN, SUBSTR( SSN,1,3 ) )
```

SSN	ENCRYPTED VALUE
832-17-1672	07FB945926849D2B1641E708C85E4390
832-92-4731	9153ACAB89D65A4B81AD2ABF151B099D
832-46-7552	AF6B5E4E39F974B3F3FB0F22320CC60B
832-53-6194	992D6A5D91E7F59D03B940A4B1CBBCBE
832-81-9528	992D6A5D91E7F59D03B940A4B1CBBCBE

Tip

If the target does not support binary data, use AES_ENCRYPT with the ENC_BASE64 function to store the data in a format that is compatible with the database.

AES_GCM_DECRYPT

Returns plaintext as a string. Data Integration uses the Advanced Encryption Standard (AES) algorithm with the Galois/Counter Mode (GCM) of operation. The AES algorithm is a FIPS-approved cryptographic algorithm that uses 128, 192, or 256-bit keys.

Syntax

```
AES_GCM_DECRYPT ( value, init_vector, key [, keysize] )
```

Argument	Required/ Optional	Description
value	Required	Binary data type. The ciphertext value to be decrypted into plaintext.
init_vector	Required	String data type. Use the same initialization vector (IV) to decrypt a value that you used to encrypt the ciphertext. The IV must be 96-bit and randomly generated.
key	Required	String data type of size 128, 192, or 256 bits. Use the same key to decrypt a value that you used to encrypt it.
keysize	The size of the key argument, in bits, determines whether the keysize argument is optional or required. <ul style="list-style-type: none">- If the key argument size is <= 128 bits, then the keysize is optional.- If the key argument size is > 128 bits and <= 192 bits, then the keysize is 192 bits, and required.- If the key argument size is >192 and <=256 bits, then the keysize is 256 bits, and required.	Integer data type. Size of the key provided. Possible values:128, 192, 256 bits. Default value is 128 bits.

Return Value

Decrypted string plaintext.

NULL if the input value is a null value.

Example

The following examples return decrypted Social Security numbers. The *init_vector* and *key* are the same values that were used to encrypt the Social Security number.

In this example, the *init_vector* is 12 characters, or 96 bits; the *key* is 16 characters, or 128 bits; the *keysize* is optional because the key is the default value of 128 bits:

```
AES_GCM_DECRYPT(SSN_ENCRYPT, '012345678901', '1234567890123456', 128)
```

In this example, the *init_vector* is 12 characters, or 96 bits; the *key* is 17 characters, or 136 bits; the *keysize* is required because the key is > 128 bits. Because the size of the key is less than 192 bits, the key is padded with null characters:

```
AES_GCM_DECRYPT(SSN_ENCRYPT, '123456789012', '12345678901234567', 192)
```

AES_GCM_ENCRYPT

Returns binary ciphertext. Data Integration uses the Advanced Encryption Standard (AES) algorithm with the Galois/Counter Mode (GCM) of operation. The AES algorithm is a FIPS-approved cryptographic algorithm that uses 128, 192, or 256-bit keys.

Use this function to prevent sensitive data from being visible to everyone. For example, to store Social Security numbers in a database, use the AES_GCM_ENCRYPT function to encrypt the Social Security numbers to maintain confidentiality.

AES-GCM creates an authentication tag of 128 bits and appends it to encrypted ciphertext. Decryption verifies and removes the authentication tag. An authentication tag is a cryptographic checksum on data that reveals both accidental errors and the intentional modification of the data.

Syntax

```
AES_GCM_ENCRYPT ( value, init_vector, key [, keysize] )
```

Argument	Required/Optional	Description
value	Required	String data type. The plaintext value to be encrypted into ciphertext.
init_vector	Required	String data type. Use the initialization vector (IV) to encrypt the plaintext. The IV must be 96-bit and randomly generated. The IV is a block of bits that is used along with the key during encryption to add randomness to the start of the encryption process. Note: Do not re-use the IV with the same key and a different encryption string.
key	Required	String data type of size 128, 192, or 256 bits. If the size of the key is less than the keysize, the remainder is padded as null.
keysize	The size of the key argument, in bits, determines whether the keysize argument is optional or required. <ul style="list-style-type: none">- If the key argument size is <= 128 bits, then the keysize is optional.- If the key argument size is > 128 bits and <= 192 bits, then the keysize is 192 bits, and required.- If the key argument size is >192 and <=256 bits, then the keysize is 256 bits, and required.	Integer data type. Size of the key provided. Possible values:128, 192, or 256 bits. Default value is 128 bits.

Return Value

Encrypted binary ciphertext.

NULL if the input is a null value.

Example

The following examples return encrypted values for a Social Security number. The *init_vector* and *key* values will be used later to decrypt the Social Security number.

In this example, the *init_vector* is 12 characters, or 96 bits; the *key* is 16 characters, or 128 bits; the *keysize* is optional because the key is the default value of 128 bits:

```
AES_GCM_ENCRYPT('832-17-1672', '012345678901', '1234567890123456', 128)
```

In this example, the *init_vector* is 12 characters, or 96 bits; the *key* is 17 characters, or 136 bits; the *keysize* is required. Because the size of the key is less than 192 bits, the key is padded with null characters:

```
AES_GCM_ENCRYPT('832-17-1672', '123456789012', '12345678901234567', 192)
```

Tip

If the target does not support binary data, use AES_GCM_ENCRYPT with the ENC_BASE64 function to store the data in a format that is compatible with the database.

ASCII

The ASCII function returns the numeric UNICODE value of the first character of the string passed to the function.

You can pass a string of any size to ASCII, but it evaluates only the first character in the string. Before you pass any string value to ASCII, you can parse out the specific character you want to convert to a UNICODE value. For example, you might use RTRIM or another string-manipulation function. If you pass a numeric value, ASCII converts it to a character string and returns the UNICODE value of the first character in the string.

Note: This function is identical in behavior to the CHRCODE function. If you use ASCII in existing expressions, they will still work correctly. However, when you create new expressions, use the CHRCODE function instead of the ASCII function.

Syntax

```
ASCII ( string )
```

Argument	Required/Optional	Description
<i>string</i>	Required	Character string. Passes the value you want to return as an UNICODE value. You can enter any valid expression.

Return Value

Integer. The UNICODE value of the first character in the string.

NULL if a value passed to the function is NULL.

Example

The following expression returns the UNICODE value for the first character of each value in the ITEMS column:

```
ASCII( ITEMS )
```

ITEMS	RETURN VALUE
Flashlight	70
Compass	67

ITEMS	RETURN VALUE
Safety Knife	83
Depth/Pressure Gauge	68
Regulator System	82

AVG

Returns the average of all values in a group of rows. Optionally, you can apply a filter to limit the rows you read to calculate the average.

You can nest only one other aggregate function within AVG, and the nested function must return a numeric data type.

Use only in mapping tasks.

Syntax

```
AVG( numeric_value [, filter_condition ] )
```

Argument	Required/Optional	Description
<i>numeric_value</i>	Required	Numeric data type. Passes the values for which you want to calculate an average. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL or if no rows are selected. For example, the filter condition evaluates to FALSE or NULL for all rows.

Nulls

If a value is NULL, AVG ignores the row. However, if all values passed are NULL, AVG returns NULL.

Group By

AVG groups values based on group by fields you define in the transformation, returning one result for each group.

If there is not a group by field, AVG treats all rows as one group, returning one value.

Example

The following expression returns the average wholesale cost of flashlights:

```
AVG( WHOLESALE_COST, ITEM_NAME='Flashlight' )
```

ITEM_NAME	WHOLESALE_COST
Flashlight	35.00
Navigation Compass	8.05
Regulator System	150.00
Flashlight	29.00
Depth/Pressure Gauge	88.00
Flashlight	31.00

RETURN VALUE: 31.66

Tip

You can perform arithmetic on the values passed to AVG before the function calculates the average. For example:

```
AVG( QTY * PRICE - DISCOUNT )
```

CEIL

Returns the smallest integer greater than or equal to the numeric value passed to this function. For example, if you pass 3.14 to CEIL, the function returns 4. If you pass 3.98 to CEIL, the function returns 4. Likewise, if you pass -3.17 to CEIL, the function returns -3.

Syntax

```
CEIL( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. You can enter any valid expression.

Return Value

Integer if you pass a numeric value with declared precision between 0 and 28.

Double value if you pass a numeric value with declared precision greater than 28.

NULL if a value passed to the function is NULL.

Example

The following expression returns the price rounded to the next integer:

```
CEIL( PRICE )
```

PRICE	RETURN VALUE
39.79	40
125.12	126
74.24	75
NULL	NULL
-100.99	-100

Tip

You can perform arithmetic on the values passed to CEIL before CEIL returns the next integer value. For example, if you wanted to multiply a numeric value by 10 before you calculated the smallest integer less than the modified value, you might write the function as follows:

```
CEIL( PRICE * 10 )
```

CHOOSE

Chooses a string from a list of strings based on a given position. You specify the position and the value. If the value matches the position, Data Integration returns the value.

Syntax

```
CHOOSE( index, string1, [string2, ..., stringN] )
```

Argument	Required/Optional	Description
index	Required	Numeric datatype. Enter a number based on the position of the value you want to match.
string	Required	Any character value.

Return Value

The string that matches the position of the index value.

NULL if no string matches the position of the index value.

Example

The following expression returns the string 'flashlight' based on an index value of 2:

```
CHOOSE( 2, 'knife', 'flashlight', 'diving hood' )
```

The following expression returns NULL based on an index value of 4:

```
CHOOSE( 4, 'knife', 'flashlight', 'diving hood' )
```

CHOOSE returns NULL because the expression does not contain a fourth argument.

CHR

CHR returns the ASCII character corresponding to the numeric value you pass to this function. ASCII values fall in the range 0 to 255. You can pass any integer to CHR, but only ASCII codes 32 to 126 are printable characters.

Syntax

```
CHR( numeric_value )
```

Argument	Required/Optional	Description
numeric_value	Required	Numeric datatype. The value you want to return as an ASCII character. You can enter any valid expression.

Return Value

ASCII character. A string containing one character.

NULL if a value passed to the function is NULL.

Example

The following expression returns the ASCII character for each numeric value in the ITEM_ID column:

```
CHR( ITEM_ID )
```

ITEM_ID	RETURN VALUE
65	A
122	z
NULL	NULL
88	X
100	d
71	G

Use the CHR function to concatenate a single quotation mark onto a string. The single quotation mark is the only character that you cannot use inside a string literal. Consider the following example:

```
'Joan' || CHR(39) || 's car'
```

The return value is:

```
Joan's car
```

CHRCODE

CHRCODE returns the numeric UNICODE value of the first character of the string passed to the function.

Normally, before you pass any string value to CHRCODE, you parse out the specific character you want to convert to a UNICODE value. For example, you might use RTRIM or another string-manipulation function. If you pass a numeric value, CHRCODE converts it to a character string and returns the UNICODE value of the first character in the string.

Note: This function is identical in behavior to the ASCII function. If you currently use ASCII in expressions, it will still work correctly. However, when you create new expressions, use the CHRCODE function instead of the ASCII function.

Syntax

```
CHRCODE ( string )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	Character string. Passes the values you want to return as UNICODE values. You can enter any valid expression.

Return Value

Integer. The UNICODE value of the first character in the string.

NULL if a value passed to the function is NULL.

Example

The following expression returns the UNICODE value for the first character of each value in the ITEMS column:

```
CHRCODE( ITEMS )
```

ITEMS	RETURN VALUE
Flashlight	70
Compass	67
Safety Knife	83
Depth/Pressure Gauge	68
Regulator System	82

COMPRESS

Compresses data using the zlib compression algorithm. The zlib compression algorithm is compatible with WinZip. Use the COMPRESS function before you send large amounts of data over a wide area network.

Syntax

```
COMPRESS( value )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	String datatype. Data that you want to compress.

Return Value

Compressed binary value of the input value.

NULL if the input is a null value.

Example

Your organization has an online order service. You want to send customer order data over a wide area network. The source contains a row that is 10 MB. You can compress the data in this row using COMPRESS. When you compress the data, you decrease the amount of data Data Integration writes over the network. As a result, you may improve task performance.

CONCAT

Concatenates two strings. CONCAT converts all data to text before concatenating the strings. Alternatively, use the || string operator to concatenate strings. Using the || string operator instead of CONCAT improves performance when you run tasks.

Syntax

```
CONCAT( first_string, second_string )
```

Argument	Required/ Optional	Description
<i>first_string</i>	Required	Any datatype except Binary. The first part of the string you want to concatenate. You can enter any valid expression.
<i>second_string</i>	Required	Any datatype except Binary. The second part of the string you want to concatenate. You can enter any valid expression.

Return Value

String.

NULL if both string values are NULL.

Nulls

If one of the strings is NULL, CONCAT ignores it and returns the other string.

If both strings are NULL, CONCAT returns NULL.

Example

The following expression concatenates the names in the FIRST_NAME and LAST_NAME columns:

```
CONCAT( FIRST_NAME, LAST_NAME )
```

FIRST_NAME	LAST_NAME	RETURN VALUE
John	Baer	JohnBaer
NULL	Campbell	Campbell
Bobbi	Apperley	BobbiApperley
Jason	Wood	JasonWood
Dan	Covington	DanCovington
Greg	NULL	Greg
NULL	NULL	NULL
100	200	100200

CONCAT does not add spaces to separate strings. If you want to add a space between two strings, you can write an expression with two nested CONCAT functions. For example, the following expression first concatenates a space on the end of the first name and then concatenates the last name:

```
CONCAT( CONCAT( FIRST_NAME, ' ' ), LAST_NAME )
```

FIRST_NAME	LAST_NAME	RETURN VALUE
John	Baer	John Baer
NULL	Campbell	Campbell (includes leading space)
Bobbi	Apperley	Bobbi Apperley
Jason	Wood	Jason Wood
Dan	Covington	Dan Covington
Greg	NULL	Greg
NULL	NULL	NULL

Use the CHR and CONCAT functions to concatenate a single quotation mark onto a string. The single quotation mark is the only character you cannot use inside a string literal. Consider the following example:

```
CONCAT( 'Joan', CONCAT( CHR(39), 's car' ) )
```

The return value is:

```
Joan's car
```

CONVERT_BASE

Converts a number from one base value to another base value.

Syntax

```
CONVERT_BASE( value, source_base, dest_base )
```

Argument	Required/ Optional	Description
value	Required	String datatype. Value you want to convert from one base to another base.
source_base	Required	Numeric datatype. Current base value of the data you want to convert. Minimum base is 2. Maximum base is 36.
dest_base	Required	Numeric datatype. Base value you want to convert the data to. Minimum base is 2. Maximum base is 36.

Return Value

Numeric value.

Example

The following example converts 2222 from the decimal base value 10 to the binary base value 2:

```
CONVERT_BASE( 2222, 10, 2 )
```

Data Integration returns 100010101110.

COS

Returns the cosine of a numeric value (expressed in radians).

Syntax

```
COS( numeric_value )
```

Argument	Required/ Optional	Description
numeric_value	Required	Numeric datatype. Numeric data expressed in radians (degrees multiplied by pi divided by 180). Passes the values for which you want to calculate a cosine. You can enter any valid expression.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the cosine for all values in the DEGREES column:

```
COS( DEGREES * 3.14159265359 / 180 )
```

DEGREES	RETURN VALUE
0	1.0
90	0.0
70	0.342020143325593
30	0.866025403784421
5	0.996194698091745
18	0.951056516295147
89	0.0174524064371813
NULL	NULL

Tip

You can perform arithmetic on the values passed to COS before the function calculates the cosine. For example, you can convert the values in the column to radians before calculating the cosine, as follows:

```
COS( ARCS * 3.14159265359 / 180 )
```

COSH

Returns the hyperbolic cosine of a numeric value (expressed in radians).

Syntax

```
COSH( numeric_value )
```

Argument	Required/ Optional	Description
numeric_value	Required	Numeric datatype. Numeric data expressed in radians (degrees multiplied by pi divided by 180). Passes the values for which you want to calculate the hyperbolic cosine. You can enter any valid expression.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the hyperbolic cosine for the values in the ANGLES column:

```
COSH( ANGLES )
```

ANGLES	RETURN VALUE
1.0	1.54308063481524
2.897	9.0874465864177
3.66	19.4435376920294
5.45	116.381231106176
0	1.0
0.345	1.06010513656773
NULL	NULL

Tip

You can perform arithmetic on the values passed to COSH before the function calculates the hyperbolic cosine. For example:

```
COSH( MEASURES.ARCS / 360 )
```

COUNT

Returns the number of rows that have non-null values in a group. Optionally, you can include the asterisk (*) argument to count all input values in a transformation. You can apply a condition to filter rows before counting them.

You can nest only one other aggregate function within COUNT.

Use only in mapping tasks.

Syntax

```
COUNT( value [, filter_condition] )
```

or

```
COUNT( * [, filter_condition] )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	Any data type except binary. Passes the values you want to count. You can enter any valid transformation expression.
<i>*</i>	Optional	Use to count <i>all rows</i> in a transformation.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Integer.

0 if all values passed to this function are NULL (unless you include the asterisk argument).

Nulls

If all values are NULL, the function returns 0.

If you apply the asterisk argument, this function counts all rows, regardless if a column in a row contains a null value.

If you apply the *value* argument, this function ignores columns with null values.

Group By

COUNT groups values based on group by fields you define in the transformation, returning one result for each group. If there is no group by field COUNT treats all rows as one group, returning one value.

Examples

The following expression counts the items with less than 5 quantity in stock, excluding null values:

```
COUNT( ITEM_NAME, IN_STOCK < 5 )
```

ITEM_NAME	IN_STOCK
Flashlight	10
NULL	2
Compass	NULL
Regulator System	5
Safety Knife	8
Halogen Flashlight	1
RETURN VALUE: 1	

In this example, the function counted the Halogen flashlight but not the NULL item. The function counts all rows in a transformation, including null values, as illustrated in the following example:

```
COUNT( *, QTY < 5 )
```

ITEM_NAME	QTY
Flashlight	10
NULL	2
Compass	NULL
Regulator System	5
Safety Knife	8
Halogen Flashlight	1
RETURN VALUE: 2	

In this example, the function counts the NULL item and the Halogen Flashlight. If you include the asterisk argument, but do not use a filter, the function counts all rows that pass into the transformation. For example:

```
COUNT( * )
```

ITEM_NAME	QTY
Flashlight	10
NULL	2
Compass	NULL
Regulator System	5
Safety Knife	8
Halogen Flashlight	1
RETURN VALUE: 6	

CRC32

Returns a 32-bit Cyclic Redundancy Check (CRC32) value. Use CRC32 to find data transmission errors. You can also use CRC32 if you want to verify that data stored in a file has not been modified.

Note: CRC32 can return the same output for different input strings. If you use CRC32 to generate keys, you may receive unexpected results.

Syntax

```
CRC32( value )
```

Argument	Required/ Optional	Description
value	Required	String or Binary datatype. Passes the values you want to perform a redundancy check on. Input value is case sensitive. The case of the input value affects the return value. For example, CRC32(informatica) and CRC32 (Informatica) return different values.

Return Value

32-bit integer value.

Example

You want to read data from a source across a wide area network. You want to make sure the data has been modified during transmission. You can compute the checksum for the data in the file and store it along with the file. When Data Integration reads the source data, Data Integration can use CRC32 to compute the checksum and compare it to the stored value. If the two values are the same, the data has not been modified.

CUME

Returns a running total. A running total means CUME returns a total each time it adds a value. You can add a condition to filter rows out of the row set before calculating the running total.

Use CUME and similar functions, such as MOVINGAVG and MOVINGSUM, to simplify reporting by calculating running values.

Syntax

```
CUME( numeric_value [, filter_condition] )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. Passes the values for which you want to calculate a running total. You can enter any valid expression. You can create a nested expression to calculate a running total based on the results of the function as long as the result is a numeric value.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a value is NULL, CUME returns the running total for the previous row. However, if all values in the selected column are NULL, CUME returns NULL.

Examples

The following example returns the running total of the PERSONAL_SALES column:

```
CUME( PERSONAL_SALES )
```

PERSONAL_SALES	RETURN VALUE
40000	40000
80000	120000
40000	160000
60000	220000
NULL	220000
50000	270000

Likewise, you can add values before calculating a running total:

```
CUME( CA_SALES + OR_SALES )
```

CA_SALES	OR_SALES	RETURN VALUE
40000	10000	50000
80000	50000	180000
40000	2000	222000
60000	NULL	222000
NULL	NULL	222000
50000	3000	275000

DATE_COMPARE

Returns an integer indicating which of two dates is earlier. DATE_COMPARE returns an integer value rather than a date value.

Syntax

```
DATE_COMPARE( date1, date2 )
```

Argument	Required/Optional	Description
<i>date1</i>	Required	Date/Time datatype. The first date you want to compare. You can enter any valid expression as long as it evaluates to a date.
<i>date2</i>	Required	Date/Time datatype. The second date you want to compare. You can enter any valid expression as long as it evaluates to a date.

Return Value

-1 if the first date is earlier.

0 if the two dates are equal.

1 if the second date is earlier.

NULL if one of the date values is NULL.

Example

The following expression compares each date in the DATE_PROMISED and DATE_SHIPPED columns, and returns an integer indicating which date is earlier:

```
DATE_COMPARE( DATE_PROMISED, DATE_SHIPPED )
```

DATE_PROMISED	DATE_SHIPPED	RETURN VALUE
Jan 1 1997	Jan 13 1997	-1
Feb 1 1997	Feb 1 1997	0
Dec 22 1997	Dec 15 1997	1
Feb 29 1996	Apr 12 1996	-1 (Leap year)
NULL	Jan 6 1997	NULL
Jan 13 1997	NULL	NULL

DATE_DIFF

Returns the length of time between two dates. You can request the format to be years, months, days, hours, minutes, or seconds. Data Integration subtracts the second date from the first date and returns the difference.

Syntax

```
DATE_DIFF( date1, date2, format )
```

Argument	Required/Optional	Description
date1	Required	Date/Time datatype. Passes the values for the first date you want to compare. You can enter any valid expression.
date2	Required	Date/Time datatype. Passes the values for the second date you want to compare. You can enter any valid expression.
format	Required	Format string specifying the date or time measurement. You can specify years, months, days, hours, minutes, or seconds. You can specify only one part of the date, such as 'mm'. Enclose the format strings within single quotation marks. The format string is not case sensitive. For example, the format string 'mm' is the same as 'MM', 'Mm' or 'mM'.

Return Value

Double value. If *date1* is later than *date2*, the return value is a positive number. If *date1* is earlier than *date2*, the return value is a negative number.

0 if the dates are the same.

NULL if one (or both) of the date values is NULL.

Example

The following expressions return the number of hours between the DATE_PROMISED and DATE_SHIPPED columns:

```
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'HH' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'HH12' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'HH24' )
```

DATE_PROMISED	DATE_SHIPPED	RETURN VALUE
Jan 1 1997 12:00:00AM	Mar 29 1997 12:00:00PM	-2100
Mar 29 1997 12:00:00PM	Jan 1 1997 12:00:00AM	2100
NULL	Dec 10 1997 5:55:10PM	NULL
Dec 10 1997 5:55:10PM	NULL	NULL
Jun 3 1997 1:13:46PM	Aug 23 1996 4:20:16PM	6812.89166666667
Feb 19 2004 12:00:00PM	Feb 19 2005 12:00:00PM	-8784

The following expressions return the number of days between the DATE_PROMISED and the DATE_SHIPPED columns:

```
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'D' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'DD' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'DDD' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'DY' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'DAY' )
```

DATE_PROMISED	DATE_SHIPPED	RETURN VALUE
Jan 1 1997 12:00:00AM	Mar 29 1997 12:00:00PM	-87.5
Mar 29 1997 12:00:00PM	Jan 1 1997 12:00:00AM	87.5
NULL	Dec 10 1997 5:55:10PM	NULL
Dec 10 1997 5:55:10PM	NULL	NULL
Jun 3 1997 1:13:46PM	Aug 23 1996 4:20:16PM	283.870486111111
Feb 19 2004 12:00:00PM	Feb 19 2005 12:00:00PM	-366

The following expressions return the number of months between the DATE_PROMISED and DATE_SHIPPED columns:

```
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'MM' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'MON' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'MONTH' )
```

DATE_PROMISED	DATE_SHIPPED	RETURN VALUE
Jan 1 1997 12:00:00AM	Mar 29 1997 12:00:00PM	-2.91935483870968
Mar 29 1997 12:00:00PM	Jan 1 1997 12:00:00AM	2.91935483870968
NULL	Dec 10 1997 5:55:10PM	NULL
Dec 10 1997 5:55:10PM	NULL	NULL
Jun 3 1997 1:13:46PM	Aug 23 1996 4:20:16PM	9.3290162037037
Feb 19 2004 12:00:00PM	Feb 19 2005 12:00:00PM	-12

The following expressions return the number of years between the DATE_PROMISED and DATE_SHIPPED columns:

```
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'Y' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'YY' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'YYY' )
DATE_DIFF( DATE_PROMISED, DATE_SHIPPED, 'YYYY' )
```

DATE_PROMISED	DATE_SHIPPED	RETURN VALUE
Jan 1 1997 12:00:00AM	Mar 29 1997 12:00:00PM	-0.24327956989247
Mar 29 1997 12:00:00PM	Jan 1 1997 12:00:00AM	0.24327956989247
NULL	Dec 10 1997 5:55:10PM	NULL
Dec 10 1997 5:55:10PM	NULL	NULL
Jun 3 1997 1:13:46PM	Aug 23 1996 4:20:16PM	0.77741801697531
Feb 19 2004 12:00:00PM	Feb 19 2005 12:00:00PM	-1

DEC_BASE64

Decodes a base 64 encoded value and returns a string with the binary data representation of the data.

Syntax

```
DEC_BASE64( value )
```

Argument	Required/Optional	Description
<i>value</i>	Required	String datatype. Data that you want to decode.

Return Value

Binary decoded value.

NULL if the input is a null value.

DECODE

Searches a column for a value that you specify. If the function finds the value, it returns a result value, which you define. You can build an unlimited number of searches within a DECODE function.

If you use DECODE to search for a value in a string column, you can either trim trailing blanks with the RTRIM function or include the blanks in the search string.

Syntax

```
DECODE( value, first_search, first_result [, second_search, second_result]...[,default] )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	Any datatype except Binary. Passes the values you want to search. You can enter any valid expression.
<i>search</i>	Required	Any value with the same datatype as the value argument. Passes the values for which you want to search. The search value must match the value argument. You cannot search for a portion of a value. Also, the search value is case sensitive. For example, if you want to search for the string 'Halogen Flashlight' in a particular column, you must enter 'Halogen Flashlight, not just 'Halogen'. If you enter 'Halogen', the search does not find a matching value. You can enter any valid expression.
<i>result</i>	Required	Any datatype except Binary. The value you want to return if the search finds a matching value. You can enter any valid expression.
<i>default</i>	Optional	Any datatype except Binary. The value you want to return if the search does not find a matching value. You can enter any valid expression.

Return Value

First_result if the search finds a matching value.

Default value if the search does not find a matching value.

NULL if you omit the default argument and the search does not find a matching value.

Even if multiple conditions are met, Data Integration returns the first matching result.

If the data contains multibyte characters and the DECODE expression compares string data, the return value depends on the code page of the Secure Agent that runs the task.

DECODE and Datatypes

When you use DECODE, the datatype of the return value is always the same as the datatype of the result with the greatest precision.

For example, you have the following expression:

```
DECODE ( CONST NAME,
         'Five', 5,
         'Pythagoras', 1.414213562,
         'Archimedes', 3.141592654,
         'Pi', 3.141592654 )
```

The return values in this expression are 5, 1.414213562, and 3.141592654. The first result is an Integer, and the other results are Decimal. The Decimal datatype has greater precision than Integer. This expression always writes the result as a Decimal.

If at least one result is Double, the datatype of the return value is Double.

You cannot create a DECODE function with both string and numeric return values.

For example, the following expression is invalid because the return values include both string and numeric values:

```
DECODE ( CONST NAME,
         'Five', 5,
         'Pythagoras', '1.414213562',
         'Archimedes', '3.141592654',
         'Pi', 3.141592654 )
```

Example

You might use DECODE in an expression that searches for a particular ITEM_ID and returns the ITEM_NAME:

```
DECODE( ITEM_ID, 10, 'Flashlight',
        14, 'Regulator',
        20, 'Knife',
        40, 'Tank',
        'NONE' )
```

ITEM_ID	RETURN VALUE
10	Flashlight
14	Regulator
17	NONE
20	Knife
25	NONE
NULL	NONE
40	Tank

DECODE returns the default value of NONE for items 17 and 25 because the search values did not match the ITEM_ID. Also, DECODE returns NONE for the NULL ITEM_ID.

The following expression tests multiple columns and conditions, evaluated in a top to bottom order for TRUE or FALSE:

```
DECODE( TRUE,
        Var1 = 22, 'Variable 1 was 22!',
        Var2 = 49, 'Variable 2 was 49!',
        Var1 < 23, 'Variable 1 was less than 23.',
```



```
Var2 > 30, 'Variable 2 was more than 30.',
'Variables were out of desired ranges.')
```

Var1	Var2	RETURN VALUE
21	47	Variable 1 was less than 23.
22	49	Variable 1 was 22!
23	49	Variable 2 was 49!
24	27	Variables were out of desired ranges.
25	50	Variable 2 was more than 30.

DECOMPRESS

Decompresses data using the zlib compression algorithm. The zlib compression algorithm is compatible with WinZip. Use the DECOMPRESS function when you receive data over a wide area network.

Syntax

```
DECOMPRESS( value, precision)
```

Argument	Required/Optional	Description
<i>value</i>	Required	Binary datatype. Data that you want to decompress.
<i>precision</i>	Optional	Integer datatype.

Return Value

Decompressed binary value of the input value.

NULL if the input is a null value.

Example

Your organization has an online order service. You received compressed customer order data over a wide area network. You want to read the data using Data Integration and load the data to a data warehouse. You can decompress each row of data using DECOMPRESS for the row. Data Integration can then load the decompressed data to the target.

ENC_BASE64

Encodes data by converting binary data to string data using Multipurpose Internet Mail Extensions (MIME) encoding.

Encode data when you want to store data in a database or file that does not allow binary data. You can also encode data to pass binary data in string format. The encoded data is approximately 33% longer than the original data. It displays as a set of random characters.

Syntax

```
ENC_BASE64( value )
```

Argument	Required/ Optional	Description
value	Required	Binary or String datatype. Data that you want to encode.

Return Value

Encoded value.

NULL if the input is a null value.

ERROR

Causes Data Integration to skip a row and issue an error message, which you define. Data Integration writes the skipped row and the error message into the error rows file.

Use ERROR in expressions to validate data. Generally, you use ERROR within an IIF or DECODE function to set rules for skipping rows. You might use ERROR to keep null values from passing into a target.

You can also include ERROR in expression to handle transformation errors.

Syntax

```
ERROR( string )
```

Argument	Required/ Optional	Description
string	Required	String value. The message you want to display when Data Integration skips a row based on the expression containing the ERROR function. The string can be any length.

Return Value

String.

Example

The following example shows how to reference a mapping that calculates the average salary for employees in all departments of the organization, but skip negative values. The following expression nests the ERROR

function in an IIF expression so that if Data Integration finds a negative salary in the Salary column, it skips the row and displays an error:

```
IIF( SALARY < 0, ERROR ('Error. Negative salary found. Row skipped.', EMP_SALARY )
```

SALARY	RETURN VALUE
10000	10000
-15000	'Error. Negative salary found. Row skipped.'
NULL	NULL
150000	150000
1005	1005

EXP

Returns e raised to the specified power (exponent), where e=2.71828183. For example, EXP(2) returns 7.38905609893065. Use this function to analyze scientific and technical data. EXP is the reciprocal of the LN function, which returns the natural logarithm of a numeric value.

Syntax

```
EXP( exponent )
```

Argument	Required/ Optional	Description
<i>exponent</i>	Required	Numeric datatype. The value to which you want to raise e. The exponent in the equation e^{value} . You can enter any valid expression.

Return Value

Double value.

NULL if a value passed as an argument to the function is NULL.

Example

The following expression uses the values stored in the Numbers column as the exponent value:

```
EXP( NUMBERS )
```

NUMBERS	RETURN VALUE
10	22026.4657948067
-2	0.135335283236613
8.55	5166.754427176
NULL	NULL

FIRST

Returns the first value found within a field or group. Optionally, you can apply a filter to limit the rows read. You can nest only one other aggregate function within FIRST.

Use only in mapping tasks.

Syntax

```
FIRST( value [, filter_condition ] )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	Any data type except binary. Passes the values for which you want to return the first value. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

First value in a group.

NULL if all values passed to the function are NULL or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a value is NULL, FIRST ignores the row. However, if all values passed from the field are NULL, FIRST returns NULL.

Group By

FIRST groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, FIRST treats all rows as one group, returning one value.

Examples

The following expression returns the first value in the ITEM_NAME field with a price greater than \$10.00:

```
FIRST( ITEM_NAME, ITEM_PRICE > 10 )
```

ITEM_NAME	ITEM_PRICE
Flashlight	35.00
Navigation Compass	8.05
Regulator System	150.00
Flashlight	29.00
Depth/Pressure Gauge	88.00
Flashlight	31.00

RETURN VALUE: Flashlight

The following expression returns the first value in the ITEM_NAME field with a price greater than \$40.00:

```
FIRST( ITEM_NAME, ITEM_PRICE > 40 )
```

ITEM_NAME	ITEM_PRICE
Flashlight	35.00
Navigation Compass	8.05
Regulator System	150.00
Flashlight	29.00
Depth/Pressure Gauge	88.00
Flashlight	31.00
RETURN VALUE: Regulator System	

FLOOR

Returns the largest integer less than or equal to the numeric value you pass to this function. For example, if you pass 3.14 to FLOOR, the function returns 3. If you pass 3.98 to FLOOR, the function returns 3. Likewise, if you pass -3.17 to FLOOR, the function returns -4.

Syntax

```
FLOOR( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. You can enter any valid expression as long as it evaluates to numeric data.

Return Value

Integer if you pass a numeric value with declared precision between 0 and 28.

Double if you pass a numeric value with declared precision greater than 28.

NULL if a value passed to the function is NULL.

Example

The following expression returns the largest integer less than or equal to the values in the PRICE column:

```
FLOOR( PRICE )
```

PRICE	RETURN VALUE
39.79	39
125.12	125
74.24	74

PRICE	RETURN VALUE
NULL	NULL
-100.99	-101

Tip

You can perform arithmetic on the values you pass to FLOOR. For example, to multiply a numeric value by 10 and then calculate the largest integer that is less than the product, you might write the function as follows:

```
FLOOR( UNIT_PRICE * 10 )
```

FV

Returns the future value of an investment, where you make periodic, constant payments and the investment earns a constant interest rate.

Syntax

```
FV( rate, terms, payment [, present value, type] )
```

Argument	Required/Optional	Description
rate	Required	Numeric. Interest rate earned in each period. Expressed as a decimal number. Divide the percent rate by 100 to express it as a decimal number. Must be greater than or equal to 0.
terms	Required	Numeric. Number of periods or payments. Must be greater than 0.
payment	Required	Numeric. Payment amount due per period. Must be a negative number.
present value	Optional	Numeric. Current value of the investment. If you omit this argument, FV uses 0.
type	Optional	Integer. Timing of the payment. Enter 1 if payment is at the beginning of period. Enter 0 if payment is at the end of period. Default is 0. If you enter a value other than 0 or 1, Data Integration treats the value as 1.

Return Value

Numeric.

Example

You deposit \$2,000 into an account that earns 9% annual interest compounded monthly (monthly interest of 9%/12, or 0.75%). You plan to deposit \$250 at the beginning of every month for the next 12 months. The following expression returns \$5,337.96 as the account balance at the end of 12 months:

```
FV(0.0075, 12, -250, -2000, TRUE)
```

Notes

To calculate interest rate earned in each period, divide the annual rate by the number of payments made in a year. The payment value and present value are negative because these are amounts that you pay.

GET_DATE_PART

Returns the specified part of a date as an integer value. For example, if you create an expression that returns the month portion of the date, and pass a date such as Apr 1 1997 00:00:00, GET_DATE_PART returns 4.

Syntax

```
GET_DATE_PART( date, format )
```

Argument	Required/ Optional	Description
<i>date</i>	Required	Date/Time datatype. You can enter any valid expression.
<i>format</i>	Required	A format string specifying the portion of the date value you want to change. Enclose format strings within single quotation marks, for example, 'mm'. The format string is not case sensitive. Each format string returns the entire part of the date based on the default format of MM/DD/YYYY HH24:MI:SS. For example, if you pass the date Apr 1 1997 to GET_DATE_PART, the format strings 'Y', 'YY', 'YYY', or 'YYYY' all return 1997.

Return Value

Integer representing the specified part of the date.

NULL if a value passed to the function is NULL.

Example

The following expressions return the hour for each date in the DATE_SHIPPED column. 12:00:00AM returns 0 because the default date format is based on the 24 hour interval:

```
GET_DATE_PART( DATE_SHIPPED, 'HH' )
GET_DATE_PART( DATE_SHIPPED, 'HH12' )
GET_DATE_PART( DATE_SHIPPED, 'HH24' )
```

DATE_SHIPPED	RETURN VALUE
Mar 13 1997 12:00:00AM	0
Sep 2 1997 2:00:01AM	2
Aug 22 1997 12:00:00PM	12
June 3 1997 11:30:44PM	23
NULL	NULL

The following expressions return the day for each date in the DATE_SHIPPED column:

```
GET_DATE_PART( DATE_SHIPPED, 'D' )
GET_DATE_PART( DATE_SHIPPED, 'DD' )
GET_DATE_PART( DATE_SHIPPED, 'DDD' )
GET_DATE_PART( DATE_SHIPPED, 'DY' )
GET_DATE_PART( DATE_SHIPPED, 'DAY' )
```

DATE_SHIPPED	RETURN VALUE
Mar 13 1997 12:00:00AM	13
June 3 1997 11:30:44PM	3

DATE_SHIPPED	RETURN VALUE
Aug 22 1997 12:00:00PM	22
NULL	NULL

The following expressions return the month for each date in the DATE_SHIPPED column:

```
GET_DATE_PART( DATE_SHIPPED, 'MM' )
GET_DATE_PART( DATE_SHIPPED, 'MON' )
GET_DATE_PART( DATE_SHIPPED, 'MONTH' )
```

DATE_SHIPPED	RETURN VALUE
Mar 13 1997 12:00:00AM	3
June 3 1997 11:30:44PM	6
NULL	NULL

The following expression return the year for each date in the DATE_SHIPPED column:

```
GET_DATE_PART( DATE_SHIPPED, 'Y' )
GET_DATE_PART( DATE_SHIPPED, 'YY' )
GET_DATE_PART( DATE_SHIPPED, 'YYY' )
GET_DATE_PART( DATE_SHIPPED, 'YYYY' )
```

DATE_SHIPPED	RETURN VALUE
Mar 13 1997 12:00:00AM	1997
June 3 1997 11:30:44PM	1997
NULL	NULL

GREATEST

Returns the greatest value from a list of input values. Use this function to return the greatest string, date, or number. By default, the match is case sensitive.

Syntax

```
GREATEST( value1, [value2, ..., valueN,] CaseFlag )
```

Argument	Required/ Optional	Description
value	Required	Any datatype except Binary. Datatype must be compatible with other values. Value you want to compare against other values. You must enter at least one value argument. If the value is numeric, and other input values are numeric, all values use the highest precision possible. For example, if some values are Integer datatype and others are Double datatype, Data Integration converts the values to Double.
CaseFlag	Optional	Must be an integer. Determines whether the arguments in this function are case sensitive. You can enter any valid expression. When <i>CaseFlag</i> is a number other than 0, the function is case sensitive. When <i>CaseFlag</i> is a null value or 0, the function is not case sensitive.

Return Value

value1 if it is the greatest of the input values, *value2* if it is the greatest of the input values, and so on.

NULL if all the arguments are null.

Example

The following expression returns the greatest quantity of items ordered:

```
GREATEST( QUANTITY1, QUANTITY2, QUANTITY3 )
```

QUANTITY1	QUANTITY2	QUANTITY3	RETURN VALUE
150	756	27	756
			NULL
5000	97	17	5000
120	1724	965	1724

IIF

Returns one of two values you specify, based on the results of a condition.

Syntax

```
IIF( condition, value1 [,value2] )
```

Argument	Required/ Optional	Description
<i>condition</i>	Required	The condition you want to evaluate. You can enter any valid expression that evaluates to TRUE or FALSE.
<i>value1</i>	Required	Any datatype except Binary. The value you want to return if the condition is TRUE. The return value is always the datatype specified by this argument. You can enter any valid expression, including another IIF expression.
<i>value2</i>	Optional	Any datatype except Binary. The value you want to return if the condition is FALSE. You can enter any valid expression, including another IIF expression.

Unlike conditional functions in some systems, the FALSE (*value2*) condition in the IIF function is not required. If you omit *value2*, the function returns the following when the condition is FALSE:

- 0 if *value1* is a Numeric datatype.
- Empty string if *value1* is a String datatype.
- NULL if *value1* is a Date/Time datatype.

For example, the following expression does not include a FALSE condition and *value1* is a string datatype so Data Integration returns an empty string for each row that evaluates to FALSE:

```
IIF( SALES > 100, EMP_NAME )
```

SALES	EMP_NAME	RETURN VALUE
150	John Smith	John Smith
50	Pierre Bleu	' ' (empty string)
120	Sally Green	Sally Green
NULL	Greg Jones	' ' (empty string)

Return Value

value1 if the condition is TRUE.

value2 if the condition is FALSE.

For example, the following expression includes the FALSE condition NULL so Data Integration returns NULL for each row that evaluates to FALSE:

```
IIF( SALES > 100, EMP_NAME, NULL )
```

SALES	EMP_NAME	RETURN VALUE
150	John Smith	John Smith

SALES	EMP_NAME	RETURN VALUE
50	Pierre Bleu	NULL
120	Sally Green	Sally Green
NULL	Greg Jones	NULL

If the data contains multibyte characters and the condition argument compares string data, the return value depends on the code page of the Secure Agent that runs the task.

IIF and Datatypes

When you use IIF, the datatype of the return value is the same as the datatype of the result with the greatest precision.

For example, you have the following expression:

```
IIF( SALES < 100, 1, .3333 )
```

The TRUE result (1) is an integer and the FALSE result (.3333) is a decimal. The Decimal datatype has greater precision than Integer, so the datatype of the return value is always a Decimal.

When at least one result is Double, the datatype of the return value is Double.

Special Uses of IIF

Use nested IIF statements to test multiple conditions. The following example tests for various conditions and returns 0 if sales is 0 or negative:

```
IIF( SALES > 0, IIF( SALES < 50, SALARY1, IIF( SALES < 100, SALARY2, IIF( SALES < 200, SALARY3, BONUS))), 0 )
```

You can make this logic more readable by adding comments:

```
IIF( SALES > 0,
  --then test to see if sales is between 1 and 49:
  IIF( SALES < 50,
    --then return SALARY1
    SALARY1,
    --else test to see if sales is between 50 and 99:
    IIF( SALES < 100,
      --then return
      SALARY2,
      --else test to see if sales is between 100 and 199:
      IIF( SALES < 200,
        --then return
        SALARY3,
        --else for sales over 199, return
        BONUS)
      )
    ),
  --else for sales less than or equal to zero, return
  0)
```

Use IIF in update strategies. For example:

```
IIF( ISNULL( ITEM_NAME ), DD_REJECT, DD_INSERT)
```

Alternative to IIF

Use [“DECODE” on page 79](#) instead of IIF in many cases. DECODE may improve readability. The following shows how you use DECODE instead of IIF using the first example from the previous section:

```
DECODE( TRUE,
  SALES > 0 and SALES < 50, SALARY1,
  SALES > 49 AND SALES < 100, SALARY2,
  SALES > 99 AND SALES < 200, SALARY3,
  SALES > 199, BONUS)
```

IN

Matches input data to a list of values. By default, the match is case sensitive.

Syntax

```
IN( valueToSearch, value1, [value2, ..., valueN,] CaseFlag )
```

Argument	Required/Optional	Description
valueToSearch	Required	Can be a string, date, or numeric value. Input value you want to match against a comma-separated list of values.
value	Required	Can be a string, date, or numeric value. Comma-separated list of values you want to search for. Values can be columns. There is no maximum number of values you can list.
CaseFlag	Optional	Must be an integer. Determines whether the arguments in this function are case sensitive. You can enter any valid expression. When <i>CaseFlag</i> is a number other than 0, the function is case sensitive. When <i>CaseFlag</i> is a null value or 0, the function is not case sensitive.

Return Value

TRUE (1) if the input value matches the list of values.

FALSE (0) if the input value does not match the list of values.

NULL if the input is a null value.

Example

The following expression determines if the input value is a safety knife, chisel point knife, or medium titanium knife. The input values do not have to match the case of the values in the comma-separated list:

```
IN( ITEM_NAME, 'Chisel Point Knife', 'Medium Titanium Knife', 'Safety Knife', 0 )
```

ITEM_NAME	RETURN VALUE
Stabilizing Vest	0 (FALSE)
Safety knife	1 (TRUE)
Medium Titanium knife	1 (TRUE)
	NULL

INDEXOF

Finds the index of a value among a list of values. By default, the match is case sensitive.

Syntax

```
INDEXOF( valueToSearch, string1, [string2, ..., stringN,] CaseFlag )
```

Argument	Required/ Optional	Description
valueToSearch	Required	String datatype. Value you want to search for in the list of strings.
string	Required	String datatype. Comma-separated list of values you want to search against. Values can be in string format. There is no maximum number of values you can list. The value is case sensitive, unless you set MatchCase to 0.
CaseFlag	Required	Must be an integer. Determines whether the arguments in this function are case sensitive. You can enter any valid expression. When <i>CaseFlag</i> is a number other than 0, the function is case sensitive. When <i>CaseFlag</i> is a null value or 0, the function is not case sensitive.

Return Value

1 if the input value matches *string1*, 2 if the input value matches *string2*, and so on.

0 if the input value is not found.

NULL if the input is a null value.

Example

The following expression determines if values from the ITEM_NAME column match the first, second, or third string:

```
INDEXOF( ITEM_NAME, 'diving hood', 'flashlight', 'safety knife')
```

ITEM_NAME	RETURN VALUE
Safety Knife	0
diving hood	1
Compass	0
safety knife	3
flashlight	2

Safety Knife returns a value of 0 because it does not match the case of the input value.

INITCAP

Capitalizes the first letter in each word of a string and converts all other letters to lowercase. Words are delimited by white space (a blank space, formfeed, newline, carriage return, tab, or vertical tab) and

characters that are not alphanumeric. For example, if you pass the string '...THOMAS', the function returns Thomas.

Syntax

```
INITCAP( string )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	Any datatype except Binary. You can enter any valid expression.

Return Value

String. If the data contains multibyte characters, the return value depends on the code page of the Secure Agent that runs the task.

NULL if a value passed to the function is NULL.

Example

The following expression capitalizes all names in the FIRST_NAME column:

```
INITCAP( FIRST_NAME )
```

FIRST_NAME	RETURN VALUE
ramona	Ramona
18-albert	18-Albert
NULL	NULL
?!SAM	?!Sam
THOMAS	Thomas
PierRe	Pierre

INSTR

Returns the position of a character set in a string, counting from left to right.

Syntax

```
INSTR( string, search_value [,start [,occurrence]] )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	The string must be a character string. Passes the value you want to evaluate. You can enter any valid expression. The results of the expression must be a character string. If not, INSTR converts the value to a string before evaluating it.
<i>search_value</i>	Required	Any value. The search value is case sensitive. The set of characters you want to search for. The <i>search_value</i> must match a part of the string. For example, if you write <code>INSTR('Alfred Pope', 'Alfred Smith')</code> the function returns 0. You can enter any valid expression. If you want to search for a character string, enclose the characters you want to search for in single quotation marks, for example 'abc'.
<i>start</i>	Optional	Must be an integer value. The position in the string where you want to start the search. You can enter any valid expression. The default is 1, meaning that INSTR starts the search at the first character in the string. If the start position is 0, INSTR searches from the first character in the string. If the start position is a positive number, INSTR locates the start position by counting from the beginning of the string. If the start position is a negative number, INSTR locates the start position by counting from the end of the string. If you omit this argument, the function uses the default value of 1.
<i>occurrence</i>	Optional	A positive integer greater than 0. You can enter any valid expression. If the search value appears more than once in the string, you can specify which occurrence you want to search for. For example, you would enter 2 to search for the second occurrence from the start position. If you omit this argument, the function uses the default value of 1, meaning that INSTR searches for the first occurrence of the search value. If you pass a decimal, Data Integration rounds it to the nearest integer value. If you pass a negative integer or 0, the mapping fails when you run a workflow.

Return Value

Integer if the search is successful. Integer represents the position of the first character in the *search_value*, counting from left to right.

0 if the search is unsuccessful.

NULL if a value passed to the function is NULL.

Example

The following expression returns the position of the first occurrence of the letter 'a', starting at the beginning of each company name. Because the *search_value* argument is case sensitive, it skips the 'A' in 'Blue Fin Aqua Center', and returns the position for the 'a' in 'Aqua':

```
INSTR( COMPANY, 'a' )
```

COMPANY

Blue Fin Aqua Center

RETURN VALUE

13

COMPANY	RETURN VALUE
Maco Shark Shop	2
Scuba Gear	5
Frank's Dive Shop	3
VIP Diving Club	0

The following expression returns the position of the second occurrence of the letter 'a', starting at the beginning of each company name. Because the *search_value* argument is case sensitive, it skips the 'A' in 'Blue Fin Aqua Center', and returns 0:

```
INSTR( COMPANY, 'a', 1, 2 )
```

COMPANY	RETURN VALUE
Blue Fin Aqua Center	0
Maco Shark Shop	8
Scuba Gear	9
Frank's Dive Shop	0
VIP Diving Club	0

The following expression returns the position of the second occurrence of the letter 'a' in each company name, starting from the last character in the company name. Because the *search_value* argument is case sensitive, it skips the 'A' in 'Blue Fin Aqua Center', and returns 0:

```
INSTR( COMPANY, 'a', -1, 2 )
```

COMPANY	RETURN VALUE
Blue Fin Aqua Center	0
Maco Shark Shop	2
Scuba Gear	5
Frank's Dive Shop	0
VIP Diving Club	0

The following expression returns the position of the first character in the string 'Blue Fin Aqua Center' (starting from the last character in the company name):

```
INSTR( COMPANY, 'Blue Fin Aqua Center', -1, 1 )
```

COMPANY	RETURN VALUE
Blue Fin Aqua Center	1
Maco Shark Shop	0
Scuba Gear	0

COMPANY	RETURN VALUE
Frank's Dive Shop	0
VIP Diving Club	0

Using Nested INSTR

You can nest the INSTR function within other functions to accomplish more complex tasks.

The following expression evaluates a string, starting from the end of the string. The expression finds the last (rightmost) space in the string and then returns all characters to the left of it:

```
SUBSTR( CUST_NAME,1,INSTR( CUST_NAME,' ', -1,1 ) )
```

CUST_NAME	RETURN VALUE
PATRICIA JONES	PATRICIA
MARY ELLEN SHAH	MARY ELLEN

The following expression removes the character '#' from a string:

```
SUBSTR( CUST_ID, 1, INSTR(CUST_ID, '#')-1 ) || SUBSTR( CUST_ID, INSTR(CUST_ID, '#')+1 )
```

CUST_ID	RETURN VALUE
ID#33	ID33
#A3577	A3577
SS #712403399	SS 712403399

IS_DATE

Returns whether a string value is a valid date.

A valid date is any string in the default date format of MM/DD/YYYY HH24:MI:SS. If the strings you want to test are not in the default date format, use the TO_DATE format strings to specify the date format. If the strings passed to IS_DATE do not match the format string specified, the function returns FALSE (0). If the strings match the format string, the function returns TRUE (1).

IS_DATE evaluates strings and returns an integer value.

The target column for an IS_DATE expression must be String or Numeric datatype.

You might use IS_DATE to test or filter data in a flat file before writing it to a target.

Use the RR format string with IS_DATE instead of the YY format string. In most cases, the two format strings return the same values, but there are some unique cases where YY returns incorrect results. For example, the expression IS_DATE('02/29/00', 'YY') is internally computed as IS_DATE(02/29/1900 00:00:00), which returns false. However, Data Integration computes the expression IS_DATE('02/29/00', 'RR') as IS_DATE(02/29/2000 00:00:00), which returns TRUE. In the first case, year 1900 is not a leap year, so there is no February 29th.

Note: IS_DATE uses the same format strings as TO_DATE.

Syntax

```
IS_DATE( value [,format] )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	Must be a string datatype. Passes the rows you want to evaluate. You can enter any valid expression.
<i>format</i>	Optional	Enter a valid TO_DATE format string. The format string must match the parts of the <i>string</i> argument. For example, if you pass the string 'Mar 15 1997 12:43:10AM', you must use the format string 'MON DD YYYY HH12:MI:SSAM'. If you omit the format string, the string value must be in the default date of MM/DD/YYYY HH24:MI:SS. For more information about TO_DATE and IS_DATE format strings, see "TO_DATE and IS_DATE format strings" on page 26 .

Return Value

TRUE (1) if the row is a valid date.

FALSE (0) if the row is not a valid date.

NULL if a value in the expression is NULL or if the format string is NULL.

Warning: The format of the IS_DATE string must match the format string, including any date separators. If it does not, Data Integration might return inaccurate values or skip the row.

Example

The following expression checks the INVOICE_DATE column for valid dates:

```
IS_DATE( INVOICE_DATE )
```

This expression returns data similar to the following:

INVOICE_DATE	RETURN VALUE
NULL	NULL
'180'	0 (FALSE)
'04/01/98'	0 (FALSE)
'04/01/1998 00:12:15'	1 (TRUE)
'02/31/1998 12:13:55'	0 (FALSE) (February does not have 31 days)
'John Smith'	0 (FALSE)

The following IS_DATE expression specifies a format string of 'YYYY/MM/DD':

```
IS_DATE( INVOICE_DATE, 'YYYY/MM/DD' )
```

If the string value does not match this format, IS_DATE returns FALSE:

INVOICE_DATE	RETURN VALUE
NULL	NULL
'180'	0 (FALSE)

INVOICE_DATE	RETURN VALUE
'04/01/98'	0 (FALSE)
'1998/01/12'	1 (TRUE)
'1998/11/21 00:00:13'	0 (FALSE)
'1998/02/31'	0 (FALSE) (February does not have 31 days)
'John Smith'	0 (FALSE)

The following example shows how you use IS_DATE to test data before using TO_DATE to convert the strings to dates. This expression checks the values in the INVOICE_DATE column and converts each valid date to a date value. If the value is not a valid date, Data Integration returns ERROR and skips the row.

This example returns a Date/Time value. Therefore, the target column for the expression needs to be Date/Time:

```
IIF( IS_DATE ( INVOICE_DATE, 'YYYY/MM/DD' ), TO_DATE( INVOICE_DATE ), ERROR('Not a valid date' ) )
```

INVOICE_DATE	RETURN VALUE
NULL	NULL
'180'	'Not a valid date'
'04/01/98'	'Not a valid date'
'1998/01/12'	1998/01/12
'1998/11/21 00:00:13'	'Not a valid date'
'1998/02/31'	'Not a valid date'
'John Smith'	'Not a valid date'

IS_NUMBER

Returns whether a string is a valid number.

A valid number consists of the following parts:

- Optional space before the number
- Optional sign (+/-)
- One or more digits with an optional decimal point
- Optional scientific notation, such as the letter 'e' or 'E' (and the letter 'd' or 'D' on Windows) followed by an optional sign (+/-), followed by one or more digits
- Optional white space following the number

The following numbers are all valid:

```
' 100 '
' +100 '
```

```
'-100'
'-3.45e+32'
'+3.45E-32'
'+3.45d+32' (Windows only)
'+3.45D-32' (Windows only)
'.6804'
```

The target column for an IS_NUMBER expression must be a String or Numeric datatype.

You might use IS_NUMBER to test or filter data in a flat file before writing it to a target.

Syntax

```
IS_NUMBER( value )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	Must be a String datatype. Passes the rows you want to evaluate. You can enter any valid expression.

Return Value

TRUE (1) if the row is a valid number.

FALSE (0) if the row is not a valid number.

NULL if a value in the expression is NULL.

Example

The following expression checks the ITEM_PRICE column for valid numbers:

```
IS_NUMBER( ITEM_PRICE )
```

ITEM_PRICE	RETURN VALUE
'123.00'	1 (True)
'-3.45e+3'	1 (True)
'-3.45D-3'	1 (True - Windows only)
'-3.45d-3'	0 (False - UNIX only)
'3.45E-'	0 (False) <i>Incomplete number</i>
' '	0 (False) <i>Consists entirely of whitespace</i>
''	0 (False) <i>Empty string</i>
'+123abc'	0 (False)
' 123'	1 (True) <i>Leading whitespace</i>
'123 '	1 (True) <i>Trailing whitespace</i>
'ABC'	0 (False)
'-ABC'	0 (False)
NULL	NULL

Use IS_NUMBER to test data before using one of the numeric conversion functions, such as TO_FLOAT. For example, the following expression checks the values in the ITEM_PRICE column and converts each valid number to a double-precision floating point value. If the value is not a valid number, Data Integration returns 0.00:

```
IIF( IS_NUMBER ( ITEM_PRICE ), TO_FLOAT( ITEM_PRICE ), 0.00 )
```

ITEM_PRICE	RETURN VALUE
'123.00'	123
'-3.45e+3'	-3450
'3.45E-3'	0.00345
' '	0.00 <i>Consists entirely of whitespace</i>
''	0.00 <i>Empty string</i>
'+123abc'	0.00
'' 123ABC'	0.00
'ABC'	0.00
'-ABC'	0.00
NULL	NULL

IS_SPACES

Returns whether a string value consists entirely of spaces. A space is a blank space, a formfeed, a newline, a carriage return, a tab, or a vertical tab.

IS_SPACES evaluates an empty string as FALSE because there are no spaces. To test for an empty string, use LENGTH.

Syntax

```
IS_SPACES( value )
```

Argument	Required/Optional	Description
value	Required	Must be a string datatype. Passes the rows you want to evaluate. You can enter any valid expression.

Return Value

TRUE (1) if the row consists entirely of spaces.

FALSE (0) if the row contains data.

NULL if a value in the expression is NULL.

Example

The following expression checks the ITEM_NAME column for rows that consist entirely of spaces:

```
IS_SPACES( ITEM_NAME )
```

ITEM_NAME	RETURN VALUE
Flashlight	0 (False)
	1 (True)
Regulator system	0 (False)
NULL	NULL
' '	0 (FALSE) (<i>Empty string does not contain spaces.</i>)

Tip

Use IS_SPACES to avoid writing spaces to a character column in a target table. For example, if you want to write customer names to a fixed length CHAR(5) column in a target table, you might want to write '00000' instead of spaces. You would create an expression similar to the following:

```
IIF( IS_SPACES( CUST_NAMES ), '00000', CUST_NAMES )
```

ISNULL

Returns whether a value is NULL. ISNULL evaluates an empty string as FALSE.

Note: To test for empty strings, use LENGTH.

Syntax

```
ISNULL( value )
```

Argument	Required/ Optional	Description
value	Required	Any datatype except Binary. Passes the rows you want to evaluate. You can enter any valid expression.

Return Value

TRUE (1) if the value is NULL.

FALSE (0) if the value is not NULL.

Example

The following example checks for null values in the items table:

```
ISNULL( ITEM_NAME )
```

ITEM_NAME	RETURN VALUE
Flashlight	0 (FALSE)

ITEM_NAME	RETURN VALUE
NULL	1 (TRUE)
Regulator system	0 (FALSE)
' '	0 (FALSE) <i>Empty string is not NULL</i>

LAST

Returns the last row in the selected field. Optionally, you can apply a filter to limit the rows read. You can nest only one other aggregate function within LAST.

Use only in mapping tasks.

Syntax

```
LAST( value [, filter_condition ] )
```

Argument	Required/Optional	Description
<i>value</i>	Required	Any data type except binary. Passes the values for which you want to return the last row. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Last row in a field.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Example

The following expression returns the last row in the ITEMS_NAME field with a price greater than \$10.00:

```
LAST( ITEM_NAME, ITEM_PRICE > 10 )
```

ITEM_NAME	ITEM_PRICE
Flashlight	35.00
Navigation Compass	8.05
Regulator System	150.00
Flashlight	29.00
Depth/Pressure Gauge	88.00

ITEM_NAME	ITEM_PRICE
Vest	31.00
RETURN VALUE: Vest	

LAST_DAY

Returns the date of the last day of the month for each date in a column.

Syntax

```
LAST_DAY( date )
```

Argument	Required/ Optional	Description
<i>date</i>	Required	Date/Time datatype. Passes the dates for which you want to return the last day of the month. You can enter any valid expression that evaluates to a date.

Return Value

Date. The last day of the month for that date value you pass to this function.

NULL if a value in the selected column is NULL.

Null

If a value is NULL, LAST_DAY ignores the row. However, if all values passed from the column are NULL, LAST_DAY returns NULL.

Example

The following expression returns the last day of the month for each date in the ORDER_DATE column:

```
LAST_DAY( ORDER_DATE )
```

ORDER_DATE	RETURN VALUE
Apr 1 1998 12:00:00AM	Apr 30 1998 12:00:00AM
Jan 6 1998 12:00:00AM	Jan 31 1998 12:00:00AM
Feb 2 1996 12:00:00AM	Feb 29 1996 12:00:00AM (Leap year)
NULL	NULL
Jul 31 1998 12:00:00AM	Jul 31 1998 12:00:00AM

You can nest TO_DATE to convert string values to a date. TO_DATE always includes time information. If you pass a string that does not have a time value, the date returned will include the time 00:00:00.

The following example returns the last day of the month for each order date in the same format as the string:

```
LAST_DAY( TO_DATE( ORDER_DATE, 'DD-MON-YY' ) )
```

ORDER_DATE	RETURN VALUE
'18-NOV-98'	Nov 30 1998 00:00:00
'28-APR-98'	Apr 30 1998 00:00:00
NULL	NULL
'18-FEB-96'	Feb 29 1996 00:00:00 (<i>Leap year</i>)

LEAST

Returns the smallest value from a list of input values. By default, the match is case sensitive.

Syntax

```
LEAST( value1, [value2, ..., valueN,] CaseFlag )
```

Argument	Required/ Optional	Description
value	Required	Any datatype except Binary. Datatype must be compatible with other values. Value you want to compare against other values. You must enter at least one value argument. If the value is Numeric, and other input values are of other numeric datatypes, all values use the highest precision possible. For example, if some values are of the Integer datatype and others are of the Double datatype, Data Integration converts the values to Double.
CaseFlag	Optional	Must be an integer. Determines whether the arguments in this function are case sensitive. You can enter any valid expression. When <i>CaseFlag</i> is a number other than 0, the function is case sensitive. When <i>CaseFlag</i> is a null value or 0, the function is not case sensitive.

Return Value

value1 if it is the smallest of the input values, *value2* if it is the smallest of the input values, and so on.

NULL if all the arguments are null.

Example

The following expression returns the smallest quantity of items ordered:

```
LEAST( QUANTITY1, QUANTITY2, QUANTITY3 )
```

QUANTITY1	QUANTITY2	QUANTITY3	RETURN VALUE
150	756	27	27
			NULL
5000	97	17	17

QUANTITIY1	QUANTITY2	QUANTITY3	RETURN VALUE
120	1724	965	120

LENGTH

Returns the number of characters in a string, including trailing blanks.

Syntax

```
LENGTH( string )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	String datatype. The strings you want to evaluate. You can enter any valid expression.

Return Value

Integer representing the length of the string.

NULL if a value passed to the function is NULL.

Example

The following expression returns the length of each customer name:

```
LENGTH( CUSTOMER_NAME )
```

CUSTOMER_NAME	RETURN VALUE
Bernice Davis	13
NULL	NULL
John Baer	9
Greg Brown	10

Tips

Use LENGTH to test for empty string conditions. If you want to find fields in which customer name is empty, use an expression such as:

```
IIF( LENGTH( CUSTOMER_NAME ) = 0, 'EMPTY STRING' )
```

To test for a null field, use ISNULL. To test for spaces, use IS_SPACES.

LN

Returns the natural logarithm of a numeric value.

For example, `LN(3)` returns 1.098612. You usually use this function to analyze scientific data rather than business data.

This function is the reciprocal of the function EXP.

Syntax

```
LN( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. It must be a positive number, greater than 0. Passes the values for which you want to calculate the natural logarithm. You can enter any valid expression.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the natural logarithm for all values in the NUMBERS column:

```
LN( NUMBERS )
```

NUMBERS	RETURN VALUE
10	2.302585092994
125	4.828313737302
0.96	-0.04082199452026
NULL	NULL
-90	None. (Data Integration writes the row to the error rows file.)
0	None. (Data Integration writes the row to the error rows file.)

Note: When you pass a negative number or 0, Data Integration writes the row into the error rows file. The *numeric_value* must be a positive number greater than 0.

LOG

Returns the logarithm of a numeric value.

Most often, you use this function to analyze scientific data rather than business data.

Syntax

`LOG(base, exponent)`

Argument	Required/ Optional	Description
<i>base</i>	Required	The base of the logarithm. Must be a positive numeric value other than 0 or 1. Any valid expression that evaluates to a positive number other than 0 or 1.
<i>exponent</i>	Required	The exponent of the logarithm. Must be a positive numeric value greater than 0. Any valid expression that evaluates to a positive number greater than 0.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the logarithm for all values in the NUMBERS column:

`LOG(BASE, EXPONENT)`

BASE	EXPONENT	RETURN VALUE
15	1	0
.09	10	-0.956244644696599
NULL	18	NULL
35.78	NULL	NULL
-9	18	None. (Data Integration writes the row to the error rows file.)
0	5	None. (Data Integration writes the row to the error rows file.)
10	-2	None. (Data Integration writes the row to the error rows file.)

If you pass a negative number, 0, or 1 as a base value, or if you pass a negative value for the exponent, Data Integration writes the row to the error rows file.

LOWER

Converts uppercase string characters to lowercase.

Syntax

```
LOWER( string )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	Any string value. The argument passes the string values that you want to return as lowercase. You can enter any valid expression that evaluates to a string.

Return Value

Lowercase character string. If the data contains multibyte characters, the return value depends on the code page of the Secure Agent that runs the task.

NULL if a value in the selected column is NULL.

Example

The following expression returns all first names to lowercase:

```
LOWER( FIRST_NAME )
```

FIRST_NAME	RETURN VALUE
antonia	antonia
NULL	NULL
THOMAS	thomas
PierRe	pierre
BERNICE	bernice

LPAD

Adds a set of blanks or characters to the beginning of a string to set the string to a specified length.

Syntax

```
LPAD( first_string, length [,second_string] )
```

Argument	Required/ Optional	Description
<i>first_string</i>	Required	Can be a character string. The strings you want to change. You can enter any valid expression.
<i>length</i>	Required	Must be a positive integer literal. This argument specifies the length you want each string to be. When <i>length</i> is a negative number, RPAD returns NULL.
<i>second_string</i>	Optional	Can be any string value. The characters you want to append to the left-side of the <i>first_string</i> values. You can enter any valid expression. You can enter a specific string literal. However, enclose the characters you want to add to the beginning of the string within single quotation marks, as in 'abc'. This argument is case sensitive. If you omit the <i>second_string</i> , the function pads the beginning of the first string with blanks.

Return Value

String of the specified length.

NULL if a value passed to the function is NULL or if *length* is a negative number.

Example

The following expression standardizes numbers to six digits by padding them with leading zeros.

```
LPAD( PART_NUM, 6, '0' )
```

PART_NUM	RETURN VALUE
702	000702
1	000001
0553	000553
484834	484834

LPAD counts the length from left to right. If the first string is longer than the length, LPAD truncates the string from right to left. For example, LPAD('alphabetical', 5, 'x') returns the string 'alpha'.

If the second string is longer than the total characters needed to return the specified length, LPAD uses a portion of the second string:

```
LPAD( ITEM_NAME, 16, '*.*.*' )
```

ITEM_NAME	RETURN VALUE
Flashlight	*.*.*.Flashlight
Compass	*.*.*.*.Compass
Regulator System	Regulator System

ITEM_NAME	RETURN VALUE
Safety Knife	*..*Safety Knife

The following expression shows how LPAD handles negative values for the `length` argument for each row in the `ITEM_NAME` column:

```
LPAD( ITEM_NAME, -5, '.')
```

ITEM_NAME	RETURN VALUE
Flashlight	NULL
Compass	NULL
Regulator System	NULL

LTRIM

Removes blanks or characters from the beginning of a string. You can use LTRIM with IIF or DECODE in an expression to avoid spaces in a target table.

If you do not specify a *trim_set* parameter in the expression, LTRIM removes only single-byte spaces.

If you use LTRIM to remove characters from a string, LTRIM compares the *trim_set* to each character in the *string* argument, character-by-character, starting with the left side of the string. If the character in the string matches any character in the *trim_set*, LTRIM removes it. LTRIM continues comparing and removing characters until it fails to find a matching character in the *trim_set*. Then it returns the string, which does not include matching characters.

Syntax

```
LTRIM( string [, trim_set] )
```

Arguments	Required/Optional	Description
<i>string</i>	Required	Any string value. Passes the strings you want to modify. You can enter any valid expression. Use operators to perform comparisons or concatenate strings before removing characters from the beginning of a string.
<i>trim_set</i>	Optional	Any string value. Passes the characters you want to remove from the beginning of the first string. You can enter any valid expression. You can also enter a character string. However, you must enclose the characters you want to remove from the beginning of the string within single quotation marks, for example, 'abc'. If you omit the second string, the function removes any blanks from the beginning of the string. LTRIM is case sensitive. For example, if you want to remove the 'A' character from the string 'Alfredo', you would enter 'A', not 'a'.

Return Value

String. The string values with the specified characters in the *trim_set* argument removed.

NULL if a value passed to the function is NULL. If the *trim_set* is NULL, the function returns NULL.

Example

The following expression removes the characters 'S' and '.' from the strings in the LAST_NAME column:

```
LTRIM( LAST_NAME, 'S.')
```

LAST_NAME	RETURN VALUE
Nelson	Nelson
Osborne	Osborne
NULL	NULL
S. MacDonald	MacDonald
Sawyer	awyer
H. Bender	H. Bender
Steadman	teadman

LTRIM removes 'S.' from S. MacDonald and the 'S' from both Sawyer and Steadman, but not the period from H. Bender. This is because LTRIM searches, character-by-character, for the set of characters you specify in the *trim_set* argument. If the first character in the string matches the first character in the *trim_set*, LTRIM removes it. Then LTRIM looks at the second character in the string. If it matches the second character in the *trim_set*, LTRIM removes it, and so on. When the first character in the string does not match the corresponding character in the *trim_set*, LTRIM returns the string and evaluates the next row.

In the example of H. Bender, H does not match either character in the *trim_set* argument, so LTRIM returns the string in the LAST_NAME column and moves to the next row.

Tips

Use RTRIM and LTRIM with || or CONCAT to remove leading and trailing blanks after you concatenate two strings.

You can also remove multiple sets of characters by nesting LTRIM. For example, if you want to remove leading blanks and the character 'T' from a column of names, you might create an expression similar to the following:

```
LTRIM( LTRIM( NAMES ), 'T' )
```

MAKE_DATE_TIME

Returns the date and time based on the input values.

Syntax

```
MAKE_DATE_TIME( year, month, day, hour, minute, second )
```

Argument	Required/ Optional	Description
<i>year</i>	Required	Numeric datatype. Positive integer.
<i>month</i>	Required	Numeric datatype. Positive integer between 1 and 12 (January=1 and December=12).
<i>day</i>	Required	Numeric datatype. Positive integer between 1 and 31 (except for the months that have less than 31 days: February, April, June, September, and November).
<i>hour</i>	Optional	Numeric datatype. Positive integer between 0 and 24 (where 0=12AM, 12=12PM, and 24 =12AM).
<i>minute</i>	Optional	Numeric datatype. Positive integer between 0 and 59.
<i>second</i>	Optional	Numeric datatype. Positive integer between 0 and 59.

Return Value

Date as MM/DD/YYYY HH24:MI:SS.

Example

The following expression creates a date and time from the source columns:

```
MAKE_DATE_TIME( SALE_YEAR, SALE_MONTH, SALE_DAY, SALE_HOUR, SALE_MIN, SALE_SEC )
```

SALE_YR	SALE_MTH	SALE_DAY	SALE_HR	SALE_MIN	SALE_SEC	RETURN VALUE
2002	10	27	8	36	22	10/27/2002 08:36:22
2000	6	15	15	17		06/15/200 15:17:00
2003	1	3		22	45	01/03/2003 ??:22:45
04	3	30	12	5	10	03/30/2004 12:05:10
99	12	12	5		16	12/12/1999?? 05:?:16

MAX (Dates)

Returns the latest date found within a field or group. You can apply a filter to limit the rows in the search. You can also use MAX to return the largest numeric value or the highest string value in a field or group.

You can nest only one other aggregate function within MAX.

Use only in mapping tasks.

Syntax

```
MAX( date [, filter_condition] )
```

Argument	Required/ Optional	Description
<i>date</i>	Required	Date/time data type. Passes the date for which you want to return a maximum date. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Date.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Example

You can return the maximum date for a field or group. The following expression returns the maximum order date for flashlights:

```
MAX( ORDERDATE, ITEM_NAME='Flashlight' )
```

ITEM_NAME	ORDER_DATE
Flashlight	Apr 20 1998
Regulator System	May 15 1998
Flashlight	Sep 21 1998
Diving Hood	Aug 18 1998
Flashlight	NULL
RETURN VALUE: Sep 21 1998	

MAX (Numbers)

Returns the maximum numeric value found within a field or group. You can apply a filter to limit the rows in the search. You can also use MAX to return the latest date or the highest string value in a field or group.

You can nest only one other aggregate function within MAX.

Use only in mapping tasks.

Syntax

```
MAX( numeric_value [, filter_condition] )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric data type. Passes the numeric values for which you want to return a maximum numeric value. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a value is NULL, MAX ignores it. However, if all values passed from the field are NULL, MAX returns NULL.

Group By

MAX groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, MAX treats all rows as one group, returning one value.

Example

The first expression returns the maximum price for flashlights:

```
MAX( PRICE, ITEM_NAME='Flashlight' )
```

ITEM_NAME	PRICE
Flashlight	10.00
Regulator System	360.00
Flashlight	55.00
Diving Hood	79.00
Halogen Flashlight	162.00
Flashlight	85.00
Flashlight	NULL
RETURN VALUE: 85.00	

MAX (String)

Returns the highest string value found within a field or group. You can apply a filter to limit the rows in the search. You can also use MAX to return the latest date or the largest numeric value in a field or group.

Note: The MAX function uses the same sort order that the Sorter transformation uses. However, the MAX function is case sensitive, and the Sorter transformation may not be case sensitive.

You can nest only one other aggregate function within MAX.

Use only in mapping tasks.

Syntax

```
MAX( string [, filter_condition] )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	String data type. Passes the string values for which you want to return a maximum string value. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

String.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a value is NULL, MAX ignores it. However, if all values passed from the field are NULL, MAX returns NULL.

Group By

MAX groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, MAX treats all rows as one group, returning one value.

Example

The following expression returns the maximum item name for manufacturer ID 104:

```
MAX( ITEM_NAME, MANUFACTURER_ID='104' )
```

MANUFACTURER_ID	ITEM_NAME
101	First Stage Regulator
102	Electronic Console
104	Flashlight
104	Battery (9 volt)
104	Rope (20 ft)

MANUFACTURER_ID	ITEM_NAME
104	60.6 cu ft Tank
107	75.4 cu ft Tank
108	Wristband Thermometer

RETURN VALUE: Rope (20 ft)

MD5

Calculates the checksum of the input value. The function uses Message-Digest algorithm 5 (MD5). MD5 is a one-way cryptographic hash function with a 128-bit hash value. It calculates a unique value for each input. Use MD5 to verify data integrity.

Syntax

```
MD5( value )
```

Argument	Required/Optional	Description
<i>value</i>	Required	String or Binary datatype. Value for which you want to calculate checksum. The case of the input value affects the return value. For example, MD5(informatica) and MD5(Informatica) return different values.

Return Value

Unique 32-character string of hexadecimal digits 0-9 and a-f.

NULL if the input is a null value.

Example

You want to write changed data to a database. You can use the MD5 function to generate a unique checksum value for a row of data each time you read data from a source. When you run new sessions to read data from the same source, you can compare the previously generated checksum value against new checksum values. You can then write rows with new checksum values to the target. Those rows represent data that is changed in the source.

Tip

You can use the return value as a hash key.

MEDIAN

Returns the median of all values in a selected field.

If there is an even number of values in the field, the median is the average of the middle two values when all values are placed ordinally on a number line. If there is an odd number of values in the field, the median is the middle number.

You can nest only one other aggregate function within MEDIAN, and the nested function must return a numeric data type.

Data Integration reads all rows of data to perform the median calculation. The process of reading rows of data to perform the calculation may affect performance. Optionally, you can apply a filter to limit the rows you read to calculate the median.

Use only in mapping tasks.

Syntax

```
MEDIAN( numeric_value [, filter_condition ] )
```

Argument	Required/Optional	Description
<i>numeric_value</i>	Required	Numeric data type. Passes the values for which you want to calculate a median. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL, or if no rows are selected. For example, the filter condition evaluates to FALSE or NULL for all rows.

Nulls

If a value is NULL, MEDIAN ignores the row. However, if all values passed from the field are NULL, MEDIAN returns NULL.

Group By

MEDIAN groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, MEDIAN treats all rows as one group, returning one value.

Example

To calculate the median salary for all departments, you create an Aggregator transformation grouped by departments with a field specifying the following expression:

```
MEDIAN( SALARY )
```

The following expression returns the median value for orders of stabilizing vests:

```
MEDIAN( SALES, ITEM = 'Stabilizing Vest' )
```

ITEM	SALES
Flashlight	85
Stabilizing Vest	504
Stabilizing Vest	36
Safety Knife	5
Medium Titanium Knife	150
Tank	NULL
Stabilizing Vest	441
Chisel Point Knife	60
Stabilizing Vest	NULL
Stabilizing Vest	1044
Wrist Band Thermometer	110

RETURN VALUE: 472.5

METAPHONE

Encodes string values. You can specify the length of the string that you want to encode.

METAPHONE encodes characters of the English language alphabet (A-Z). It encodes both uppercase and lowercase letters in uppercase.

METAPHONE encodes characters according to the following list of rules:

- Skips vowels (A, E, I, O, and U) unless one of them is the first character of the input string.
METAPHONE('CAR') returns 'KR' and METAPHONE('AAR') returns 'AR'.
- Uses special encoding guidelines.

The following table lists the METAPHONE encoding guidelines:

Input	Returns	Condition	Example
B	n/a	When it follows M.	METAPHONE ('Lamb') returns LM.
B	In all other cases.	METAPHONE ('Box') returns BKS.	
C	X	When followed by IA or H.	METAPHONE ('Facial') returns FXL.

Input	Returns	Condition	Example
S	When followed by I, E, or Y.	METAPHONE ('Fence') returns FNS.	
n/a	When it follows S, and is followed by I, E, or Y.	METAPHONE ('Scene') returns SN.	
K	In all other cases.	METAPHONE ('Cool') returns KL.	
D	J	When followed by GE, GY, or GI.	METAPHONE ('Dodge') returns TJ.
T	In all other cases.	METAPHONE ('David') returns TFT.	
F	F	In all cases.	METAPHONE ('FOX') returns FKS.
G	F	When followed by H and the first character in the input string is not B, D, or H.	METAPHONE ('Tough') returns TF.
n/a	When followed by H and the first character in the input string is B, D, or H.	METAPHONE ('Hugh') returns HF.	
J	When followed by I, E or Y and does not repeat.	METAPHONE ('Magic') returns MJK.	
K	In all other cases.	METAPHONE ('GUN') returns KN.	
H	H	When it does not follow C, G, P, S, or T and is followed by A, E, I, or U.	METAPHONE ('DHAT') returns THT.
n/a	In all other cases.	METAPHONE ('Chain') returns XN.	
J	J	In all cases.	METAPHONE ('Jen') returns JN.
K	n/a	When it follows C.	METAPHONE ('Ckim') returns KM.
K	In all other cases.	METAPHONE ('Kim') returns KM.	
L	L	In all cases.	METAPHONE ('Laura') returns LR.
M	M	In all cases.	METAPHONE ('Maggi') returns MK.
N	N	In all cases.	METAPHONE ('Nancy') returns NNS.
P	F	When followed by H.	METAPHONE ('Phone') returns FN.
P	In all other cases.	METAPHONE ('Pip') returns PP.	

Input	Returns	Condition	Example
Q	K	In all cases.	METAPHONE ('Queen') returns KN.
R	R	In all cases.	METAPHONE ('Ray') returns R.
S	X	When followed by H, IO, IA, or CHW.	METAPHONE ('Cash') returns KX.
S	In all other cases.	METAPHONE ('Sing') returns SNK.	
T	X	When followed by IA or IO.	METAPHONE ('Patio') returns PX.
0 *	When followed by H.	METAPHONE ('Thor') returns OR.	
n/a	When followed by CH.	METAPHONE ('Glitch') returns KLTx.	
T	In all other cases.	METAPHINE ('Tim') returns TM.	
V	F	In all cases.	METAPHONE ('Vin') returns FN.
W	W	When followed by A, E, I, O, or U.	METAPHONE ('Wang') returns WNK.
n/a	In all other cases.	METAPHONE ('When') returns HN.	
X	KS	In all cases.	METAPHONE ('Six') returns SKS.
Y	Y	When followed by A, E, I, O, or U.	METAPHONE ('Yang') returns YNK.
n/a	In all other cases.	METAPHONE ('Bobby') returns BB.	
Z	S	In all cases.	METAPHONE ('Zack') returns SK.
* The integer 0.			

- Skips the initial character and encodes the remaining string if the first two characters of the input string have one of the following values:
 - **KN**. For example, METAPHONE('KNOT') returns 'NT'.
 - **GN**. For example, METAPHONE('GNOB') returns 'NB'.
 - **PN**. For example, METAPHONE('PNRX') returns 'NRKS'.
 - **AE**. For example, METAPHONE('AERL') returns 'ERL'.
- If a character other than "C" occurs more than once in the input string, encodes the first occurrence only. For example, METAPHONE('BBOX') returns 'BKS' and METAPHONE('CCOX') returns 'KKKS'.

Syntax

```
METAPHONE( string [,length] )
```

Argument	Required/ Optional	Description
string	Required	Must be a character string. Passes the value you want to encode. The first character must be a character in the English language alphabet (A-Z). You can enter any valid expression. Skips any non-alphabetic character in <i>string</i> .
length	Optional	Must be an integer greater than 0. Specifies the number of characters in <i>string</i> that you want to encode. You can enter any valid expression. When <i>length</i> is 0 or a value greater than the length of <i>string</i> , encodes the entire input string. Default is 0.

Return Value

String.

NULL if one of the following conditions is true:

- All values passed to the function are NULL.
- No character in *string* is a letter of the English alphabet.
- *string* is empty.

Examples

The following expression encodes the first two characters in EMPLOYEE_NAME column to a string:

```
METAPHONE( EMPLOYEE_NAME, 2 )
```

Employee_Name	Return Value
John	JH
*@#\$	NULL
P\$%%oc&&KMNL	PK

The following expression encodes the first four characters in EMPLOYEE_NAME column to a string:

```
METAPHONE( EMPLOYEE_NAME, 4 )
```

Employee_Name	Return Value
John	JHNL
1ABC	ABK
*@#\$	NULL
P\$%%oc&&KMNL	PKKM

MIN (Dates)

Returns the earliest date found in a field or group. You can apply a filter to limit the rows in the search. You can also use MIN to return the smallest numeric value or the lowest string value in a field or group.

You can nest only one other aggregate function within MIN, and the nested function must return a date data type.

Use only in mapping tasks.

Syntax

```
MIN( date [, filter_condition] )
```

Argument	Required/Optional	Description
<i>date</i>	Required	Date/time data type. Passes the values for which you want to return minimum value. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Date if the *value* argument is a date.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a single value is NULL, MIN ignores it. However, if all values passed from the field are NULL, MIN returns NULL.

Group By

MIN groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, MIN treats all rows as one group, returning one value.

Example

The following expression returns the oldest order date for flashlights:

```
MIN( ORDER_DATE, ITEM_NAME='Flashlight' )
```

ITEM_NAME	ORDER_DATE
Flashlight	Apr 20 1998
Regulator System	May 15 1998
Flashlight	Sep 21 1998
Diving Hood	Aug 18 1998
Halogen Flashlight	Feb 1 1998

ITEM_NAME	ORDER_DATE
Flashlight	Oct 10 1998
Flashlight	NULL
RETURN VALUE: Feb 1 1998	

MIN (Numbers)

Returns the smallest numeric value found in a field or group. You can apply a filter to limit the rows in the search. You can also use MIN to return the latest date or the lowest string value in a field or group.

You can nest only one other aggregate function within MIN, and the nested function must return a numeric data type.

Use only in mapping tasks.

Syntax

```
MIN( numeric_value [, filter_condition] )
```

Argument	Required/Optional	Description
<i>numeric_value</i>	Required	Numeric data types. Passes the values for which you want to return minimum value. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a single value is NULL, MIN ignores it. However, if all values passed from the field are NULL, MIN returns NULL.

Group By

MIN groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, MIN treats all rows as one group, returning one value.

Example

The following expression returns the minimum price for flashlights:

```
MIN ( PRICE, ITEM_NAME='Flashlight' )
```

ITEM_NAME	PRICE
Flashlight	10.00
Regulator System	360.00
Flashlight	55.00
Diving Hood	79.00
Halogen Flashlight	162.00
Flashlight	85.00
Flashlight	NULL
RETURN VALUE: 10.00	

MIN (String)

Returns the lowest string value found in a field or group. You can apply a filter to limit the rows in the search.

Note: The MIN function uses the same sort order that the Sorter transformation uses. However, the MIN function is case sensitive, but the Sorter transformation may not be case sensitive.

You can also use MIN to return the latest date or the minimum numeric value in a field or group.

You can nest only one other aggregate function within MIN, and the nested function must return a string data type.

Use only in mapping tasks.

Syntax

```
MIN( string [, filter_condition] )
```

Argument	Required/Optional	Description
<i>string</i>	Required	String data type. Passes the values for which you want to return minimum value. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

String value.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a single value is NULL, MIN ignores it. However, if all values passed from the field are NULL, MIN returns NULL.

Group By

MIN groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, MIN treats all rows as one group, returning one value.

Example

The following expression returns the minimum item name for manufacturer ID 104:

```
MIN ( ITEM_NAME, MANUFACTURER_ID='104' )
```

MANUFACTURER_ID	ITEM_NAME
101	First Stage Regulator
102	Electronic Console
104	Flashlight
104	Battery (9 volt)
104	Rope (20 ft)
104	60.6 cu ft Tank
107	75.4 cu ft Tank
108	Wristband Thermometer

RETURN VALUE: 60.6 cu ft Tank

MOD

Returns the remainder of a division calculation. For example, `MOD(8,5)` returns 3.

Syntax

```
MOD( numeric_value, divisor )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. The values you want to divide. You can enter any valid expression.
<i>divisor</i>	Required	The numeric value you want to divide by. The divisor cannot be 0.

Return Value

Numeric value of the datatype you pass to the function. The remainder of the numeric value divided by the divisor.

NULL if a value passed to the function is NULL.

Example

The following expression returns the modulus of the values in the PRICE column divided by the values in the QTY column:

```
MOD( PRICE, QTY )
```

PRICE	QTY	RETURN VALUE
10.00	2	0
12.00	5	2
9.00	2	1
15.00	3	0
NULL	3	NULL
20.00	NULL	NULL
25.00	0	None. Data Integration writes the row into the error rows file.

The last row (25, 0) produced an error because you cannot divide by 0. To avoid dividing by 0, you can create an expression similar to the following, which returns the modulus of Price divided by Quantity only if the quantity is not 0. If the quantity is 0, the function returns NULL:

```
MOD( PRICE, IIF( QTY = 0, NULL, QTY ) )
```

PRICE	QTY	RETURN VALUE
10.00	2	0
12.00	5	2
9.00	2	1

PRICE	QTY	RETURN VALUE
15.00	3	0
NULL	3	NULL
20.00	NULL	NULL
25.00	0	NULL

The last row (25, 0) produced a NULL rather than an error because the IIF function replaces NULL with the 0 in the QTY column.

MOVINGAVG

Returns the average (row-by-row) of a specified set of rows. Optionally, you can apply a condition to filter rows before calculating the moving average.

Syntax

```
MOVINGAVG( numeric_value, rowset [, filter_condition] )
```

Argument	Required/Optional	Description
<i>numeric_value</i>	Required	Numeric data type. The values for which you want to calculate a moving average. You can enter any valid transformation expression.
<i>rowset</i>	Required	Must be a positive integer literal greater than 0. Defines the row set for which you want to calculate the moving average. For example, if you want to calculate a moving average for a column of data, five rows at a time, you might write an expression such as: <code>MOVINGAVG(SALES, 5)</code> .
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Note: If the return value is Decimal with precision greater than 15, you can enable high precision to ensure decimal precision up to 28 digits.

Nulls

MOVINGAVG ignores null values when calculating the moving average. However, if all values are NULL, the function returns NULL.

Example

The following expression returns the average order for a Stabilizing Vest, based on the first five rows in the SALES column, and thereafter, returns the average for the last five rows read:

```
MOVINGAVG( SALES, 5 )
```

ROW_NO	SALES	RETURN VALUE
1	600	NULL
2	504	NULL
3	36	NULL
4	100	NULL
5	550	358
6	39	245.8
7	490	243

The function returns the average for a set of five rows: 358 based on rows 1 through 5, 245.8 based on rows 2 through 6, and 243 based on rows 3 through 7.

MOVINGSUM

Returns the sum (row-by-row) of a specified set of rows. Optionally, you can apply a condition to filter rows before calculating the moving sum.

Syntax

```
MOVINGSUM( numeric_value, rowset [, filter_condition] )
```

Argument	Required/Optional	Description
<i>numeric_value</i>	Required	Numeric data type. The values for which you want to calculate a moving sum. You can enter any valid transformation expression.
<i>rowset</i>	Required	Must be a positive integer literal greater than 0. Defines the rowset for which you want to calculate the moving sum. For example, if you want to calculate a moving sum for a column of data, five rows at a time, you might write an expression such as: <code>MOVINGSUM(SALES, 5)</code>
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL, or if the function does not select any rows (for example, the filter condition evaluates to FALSE or NULL for all rows).

Note: If the return value is Decimal with precision greater than 15, you can enable high precision to ensure decimal precision up to 28 digits.

Nulls

MOVINGSUM ignores null values when calculating the moving sum. However, if all values are NULL, the function returns NULL.

Example

The following expression returns the sum of orders for a Stabilizing Vest, based on the first five rows in the SALES column, and thereafter, returns the average for the last five rows read:

```
MOVINGSUM( SALES, 5 )
```

ROW_NO	SALES	RETURN VALUE
1	600	NULL
2	504	NULL
3	36	NULL
4	100	NULL
5	550	1790
6	39	1229
7	490	1215

The function returns the sum for a set of five rows: 1790 based on rows 1 through 5, 1229 based on rows 2 through 6, and 1215 based on rows 3 through 7.

NPER

Returns the number of periods for an investment based on a constant interest rate and periodic, constant payments.

Syntax

```
NPER( rate, present value, payment [, future value, type] )
```

Argument	Required/ Optional	Description
rate	Required	Numeric. Interest rate earned in each period. Expressed as a decimal number. Divide the rate by 100 to express it as a decimal number. Must be greater than or equal to 0.
present value	Required	Numeric. Lump-sum amount a series of future payments is worth.

Argument	Required/Optional	Description
payment	Required	Numeric. Payment amount due per period. Must be a negative number.
future value	Optional	Numeric. Cash balance you want to attain after the last payment is made. If you omit this value, NPER uses 0.
type	Optional	Boolean. Timing of the payment. Enter 1 if payment is at the beginning of period. Enter 0 if payment is at the end of period. Default is 0. If you enter a value other than 0 or 1, Data Integration treats the value as 1.

Return Value

Numeric.

Example

The present value of an investment is \$2,000. Each payment is \$500 and the future value of the investment is \$20,000. The following expression returns 9 as the number of periods for which you need to make the payments:

```
NPER( 0.01, -2000, -500, 20000, TRUE )
```

Notes

To calculate interest rate earned in each period, divide the annual rate by the number of payments made in an year. For example, if you make monthly payments at an annual interest rate of 15 percent, the value of the Rate argument is 15% divided by 12. If you make annual payments, the value of the Rate argument is 15%.

The payment value and present value are negative because these are amounts that you pay.

PERCENTILE

Calculates the value that falls at a given percentile in a group of numbers.

Data Integration reads all rows of data to perform the percentile calculation. The process of reading rows to perform the calculation may affect performance. Optionally, you can apply a filter to limit the rows you read to calculate the percentile.

You can nest only one other aggregate function within PERCENTILE, and the nested function must return a numeric data type.

Use only in mapping tasks.

Syntax

```
PERCENTILE( numeric_value, percentile [, filter_condition ] )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric data type. Passes the values for which you want to calculate a percentile. You can enter any valid transformation expression.
<i>percentile</i>	Required	Integer between 0 and 100, inclusive. Passes the percentile you want to calculate. You can enter any valid transformation expression. If you pass a number outside the 0 to 100 range, Data Integration displays an error and does not write the row.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL, or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a value is NULL, PERCENTILE ignores the row. However, if all values in a group are NULL, PERCENTILE returns NULL.

Group By

PERCENTILE groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, PERCENTILE treats all rows as one group, returning one value.

Example

Data Integration calculates a percentile using the following logic:

$$i = \frac{(x + 1) \times \text{percentile}}{100}$$

Use the following guidelines for this equation:

- x is the number of elements in the group of values for which you are calculating a percentile.
- If $i < 1$, PERCENTILE returns the value of the first element in the list.
- If i is an integer value, PERCENTILE returns the value of the i th element in the list.
- Otherwise PERCENTILE returns the value of n :

$$n = [\lfloor i \rfloor \text{th?element} \times (\lceil i \rceil - i)] + [\lceil i \rceil \text{th?element} \times (i - \lfloor i \rfloor)]$$

The following expression returns the salary that falls at the 75th percentile of salaries greater than \$50,000:

```
PERCENTILE( SALARY, 75, SALARY > 50000 )
```

SALARY

125000.0

27900.0

100000.0

NULL

55000.0

9000.0

85000.0

86000.0

48000.0

99000.0

RETURN VALUE: 106250.0

PMT

Returns the payment for a loan based on constant payments and a constant interest rate.

Syntax

```
PMT( rate, terms, present value, future value, type ] )
```

Argument	Required/ Optional	Description
rate	Required	Numeric. Interest rate of the loan for each period. Expressed as a decimal number. Divide the rate by 100 to express it as a decimal number. Must be greater than or equal to 0.
terms	Required	Numeric. Number of periods or payments. Must be greater than 0.
present value	Required	Numeric. Principal for the loan.
future value	Optional	Numeric. Cash balance you want to attain after the last payment. If you omit this value, PMT uses 0.
type	Optional	Boolean. Timing of the payment. Enter 1 if payment is at the beginning of period. Enter 0 if payment is at the end of period. Default is 0. If you enter a value other than 0 or 1, Data Integration treats the value as 1.

Return Value

Numeric.

Example

The following expression returns -2111.64 as the monthly payment amount of a loan:

```
PMT( 0.01, 10, 20000 )
```

Notes

To calculate interest rate earned in each period, divide the annual rate by the number of payments made in a year. For example, if you make monthly payments at an annual interest rate of 15%, the rate is 15%/12. If you make annual payments, the rate is 15%.

The payment value is negative because these are amounts that you pay.

POWER

Returns a value raised to the exponent you pass to the function.

Syntax

```
POWER( base, exponent )
```

Argument	Required/ Optional	Description
<i>base</i>	Required	Numeric value. This argument is the base value. You can enter any valid expression. If the base value is negative, the exponent must be an integer.
<i>exponent</i>	Required	Numeric value. This argument is the exponent value. You can enter any valid expression. If the base value is negative, the exponent must be an integer. In this case, the function rounds any decimal values to the nearest integer before returning a value.

Return Value

Double value.

NULL if you pass a null value to the function.

Example

The following expression returns the values in the Numbers column raised to the values in the Exponent column:

```
POWER( NUMBERS, EXPONENT )
```

NUMBERS	EXPONENT	RETURN VALUE
10.0	2.0	100
3.5	6.0	1838.265625
3.5	5.5	982.594307804838
NULL	2.0	NULL

NUMBERS	EXPONENT	RETURN VALUE
10.0	NULL	NULL
-3.0	-6.0	0.00137174211248285
3.0	-6.0	0.00137174211248285
-3.0	6.0	729.0
-3.0	5.5	729.0

The value -3.0 raised to 6 returns the same results as -3.0 raised to 5.5. If the base is negative, the exponent must be an integer. Otherwise, Data Integration rounds the exponent to the nearest integer value.

PV

Returns the present value of an investment.

Syntax

```
PV( rate, terms, payment [, future value, type] )
```

Argument	Required/Optional	Description
rate	Required	Numeric. Interest rate earned in each period. Expressed as a decimal number. Divide the rate by 100 to express it as a decimal number. Must be greater than or equal to 0.
terms	Required	Numeric. Number of periods or payments. Must be greater than 0.
payment	Required	Numeric. Payment amount due per period. Must be a negative number.
future value	Optional	Numeric. Cash balance after the last payment. If you omit this value, PV uses 0.
type	Optional	Boolean. Timing of the payment. Enter 1 if payment is at the beginning of period. Enter 0 if payment is at the end of period. Default is 0. If you enter a value other than 0 or 1, Data Integration treats the value as 1.

Return Value

Numeric.

Example

The following expression returns 12,524.43 as the amount you must deposit in the account today to have a future value of \$20,000 in one year if you also deposit \$500 at the beginning of each period:

```
PV( 0.0075, 12, -500, 20000, TRUE )
```

RAND

Returns a random number between 0 and 1. This is useful for probability calculations.

Syntax

```
RAND( seed )
```

Argument	Required/ Optional	Description
seed	Optional	Numeric. Starting value for Data Integration to generate the random number. Value must be a constant. If you do not enter a seed, Data Integration uses the current system time to derive the numbers of seconds since January 1, 1971. It uses this value as the seed.

Return Value

Numeric.

For the same seed, Data Integration generates the same sequence of numbers.

Example

The following expression may return a value of 0.417022004702574:

```
RAND (1)
```

RATE

Returns the interest rate earned for each period by a security.

Syntax

```
RATE( terms, payment, present value[, future value, type] )
```

Argument	Required/ Optional	Description
terms	Required	Numeric. Number of periods or payments. Must be greater than 0.
payment	Required	Numeric. Payment amount due for each period. Must be a negative number.
present value	Required	Numeric. Lump-sum amount that a series of future payments is worth now.
future value	Optional	Numeric. Cash balance you want to attain after the last payment. For example, the future value of a loan is 0. If you omit this argument, RATE uses 0.
type	Optional	Boolean. Timing of the payment. Enter 1 if payment is at the beginning of period. Enter 0 if payment is at the end of period. Default is 0. If you enter a value other than 0 or 1, Data Integration treats the value as 1.

Return Value

Numeric.

Example

The following expression returns 0.0077 as the monthly interest rate of a loan:

```
RATE( 48, -500, 20000 )
```

To calculate the annual interest rate of the loan, multiply 0.0077 by 12. The annual interest rate is 0.0924 or 9.24%.

REG_EXTRACT

Extracts subpatterns of a regular expression within an input value. For example, from a regular expression pattern for a full name, you can also extract the first name or last name.

Note: Use the REG_REPLACE function to replace a character pattern in a string with another character pattern.

Syntax

```
REG_EXTRACT (subject, pattern, subPatternNum)
```

Argument	Required/Optional	Description
subject	Required	String datatype. Passes the value you want to compare against the regular expression pattern.
pattern	Required	String datatype. Regular expression pattern that you want to match. You must use perl compatible regular expression syntax. Enclose the pattern in single quotation marks.
subPatternNum	Optional	Integer value. Subpattern number of the regular expression you want to match. Use the following guidelines to determine the subpattern number: <ul style="list-style-type: none">- no value or 1. Extracts the first regular expression subpattern.- 2. Extracts the second regular expression subpattern.- n. Extracts the nth regular expression subpattern. Default is 1.

Using perl Compatible Regular Expression Syntax

You must use perl compatible regular expression syntax with REG_EXTRACT, REG_MATCH and REG_REPLACE functions.

The following table provides perl compatible regular expression syntax guidelines:

Syntax	Description
.	(period) Matches any one character.
[a-z]	Matches one instance of a character in lower case. For example, [a-z] matches ab. Use [A-Z] to match characters in upper case.
\d	Matches one instance of any digit from 0-9.
\s	Matches a whitespace character.

Syntax	Description
\w	Matches one alphanumeric character, including underscore (_)
()	Groups an expression. For example, the parentheses in (\d-\d-\d\d) groups the expression \d\d-\d\d, which finds any two numbers followed by a hyphen and any two numbers, as in 12-34.
{}	Matches the number of characters. For example, \d{3} matches any three numbers, such as 650 or 510. Or, [a-z]{2} matches any two letters, such as CA or NY.
?	Matches the preceding character or group of characters zero or one time. For example, \d{3}(-\d{4})? matches any three numbers, which can be followed by a hyphen and any four numbers.
* (asterisk)	Matches zero or more instances of the values that follow the asterisk. For example, *0 is any value that precedes a 0.
+	Matches one or more instances of the values that follow the plus sign. For example, \w+ is any value that follows an alphanumeric character.

For example, the following regular expression finds 5-digit U.S.A. zip codes, such as 93930, and 9-digit zip codes, such as 93930-5407:

```
\d{5}(-\d{4})?
```

\d{5} refers to any five numbers, such as 93930. The parentheses surrounding -\d{4} group this segment of the expression. The hyphen represents the hyphen of a 9-digit zip code, as in 93930-5407. \d{4} refers to any four numbers, such as 5407. The question mark states that the hyphen and last four digits are optional or can appear one time.

Converting COBOL Syntax to perl Compatible Regular Expression Syntax

If you are familiar with COBOL syntax, you can use the following information to write perl compatible regular expressions.

The following table shows examples of COBOL syntax and their perl equivalents:

COBOL Syntax	perl Syntax	Description
9	\d	Matches one instance of any digit from 0-9.
9999	\d\d\d\d or \d{4}	Matches any four digits from 0-9, as in 1234 or 5936.
x	[a-z]	Matches one instance of a letter.
9xx9	\d[a-z][a-z]\d	Matches any number followed by two letters and another number, as in 1ab2.

Converting SQL Syntax to perl Compatible Regular Expression Syntax

If you are familiar with SQL syntax, you can use the following information to write perl compatible regular expressions.

The following table shows examples of SQL syntax and their perl equivalents:

SQL Syntax	perl Syntax	Description
%	. *	Matches any string.
A%	A. *	Matches the letter "A" followed by any string, as in Area.
_	. (a period)	Matches any one character.
A_	A.	Matches "A" followed by any one character, such as AZ.

Return Value

Returns the value of the *n*th subpattern that is part of the input value. The *n*th subpattern is based on the value you specify for subPatternNum.

NULL if the input is a null value or if the pattern is null.

Example

You might use REG_EXTRACT in an expression to extract middle names from a regular expression that matches first name, middle name, and last name. For example, the following expression returns the middle name of a regular expression:

```
REG_EXTRACT (Employee_Name, '(\w+)\s+(\w+)\s+(\w+)', 2)
```

Employee_Name	Return Value
Stephen Graham Smith	Graham
Juan Carlos Fernando	Carlos

REG_MATCH

Returns whether a value matches a regular expression pattern. This lets you validate data patterns, such as IDs, telephone numbers, postal codes, and state names.

Note: Use the REG_REPLACE function to replace a character pattern in a string with a new character pattern.

Syntax

```
REG_MATCH( subject, pattern )
```

Argument	Required/Optional	Description
subject	Required	String datatype. Passes the value you want to match against the regular expression pattern.
pattern	Required	String datatype. Regular expression pattern that you want to match. You must use perl compatible regular expression syntax. Enclose the pattern in single quotation marks. For more information, see "REG_EXTRACT" on page 137 .

Return Value

TRUE if the data matches the pattern.

FALSE if the data does not match the pattern.

NULL if the input is a null value or if the pattern is NULL.

Example

You might use REG_MATCH in an expression to validate telephone numbers. For example, the following expression matches a 10-digit telephone number against the pattern and returns a Boolean value based on the match:

```
REG_MATCH (Phone_Number, '(\d\d\d-\d\d\d-\d\d\d\d) ' )
```

Phone_Number	Return Value
408-555-1212	TRUE
	NULL
510-555-1212	TRUE
92 555 51212	FALSE
650-555-1212	TRUE
415-555-1212	TRUE
831 555 12123	FALSE

Tip

You can also use REG_MATCH for the following tasks:

- To verify that a value matches a pattern. This use is similar to the SQL LIKE function.
- To verify that values are characters. This use is similar to the SQL IS_CHAR function.

To verify that a value matches a pattern, use a period (.) and an asterisk (*) with the REG_MATCH function in an expression. A period matches any one character. An asterisk matches 0 or more instances of values that follow it.

For example, use the following expression to find account numbers that begin with 1835:

```
REG_MATCH (ACCOUNT_NUMBER, '1835.*')
```

To verify that values are characters, use a REG_MATCH function with the regular expression [a-zA-Z]+. a-z matches all lowercase characters. A-Z matches all uppercase characters. The plus sign (+) indicates that there should be at least one character.

For example, use the following expression to verify that a list of last names contain only characters:

```
REG_MATCH (LAST_NAME, '[a-zA-Z]+')
```

REG_REPLACE

Replaces characters in a string with a another character pattern. By default, REG_REPLACE searches the input string for the character pattern you specify and replaces all occurrences with the replacement pattern. You can also indicate the number of occurrences of the pattern you want to replace in the string.

Syntax

```
REG_REPLACE( subject, pattern, replace, numReplacements )
```

Argument	Required/ Optional	Description
<i>subject</i>	Required	String datatype. Passes the string you want to search.
<i>pattern</i>	Required	String datatype. Passes the character string to be replaced. You must use perl compatible regular expression syntax. Enclose the pattern in single quotation marks. For more information, see "REG_EXTRACT" on page 137 .
<i>replace</i>	Required	String datatype. Passes the new character string.
<i>numReplacements</i>	Optional	Numeric datatype. Specifies the number of occurrences you want to replace. If you omit this option, REG_REPLACE will replace all occurrences of the character string.

Return Value

String.

Example

The following expression removes additional spaces from the Employee name data for each row of the Employee_name column:

```
REG_REPLACE( Employee_Name, '\s+', ' ' )
```

Employee_Name	RETURN VALUE
Adam Smith	Adam Smith
Greg Sanders	Greg Sanders
Sarah Fe	Sarah Fe
Sam Cooper	Sam Cooper

REPLACECHR

Replaces characters in a string with a single character or no character. REPLACECHR searches the input string for the characters you specify and replaces all occurrences of all characters with the new character you specify.

Syntax

```
REPLACECHR( CaseFlag, InputString, OldCharSet, NewChar )
```

Argument	Required/ Optional	Description
<i>CaseFlag</i>	Required	Must be an integer. Determines whether the arguments in this function are case sensitive. You can enter any valid expression. When <i>CaseFlag</i> is a number other than 0, the function is case sensitive. When <i>CaseFlag</i> is a null value or 0, the function is not case sensitive.
<i>InputString</i>	Required	Must be a character string. Passes the string you want to search. You can enter any valid expression. If you pass a numeric value, the function converts it to a character string. If <i>InputString</i> is NULL, REPLACECHR returns NULL.
<i>OldCharSet</i>	Required	Must be a character string. The characters you want to replace. You can enter one or more characters. You can enter any valid expression. You can also enter a text literal enclosed within single quotation marks, for example, 'abc'. If you pass a numeric value, the function converts it to a character string. If <i>OldCharSet</i> is NULL or empty, REPLACECHR returns <i>InputString</i> .
<i>NewChar</i>	Required	Must be a character string. You can enter one character, an empty string, or NULL. You can enter any valid expression. If <i>NewChar</i> is NULL or empty, REPLACECHR removes all occurrences of all characters in <i>OldCharSet</i> in <i>InputString</i> . If <i>NewChar</i> contains more than one character, REPLACECHR uses the first character to replace <i>OldCharSet</i> .

Return Value

String.

Empty string if REPLACECHR removes all characters in *InputString*.

NULL if *InputString* is NULL.

InputString if *OldCharSet* is NULL or empty.

Example

The following expression removes the double quotation marks from web log data for each row in the WEBLOG column:

```
REPLACECHR( 0, WEBLOG, '"', NULL )
```

WEBLOG

```
"GET /news/index.html HTTP/1.1"
```

```
"GET /companyinfo/index.html HTTP/1.1"
```

```
GET /companyinfo/index.html HTTP/1.1
```

RETURN VALUE

```
GET /news/index.html HTTP/1.1
```

```
GET /companyinfo/index.html HTTP/1.1
```

```
GET /companyinfo/index.html HTTP/1.1
```

WEBLOG	RETURN VALUE
NULL	NULL

The following expression removes multiple characters for each row in the WEBLOG column:

```
REPLACECHR ( 1, WEBLOG, ']['', NULL )
```

WEBLOG	RETURN VALUE
[29/Oct/2001:14:13:50 -0700]	29/Oct/2001:14:13:50 -0700
[31/Oct/2000:19:45:46 -0700] "GET /news/index.html HTTP/1.1"	31/Oct/2000:19:45:46 -0700 GET /news/index.html HTTP/1.1
[01/Nov/2000:10:51:31 -0700] "GET /news/index.html HTTP/1.1"	01/Nov/2000:10:51:31 -0700 GET /news/index.html HTTP/1.1
NULL	NULL

The following expression changes part of the value of the customer code for each row in the CUSTOMER_CODE column:

```
REPLACECHR ( 1, CUSTOMER_CODE, 'A', 'M' )
```

CUSTOMER_CODE	RETURN VALUE
ABA	MBM
abA	abM
BBC	BBC
ACC	MCC
NULL	NULL

The following expression changes part of the value of the customer code for each row in the CUSTOMER_CODE column:

```
REPLACECHR ( 0, CUSTOMER_CODE, 'A', 'M' )
```

CUSTOMER_CODE	RETURN VALUE
ABA	MBM
abA	MbM
BBC	BBC
ACC	MCC

The following expression changes part of the value of the customer code for each row in the CUSTOMER_CODE column:

```
REPLACECHR ( 1, CUSTOMER_CODE, 'A', NULL )
```

CUSTOMER_CODE	RETURN VALUE
ABA	B

CUSTOMER_CODE	RETURN VALUE
BBC	BBC
ACC	CC
AAA	<i>[empty string]</i>
aaa	aaa
NULL	NULL

The following expression removes multiple numbers for each row in the INPUT column:

```
REPLACECHR ( 1, INPUT, '14', NULL )
```

INPUT	RETURN VALUE
12345	235
4141	NULL
111115	5
NULL	NULL

When you want to use a single quotation mark (') in either *OldCharSet* or *NewChar*, you must use the CHR function. The single quotation mark is the only character that cannot be used inside a string literal.

The following expression removes multiple characters, including the single quotation mark, for each row in the INPUT column:

```
REPLACECHR (1, INPUT, CHR(39), NULL )
```

INPUT	RETURN VALUE
'Tom Smith' 'Laura Jones'	Tom Smith Laura Jones
Tom's	Toms
NULL	NULL

REPLACESTR

Replaces characters in a string with a single character, multiple characters, or no character. REPLACESTR searches the input string for all strings you specify and replaces them with the new string you specify.

Syntax

```
REPLACESTR ( CaseFlag, InputString, OldString1, [OldString2, ... OldStringN,] NewString )
```

Argument	Required/ Optional	Description
<i>CaseFlag</i>	Required	Must be an integer. Determines whether the arguments in this function are case sensitive. You can enter any valid expression. When <i>CaseFlag</i> is a number other than 0, the function is case sensitive. When <i>CaseFlag</i> is a null value or 0, the function is not case sensitive.
<i>InputString</i>	Required	Must be a character string. Passes the strings you want to search. You can enter any valid expression. If you pass a numeric value, the function converts it to a character string. If <i>InputString</i> is NULL, REPLACESTR returns NULL.
<i>OldString</i>	Required	Must be a character string. The string you want to replace. You must enter at least one <i>OldString</i> argument. You can enter one or more characters per <i>OldString</i> argument. You can enter any valid expression. You can also enter a text literal enclosed within single quotation marks, for example, 'abc'. If you pass a numeric value, the function converts it to a character string. When REPLACESTR contains multiple <i>OldString</i> arguments, and one or more <i>OldString</i> arguments is NULL or empty, REPLACESTR ignores the <i>OldString</i> argument. When all <i>OldString</i> arguments are NULL or empty, REPLACESTR returns <i>InputString</i> . The function replaces the characters in the <i>OldString</i> arguments in the order they appear in the function. For example, if you enter multiple <i>OldString</i> arguments, the first <i>OldString</i> argument has precedence over the second <i>OldString</i> argument, and the second <i>OldString</i> argument has precedence over the third <i>OldString</i> argument. When REPLACESTR replaces a string, it places the cursor after the replaced characters in <i>InputString</i> before searching for the next match. For more information, see the examples.
<i>NewString</i>	Required	Must be a character string. You can enter one character, multiple characters, an empty string, or NULL. You can enter any valid expression. If <i>NewString</i> is NULL or empty, REPLACESTR removes all occurrences of <i>OldString</i> in <i>InputString</i> .

Return Value

String.

Empty string if REPLACESTR removes all characters in *InputString*.

NULL if *InputString* is NULL.

InputString if all *OldString* arguments are NULL or empty.

Example

The following expression removes double quotation marks and two different text strings from web log data for each row in the WEBLOG column:

```
REPLACESTR( 1, WEBLOG, '"', 'GET ', ' HTTP/1.1', NULL )
```

WEBLOG	RETURN VALUE
"GET /news/index.html HTTP/1.1"	/news/index.html
"GET /companyinfo/index.html HTTP/1.1"	/companyinfo/index.html
GET /companyinfo/index.html	/companyinfo/index.html
GET	<i>[empty string]</i>
NULL	NULL

The following expression changes the title for certain values for each row in the TITLE column:

```
REPLACESTR ( 1, TITLE, 'rs.', 'iss', 's.' )
```

TITLE	RETURN VALUE
Mrs.	Ms.
Miss	Ms.
Mr.	Mr.
MRS.	MRS.

The following expression changes the title for certain values for each row in the TITLE column:

```
REPLACESTR ( 0, TITLE, 'rs.', 'iss', 's.' )
```

TITLE	RETURN VALUE
Mrs.	Ms.
MRS.	Ms.

The following expression shows how the REPLACESTR function replaces multiple *OldString* arguments for each row in the INPUT column:

```
REPLACESTR ( 1, INPUT, 'ab', 'bc', '*' )
```

INPUT	RETURN VALUE
abc	*c
abbc	**
abbbbc	*bb*
bc	*

The following expression shows how the REPLACESTR function replaces multiple *OldString* arguments for each row in the INPUT column:

```
REPLACESTR ( 1, INPUT, 'ab', 'bc', 'b' )
```

INPUT	RETURN VALUE
ab	b
bc	b
abc	bc
abbc	bb
abbcc	bbcc

When you want to use a single quotation mark (') in either *OldString* or *NewString*, you must use the CHR function. Use both the CHR and CONCAT functions to concatenate a single quotation mark onto a string. The single quotation mark is the only character that cannot be used inside a string literal. Consider the following example:

```
CONCAT( 'Joan', CONCAT( CHR(39), 's car' ) )
```

The return value is:

```
Joan's car
```

The following expression changes a string that includes the single quotation mark, for each row in the INPUT column:

```
REPLACESTR ( 1, INPUT, CONCAT('it', CONCAT(CHR(39), 's' )), 'its' )
```

INPUT	RETURN VALUE
it's	its
mit's	mits
mits	mits
mits'	mits'

REVERSE

Reverses the input string.

Syntax

```
REVERSE( string )
```

Argument	Required/ Optional	Description
string	Required	Any character value. Value you want to reverse.

Return Value

String. Reverse of the input value.

Example

The following expression reverses the numbers of the customer code:

```
REVERSE ( CUSTOMER_CODE )
```

CUSTOMER_CODE	RETURN VALUE
0001	1000
0002	2000
0003	3000
0004	4000

ROUND (Dates)

Rounds one part of a date. You can also use ROUND to round numbers.

This functions can round the following parts of a date:

- **Year.** Rounds the year portion of a date based on the month. If the month is between January and June, the function returns January 1 of the input year, and sets the time to 00:00:00. If the month is between July and December, the function returns January 1 of the next year with the time set to 00:00:00. For example, the expression `ROUND(06/30/1998 2:30:55, 'YY')` returns 01/01/1998 00:00:00, and `ROUND(07/1/1998 3:10:15, 'YY')` returns 1/1/1998 00:00:00.
- **Month.** Rounds the month portion of a date based on the day of the month. If the day of the month is between 1 and 15, it rounds the date to the first day of the input month with the time set to 00:00:00. If the day of the month is between 16 and the last day of the month, it rounds to the first day of the next month with the time set to 00:00:00. For example, the expression `ROUND(4/15/1998 12:15:00, 'MM')` returns 4/1/1998 00:00:00, and `ROUND(4/16/1998 8:24:19, 'MM')` returns 5/1/1998 00:00:00.
- **Day.** Rounds the day portion of the date based on the time. If the time is between 00:00:00 (12AM) and 11:59:59AM, the function returns the current date with the time set to 00:00:00 (12AM). If the time is 12:00:00 (12PM) or later, the function rounds the date to the next day with the time set to 00:00:00 (12AM). For example, the expression `ROUND(06/13/1998 2:30:45, 'DD')` returns 06/13/1998 00:00:00, and `ROUND(06/13/1998 22:30:45, 'DD')` returns 06/14/1998 00:00:00.
- **Hour.** Rounds the hour portion of the date based on the minutes in the hour. If the minute portion of the time is between 0 and 29, the function returns the current hour with the minutes and seconds set to 0. If the minute portion is 30 or greater, the function rounds to the next hour and sets the minutes and seconds to 0. For example, the expression `ROUND(04/01/1998 11:29:35, 'HH')` returns 04/01/1998 11:00:00, and `ROUND(04/01/1998 13:39:00, 'HH')` returns 04/01/1998 14:00:00.
- **Minute.** Rounds the minute portion of the date based on the seconds. If time has 0 to 29 seconds, the function returns the current minutes and sets the seconds to 0. If the time has 30 to 59 seconds, the function rounds to the next minute and sets the seconds to 0. For example, the expression `ROUND(05/22/1998 10:15:29, 'MI')` returns 05/22/1998 10:15:00, and `ROUND(05/22/1998 10:15:30, 'MI')` returns 05/22/1998 10:16:00.

Syntax

```
ROUND( date [,format] )
```

Argument	Required/ Optional	Description
<i>date</i>	Required	Date/Time datatype. You can nest TO_DATE to convert strings to dates before rounding.
<i>format</i>	Optional	Enter a valid format string. This is the portion of the date that you want to round. You can round only one portion of the date. If you omit the format string, the function rounds the date to the nearest day.

Return Value

Date with the specified part rounded. ROUND returns a date in the same format as the source date. You can link the results of this function to any column with a Date/Time datatype.

NULL if you pass a null value to the function.

Example

The following expressions round the year portion of dates in the DATE_SHIPPED column:

```
ROUND( DATE_SHIPPED, 'Y' )
ROUND( DATE_SHIPPED, 'YY' )
ROUND( DATE_SHIPPED, 'YYY' )
ROUND( DATE_SHIPPED, 'YYYY' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 1 1998 12:00:00AM
Apr 19 1998 1:31:20PM	Jan 1 1998 12:00:00AM
Dec 20 1998 3:29:55PM	Jan 1 1999 12:00:00AM
NULL	NULL

The following expressions round the month portion of each date in the DATE_SHIPPED column:

```
ROUND( DATE_SHIPPED, 'MM' )
ROUND( DATE_SHIPPED, 'MON' )
ROUND( DATE_SHIPPED, 'MONTH' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 1 1998 12:00:00AM
Apr 19 1998 1:31:20PM	May 1 1998 12:00:00AM
Dec 20 1998 3:29:55PM	Jan 1 1999 12:00:00AM
NULL	NULL

The following expressions round the day portion of each date in the DATE_SHIPPED column:

```
ROUND( DATE_SHIPPED, 'D' )
ROUND( DATE_SHIPPED, 'DD' )
ROUND( DATE_SHIPPED, 'DDD' )
```

```
ROUND( DATE_SHIPPED, 'DY' )
ROUND( DATE_SHIPPED, 'DAY' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 15 1998 12:00:00AM
Apr 19 1998 1:31:20PM	Apr 20 1998 12:00:00AM
Dec 20 1998 3:29:55PM	Dec 21 1998 12:00:00AM
Dec 31 1998 11:59:59PM	Jan 1 1999 12:00:00AM
NULL	NULL

The following expressions round the hour portion of each date in the DATE_SHIPPED column:

```
ROUND( DATE_SHIPPED, 'HH' )
ROUND( DATE_SHIPPED, 'HH12' )
ROUND( DATE_SHIPPED, 'HH24' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:31AM	Jan 15 1998 2:00:00AM
Apr 19 1998 1:31:20PM	Apr 19 1998 2:00:00PM
Dec 20 1998 3:29:55PM	Dec 20 1998 3:00:00PM
Dec 31 1998 11:59:59PM	Jan 1 1999 12:00:00AM
NULL	NULL

The following expression rounds the minute portion of each date in the DATE_SHIPPED column:

```
ROUND( DATE_SHIPPED, 'MI' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 15 1998 2:11:00AM
Apr 19 1998 1:31:20PM	Apr 19 1998 1:31:00PM
Dec 20 1998 3:29:55PM	Dec 20 1998 3:30:00PM
Dec 31 1998 11:59:59PM	Jan 1 1999 12:00:00AM
NULL	NULL

ROUND (Numbers)

Rounds numbers to a specified number of digits or decimal places. You can also use ROUND to round dates.

Syntax

```
ROUND( numeric_value [, precision] )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. You can enter any valid expression. Use operators to perform arithmetic before you round the values.
<i>precision</i>	Optional	<p>Positive or negative integer. If you enter a positive <i>precision</i>, the function rounds to this number of decimal places. For example, ROUND(12.99, 1) returns 13.0 and ROUND(15.44, 1) returns 15.4.</p> <p>If you enter a negative <i>precision</i>, the function rounds this number of digits to the left of the decimal point, returning an integer. For example, ROUND(12.99, -1) returns 10 and ROUND(15.99, -1) returns 20.</p> <p>If you enter decimal <i>precision</i>, the function rounds to the nearest integer before evaluating the expression. For example, ROUND(12.99, 0.8) returns 13.0 because the function rounds 0.8 to 1 and then evaluates the expression.</p> <p>If you omit the <i>precision</i> argument, the function rounds to the nearest integer, truncating the decimal portion of the number. For example, ROUND(12.99) returns 13.</p>

Return Value

Numeric value.

If one of the arguments is NULL, ROUND returns NULL.

Example

The following expression returns the values in the Price column rounded to three decimal places.

```
ROUND( PRICE, 3 )
```

PRICE	RETURN VALUE
12.9936	12.994
15.9949	15.995
-18.8678	-18.868
56.9561	56.956
NULL	NULL

You can round digits to the left of the decimal point by passing a negative integer in the *precision* argument:

```
ROUND( PRICE, -2 )
```

PRICE	RETURN VALUE
13242.99	13200.0
1435.99	1400.0

PRICE	RETURN VALUE
-108.95	-100.0
NULL	NULL

If you pass a decimal value in the *precision* argument, Data Integration rounds it to the nearest integer before evaluating the expression:

```
ROUND( PRICE, 0.8 )
```

PRICE	RETURN VALUE
12.99	13.0
56.34	56.3
NULL	NULL

If you omit the *precision* argument, the function rounds to the nearest integer:

```
ROUND( PRICE )
```

PRICE	RETURN VALUE
12.99	13.0
-15.99	-16.0
-18.99	-19.0
56.95	57.0
NULL	NULL

Tip

You can also use ROUND to explicitly set the precision of calculated values and achieve expected results.

RPAD

Converts a string to a specified length by adding blanks or characters to the end of the string.

Syntax

```
RPAD( first_string, length [,second_string] )
```

Argument	Required/ Optional	Description
<i>first_string</i>	Required	Any string value. The strings you want to change. You can enter any valid expression.
<i>length</i>	Required	Must be a positive integer literal. Specifies the length you want each string to be. When <i>length</i> is a negative number, RPAD returns NULL.
<i>second_string</i>	Optional	Any string value. Passes the string you want to append to the right-side of the <i>first_string</i> values. Enclose the characters you want to add to the end of the string within single quotation marks, for example, 'abc'. This argument is case sensitive. If you omit the second string, the function pads the end of the first string with blanks.

Return Value

String of the specified length.

NULL if a value passed to the function is NULL or if length is a negative number.

Example

The following expression returns the item name with a length of 16 characters, appending the string '.' to the end of each item name:

```
RPAD( ITEM_NAME, 16, '.')
```

ITEM_NAME	RETURN VALUE
Flashlight	Flashlight.....
Compass	Compass.....
Regulator System	Regulator System
Safety Knife	Safety Knife....

RPAD counts the length from left to right. So, if the first string is longer than the length, RPAD truncates the string from right to left. For example, RPAD('alphabetical', 5, 'x') would return the string 'alpha'. RPAD uses a partial part of the *second_string* when necessary.

The following expression returns the item name with a length of 16 characters, appending the string '*.*' to the end of each item name:

```
RPAD( ITEM_NAME, 16, '*.*' )
```

ITEM_NAME	RETURN VALUE
Flashlight	Flashlight*.*.*.
Compass	Compass*.*.*.*.*

ITEM_NAME	RETURN VALUE
Regulator System	Regulator System
Safety Knife	Safety Knife*..*

The following expression shows how RPAD handles negative values for the *length* argument for each row in the ITEM_NAME column:

```
RPAD( ITEM_NAME, -5, '.')
```

ITEM_NAME	RETURN VALUE
Flashlight	NULL
Compass	NULL
Regulator System	NULL

RTRIM

Removes blanks or characters from the end of a string.

If you do not specify a *trim_set* parameter in the expression, RTRIM removes only single-byte spaces.

If you use RTRIM to remove characters from a string, RTRIM compares the *trim_set* to each character in the *string* argument, character-by-character, starting with the right side of the string. If the character in the string matches any character in the *trim_set*, RTRIM removes it. RTRIM continues comparing and removing characters until it fails to find a matching character in the *trim_set*. It returns the string without the matching characters.

Syntax

```
RTRIM( string [, trim_set] )
```

Argument	Required/Optional	Description
<i>string</i>	Required	Any string value. Passes the values you want to trim. You can enter any valid expression. Use operators to perform comparisons or concatenate strings before removing blanks from the end of a string.
<i>trim_set</i>	Optional	Any string value. Passes the characters you want to remove from the end of the string. You can also enter a text literal. However, you must enclose the characters you want to remove from the end of the string within single quotation marks, for example, 'abc'. If you omit the second string, the function removes blanks from the end of the first string. RTRIM is case sensitive.

Return Value

String. The string values with the specified characters in the *trim_set* argument removed.

NULL if a value passed to the function is NULL.

Example

The following expression removes the characters 're' from the strings in the LAST_NAME column:

```
RTRIM( LAST_NAME, 're')
```

LAST_NAME	RETURN VALUE
Nelson	Nelson
Page	Pag
Osborne	Osborn
NULL	NULL
Sawyer	Sawy
H. Bender	H. Bend
Steadman	Steadman

RTRIM removes 'e' from Page even though 'r' is the first character in the *trim_set*. This is because RTRIM searches, character-by-character, for the set of characters you specify in the *trim_set* argument. If the last character in the string matches the first character in the *trim_set*, RTRIM removes it. If, however, the last character in the string does not match, RTRIM compares the second character in the *trim_set*. If the second from last character in the string matches the second character in the *trim_set*, RTRIM removes it, and so on. When the character in the string fails to match the *trim_set*, RTRIM returns the string and evaluates the next row.

In the last example, the last character in Nelson does not match any character in the *trim_set* argument, so RTRIM returns the string 'Nelson' and evaluates the next row.

Tips

Use RTRIM and LTRIM with || or CONCAT to remove leading and trailing blanks after you concatenate two strings.

You can also remove multiple sets of characters by nesting RTRIM. For example, if you want to remove trailing blanks and the character 't' from the end of each string in a column of names, you might create an expression similar to the following:

```
RTRIM( RTRIM( NAMES ), 't' )
```

SET_DATE_PART

Sets one part of a date/time value to a value you specify.

With SET_DATE_PART, you can change the following parts of a date:

Year

Change the year by entering a positive integer in the *value* argument. Use any of the year format strings: Y, YY, YYYY, or YYYY to set the year. For example, the expression `SET_DATE_PART(SHIP_DATE, 'YY', 2001)` changes the year to 2001 for all dates in the SHIP_DATE column.

Month

Change the month by entering a positive integer between 1 and 12 (January=1 and December=12) in the *value* argument. Use any of the month format strings: MM, MON, MONTH to set the month. For example, the expression `SET_DATE_PART(SHIP_DATE, 'MONTH', 10)` changes the month to October for all dates in the SHIP_DATE column.

Day

Change the day by entering a positive integer between 1 and 31 (except for the months that have less than 31 days: February, April, June, September, and November) in the *value* argument. Use any of the month format strings (D, DD, DDD, DY, and DAY) to set the day. For example, the expression `SET_DATE_PART(SHIP_DATE, 'DD', 10)` changes the day to 10 for all dates in the SHIP_DATE column.

Hour

Change the hour by entering a positive integer between 0 and 24 (where 0=12AM, 12=12PM, and 24 =12AM) in the *value* argument. Use any of the hour format strings (HH, HH12, HH24) to set the hour. For example, the expression `SET_DATE_PART(SHIP_DATE, 'HH', 14)` changes the hour to 14:00:00 (or 2:00:00PM) for all dates in the SHIP_DATE column.

Minute

Change the minutes by entering a positive integer between 0 and 59 in the *value* argument. You use the MI format string to set the minute. For example, the expression `SET_DATE_PART(SHIP_DATE, 'MI', 25)` changes the minute to 25 for all dates in the SHIP_DATE column.

Seconds

You can change the seconds by entering a positive integer between 0 and 59 in the *value* argument. You use the SS format string to set the second. For example, the expression `SET_DATE_PART(SHIP_DATE, 'SS', 59)` changes the second to 59 for all dates in the SHIP_DATE column.

Syntax

```
SET_DATE_PART( date, format, value )
```

Argument	Required/Optional	Description
<i>date</i>	Required	Date/Time datatype. The date you want to modify. You can enter any valid expression.
<i>format</i>	Required	A format string specifying the portion of the date to be changed. The format string is not case sensitive.
<i>value</i>	Required	A positive integer value assigned to the specified portion of the date. The integer must be a valid value for the part of the date you want to change. If you enter an improper value (for example, February 30), the session fails.

Return Value

Date in the same format as the source date with the specified part changed.

NULL if a value passed to the function is NULL.

Example

The following expressions change the hour to 4PM for each date in the DATE_PROMISED column:

```
SET_DATE_PART( DATE_PROMISED, 'HH', 16 )
SET_DATE_PART( DATE_PROMISED, 'HH12', 16 )
SET_DATE_PART( DATE_PROMISED, 'HH24', 16 )
```

DATE_PROMISED	RETURN VALUE
Jan 1 1997 12:15:56AM	Jan 1 1997 4:15:56PM
Feb 13 1997 2:30:01AM	Feb 13 1997 4:30:01PM
Mar 31 1997 5:10:15PM	Mar 31 1997 4:10:15PM
Dec 12 1997 8:07:33AM	Dec 12 1997 4:07:33PM
NULL	NULL

The following expressions change the month to June for the dates in the DATE_PROMISED column. Data Integration displays an error when you try to create a date that does not exist, such as changing March 31 to June 31:

```
SET_DATE_PART( DATE_PROMISED, 'MM', 6 )
SET_DATE_PART( DATE_PROMISED, 'MON', 6 )
SET_DATE_PART( DATE_PROMISED, 'MONTH', 6 )
```

DATE_PROMISED	RETURN VALUE
Jan 1 1997 12:15:56AM	Jun 1 1997 12:15:56AM
Feb 13 1997 2:30:01AM	Jun 13 1997 2:30:01AM
Mar 31 1997 5:10:15PM	None. Data Integration writes the row into the error rows file.
Dec 12 1997 8:07:33AM	Jun 12 1997 8:07:33AM
NULL	NULL

The following expressions change the year to 2000 for the dates in the DATE_PROMISED column:

```
SET_DATE_PART( DATE_PROMISED, 'Y', 2000 )
SET_DATE_PART( DATE_PROMISED, 'YY', 2000 )
SET_DATE_PART( DATE_PROMISED, 'YYY', 2000 )
SET_DATE_PART( DATE_PROMISED, 'YYYY', 2000 )
```

DATE_PROMISED	RETURN VALUE
Jan 1 1997 12:15:56AM	Jan 1 2000 12:15:56AM
Feb 13 1997 2:30:01AM	Feb 13 2000 2:30:01AM
Mar 31 1997 5:10:15PM	Mar 31 2000 5:10:15PM
Dec 12 1997 8:07:33AM	Dec 12 2000 4:07:33PM
NULL	NULL

Tip

If you want to change multiple parts of a date at one time, you can nest multiple `SET_DATE_PART` functions within the *date* argument. For example, you might write the following expression to change all of the dates in the `DATE_ENTERED` column to July 1 1998:

```
SET_DATE_PART( SET_DATE_PART( SET_DATE_PART( DATE_ENTERED, 'YYYY', 1998), MM, 7), 'DD', 1)
```

SETCOUNTVARIABLE

Counts the rows evaluated by the function and increments the current value of an in-out parameter based on the count. Returns the new current value.

At the end of each task session, Data Integration saves the last current value in the job details. Unless overridden, Data Integration uses the saved value as the initial value of the variable for the next time you use the task.

Use the `SETCOUNTVARIABLE` function only once for each in-out parameter in a pipeline. Data Integration processes variable functions as it encounters them in the mapping. The order in which Data Integration encounters variable functions in the mapping might not be the same for every session run. This could cause inconsistent results when you use the same variable function multiple times in a mapping.

You can use `SETCOUNTVARIABLE` in an Expression transformation.

Syntax

```
SETCOUNTVARIABLE( $$Variable )
```

Argument	Required/ Optional	Description
<code>\$\$Variable</code>	Required	Name of the in-out parameter that you want to set.

Return Value

The current value of the in-out parameter.

SETMAXVARIABLE

Sets the current value of an in-out parameter to the higher of two values: the current value of the parameter or the value you specify. Returns the new current value.

At the end of a task session, Data Integration saves the final current value and writes it to the job details. Unless overridden, it uses the saved value as the initial value of the parameter for the next task session.

When used with a string in-out parameter, `SETMAXVARIABLE` returns the higher string based on the sort order selected in the mapping.

Use the `SETMAXVARIABLE` function only once for each in-out parameter in a pipeline. Data Integration processes in-out parameters as it encounters them in a mapping. The order in which Data Integration

encounters variable functions in the mapping might not be the same for every task session. This could cause inconsistent results if you use the same variable function multiple times in a mapping.

You can use SETMAXVARIABLE with the Expression transformation.

Syntax

```
SETMAXVARIABLE( $$Variable, value )
```

Argument	Required/ Optional	Description
<i>\$\$ Variable</i>	Required	Name of the in-out parameter you want to set. Use in-out parameters with Max aggregation type.
<i>value</i>	Required	The value you want Data Integration to compare against the current value of the in-out parameter. You can enter any valid transformation expression that evaluates to a data type compatible with the data type of the parameter.

Return Value

The higher of two values: the current value of the in-out parameter or the value you specified. The return value is the new current value of the parameter.

When *value* is NULL Data Integration returns the current value of *\$\$Variable*.

SETMINVARIABLE

Sets the current value of an in-out parameter to the lower of two values: the current value of the parameter or the value you specify. Returns the new current value.

Data Integration saves the final current value in the job details. Unless overridden, it uses the saved value as the initial value of the parameter for the next task session.

When used with a string in-out parameter, SETMINVARIABLE returns the lower string based on the sort order selected for the mapping.

Use the SETMINVARIABLE function only once for each in-out parameter in a pipeline. Data Integration processes variable functions as it encounters them in the mapping. The order in which Data Integration encounters variable functions in the mapping might not be the same for every session. This could cause inconsistent results if you use the same variable function multiple times in a mapping.

You can use SETMINVARIABLE in the Expression transformation.

Syntax

```
SETMINVARIABLE( $$Variable, value )
```

Argument	Required/Optional	Description
<i>\$\$ Variable</i>	Required	Name of the in-out parameter you want to set. Use with in-out parameter with Min aggregation type.
<i>value</i>	Required	The value you want Data Integration to compare against the current value of the parameter. You can enter any valid expression that evaluates to a data type compatible with the data type of the parameter.

Return Value

The lower of two values: the current value of the parameter or the value you specified. The return value is the new current value of the parameter.

When *value* is NULL, Data Integration returns the current value of *\$\$Variable*.

SETVARIABLE

Sets the current value of an in-out parameter to a value you specify. Returns the specified value.

During task execution, Data Integration compares the final current value of the in-out parameter to the start value. Based on the aggregate type of the in-out parameter, it saves a final current value in the job details. Unless overridden, it uses the saved value as the initial value of the in-out parameter for the next task run.

Use the SETVARIABLE function only once for each in-out parameter in a pipeline. Data Integration processes variable functions as it encounters them in the mapping. The order in which Data Integration encounters variable functions in the mapping may not be the same for every task session. This could cause inconsistent results if you use the same variable function multiple times in a mapping.

You can use SETVARIABLE in the Expression transformation.

Syntax

```
SETVARIABLE( $$Variable, value )
```

Argument	Required/Optional	Description
<i>\$\$ Variable</i>	Required	Name of the in-out parameter you want to set. Use with in-out parameters configured with the Max or Min aggregation type.
<i>value</i>	Required	The value to set as the current value of the in-out parameter. You can use a valid expression that evaluates to a datatype compatible with the datatype of the parameter.

Return Value

Current value of the in-out parameter.

When *value* is NULL, Data Integration returns the current value of *\$\$Variable*.

Examples

The following expression sets an in-out parameter \$\$Time to the system date at the time Data Integration evaluates the row and returns the system date to the SET_\$\$TIME port:

```
SETVARIABLE ($$Time, SYSDATE)
```

TRANSACTION	TOTAL	SET_\$\$TIME
0100002	534.23	10/10/2016 01:34:33
0100003	699.01	10/10/2016 01:34:34
0100004	97.50	10/10/2016 01:34:35
0100005	116.43	10/10/2016 01:34:36
0100006	323.95	10/10/2016 01:34:37

At the end of the session, Data Integration saves 10/10/2016 01:34:37 in the job details as the last evaluated current value for \$\$Time. The next time the task runs, Data Integration evaluates all references to \$\$Time to 10/10/2016 01:34:37.

The following expression sets the in-out parameter \$\$Timestamp to the timestamp associated with the row and returns the timestamp to the SET_\$\$TIMESTAMP port:

```
SETVARIABLE ($$Time, TIMESTAMP)
```

TRANSACTION	TIMESTAMP	TOTAL	SET_\$\$TIME
0100002	10/01/2016 12:01:01	534.23	10/01/2016 12:01:01
0100003	10/01/2016 12:10:22	699.01	10/01/2016 12:10:22
0100004	10/01/2016 12:16:45	97.50	10/01/2016 12:16:45
0100005	10/01/2016 12:23:10	116.43	10/01/2016 12:23:10
0100006	10/01/2016 12:40:31	323.95	10/01/2016 12:40:31

At the end of the session, Data Integration saves 10/01/2016 12:40:31 in the job details as the last evaluated current value for \$\$Timestamp.

The next time the session runs, Data Integration sets the initial value of \$\$Timestamp to 10/01/2016 12:40:31.

SIGN

Returns whether a numeric value is positive, negative, or 0.

Syntax

```
SIGN( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric value. Passes the values you want to evaluate. You can enter any valid expression.

Return Value

-1 for negative values.

0 for 0.

1 for positive values.

NULL if NULL.

Example

The following expression determines if the SALES column includes any negative values:

```
SIGN( SALES )
```

SALES	RETURN VALUE
100	1
-25.99	-1
0	0
NULL	NULL

SIN

Returns the sine of a numeric value (expressed in radians).

Syntax

```
SIN( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. Numeric data expressed in radians (degrees multiplied by pi divided by 180). Passes the values for which you want to calculate the sine. You can enter any valid expression. You can also use operators to convert a numeric value to radians or perform arithmetic within the SIN calculation.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression converts the values in the Degrees column to radians and then calculates the sine for each radian:

```
SIN( DEGREES * 3.14159265359 / 180 )
```

DEGREES	RETURN VALUE
0	0
90	1
70	0.939692620785936
30	0.500000000000003
5	0.0871557427476639
18	0.309016994374967
89	0.999847695156393
NULL	NULL

You can perform arithmetic on the values passed to SIN before the function calculates the sine. For example:

```
SIN( ARCS * 3.14159265359 / 180 )
```

SINH

Returns the hyperbolic sine of the numeric value.

Syntax

```
SINH( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. Numeric data expressed in radians (degrees multiplied by pi divided by 180). Passes the values for which you want to calculate the hyperbolic sine. You can enter any valid expression.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the hyperbolic sine for the values in the ANGLES column:

```
SINH ( ANGLES )
```

ANGLES	RETURN VALUE
1.0	1.1752011936438
2.897	9.03225804884884
3.66	19.4178051793031
5.45	116.376934801486
0	0.0
0.345	0.35188478309993
NULL	NULL

Tip

You can perform arithmetic on the values passed to SINH before the function calculates the hyperbolic sine. For example:

```
SINH ( MEASURES.ARCS / 180 )
```

SOUNDEX

Encodes a string value into a four-character string.

SOUNDEX works for characters in the English alphabet (A-Z). It uses the first character of the input string as the first character in the return value and encodes the remaining three unique consonants as numbers.

SOUNDEX encodes characters according to the following list of rules:

- Uses the first character in *string* as the first character in the return value and encodes it in uppercase. For example, both SOUNDEX('John') and SOUNDEX('john') return 'J500'.
- Encodes the first three unique consonants following the first character in *string* and ignores the rest. For example, both SOUNDEX('JohnRB') and SOUNDEX('JohnRBCD') return 'J561'.

- Assigns a single code to consonants that sound alike.

The following table lists SOUNDEX encoding guidelines for consonants:

Code	Consonant
1	B, P, F, V
2	C, S, G, J, K, Q, X, Z
3	D, T

Code	Consonant
4	L
5	M, N
6	R

- Skips the characters A, E, I, O, U, H, and W unless one of them is the first character in *string*. For example, SOUNDEX('A123') returns 'A000' and SOUNDEX('MAeiouhwC') returns 'M000'.
- If *string* produces fewer than four characters, SOUNDEX pads the resulting string with zeroes. For example, SOUNDEX('J') returns 'J000'.
- If *string* contains a set of consecutive consonants that use the same code listed in the table above, SOUNDEX encodes the first occurrence and skips the remaining occurrences in the set. For example, SOUNDEX('AbbpdMN') returns 'A135'.
- Skips numbers in *string*. For example, both SOUNDEX('Joh12n') and SOUNDEX('1John') return 'J500'.
- Returns NULL if *string* is NULL or if all the characters in *string* are not letters of the English alphabet.

Syntax

```
SOUNDEX( string )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	Character string. Passes the string value you want to encode. You can enter any valid expression.

Return Value

String.

NULL if one of the following conditions is true:

- If value passed to the function is NULL.
- No character in *string* is a letter of the English alphabet.
- *string* is empty.

Example

The following expression encodes the values in the EMPLOYEE_NAME column:

```
SOUNDEX( EMPLOYEE_NAME ) SOUNDEX
```

EMPLOYEE_NAME	RETURN VALUE
John	J500
William	W450
jane	J500
joh12n	J500
1abc	A120

EMPLOYEE_NAME	RETURN VALUE
NULL	NULL

SQRT

Returns the square root of a non-negative numeric value.

Syntax

```
SQRT( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Positive numeric value. Passes the values for which you want to calculate a square root. You can enter any valid expression.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the square root for the values in the NUMBERS column:

```
SQRT( NUMBERS )
```

NUMBERS	RETURN VALUE
100	10
-100	None. Data Integration writes the row into the error rows file.
NULL	NULL
60.54	7.78074546557076

The value -100 results in an error during the session, since the function SQRT only evaluates positive numeric values. If you pass a negative value or character value, Data Integration writes the row into the error rows file.

You can perform arithmetic on the values passed to SQRT before the function calculates the square root.

STDDEV

Returns the standard deviation of the numeric values you pass to this function. STDDEV is used to analyze statistical data.

You can nest only one other aggregate function within STDDEV, and the nested function must return a numeric data type.

Use only in mapping tasks.

Syntax

```
STDDEV( numeric_value [,filter_condition] )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric data types. This function passes the values for which you want to calculate a standard deviation or the results of a function. You can enter any valid transformation expression. You can use operators to average values in different fields.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a single value is NULL, STDDEV ignores it. However, if all values are NULL, STDDEV returns NULL.

Group By

STDDEV groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, STDDEV treats all rows as one group, returning one value.

Examples

The following expression calculates the standard deviation of all rows greater than \$2000.00 in the TOTAL_SALES field:

```
STDDEV( SALES, SALES > 2000.00 )
```

SALES

2198.0

1010.90

2256.0

153.88

3001.0

NULL

8953.0

RETURN VALUE: 3254.60361129688

The function does not include the values 1010.90 and 153.88 in the calculation because the *filter_condition* specifies sales greater than \$2,000.

The following expression calculates the standard deviation of all rows in the SALES field:

```
STDDEV (SALES)
```

SALES

2198.0

2198.0

2198.0

2198.0

RETURN VALUE: 0

The return value is 0 because each row contains the same number (no standard deviation exists). If there is no standard deviation, the return value is 0.

SUBSTR

Returns a portion of a string. SUBSTR counts all characters, including blanks, starting at the beginning of the string.

Syntax

```
SUBSTR( string, start [,length] )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	Must be a character string. Passes the strings you want to search. You can enter any valid expression. If you pass a numeric value, the function converts it to a character string.
<i>start</i>	Required	Must be an integer. The position in the string where you want to start counting. You can enter any valid expression. If the start position is a positive number, SUBSTR locates the start position by counting from the beginning of the string. If the start position is a negative number, SUBSTR locates the start position by counting from the end of the string. If the start position is 0, SUBSTR searches from the first character in the string.
<i>length</i>	Optional	Must be an integer greater than 0. The number of characters you want SUBSTR to return. You can enter any valid expression. If you omit the length argument, SUBSTR returns all of the characters from the start position to the end of the string. If you pass a negative integer or 0, the function returns an empty string. If you pass a decimal, the function rounds it to the nearest integer value.

Return Value

String.

Empty string if you pass a negative or 0 length value.

NULL if a value passed to the function is NULL.

Example

The following expressions return the area code for each row in the PHONE column:

```
SUBSTR( PHONE, 0, 3 )
```

PHONE	RETURN VALUE
809-555-0269	809
357-687-6708	357
NULL	NULL

```
SUBSTR( PHONE, 1, 3 )
```

PHONE	RETURN VALUE
809-555-3915	809
357-687-6708	357
NULL	NULL

The following expressions return the phone number without the area code for each row in the PHONE column:

```
SUBSTR( PHONE, 5, 8 )
```

PHONE	RETURN VALUE
808-555-0269	555-0269
809-555-3915	555-3915
357-687-6708	687-6708
NULL	NULL

You can also pass a negative start value to return the phone number for each row in the PHONE column. The expression still reads the source string from left to right when returning the result of the *length* argument:

```
SUBSTR( PHONE, -8, 3 )
```

PHONE	RETURN VALUE
808-555-0269	555
809-555-3915	555
357-687-6708	687
NULL	NULL

You can nest INSTR in the *start* or *length* argument to search for a specific string and return its position.

The following expression evaluates a string, starting from the end of the string. The expression finds the last (right-most) space in the string and then returns all characters preceding it:

```
SUBSTR( CUST_NAME,1,INSTR( CUST_NAME,' ' ,-1,1 ) - 1 )
```

CUST_NAME	RETURN VALUE
PATRICIA JONES	PATRICIA
MARY ELLEN SHAH	MARY ELLEN

The following expression removes the character '#' from a string:

```
SUBSTR( CUST_ID, 1, INSTR(CUST_ID, '#')-1 ) || SUBSTR( CUST_ID, INSTR(CUST_ID, '#')+1 )
```

When the *length* argument is longer than the string, SUBSTR returns all the characters from the start position to the end of the string. Consider the following example:

```
SUBSTR('abcd', 2, 8)
```

The return value is 'bcd'. Compare this result to the following example:

```
SUBSTR('abcd', -2, 8)
```

The return value is 'cd'.

SUM

Returns the sum of all values in the selected field. Optionally, you can apply a filter to limit the rows you read to calculate the total.

You can nest only one other aggregate function within SUM, and the nested function must return a numeric data type.

Use only in mapping tasks.

Syntax

```
SUM( numeric_value [, filter_condition ] )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric data type. Passes the values you want to add. You can enter any valid transformation expression. You can use operators to add values in different fields.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Return Value

Numeric value.

NULL if all values passed to the function are NULL or if no rows are selected (for example, the filter condition evaluates to FALSE or NULL for all rows).

Nulls

If a single value is NULL, SUM ignores it. However, if all values passed from the field are NULL, SUM returns NULL.

Group By

SUM groups values based on group by fields you define in the transformation, returning one result for each group.

If there is no group by field, SUM treats all rows as one group, returning one value.

Example

The following expression returns the sum of all values greater than 2000 in the Sales field:

```
SUM( SALES, SALES > 2000 )
```

SALES

2500.0

1900.0

1200.0

NULL

3458.0

4519.0

RETURN VALUE: 10477.0

Tip

You can perform arithmetic on the values passed to SUM before the function calculates the total. For example:

```
SUM( QTY * PRICE - DISCOUNT )
```

SYSTIMESTAMP

Returns the current date and time with precision to the nanosecond of the system that hosts the Secure Agent that starts the task. The precision to which you can retrieve the date and time depends on the system that hosts the Secure Agent.

The return value of the function varies depending on how you configure the argument:

- When you configure the argument of SYSTIMESTAMP as a variable, Data Integration evaluates the function for each row in the transformation.
- When you configure the argument of SYSTIMESTAMP as a constant, Data Integration evaluates the function once and retains the value for each row in the transformation.

Syntax

```
SYSTIMESTAMP( [format] )
```

Argument	Required/ Optional	Description
format	Optional	Precision to which you want to retrieve the timestamp. You can specify precision up to seconds (SS), milliseconds (MS), microseconds (US), or nanoseconds (NS). Enclose the format string within single quotation marks. The format string is not case sensitive. For example, to display the date and time to the precision of milliseconds use the following syntax: SYSTIMESTAMP('MS'). Default precision is microseconds (US).

Return Value

Timestamp. Returns date and time to the specified precision. Precision dependent on platform.

Examples

Your organization has an online order service and processes real-time data. You can use the SYSTIMESTAMP function to generate a primary key for each transaction in the target database.

Create an Expression transformation with the following fields and values:

Field Name	Field Type	Expression
Customer_Name	Input	n/a
Order_Qty	Input	n/a
Time_Counter	Variable	'US'
Transaction_ID	Output	SYSTIMESTAMP (Time_Counter)

At run time, the SYSTIMESTAMP generates the system time to the precision of microseconds for each row:

Customer_Name	Order_Qty	Transaction_Id
Vani Deed	14	07/06/2007 18:00:30.701015000
Kalia Crop	3	07/06/2007 18:00:30.701029000
Vani Deed	6	07/06/2007 18:00:30.701039000
Harry Spoon	32	07/06/2007 18:00:30.701048000

TAN

Returns the tangent of a numeric value (expressed in radians).

Syntax

```
TAN( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. Numeric data expressed in radians (degrees multiplied by pi divided by 180). Passes the numeric values for which you want to calculate the tangent. You can enter any valid expression.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the tangent for all values in the DEGREES column:

```
TAN( DEGREES * 3.14159 / 180 )
```

DEGREES	RETURN VALUE
70	2.74747741945531
50	1.19175359259435
30	0.577350269189672
5	0.0874886635259298
18	0.324919696232929
89	57.2899616310952
NULL	NULL

TANH

Returns the hyperbolic tangent of the numeric value passed to this function.

Syntax

```
TANH( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. Numeric data expressed in radians (degrees multiplied by pi divided by 180). Passes the numeric values for which you want to calculate the hyperbolic tangent. You can enter any valid expression.

Return Value

Double value.

NULL if a value passed to the function is NULL.

Example

The following expression returns the hyperbolic tangent for the values in the ANGLES column:

```
TANH( ANGLES )
```

ANGLES	RETURN VALUE
1.0	0.761594155955765
2.897	0.993926947790665
3.66	0.998676551914886
5.45	0.999963084213409
0	0.0
0.345	0.331933853503641
NULL	NULL

Tip

You can perform arithmetic on the values passed to TANH before the function calculates the hyperbolic tangent. For example:

```
TANH( ARCS / 360 )
```

TO_BIGINT

Converts a string or numeric value to a bigint value. TO_BIGINT syntax contains an optional argument that you can choose to round the number to the nearest integer or truncate the decimal portion. TO_BIGINT ignores leading blanks.

Syntax

```
TO_BIGINT( value [, flag] )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	String or numeric datatype. Passes the value you want to convert to a bigint value. You can enter any valid expression.
<i>flag</i>	Optional	Specifies whether to truncate or round the decimal portion. The flag must be an integer literal or the constants TRUE or FALSE: <ul style="list-style-type: none">- TO_BIGINT truncates the decimal portion when the flag is TRUE or a number other than 0.- TO_BIGINT rounds the value to the nearest integer if the flag is FALSE or 0 or if you omit this argument. The flag is not set by default.

Return Value

Bigint.

NULL if the value passed to the function is NULL.

0 if the value passed to the function contains alphanumeric characters.

Examples

The following expressions use values from the IN_TAX source column:

```
TO_BIGINT( IN_TAX, TRUE )
```

IN_TAX	RETURN VALUE
'7,245,176,201,123,435.6789'	7,245,176,201,123,435
'7,245,176,201,123,435.2'	7,245,176,201,123,435
'7,245,176,201,123,435.2.48'	7,245,176,201,123,435
NULL	NULL
'A12.3Grove'	0
' 176,201,123,435.87'	176,201,123,435
'-7,245,176,201,123,435.2'	-7,245,176,201,123,435
'-7,245,176,201,123,435.23'	-7,245,176,201,123,435
-9,223,372,036,854,775,806.9	-9,223,372,036,854,775,806
9,223,372,036,854,775,806.9	9,223,372,036,854,775,806

```
TO_BIGINT( IN_TAX )
```

IN_TAX	RETURN VALUE
'7,245,176,201,123,435.6789'	7,245,176,201,123,436
'7,245,176,201,123,435.2'	7,245,176,201,123,435

IN_TAX	RETURN VALUE
'7,245,176,201,123,435.348'	7,245,176,201,123,435
NULL	NULL
'A12.3Grove'	0
' 176,201,123,435.87'	176,201,123,436
'-7,245,176,201,123,435.6789'	-7,245,176,201,123,436
'-7,245,176,201,123,435.23'	-7,245,176,201,123,435
-9,223,372,036,854,775,806.9	-9,223,372,036,854,775,807
9,223,372,036,854,775,806.9	9,223,372,036,854,775,807

TO_CHAR (Dates)

Converts dates to character strings. TO_CHAR also converts numeric values to strings. You can convert the date into any format using the TO_CHAR format strings.

Syntax

```
TO_CHAR( date [,format] )
```

Argument	Required/Optional	Description
<i>date</i>	Required	Date/Time datatype. Passes the date values you want to convert to character strings. You can enter any valid expression.
<i>format</i>	Optional	Enter a valid TO_CHAR format string. The format string defines the format of the return value, not the format for the values in the date argument. If you omit the format string, the function returns a string based on the default date format of MM/DD/YYYY HH24:MI:SS.

Return Value

String.

NULL if a value passed to the function is NULL.

Example

The following expression converts the dates in the DATE_PROMISED column to text in the format MON DD YYYY:

```
TO_CHAR( DATE_PROMISED, 'MON DD YYYY' )
```

DATE_PROMISED	RETURN VALUE
Apr 1 1998 12:00:10AM	'Apr 01 1998'
Feb 22 1998 01:31:10PM	'Feb 22 1998'

DATE_PROMISED	RETURN VALUE
Oct 24 1998 02:12:30PM	'Oct 24 1998'
NULL	NULL

If you omit the *format_string* argument, TO_CHAR returns a string in the default date format:

```
TO_CHAR( DATE_PROMISED )
```

DATE_PROMISED	RETURN VALUE
Apr 1 1998 12:00:10AM	'04/01/1997 00:00:01'
Feb 22 1998 01:31:10PM	'02/22/1997 13:31:10'
Oct 24 1998 02:12:30PM	'10/24/1997 14:12:30'
NULL	NULL

The following expressions return the day of the week for each date in a column:

```
TO_CHAR( DATE_PROMISED, 'D' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10AM	'3'
02-22-1997 01:31:10PM	'7'
10-24-1997 02:12:30PM	'6'
NULL	NULL

```
TO_CHAR( DATE_PROMISED, 'DAY' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10AM	'Tuesday'
02-22-1997 01:31:10PM	'Saturday'
10-24-1997 02:12:30PM	'Friday'
NULL	NULL

The following expression returns the day of the month for each date in a column:

```
TO_CHAR( DATE_PROMISED, 'DD' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10AM	'01'
02-22-1997 01:31:10PM	'22'
10-24-1997 02:12:30PM	'24'
NULL	NULL

The following expression returns the day of the year for each date in a column:

```
TO_CHAR( DATE_PROMISED, 'DDD' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10AM	'091'
02-22-1997 01:31:10PM	'053'
10-24-1997 02:12:30PM	'297'
NULL	NULL

The following expressions return the hour of the day for each date in a column:

```
TO_CHAR( DATE_PROMISED, 'HH' )
TO_CHAR( DATE_PROMISED, 'HH12' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10AM	'12'
02-22-1997 01:31:10PM	'01'
10-24-1997 02:12:30PM	'02'
NULL	NULL

```
TO_CHAR( DATE_PROMISED, 'HH24' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10AM	'00'
02-22-1997 01:31:10PM	'13'
10-24-1997 11:12:30PM	'23'
NULL	NULL

The following expression converts date values to MJD values expressed as strings:

```
TO_CHAR( SHIP_DATE, 'J' )
```

SHIP_DATE	RETURN_VALUE
Dec 31 1999 03:59:59PM	2451544
Jan 1 1900 01:02:03AM	2415021

The following expression converts dates to strings in the format MM/DD/YY:

```
TO_CHAR( SHIP_DATE, 'MM/DD/RR' )
```

SHIP_DATE	RETURN_VALUE
12/31/1999 01:02:03AM	12/31/99
09/15/1996 03:59:59PM	09/15/96

SHIP_DATE	RETURN_VALUE
05/17/2003 12:13:14AM	05/17/03

You can also use the format string SSSSS in a TO_CHAR expression. For example, the following expression converts the dates in the SHIP_DATE column to strings representing the total seconds since midnight:

```
TO_CHAR( SHIP_DATE, 'SSSSS')
```

SHIP_DATE	RETURN_VALUE
12/31/1999 01:02:03AM	3783
09/15/1996 03:59:59PM	86399

In TO_CHAR expressions, the YY format string produces the same results as the RR format string.

The following expression converts dates to strings in the format MM/DD/YY:

```
TO_CHAR( SHIP_DATE, 'MM/DD/YY')
```

SHIP_DATE	RETURN_VALUE
12/31/1999 01:02:03AM	12/31/99
09/15/1996 03:59:59PM	09/15/96
05/17/2003 12:13:14AM	05/17/03

The following expression returns the week of the month for each date in a column:

```
TO_CHAR( DATE_PROMISED, 'W' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10AM	'01'
02-22-1997 01:31:10AM	'04'
10-24-1997 02:12:30PM	'04'
NULL	NULL

The following expression returns the week of the year for each date in a column:

```
TO_CHAR( DATE_PROMISED, 'WW' )
```

DATE_PROMISED	RETURN VALUE
04-01-1997 12:00:10PM	'18'
02-22-1997 01:31:10AM	'08'
10-24-1997 02:12:30AM	'43'
NULL	NULL

Tip

You can combine TO_CHAR and TO_DATE to convert a numeric value for a month into the text value for a month using a function such as:

```
TO_CHAR( TO_DATE( numeric_month, 'MM' ), 'MONTH' )
```

TO_CHAR (Numbers)

Converts numeric values to text strings. TO_CHAR also converts dates to strings.

TO_CHAR converts numeric values to text strings as follows:

- Converts double values to strings of up to 16 digits and provides accuracy up to 15 digits. If you pass a number with more than 15 digits, TO_CHAR rounds the number to the sixteenth digit.
- Returns decimal notation for numbers in the ranges (-1e16,-1e-16] and [1e-16, 1e16). TO_CHAR returns scientific notation for numbers outside these ranges.

Note: Data Integration converts the values 1e-16 and -1e16 to scientific notation, but returns the values 1e-16 and -1e-16 in decimal notation.

Syntax

```
TO_CHAR( numeric_value )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. The numeric value you want to convert to a string. You can enter any valid expression.

Return Value

String.

NULL if a value passed to the function is NULL.

Example

The following expression converts the values in the SALES column to text:

```
TO_CHAR( SALES )
```

SALES	RETURN VALUE
1010.99	'1010.99'
-15.62567	'-15.62567'
10842764968208837340	'1.084276496820884e+019' (rounded to 16th digit)
1.234567890123456789e-10	'0.0000000001234567890123457' (greater than 1e-16 but less than 1e16)
1.23456789012345e17	'1.23456789012345e17' (greater than 1e16)
0	'0'

SALES	RETURN VALUE
33.15	'33.15'
NULL	NULL

TO_DATE

Converts a character string to a date datatype in the same format as the character string. You use the TO_DATE format strings to specify the format of the source strings.

The target column must be date/time for TO_DATE expressions.

If you are converting two-digit years with TO_DATE, use either the RR or YY format string. Do not use the YYYY format string.

Syntax

```
TO_DATE( string [, format] )
```

Argument	Required/Optional	Description
<i>string</i>	Required	Must be a string datatype. Passes the values that you want to convert to dates. You can enter any valid expression.
<i>format</i>	Optional	Enter a valid TO_DATE format string. The format string must match the parts of the <i>string</i> argument. For example, if you pass the string 'Mar 15 1998 12:43:10AM', you must use the format string 'MON DD YYYY HH12:MI:SSAM'. If you omit the format string, the string value must be in the default date of MM/DD/YYYY HH24:MI:SS. For more information about TO_DATE format strings, see "TO_DATE and IS_DATE format strings" on page 26 .

Return Value

Date.

TO_DATE always returns a date and time. If you pass a string that does not have a time value, the date returned always includes the time 00:00:00. You can map the results of this function to any target column with a date datatype.

NULL if you pass a null value to this function.

Warning: The format of the TO_DATE string must match the format string including any date separators. If it does not, Data Integration might return inaccurate values or skip the row.

Example

The following expression returns date values for the strings in the DATE_PROMISED column. TO_DATE always returns a date and time. If you pass a string that does not have a time value, the date returned always

includes the time 00:00:00. If you run a session in the twentieth century, the century will be 19. The current year on the machine running Data Integration is 1998:

```
TO_DATE( DATE_PROMISED, 'MM/DD/YY' )
```

DATE_PROMISED	RETURN VALUE
'01/22/98'	Jan 22 1998 00:00:00
'05/03/98'	May 3 1998 00:00:00
'11/10/98'	Nov 10 1998 00:00:00
'10/19/98'	Oct 19 1998 00:00:00
NULL	NULL

The following expression returns date and time values for the strings in the DATE_PROMISED column. If you pass a string that does not have a time value, Data Integration writes the row into the error rows file. If you run a session in the twentieth century, the century will be 19. The current year on the machine running Data Integration is 1998:

```
TO_DATE( DATE_PROMISED, 'MON DD YYYY HH12:MI:SSAM' )
```

DATE_PROMISED	RETURN VALUE
'Jan 22 1998 02:14:56PM'	Jan 22 1998 02:14:56PM
'Mar 15 1998 11:11:11AM'	Mar 15 1998 11:11:11AM
'Jun 18 1998 10:10:10PM'	Jun 18 1998 10:10:10PM
'October 19 1998'	None. Data Integration writes the row into the error rows file.
NULL	NULL

The following expression converts strings in the SHIP_DATE_MJD_STRING column to date values in the default date format:

```
TO_DATE( SHIP_DATE_MJD_STR, 'J' )
```

SHIP_DATE_MJD_STR	RETURN_VALUE
'2451544'	Dec 31 1999 00:00:00
'2415021'	Jan 1 1900 00:00:00

Because the J format string does not include the time portion of a date, the return values have the time set to 00:00:00.

The following expression converts a string to a four-digit year format. The current year is 1998:

```
TO_DATE( DATE_STR, 'MM/DD/RR' )
```

DATE_STR	RETURN VALUE
'04/01/98'	04/01/1998 00:00:00
'08/17/05'	08/17/2005 00:00:00

The following expression converts a string to a four-digit year format. The current year is 1998:

```
TO_DATE( DATE_STR, 'MM/DD/YY')
```

DATE_STR	RETURN VALUE
'04/01/98'	04/01/1998 00:00:00
'08/17/05'	08/17/1905 00:00:00

Note: For the second row, RR returns the year 2005 and YY returns the year 1905.

The following expression converts a string to a four-digit year format. The current year is 1998:

```
TO_DATE( DATE_STR, 'MM/DD/Y')
```

DATE_STR	RETURN VALUE
'04/01/8'	04/01/1998 00:00:00
'08/17/5'	08/17/1995 00:00:00

The following expression converts a string to a four-digit year format. The current year is 1998:

```
TO_DATE( DATE_STR, 'MM/DD/YYYY')
```

DATE_STR	RETURN VALUE
'04/01/998'	04/01/1998 00:00:00
'08/17/995'	08/17/1995 00:00:00

The following expression converts strings that includes the seconds since midnight to date values:

```
TO_DATE( DATE_STR, 'MM/DD/YYYY SSSS')
```

DATE_STR	RETURN VALUE
'12/31/1999 3783'	12/31/1999 01:02:03
'09/15/1996 86399'	09/15/1996 23:59:59

If the target accepts different date formats, use TO_DATE and IS_DATE with the DECODE function to test for acceptable formats. For example:

```
DECODE( TRUE,
  --test first format
  IS_DATE( CLOSE_DATE, 'MM/DD/YYYY HH24:MI:SS' ),
  --if true, convert to date
  TO_DATE( CLOSE_DATE, 'MM/DD/YYYY HH24:MI:SS' ),
  --test second format; if true, convert to date
  IS_DATE( CLOSE_DATE, 'MM/DD/YYYY' ), TO_DATE( CLOSE_DATE, 'MM/DD/YYYY' ),
  --test third format; if true, convert to date
  IS_DATE( CLOSE_DATE, 'MON DD YYYY' ), TO_DATE( CLOSE_DATE, 'MON DD YYYY' ),
  --if none of the above
  ERROR( 'NOT A VALID DATE' ) )
```

You can combine TO_CHAR and TO_DATE to convert a numeric value for a month into the text value for a month using a function such as:

```
TO_CHAR( TO_DATE( numeric_month, 'MM' ), 'MONTH' )
```

TO_DECIMAL

Converts a string or numeric value to a decimal value. TO_DECIMAL ignores leading spaces.

Syntax

```
TO_DECIMAL( value [, scale] )
```

Argument	Required/ Optional	Description
value	Required	Must be a string or numeric datatype. Passes the values you want to convert to decimals. You can enter any valid expression.
scale	Required or Optional	Must be an integer literal between 0 and 28, inclusive. Specifies the number of digits allowed after the decimal point. If you omit this argument, the function returns a value with the same scale as the input value.

Return Value

Decimal of precision and scale between 0 and 28, inclusive.

0 if the value in the selected column is an empty string or a non-numeric character.

NULL if a value passed to the function is NULL.

Example

This expression uses values from the column IN_TAX. The data type is decimal with precision of 10 and scale of 3:

```
TO_DECIMAL( IN_TAX, 3 )
```

IN_TAX	RETURN VALUE
'15.6789'	15.679
'60.2'	60.200
'118.348'	118.348
NULL	NULL
'A12.3Grove'	0

TO_FLOAT

Converts a string or numeric value to a double-precision floating point number (the Double datatype). TO_FLOAT ignores leading spaces.

Syntax

```
TO_FLOAT( value )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	Must be a string or numeric datatype. Passes the values you want to convert to double values. You can enter any valid expression.

Return Value

Double value.

0 if the value in the column is blank or a non-numeric character.

NULL if a value passed to this function is NULL.

Example

This expression uses values from the column IN_TAX:

```
TO_FLOAT( IN_TAX )
```

IN_TAX	RETURN VALUE
'15.6789'	15.6789
'60.2'	60.2
'118.348'	118.348
NULL	NULL
'A12.3Grove'	0

TO_INTEGER

Converts a string or numeric value to an integer. TO_INTEGER syntax contains an optional argument that you can choose to round the number to the nearest integer or truncate the decimal portion. TO_INTEGER ignores leading spaces.

Syntax

```
TO_INTEGER( value [, flag] )
```

Argument	Required/ Optional	Description
<i>value</i>	Required	String or numeric datatype. Passes the value you want to convert to an integer. You can enter any valid expression.
<i>flag</i>	Optional	Specifies whether to truncate or round the decimal portion. The flag must be an integer literal or the constants TRUE or FALSE: <ul style="list-style-type: none">- TO_INTEGER truncates the decimal portion when the flag is TRUE or a number other than 0.- TO_INTEGER rounds the value to the nearest integer if the flag is FALSE or 0 or if you omit this argument.

Return Value

Integer.

NULL if the value passed to the function is NULL.

0 if the value passed to the function contains alphanumeric characters.

Example

The following expressions use values from the column IN_TAX:

```
TO_INTEGER( IN_TAX, TRUE )
```

IN_TAX	RETURN VALUE
'15.6789'	15
'60.2'	60
'118.348'	118
NULL	NULL
'A12.3Grove'	0
' 123.87'	123
'-15.6789'	-15
'-15.23'	-15

```
TO_INTEGER( IN_TAX, FALSE)
```

IN_TAX	RETURN VALUE
'15.6789'	16
'60.2'	60
'118.348'	118
NULL	NULL

IN_TAX	RETURN VALUE
'A12.3Grove'	0
' 123.87'	124
'-15.6789'	-16
'-15.23'	-15

TRUNC (Dates)

Truncates dates to a specific year, month, day, hour, or minute. You can also use TRUNC to truncate numbers.

You can truncate the following date parts:

- **Year.** If you truncate the year portion of the date, the function returns Jan 1 of the input year with the time set to 00:00:00. For example, the expression `TRUNC(6/30/1997 2:30:55, 'YY')` returns 1/1/1997 00:00:00, and `TRUNC(12/1/1997 3:10:15, 'YY')` returns 1/1/1997 00:00:00.
- **Month.** If you truncate the month portion of a date, the function returns the first day of the month with the time set to 00:00:00. For example, the expression `TRUNC(4/15/1997 12:15:00, 'MM')` returns 4/1/1997 00:00:00, and `TRUNC(4/30/1997 3:15:46, 'MM')` returns 4/1/1997 00:00:00.
- **Day.** If you truncate the day portion of a date, the function returns the date with the time set to 00:00:00. For example, the expression `TRUNC(6/13/1997 2:30:45, 'DD')` returns 6/13/1997 00:00:00, and `TRUNC(12/13/1997 22:30:45, 'DD')` returns 12/13/1997 00:00:00.
- **Hour.** If you truncate the hour portion of a date, the function returns the date with the minutes and seconds set to 0. For example, the expression `TRUNC(4/1/1997 11:29:35, 'HH')` returns 4/1/1997 11:00:00, and `TRUNC(4/1/1997 13:39:00, 'HH')` returns 4/1/1997 13:00:00.
- **Minute.** If you truncate the minute portion of a date, the function returns the date with the seconds set to 0. For example, the expression `TRUNC(5/22/1997 10:15:29, 'MI')` returns 5/22/1997 10:15:00, and `TRUNC(5/22/1997 10:18:30, 'MI')` returns 5/22/1997 10:18:00.

Syntax

```
TRUNC( date [,format] )
```

Argument	Required/Optional	Description
<i>date</i>	Required	Date/Time datatype. The date values you want to truncate. You can enter any valid expression that evaluates to a date.
<i>format</i>	Optional	Enter a valid format string. The format string is not case sensitive. If you omit the format string, the function truncates the time portion of the date, setting it to 00:00:00.

Return Value

Date.

NULL if a value passed to the function is NULL.

Example

The following expressions truncate the year portion of dates in the DATE_SHIPPED column:

```
TRUNC( DATE_SHIPPED, 'Y' )  
TRUNC( DATE_SHIPPED, 'YY' )  
TRUNC( DATE_SHIPPED, 'YYY' )  
TRUNC( DATE_SHIPPED, 'YYYY' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 1 1998 12:00:00AM
Apr 19 1998 1:31:20PM	Jan 1 1998 12:00:00AM
Jun 20 1998 3:50:04AM	Jan 1 1998 12:00:00AM
Dec 20 1998 3:29:55PM	Jan 1 1998 12:00:00AM
NULL	NULL

The following expressions truncate the month portion of each date in the DATE_SHIPPED column:

```
TRUNC( DATE_SHIPPED, 'MM' )  
TRUNC( DATE_SHIPPED, 'MON' )  
TRUNC( DATE_SHIPPED, 'MONTH' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 1 1998 12:00:00AM
Apr 19 1998 1:31:20PM	Apr 1 1998 12:00:00AM
Jun 20 1998 3:50:04AM	Jun 1 1998 12:00:00AM
Dec 20 1998 3:29:55PM	Dec 1 1998 12:00:00AM
NULL	NULL

The following expressions truncate the day portion of each date in the DATE_SHIPPED column:

```
TRUNC( DATE_SHIPPED, 'D' )  
TRUNC( DATE_SHIPPED, 'DD' )  
TRUNC( DATE_SHIPPED, 'DDD' )  
TRUNC( DATE_SHIPPED, 'DY' )  
TRUNC( DATE_SHIPPED, 'DAY' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 15 1998 12:00:00AM
Apr 19 1998 1:31:20PM	Apr 19 1998 12:00:00AM
Jun 20 1998 3:50:04AM	Jun 20 1998 12:00:00AM
Dec 20 1998 3:29:55PM	Dec 20 1998 12:00:00AM
Dec 31 1998 11:59:59PM	Dec 31 1998 12:00:00AM
NULL	NULL

The following expressions truncate the hour portion of each date in the DATE_SHIPPED column:

```
TRUNC( DATE_SHIPPED, 'HH' )  
TRUNC( DATE_SHIPPED, 'HH12' )  
TRUNC( DATE_SHIPPED, 'HH24' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:31AM	Jan 15 1998 2:00:00AM
Apr 19 1998 1:31:20PM	Apr 19 1998 1:00:00PM
Jun 20 1998 3:50:04AM	Jun 20 1998 3:00:00AM
Dec 20 1998 3:29:55PM	Dec 20 1998 3:00:00PM
Dec 31 1998 11:59:59PM	Dec 31 1998 11:00:00AM
NULL	NULL

The following expression truncates the minute portion of each date in the DATE_SHIPPED column:

```
TRUNC( DATE_SHIPPED, 'MI' )
```

DATE_SHIPPED	RETURN VALUE
Jan 15 1998 2:10:30AM	Jan 15 1998 2:10:00AM
Apr 19 1998 1:31:20PM	Apr 19 1998 1:31:00PM
Jun 20 1998 3:50:04AM	Jun 20 1998 3:50:00AM
Dec 20 1998 3:29:55PM	Dec 20 1998 3:29:00PM
Dec 31 1998 11:59:59PM	Dec 31 1998 11:59:00PM
NULL	NULL

TRUNC (Numbers)

Truncates numbers to a specific digit. You can also use TRUNC to truncate dates.

Syntax

```
TRUNC( numeric_value [, precision] )
```

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric datatype. Passes the values you want to truncate. You can enter any valid expression that evaluates to a Numeric datatype.
<i>precision</i>	Optional	Can be a positive or negative integer. You can enter any valid expression that evaluates to an integer. The integer specifies the number of digits to truncate.

If *precision* is a positive integer, TRUNC returns *numeric_value* with the number of decimal places specified by *precision*. If *precision* is a negative integer, TRUNC changes the specified digits to the left of the decimal point to zeros. If you omit the *precision* argument, TRUNC truncates the decimal portion of *numeric_value* and returns an integer.

If you pass a decimal *precision* value, Data Integration rounds *numeric_value* to the nearest integer before evaluating the expression.

Return Value

Numeric value.

NULL if one of the arguments is NULL.

Example

The following expressions truncate the values in the PRICE column:

```
TRUNC( PRICE, 3 )
```

PRICE	RETURN VALUE
12.9995	12.999
-18.8652	-18.865
56.9563	56.956
15.9928	15.992
NULL	NULL

```
TRUNC( PRICE, -1 )
```

PRICE	RETURN VALUE
12.99	10.0
-187.86	-180.0
56.95	50.0
1235.99	1230.0
NULL	NULL

```
TRUNC( PRICE )
```

PRICE	RETURN VALUE
12.99	12.0
-18.99	-18.0
56.95	56.0
15.99	15.0
NULL	NULL

UPPER

Converts lowercase string characters to uppercase.

Syntax

```
UPPER( string )
```

Argument	Required/ Optional	Description
<i>string</i>	Required	String datatype. Passes the values you want to change to uppercase text. You can enter any valid expression.

Return Value

Uppercase string. If the data contains multibyte characters, the return value depends on the code page of the Secure Agent that runs the task.

NULL if a value passed to the function is NULL.

Example

The following expression changes all names in the FIRST_NAME column to uppercase:

```
UPPER( FIRST_NAME )
```

FIRST_NAME	RETURN VALUE
Ramona	RAMONA
NULL	NULL
THOMAS	THOMAS
PierRe	PIERRE
Bernice	BERNICE

VARIANCE

Returns the variance of a value you pass to it. VARIANCE is used to analyze statistical data.

You can nest only one other aggregate function within VARIANCE, and the nested function must return a numeric data type.

Use only in mapping tasks.

Syntax

VARIANCE(*numeric_value* [, *filter_condition*])

Argument	Required/ Optional	Description
<i>numeric_value</i>	Required	Numeric data type. Passes the values for which you want to calculate a variance. You can enter any valid transformation expression.
<i>filter_condition</i>	Optional	Limits the rows in the search. The filter condition must be a numeric value or evaluate to TRUE, FALSE, or NULL. You can enter any valid transformation expression.

Formula

The function uses the following formula to calculate the variance:

$$\frac{\sum_{i=1}^n x_i^2 - \frac{1}{n} \left[\sum_{i=1}^n x_i \right]^2}{n - 1}$$

Use the following guidelines for this formula:

- *x_i* is one of the numeric values.
- *n* is the number of elements in the set of numeric values. If *n* is 1, the variance is 0.

Return Value

Double value.

NULL if all values passed to the function are NULL or if no rows are selected (for example, the *filter_condition* evaluates to FALSE or NULL for all rows).

Nulls

If a single value is NULL, VARIANCE ignores it. However, if all values passed to the function are NULL or if no rows are selected, VARIANCE returns NULL.

Group By

VARIANCE groups values based on group by fields you define in the transformation, returning one result for each group.

If there is not a group by field, VARIANCE treats all rows as one group, returning one value.

Example

The following expression calculates the variance of all rows in the TOTAL_SALES field:

```
VARIANCE( TOTAL_SALES )
```

TOTAL_SALES
2198.0
2256.0
3001.0

TOTAL_SALES

NULL

8953.0

RETURN VALUE: 10592444.6666667

CHAPTER 6

System variables

System variables return system values that change, such as the current task and run ID.

CurrentMappingName

Returns the name of the mapping that the task is based on as a string value. Use `CurrentMappingName` with any function that accepts string datatypes.

Data Integration resolves `CurrentMappingName` when you run a task. It does not resolve `CurrentMappingName` when you test run a mapping. If you want to run a mapping and return the current mapping name, use `CurrentTaskName`.

CurrentRunId

Each task run has a unique ID. `CurrentRunId` returns the system generated run ID for the mapping task as a string value. Use `CurrentRunId` with any function that accepts string datatypes.

CurrentTaskName

Returns the task name as a string value. Use `CurrentTaskName` with any function that accepts string datatypes. Also returns the mapping name in a mapping run.

SESSSTARTTIME

Returns the current date and time on the agent that runs the job.

`SESSSTARTTIME` is stored as a transformation date/time data type value. Use `SESSSTARTTIME` with any function that accepts transformation date/time data types. You can use `SESSSTARTTIME` only within the expression language.

SYSDATE

Returns the agent system date and time for each row that passes through the transformation.

SYSDATE is stored as a transformation date/time datatype variable.

To return a static date and time, use the SESSSTARTTIME variable.

CHAPTER 7

Datatype reference

This chapter includes the following topics:

- [Datatype reference overview, 196](#)
- [Rules and guidelines for datatypes, 197](#)
- [Transformation datatypes, 197](#)

Datatype reference overview

When you create a mapping or task, you create a set of instructions for Data Integration to read data from a source and write it to a target. Data Integration transforms data based on the data flow and the datatype assigned to each field.

Data Integration uses the following types of datatypes:

Native datatypes

Native datatypes are specific to sources, targets, and lookup objects in a mapping or task. In a mapping, native datatypes appear in the sources, targets, and lookup objects.

Transformation datatypes

Transformation datatypes are internal datatypes that appear in all transformations in a mapping. They are based on ANSI SQL-92 generic datatypes. Data Integration uses transformation datatypes to move data across platforms.

In tasks that move data without transforming it, Data Integration converts the native datatypes from the source to the comparable native datatypes in the target. In mappings and mapping tasks, Data Integration converts the native datatypes from the source to the comparable transformation datatypes before it starts transforming the data. When Data Integration writes to a target, it converts the transformation datatypes to the comparable native datatypes.

When you specify a multibyte character set, the datatypes allocate additional space in the database to store characters of up to three bytes.

Rules and guidelines for datatypes

Use the following rules and guidelines for datatypes and conversion:

- The default datatype for all fields in flat files is Nstring(255).
If you need to change a datatype, use the **Edit Metadata** option to edit the native type or precision for the field.
- The task may have unexpected results if you map incompatible datatypes between source and target fields or between the output of an expression and a target field.
- Numeric data with a precision greater than 28 is truncated to a precision of 15 when written to a target.
For example, 4567823451237864532451.12345678 might be written to the target as 4567823451237864000000.00000000.
- For an Oracle source or target, the precision of a Number field must be greater than or equal to the scale. Otherwise, the task fails.
- When you use an ODBC connection for an Oracle database target, ensure that the maximum precision for an Oracle table column does not exceed the following values: char(1999), varchar(3999), nvarchar(3998), and nchar(3998).
- A task may load corrupt data into the target if the data comes from a source field of the Real datatype from Microsoft SQL Server.

Transformation datatypes

The following table describes the transformation datatypes:

Datatype	Size in bytes	Description
Bigint	8 bytes	-9,223,372,036,854,775,808 to 9,223,372,036,854,775,807 Precision of 19, scale of 0 Integer value.
Binary	Precision	1 to 104,857,600 bytes You cannot use binary data for flat file sources.
Date/Time	16 bytes	Jan 1, 0001 A.D. to Dec 31, 9999 A.D. Precision of 29, scale of 9 (precision to the nanosecond) Combined date/time value.
Decimal	8 bytes (if high precision is off or precision is greater than 28) 16 bytes (if precision <= 18 and high precision is on) 20 bytes (if precision > 18 and <= 28)	Decimal value with declared precision and scale. Scale must be less than or equal to precision. Precision 1 to 28 digits, scale 0 to 28

Datatype	Size in bytes	Description
Double	8 bytes	Double-precision floating-point numeric value. You can edit the precision and scale. The scale must be less than or equal to the precision.
Integer	4 bytes	-2,147,483,648 to 2,147,483,647 Precision of 10, scale of 0 Integer value.
Nstring	Unicode mode: (precision + 1) * 2 ASCII mode: precision + 1	1 to 104,857,600 characters Fixed-length or varying-length string.
Ntext	Unicode mode: (precision + 1) * 2 ASCII mode: precision + 1	1 to 104,857,600 characters Fixed-length or varying-length string.
Real	8 bytes	Precision of 7, scale of 0 Double-precision floating-point numeric value.
Small Integer	4 bytes	-32,768 and 32,767 Precision of 5, scale of 0 Integer value.
String	Unicode mode: (precision + 1) * 2 ASCII mode: precision + 1	1 to 104,857,600 characters Fixed-length or varying-length string.
Text	Unicode mode: (precision + 1) * 2 ASCII mode: precision + 1	1 to 104,857,600 characters Fixed-length or varying-length string.

Integer datatypes

You can pass integer data from sources to targets and perform transformations on integer data. Data Integration supports Bigint, Integer, and Small Integer datatypes.

The transformation integer datatypes represent exact values.

Integer values in calculations

When you use integer values in calculations, Data Integration sometimes converts integer values to floating-point numbers before it performs the calculation.

For example, to evaluate `MOD(12.00, 5)`, Data Integration converts the integer value "5" to a floating-point number before it performs the division operation. Data Integration converts integer values to double or decimal values depending on how you set the **Enable High Precision** advanced session property in the mapping task.

Data Integration converts integer values in the following arithmetic operations:

Operation	High Precision Disabled	High Precision Enabled
Functions and calculations that cannot introduce decimal points. For example, integer addition, subtraction, and multiplication, and functions such as CUME and SUM.	No conversion. However, if the calculation produces a result that is out of range, Data Integration writes a row error.	Decimal
Non-scientific functions and calculations that can introduce decimal points. For example, integer division, and functions such as AVG, MEDIAN, and PERCENTILE.	Double	Decimal
All scientific functions and the EXP, LN, LOG, POWER, and SQRT functions.	Double	Double

The transformation Double datatype supports precision of up to 15 digits, while the Bigint datatype supports precision of up to 19 digits. Therefore, precision loss can occur in calculations that produce Bigint values with precision of more than 15 digits.

For example, an expression transformation contains the following calculation:

```
POWER( BIGINTVAL, EXPVAL )
```

Before it performs the calculation, Data Integration converts the inputs to the POWER function to double values. If the BIGINTVAL field contains the Bigint value 9223372036854775807, Data Integration converts this value to 9.22337203685478e+18, losing the last 4 digits of precision. If the EXPVAL field contains the value 1.0 and the result field is a Bigint, the calculation produces a row error because the result, 9223372036854780000, exceeds the maximum Bigint value.

When you use an Integer datatype in a calculation that can produce decimal values and you enable high precision, Data Integration converts the integer values to decimal values.

For transformations that support the Decimal datatype with precision up to 28 digits, precision loss does not occur in a calculation unless the result produces a value with precision greater than 28 digits in high precision mode. In this case, Data Integration stores the result as a double. If the field precision is less than or equal to 28 digits and the result produces a value greater than 28 digits in high precision mode, Data Integration rejects the row.

Integer constants in expressions

Data Integration interprets constants in an expression as floating-point values, even if the calculation produces an integer result.

For example, in the expression `INTVALUE + 1000`, Data Integration converts the integer value "1000" to a double value if high precision is not enabled. It converts the value 1000 to a decimal value if high precision is enabled. To process the value 1000 as an integer value, create a variable field with an Integer datatype to hold the constant, and modify the expression to add the two fields.

NaN values

NaN (Not a Number) is a value that is usually returned as the result of an operation on invalid input operands, especially in floating-point calculations. For example, when an operation attempts to divide zero by zero, it returns a NaN result.

Operating systems and programming languages may represent NaN differently. For example, the following list shows valid string representations of NaN:

```
nan
NaN
NaN%
NAN
NaNQ
NaNS
qNaN
sNaN
1.#QNAN
1.#SNAN
```

Data Integration converts QNAN values to 1.#QNAN on Win64EMT platforms. 1.#QNAN is a valid representation of NaN.

Convert string values to integer values

When Data Integration performs implicit conversion of a string value to an integer value, it truncates the data at the first non-numeric character.

For example, you link a string field that contains the value "9,000,000,000,000,000.777" to a Bigint field. Data Integration converts the string to the Bigint value 9,000,000,000,000,000.

Binary datatype

If a mapping includes binary data, set the precision for the transformation binary datatype so that Data Integration can allocate enough memory to move the data from source to target.

You cannot use binary datatypes for flat file sources.

Date/Time data type

The Date/Time data type handles years from 1 A.D. to 9999 A.D. in the Gregorian calendar system. Years beyond 9999 A.D. cause an error. Mappings process Date/Time data types in complex file formats such as Parquet, Avro, and ORC using the local time zone of the Secure Agent machine.

The Date/Time data type supports dates with precision to the nanosecond. The data type has a precision of 29 and a scale of 9. Some native data types have a smaller precision. When you import a source that contains datetime values, the import process imports the correct precision from the source column. For example, the Microsoft SQL Server Datetime data type has a precision of 23 and a scale of 3. When you import a Microsoft SQL Server source that contains Datetime values, the Datetime columns in the mapping source have a precision of 23 and a scale of 3.

Data Integration reads datetime values from the source to the precision specified in the mapping source. When Data Integration transforms the datetime values, it supports precision up to 29 digits. For example, if

you import a datetime value with precision to the millisecond, you can use the `ADD_TO_DATE` function in an Expression transformation to add nanoseconds to the date.

If you write a Date/Time value to a target column that supports a smaller precision, Data Integration truncates the value to the precision of the target column. If you write a Date/Time value to a target column that supports a larger precision, Data Integration inserts zeroes in the unsupported portion of the datetime value.

Decimal and double data types

You can pass decimal and double data from sources to targets and perform transformations on decimal and double data.

Data Integration supports the following data types:

Decimal

Precision 1 to 28 digits, scale 0 to 28. You cannot use decimal values with scale greater than precision or a negative precision. Transformations display any range that you assign to a decimal data type, but Data Integration supports precision only up to 28 digits.

When you enable high precision and the field precision is greater than 28 digits, Data Integration stores the result as a double.

Double

Double-precision floating-point numeric value.

You can edit the precision and scale. The scale must be less than or equal to the precision.

Decimal and double values in calculations

Precision loss can occur with decimal and double data types in a calculation when the result produces a value with a precision greater than the maximum.

If you disable high precision, Data Integration converts decimal values to double. Precision loss occurs if the decimal value has a precision greater than 15 digits. For example, you have a mapping with decimal (20,0) that passes the number 40012030304957666903. If you disable high precision, Data Integration converts the decimal value to double and passes $4.00120303049577 \times 10^{19}$.

For transformations that support decimal data type of precision up to 28 digits, use the decimal data type and enable high precision to ensure precision of up to 28 digits.

Precision loss does not occur in a calculation unless the result produces a value with precision greater than the maximum allowed digits. In this case, Data Integration stores the result as a double.

Do not use the double data type for data that you use in an equality condition, such as a lookup or join condition.

The following table lists how Data Integration handles decimal values based on how the **Enable High Precision** advanced session property is set:

Field Data type	Precision	High Precision Disabled	High Precision Enabled
Decimal	0 to 15	Decimal	Decimal
Decimal	15 to 28	Double	Decimal
Decimal	Over 28	Double	Double

When you enable high precision, Data Integration converts numeric constants in any expression function to decimal. If you do not enable high precision, Data Integration converts numeric constants to double.

You can ensure the maximum precision for numeric values greater than 28 or 38 digits depending on the transformation. Before you perform any calculations or transformations with the transformation functions, truncate or round any large numbers.

Rounding methods for double values

Due to differences in system run-time libraries and the computer system where the database processes double datatype calculations, the results may not be as expected. To provide calculation results that are less susceptible to platform differences, Data Integration stores the 15 significant digits of double datatype values.

The double datatype conforms to the IEEE 794 standard. Changes to database client library, different versions of a database or changes to a system run-time library affect the binary representation of mathematically equivalent values. Also, many system run-time libraries implement the round-to-even or the symmetric arithmetic method. The round-to-even method states that if a number falls midway between the next higher or lower number it round to the nearest value with an even least significant bit. For example, with the round-to-even method, 0.125 is rounded to 0.12. The symmetric arithmetic method rounds the number to next higher digit when the last digit is 5 or greater. For example, with the symmetric arithmetic method 0.125 is rounded to 0.13 and 0.124 is rounded to 0.12.

Data Integration stores the 15 significant digits of double datatype values. For example, if a calculation on Windows returns the number 1234567890.1234567890, and the same calculation on UNIX returns 1234567890.1234569999, Data Integration converts this number to 1234567890.1234600000.

String datatypes

The transformation string datatypes include Nstring, Ntext, String and Text. Although the Nstring, Ntext, String, and Text datatypes support the same precision up to 104,857,600 characters, Data Integration uses String to move string data from source to target and Text to move text data from source to target.

Because some databases store text data differently than string data, Data Integration needs to distinguish between the two types of character data. If the source displays String, set the target column to String. Likewise, if the source displays Text, set the target column to Text, Long, or Long Varchar, depending on the source.

In general, the smaller string datatypes, such as Char and Varchar, display as String in the source, Lookup transformation, and SQL transformation, while the larger text datatypes, such as Text, Long, and Long Varchar, display as Text in the source.

Use Nstring, Ntext, String, and Text interchangeably within transformations. However, in the source, Lookup transformation, and SQL transformation, the target datatypes must match. The database drivers need to match the string datatypes with the transformation datatypes, so that the data passes accurately. For example, Nchar in a lookup table must match Nstring in the Lookup transformation.

INDEX

%OPR_CONCAT% function
description [49](#)
%OPR_CONCATDELIM% function
description [50](#)
%OPR_IIF% function
description [51](#)
%OPR_SUM% function
description [52](#)

A

ABORT function
description [53](#)
ABS function
description [53](#)
absolute values
obtaining [53](#)
ADD_TO_DATE function
description [54](#)
Advanced Encryption Standard algorithm
description [58–60](#)
AES_DECRYPT function
description [57](#)
AES_ENCRYPT function
description [58](#)
AES_GCM_DECRYPT function
description [59](#)
AES_GCM_ENCRYPT function
description [60](#)
aggregate functions
AVG [62](#)
COUNT [71](#)
FIRST [84](#)
LAST [103](#)
MAX (dates) [113](#)
MAX (numbers) [114](#)
MAX (string) [116](#)
MEDIAN [118](#)
MIN (dates) [123](#)
MIN (numbers) [124, 125](#)
PERCENTILE [131](#)
STDDEV [166](#)
SUM [170](#)
usage [31](#)
VARIANCE [191](#)
arithmetic
date/time values [29](#)
arithmetic operators
description [14](#)
using strings in expressions [14](#)
using to convert data [14](#)
ASCII
CHR function [65](#)
ASCII function
description [61](#)

averages
returning [128](#)
AVG function
description [62](#)

B

bigint
converting values to [174](#)

C

calendars
date types supported [19](#)
capitalization
strings [94, 109, 191](#)
case
converting to uppercase [191](#)
CEIL function
description [63](#)
character strings
converting from dates [176](#)
converting to dates [181](#)
characters
adding to strings [110, 153](#)
capitalization [94, 109, 191](#)
counting [168](#)
encoding [119, 164](#)
removing from strings [111, 154](#)
replacing multiple [145](#)
replacing one [142](#)
returning number [106](#)
CHOOSE function
description [64](#)
CHR function
description [65](#)
inserting single quotation marks [65](#)
CHRCODE function
description [66](#)
Cloud Application Integration community
URL [8](#)
Cloud Developer community
URL [8](#)
COBOL syntax
converting to perl syntax [137](#)
comparison operators
comparing hierarchical fields [16](#)
description [16](#)
using strings in expressions [16](#)
COMPRESS function
description [67](#)
compression
compressing data [67](#)
decompressing data [81](#)

- CONCAT function
 - description [67](#)
 - inserting single quotation marks using [67](#)
- concatenating strings [49](#), [50](#), [67](#)
- constants
 - FALSE [11](#)
 - NULL [11](#)
 - TRUE [12](#)
- conversion functions
 - description [33](#)
 - TO_CHAR (dates) [176](#)
 - TO_CHAR (numbers) [180](#)
 - TO_DATE [181](#)
 - TO_DECIMAL [184](#)
 - TO_FLOAT [184](#)
 - TO_INTEGER [185](#)
- CONVERT_BASE function
 - description [69](#)
- converting date strings [20](#)
- COS function
 - description [69](#)
- COSH function
 - description [70](#)
- cosine
 - calculating [69](#)
 - calculating hyperbolic cosine [70](#)
- COUNT function
 - description [71](#)
- CRC32 function
 - description [73](#)
- CUME function
 - description [74](#)

D

- data cleansing functions
 - description [33](#)
 - GREATEST [89](#)
 - IN [92](#)
 - LEAST [105](#)
 - METAPHONE [119](#)
 - REG_EXTRACT [137](#)
 - REG_MATCH [139](#)
 - REG_REPLACE [141](#)
 - SOUNDEX [164](#)
- Data Integration community
 - URL [8](#)
- data types
 - date/time data type [200](#)
 - decimal data types [201](#)
 - decimal values in calculations [201](#)
 - double data types [201](#)
 - double values in calculations [201](#)
- databases
 - dates [21](#)
- datatypes
 - binary datatype [200](#)
 - Date/Time [18](#)
 - integer constants in expressions [199](#)
 - integer datatypes [198](#)
 - integer values in calculations [198](#)
 - NaN values [200](#)
 - overview [196](#)
 - rounding for double values [202](#)
 - rules and guidelines [197](#)

- datatypes (*continued*)
 - string datatypes [202](#)
 - string to integer conversion [200](#)
 - transformation datatypes [197](#)
- date functions
 - ADD_TO_DATE [54](#)
 - DATE_COMPARE [75](#)
 - DATE_DIFF [76](#)
 - GET_DATE_PART [87](#)
 - LAST_DAY [104](#)
 - MAKE_DATE_TIME [112](#)
 - MAX (dates) [113](#)
 - ROUND [148](#)
 - SET_DATE_PART [155](#)
 - SYSTIMESTAMP [171](#)
 - TRUNC (Dates) [187](#)
- DATE_COMPARE function
 - description [75](#)
- DATE_DIFF function
 - description [76](#)
- date/time values
 - adding [54](#)
- dates
 - converting to character strings [176](#)
 - databases [21](#)
 - default format [21](#)
 - flat files [21](#)
 - format strings [22](#)
 - functions [34](#)
 - Julian [19](#)
 - Modified Julian [19](#)
 - overview [18](#)
 - performing arithmetic [29](#)
 - rounding [148](#)
 - supported date range [19](#)
 - truncating [187](#)
- DEC_BASE64 function
 - description [78](#)
- decimal values
 - converting [184](#)
- DECODE function
 - description [79](#)
- decoding
 - DEC_BASE64 function [78](#)
- DECOMPRESS function
 - description [81](#)
- decryption
 - AES_DECRYPT function [57](#)
 - AES_GCM_DECRYPT function [59](#)
 - using the Advanced Encryption Standard algorithm [59](#)
- default date format
 - defined [21](#)
- default values
 - ERROR function [82](#)
- division calculation
 - returning remainder [127](#)
- double precision values
 - floating point numbers [184](#)

E

- empty strings
 - testing for [106](#)
- ENC_BASE64 function
 - description [82](#)
- encoding
 - characters [119](#), [164](#)

encoding (*continued*)

ENC_BASE64 function [82](#)

encoding functions

AES_DECRYPT [57](#)

AES_ENCRYPT [58](#)

AES_GCM_DECRYPT [59](#)

AES_GCM_ENCRYPT [60](#)

COMPRESS [67](#)

CRC32 [73](#)

DEC_BASE64 [78](#)

DECOMPRESS [81](#)

description [35](#)

ENC_BASE64 [82](#)

MD5 [117](#)

encryption

AES_ENCRYPT function [58](#)

AES_GCM_ENCRYPT function [60](#)

using the Advanced Encryption Standard algorithm [58](#), [60](#)

ERROR function

default value [82](#)

description [82](#)

EXP function

description [83](#)

exponent values

calculating [83](#)

returning [134](#)

F

FALSE constant

description [11](#)

field expressions

conditional [11](#)

null constraints [11](#)

using operators [13](#)

filter conditions

null values [12](#)

financial functions

description [35](#)

FV function [86](#)

NPER function [130](#)

PMT function [133](#)

PV function [135](#)

RATE function [136](#)

FIRST function

description [84](#)

flat files

dates [21](#)

FLOOR function

description [85](#)

format

from character string to date [181](#)

from date to character string [176](#)

format strings

dates [22](#)

definition [18](#)

Julian day [23](#)

matching [28](#)

Modified Julian day [23](#)

TO_CHAR function [23](#)

TO_DATE and IS_DATE format strings [26](#)

functions

categories [31](#)

conversion [33](#)

data cleansing [33](#)

date [34](#)

encoding [35](#)

functions (*continued*)

financial [35](#)

horizontal expansion [35](#)

numeric [36](#)

scientific [36](#)

SETVARIABLE [160](#)

special [36](#)

string [37](#)

test [37](#)

FV function

description [86](#)

G

GET_DATE_PART function

description [87](#)

GREATEST function

description [89](#)

Gregorian calendar

in date functions [19](#)

H

high precision

AVG function [62](#)

CUME [74](#)

EXP [83](#)

MOVINGAVG [128](#)

MOVINGSUM [129](#)

horizontal expansion functions

%OPR_CONCAT% [49](#)

%OPR_CONCATDELIM% [50](#)

%OPR_IIF% [51](#)

%OPR_SUM% [52](#)

description [35](#)

hyperbolic

cosine function [70](#)

sine function [163](#)

tangent function [173](#)

I

IIF function

description [90](#)

IN function

description [92](#)

INDEXOF function

description [92](#)

Informatica Global Customer Support

contact information [9](#)

Informatica Intelligent Cloud Services

web site [8](#)

INITCAP function

description [94](#)

INSTR function

description [95](#)

integers

converting other values [185](#)

IS_DATE function

description [97](#)

format strings [26](#)

IS_NUMBER function

description [99](#)

IS_SPACES function

description [101](#)

ISNULL function
description [102](#)

J

J format string
using with IS_DATE [28](#)
using with TO_CHAR [25](#)
using with TO_DATE [28](#)
Julian dates
in date functions [19](#)
Julian day
format string [23](#), [26](#)

L

LAST function
description [103](#)
LAST_DAY function
description [104](#)
LEAST function
description [105](#)
LENGTH function
description [106](#)
empty string test [106](#)
literals
single quotation marks in [65](#), [67](#)
LN function
description [107](#)
LOG function
description [107](#)
logarithm
returning [107](#)
logical operators
description [17](#)
LOWER function
description [109](#)
LPAD function
description [110](#)
LTRIM function
description [111](#)

M

maintenance outages [9](#)
MAKE_DATE_TIME function
description [112](#)
MAX (dates) function
description [113](#)
MAX (numbers) function
description [114](#)
MAX (string) function
description [116](#)
MD5 function
description [117](#)
MEDIAN function
description [118](#)
METAPHONE
description [119](#)
milliseconds
truncating [19](#)
MIN (dates) function
description [123](#)
MIN (numbers) function
description [124](#), [125](#)

MOD function
description [127](#)
Modified Julian day
format string [23](#), [26](#)
month
returning last day [104](#)
MOVINGAVG function
description [128](#)
MOVINGSUM function
description [129](#)
multiple searches
example of TRUE constant [12](#)

N

negative values
SIGN [161](#)
nested expressions
operators [13](#)
NPER function
description [130](#)
NULL constant
description [11](#)
null values
checking for [102](#)
filter conditions [12](#)
logical operators [17](#)
operators [12](#)
string operator [15](#)
numbers
rounding [151](#)
truncating [189](#)
numeric functions
ABS [53](#)
CEIL [63](#)
CONVERT_BASE [69](#)
CUME [74](#)
description [36](#)
EXP [83](#)
FLOOR [85](#)
LN [107](#)
LOG [107](#)
MOD [127](#)
MOVINGAVG [128](#)
MOVINGSUM [129](#)
POWER [134](#)
RAND [136](#)
ROUND (numbers) [151](#)
SIGN [161](#)
SQRT [166](#)
TRUNC (numbers) [189](#)
numeric values
converting to text strings [180](#)
returning absolute value [53](#)
returning cosine [69](#)
returning hyperbolic cosine of [70](#)
returning hyperbolic sine [163](#)
returning hyperbolic tangent [173](#)
returning logarithms [107](#)
returning sine [162](#)
returning square root [166](#)
returning standard deviation [166](#)
returning tangent [172](#)
SIGN [161](#)

O

- operator precedence
 - expressions [13](#)
- operators
 - arithmetic [14](#)
 - comparison operators [16](#)
 - logical operators [17](#)
 - null values [12](#)
 - string operators [15](#)
 - using strings in arithmetic [14](#)
 - using strings in comparison [16](#)

P

- PERCENTILE function
 - description [131](#)
- perl compatible regular expression syntax
 - using in a REG_EXTRACT function [137](#)
 - using in a REG_MATCH function [137](#)
- PMT function
 - description [133](#)
- positive values
 - SIGN [161](#)
- POWER function
 - description [134](#)
- primary key constraint
 - null values [11](#)
- PV function
 - description [135](#)

R

- RAND function
 - description [136](#)
- RATE function
 - description [136](#)
- REG_EXTRACT function
 - description [137](#)
 - using perl syntax [137](#)
- REG_MATCH function
 - description [139](#)
 - using perl syntax [137](#)
- REG_REPLACE function
 - description [141](#)
- REPLACECHR function
 - description [142](#)
- REPLACESTR function
 - description [145](#)
- REVERSE function
 - description [147](#)
- ROUND (dates) function
 - description [148](#)
- ROUND (numbers) function
 - description [151](#)
- rounding
 - dates [148](#)
 - numbers [151](#)
- rows
 - avoiding spaces [101](#)
 - counting [71](#), [158](#), [160](#)
 - returning average [128](#)
 - returning sum [129](#)
 - running total [74](#)
 - skipping [82](#)

- RPAD function
 - description [153](#)
- RR format string
 - description [20](#)
 - difference between YY and RR [20](#)
 - using with IS_DATE [29](#)
 - using with TO_CHAR [25](#)
 - using with TO_DATE [29](#)
- RTRIM function
 - description [154](#)
- running total
 - returning [74](#)

S

- scientific functions
 - COS [69](#)
 - COSH [70](#)
 - description [36](#)
 - SIN [162](#)
 - SINH [163](#)
 - TAN [172](#)
 - TANH [173](#)
- sessions
 - stopping [53](#)
- SESSSTARTTIME variable
 - using in date functions [29](#)
- SET_DATE_PART function
 - description [155](#)
- SETCOUNTVARIABLE function
 - description [158](#)
- SETMAXVARIABLE function
 - description [158](#)
- SETMINVARIABLE function
 - description [159](#)
- SETVARIABLE function
 - description [160](#)
- SIGN function
 - description [161](#)
- SIN function
 - description [162](#)
- sine
 - returning [162](#), [163](#)
- single quotation marks in string literals
 - CHR function [65](#)
 - using CHR and CONCAT functions [67](#)
- SINH function
 - description [163](#)
- skipping
 - rows [82](#)
- SOUNDEX function
 - description [164](#)
- spaces
 - avoiding in rows [101](#)
- special functions
 - ABORT [53](#)
 - DECODE [79](#)
 - description [36](#)
 - ERROR [82](#)
 - IIF [90](#)
 - SETCOUNTVARIABLE [158](#)
 - SETMAXVARIABLE [158](#)
 - SETMINVARIABLE [159](#)
- SQL IS_CHAR function
 - using REG_MATCH [139](#)
- SQL LIKE function
 - using REG_MATCH [139](#)

- SQL syntax
 - converting to perl syntax [137](#)
- SQRT function
 - description [166](#)
- square root
 - returning [166](#)
- SSSSS format string
 - using with IS_DATE [29](#)
 - using with TO_CHAR [25](#)
 - using with TO_DATE [29](#)
- status
 - Informatica Intelligent Cloud Services [9](#)
- STDDEV function
 - description [166](#)
- stopping
 - sessions [53](#)
- string conversion
 - dates [20](#)
- string functions
 - ASCII [61](#)
 - CHOOSE [64](#)
 - CHR [65](#)
 - CHRCODE [66](#)
 - CONCAT [67](#)
 - description [37](#)
 - INDEXOF [92](#)
 - INITCAP [94](#)
 - INSTR [95](#)
 - LENGTH [106](#)
 - LOWER [109](#)
 - LPAD [110](#)
 - LTRIM [111](#)
 - REPLACECHR [142](#)
 - REPLACESTR [145](#)
 - REVERSE [147](#)
 - RPAD [153](#)
 - RTRIM [154](#)
 - SUBSTR [168](#)
 - UPPER [191](#)
- string literals
 - single quotation marks in [65](#), [67](#)
- string operators
 - description [15](#)
- strings
 - adding blanks [110](#)
 - adding characters [110](#)
 - capitalization [94](#), [109](#), [191](#)
 - character set [95](#)
 - concatenating [15](#), [49](#), [50](#), [67](#)
 - converting character strings to dates [181](#)
 - converting dates to characters [176](#)
 - converting length [153](#)
 - converting numeric values to text strings [180](#)
 - number of characters [106](#)
 - removing blanks [111](#)
 - removing blanks and characters [154](#)
 - removing characters [111](#)
 - replacing multiple characters [145](#)
 - replacing one character [142](#)
 - returning portion [168](#)
- SUBSTR function
 - description [168](#)
- sum
 - returning [129](#)
- SUM function
 - description [170](#)
- system status [9](#)

- SYSTIMESTAMP function
 - description [171](#)

T

- TAN function
 - description [172](#)
- tangent
 - returning [172](#), [173](#)
- TANH function
 - description [173](#)
- test functions
 - description [37](#)
 - IS_DATE [97](#)
 - IS_NUMBER [99](#)
 - IS_SPACES [101](#)
 - ISNULL [102](#)
- text strings
 - converting numeric values [180](#)
- TO_CHAR (dates) function
 - description [176](#)
 - examples [25](#)
 - format strings [23](#)
- TO_CHAR (numbers) function
 - description [180](#)
- TO_DATE function
 - description [181](#)
 - examples [28](#)
 - format strings [26](#)
- TO_DECIMAL function
 - description [184](#)
- TO_FLOAT function
 - description [184](#)
- TO_INTEGER function
 - description [185](#)
- TRUE constant
 - description [12](#)
- TRUNC (dates) function
 - description [187](#)
- TRUNC (numbers) function
 - description [189](#)
- truncating
 - date/time values [19](#)
 - dates [187](#)
 - numbers [189](#)
- trust site
 - description [9](#)

U

- updates
 - boolean expressions [12](#)
- upgrade notifications [9](#)
- UPPER function
 - description [191](#)

V

- VARIANCE function
 - description [191](#)

W

- web site [8](#)

Y

YY format string
difference between RR and YY [20](#)

YY format string (*continued*)
using with TO_CHAR [26](#)
using with TO_DATE and IS_DATE [29](#)