



Informatica® Cloud MDM - Customer 360 for  
Salesforce

Spring 2021 Version 7.2

# API Guide

© Copyright Informatica LLC 2012, 2021

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2021-05-28

# Table of Contents

<b>Preface .....</b>	<b>5</b>
Informatica Resources. ....	5
Informatica Network. ....	5
Informatica Knowledge Base. ....	5
Informatica Documentation. ....	5
Informatica Product Availability Matrixes. ....	6
Informatica Velocity. ....	6
Informatica Marketplace. ....	6
Informatica Global Customer Support. ....	6
 <b>Chapter 1: API Reference.....</b>	<b>7</b>
API_AccountTriggerHandler Class Reference. ....	7
Package Methods. ....	8
Static Package Functions. ....	8
Constructor & Destructor Documentation. ....	8
Method Documentation. ....	9
API_CleansingStandardization Class Reference. ....	10
Package Methods. ....	10
Method Documentation. ....	10
API_AdapterTestServices Class Reference. ....	11
Package Method. ....	11
Method Documentation. ....	11
API_UserExit Class Reference. ....	12
Package Methods. ....	12
Method Documentation. ....	12
API_MultiOrgImpl Class Reference. ....	13
Package Methods. ....	14
Method Documentation. ....	14
API_Compare Class Reference. ....	15
Package Methods. ....	15
Method Documentation. ....	15
API_ContactTriggerHandler Class Reference. ....	17
Package Methods. ....	18
Constructor & Destructor Documentation. ....	18
Method Documentation. ....	18
API_CustomScoutClass Class Reference. ....	20
Package Methods. ....	20
Constructor & Destructor Documentation. ....	20
Method Documentation. ....	20
API_DataManager Class Reference. ....	21

Static Package Functions. . . . .	21
Method Documentation. . . . .	22
API_DisableDaaSTrigger Class Reference. . . . .	23
Static Package Functions. . . . .	23
Method Documentation. . . . .	24
API_DuplicateSearch Class Reference. . . . .	24
Static Package Functions. . . . .	24
Method Documentation. . . . .	24
API_EventQueueManager Class Reference. . . . .	26
Static Package Functions. . . . .	26
Method Documentation. . . . .	26
API_HierarchyHandler Class Reference. . . . .	26
Static Package Functions. . . . .	26
Method Documentation. . . . .	27
API_JobManager Class Reference. . . . .	28
Static Package Functions. . . . .	29
Method Documentation. . . . .	29
API_LeadTriggerHandler Class Reference. . . . .	34
Package Methods. . . . .	34
Constructor & Destructor Documentation. . . . .	35
Method Documentation. . . . .	35
API_LicenseManager Class Reference. . . . .	36
Static Package Functions. . . . .	36
Method Documentation. . . . .	36
API_QueueManager Class Reference. . . . .	38
Static Public Attributes. . . . .	38
Package Methods. . . . .	39
Static Package Functions. . . . .	39
Constructor & Destructor Documentation. . . . .	40
Method Documentation. . . . .	40
Member Data Documentation. . . . .	49
API_SettingsManager Class Reference. . . . .	49
Static Package Functions. . . . .	49
Method Documentation. . . . .	51
Deprecated List. . . . .	57

# Preface

Refer to the *Informatica® Cloud MDM - Customer 360 for Salesforce API Guide* for information about the Cloud MDM - Customer 360 for Salesforce APIs. This guide is written for administrators who are responsible for implementing the APIs.

## Informatica Resources

### Informatica Network

Informatica Network hosts Informatica Global Customer Support, the Informatica Knowledge Base, and other product resources. To access Informatica Network, visit <https://network.informatica.com>.

As a member, you can:

- Access all of your Informatica resources in one place.
- Search the Knowledge Base for product resources, including documentation, FAQs, and best practices.
- View product availability information.
- Review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

### Informatica Knowledge Base

Use the Informatica Knowledge Base to search Informatica Network for product resources such as documentation, how-to articles, best practices, and PAMs.

To access the Knowledge Base, visit <https://kb.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at [KB\\_Feedback@informatica.com](mailto:KB_Feedback@informatica.com).

### Informatica Documentation

To get the latest documentation for your product, browse the Informatica Knowledge Base at [https://kb.informatica.com/\\_layouts/ProductDocumentation/Page/ProductDocumentSearch.aspx](https://kb.informatica.com/_layouts/ProductDocumentation/Page/ProductDocumentSearch.aspx).

If you have questions, comments, or ideas about this documentation, contact the Informatica Documentation team through email at [infa\\_documentation@informatica.com](mailto:infa_documentation@informatica.com).

## Informatica Product Availability Matrixes

Product Availability Matrixes (PAMs) indicate the versions of operating systems, databases, and other types of data sources and targets that a product release supports. If you are an Informatica Network member, you can access PAMs at

<https://network.informatica.com/community/informatica-network/product-availability-matrices>.

## Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services. Developed from the real-world experience of hundreds of data management projects, Informatica Velocity represents the collective knowledge of our consultants who have worked with organizations from around the world to plan, develop, deploy, and maintain successful data management solutions.

If you are an Informatica Network member, you can access Informatica Velocity resources at <http://velocity.informatica.com>.

If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at [ips@informatica.com](mailto:ips@informatica.com).

## Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that augment, extend, or enhance your Informatica implementations. By leveraging any of the hundreds of solutions from Informatica developers and partners, you can improve your productivity and speed up time to implementation on your projects. You can access Informatica Marketplace at <https://marketplace.informatica.com>.

## Informatica Global Customer Support

You can contact a Global Support Center by telephone or through Online Support on Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:

<http://www.informatica.com/us/services-and-training/support-services/global-support-centers>.

If you are an Informatica Network member, you can use Online Support at <http://network.informatica.com>.

# CHAPTER 1

## API Reference

This chapter includes the following topics:

- [API\\_AccountTriggerHandler Class Reference, 7](#)
- [API\\_CleansingStandardization Class Reference, 10](#)
- [API\\_AdapterTestServices Class Reference, 11](#)
- [API\\_UserExit Class Reference, 12](#)
- [API\\_MultiOrgImpl Class Reference, 13](#)
- [API\\_Compare Class Reference, 15](#)
- [API\\_ContactTriggerHandler Class Reference, 17](#)
- [API\\_CustomScoutClass Class Reference, 20](#)
- [API\\_DataManager Class Reference, 21](#)
- [API\\_DisableDaaSTrigger Class Reference, 23](#)
- [API\\_DuplicateSearch Class Reference, 24](#)
- [API\\_EventQueueManager Class Reference, 26](#)
- [API\\_HierarchyHandler Class Reference, 26](#)
- [API\\_JobManager Class Reference, 28](#)
- [API\\_LeadTriggerHandler Class Reference, 34](#)
- [API\\_LicenseManager Class Reference, 36](#)
- [API\\_QueueManager Class Reference, 38](#)
- [API\\_SettingsManager Class Reference, 49](#)
- [Deprecated List, 57](#)

## API\_AccountTriggerHandler Class Reference

Provides methods to control the execution of the Cloud MDM - Customer 360 for Salesforce (CC360) Account trigger.

You can:

- Enable or disable the trigger.
- Check the status of the trigger.
- Initialize and execute the trigger.

- Invoke the trigger logic for insert, update, and delete operations.
- Skip the account trigger processing.
- Skip the bean trigger processing.

**Note:** If you use the methods in this API, disable the CC360 Account trigger to ensure that the trigger is not executed twice.

## Package Methods

- `global API_AccountTriggerHandler ()`  
The constructor for the Account Trigger Handler class.
- `global void disableCloudMDMTrigger ()`  
Disables the CC360 account trigger.
- `global void enableCloudMDMTrigger ()`  
Enables the CC360 account trigger.
- `global Boolean getCloudMDMTriggerStatus ()`  
Checks if the CC360 account trigger is active.
- `global void initTrigger ()`  
Initializes the CC360 account trigger.
- `global void executeTrigger ()`  
Executes the CC360 account trigger.
- `global void Trigger_InsertBefore_Handler ()`  
Invokes the trigger logic that must be executed before a new account is inserted.
- `global void Trigger_InsertAfter_Handler ()`  
Invokes the trigger logic that must be executed after a new account is inserted.
- `global void Trigger_UpdateBefore_Handler ()`  
Invokes the trigger logic that must be executed before an account is updated.
- `global void Trigger_UpdateAfter_Handler ()`  
Invokes the trigger logic that must be executed after an account is updated.
- `global void Trigger_DeleteBefore_Handler ()`  
Invokes the trigger logic that must be executed before an account is deleted.
- `global void Trigger_DeleteAfter_Handler ()`  
Invokes the trigger logic that must be executed after an account is deleted.

## Static Package Functions

- `global static void setForceSkipAccountTrigger (boolean state)`  
Allows you to skip the execution of the CC360 account trigger.
- `global static void setForceSkipBeanTrigger (boolean state)`  
Allows you to skip the execution of the bean trigger.

## Constructor & Destructor Documentation

### `global API_AccountTriggerHandler ()`

The constructor for the Account Trigger Handler class.

## Method Documentation

### global void disableCloudMDMTrigger ()

Disables the CC360 account trigger.

### global void enableCloudMDMTrigger ()

Enables the CC360 account trigger.

### global void executeTrigger ()

Executes the CC360 account trigger.

This is a single wrapper method that executes the trigger logic for operations: insert, update, and delete (before and after).

### global Boolean getCloudMDMTriggerStatus ()

Checks if the CC360 account trigger is active.

#### Returns:

TRUE if the account trigger is active.

### global void initTrigger ()

Initializes the CC360 account trigger.

#### Exceptions:

DS_CloudMDMSkipTriggerException	If you skip the execution of the account trigger using the setForceSkipAccountTrigger method.
---------------------------------	---

### global static void setForceSkipAccountTrigger (boolean state)

Allows you to skip the execution of the CC360 account trigger.

#### Parameters:

##### state

Specify True to skip the account trigger.

### global static void setForceSkipBeanTrigger (boolean state)

Allows you to skip the execution of the bean trigger.

#### Parameters:

##### state

Specify True to skip the account trigger.

### global void Trigger\_DeleteAfter\_Handler ()

Invokes the trigger logic that must be executed after an account is deleted.

### global void Trigger\_DeleteBefore\_Handler ()

Invokes the trigger logic that must be executed before an account is deleted.

### global void Trigger\_InsertAfter\_Handler ()

Invokes the trigger logic that must be executed after a new account is inserted.

### global void Trigger\_InsertBefore\_Handler ()

Invokes the trigger logic that must be executed before a new account is inserted.

### global void Trigger\_UpdateAfter\_Handler ()

Invokes the trigger logic that must be executed after an account is updated.

### global void Trigger\_UpdateBefore\_Handler ()

Invokes the trigger logic that must be executed before an account is updated.

## API\_CleansingStandardization Class Reference

Provides methods to retrieve the country name based on the ISO code or the ISO code based on the country name.

### Package Methods

- global static String getIsoCodeFromCountry (string inCountry)  
Gets the ISO code for the specified country.
- global static String getCountryFromIsoCode (string isoCode)  
Gets the country name for the specified ISO code.

### Method Documentation

### global static String getIsoCodeFromCountry (String inCountry)

Gets the ISO code for the specified country.

#### Parameters:

##### **inCountry**

The country name for which you want the ISO code.

#### Returns:

The ISO code for the specified country.

### global static String getCountryFromIsoCode (String isoCode)

Gets the country name for the specified ISO code.

#### Parameters:

##### **isoCode**

The ISO code for which you want the country name.

#### Returns:

The country name for the specified ISO code.

## API\_AdapterTestServices Class Reference

You can implement your adapter by using the sample implementation provided for integration with AddressDoctor. However, to perform a unit test of the adapter you implement, you need to register the adapter with CC360. Use the method in this API class to register the adapter.

### Package Method

- global static setExternalAdapterClassName (string className)  
Allows you to register your adapter with CC360.

### Method Documentation

#### global static String setExternalAdaptrClassName(String className)

Allows you to register your adapter with CC360.

#### Parameters:

##### **className**

The name of the class you want to register.

# API\_UserExit Class Reference

Provides methods to register user exit classes for accounts, contacts, and leads. User exit classes must be registered to invoke the implementer class. The class name specified as a parameter value must contain the namespace prefix <<NameSpacePrefix.ClassName>> if the implementing class is in some other managed package. If the implementing class is part of an inner class that is not part of a managed package, then the format is <<OuterClassName.InnerClassName>>. If the implementing class is part of an outer class, then the format is <<ClassName>>.

For example, during the merge process, if you want the users to have visibility over the details of the records before and after merge, you can use the API\_UserExit class to create a utility that provides access to the merged record for a user who had access to the deleted record.

## Package Methods

- global static setUserExitMergeAccountHandler (string className, Boolean isPartial)  
Sets up the user exit custom setting for merge of accounts.
- global static getUserExitMergeAccountHandler  
Gets the user exit custom setting for merge of accounts.
- global static setUserExitMergeLeadHandler(string className, Boolean isPartial)  
Sets up the user exit custom setting for merge of leads.
- global static getUserExitMergeLeadHandler  
Gets the user exit custom setting for merge of leads.
- global static setUserExitMergeContactHandler(string className, Boolean isPartial)  
Sets up the user exit custom setting for merge of contacts.
- global static getUserExitMergeContactHandler  
Gets the user exit custom setting for merge of contacts.

## Method Documentation

### global static setUserExitMergeAccountHandler (string className, Boolean isPartial)

Sets up the user exit custom setting for merge of accounts.

#### Parameters:

##### **className**

The name of the handler class that implements DS\_Classes.ICloudMDMUserExit interface.

##### **isPartial**

Indicates whether the transaction must fail on partial completion.

### global static getUserExitMergeAccountHandler

Gets the user exit custom setting for merge of accounts.

#### Returns:

A string with the name of the handler class and isPartial value separated by a colon in the format <<HandlerClass>>:<<Ispartial>>.

## global static setUserExitMergeLeadHandler (string className, Boolean isPartial)

Sets up the user exit custom setting for merge of leads.

### Parameters:

#### **className**

The name of the handler class that implements DS\_Classes.ICloudMDMUserExit interface.

#### **isPartial**

Indicates whether the transaction must fail on partial completion.

## global static getUserExitMergeLeadHandler

Gets the user exit custom setting for merge of leads.

### Returns:

A string with the name of the handler class and isPartial value separated by a colon in the format <<HandlerClass>>:<<Ispartial>>.

## global static setUserExitMergeContatchHandler (string className, Boolean isPartial)

Sets up the user exit custom setting for merge of contacts.

### Parameters:

#### **className**

The name of the handler class that implements DS\_Classes.ICloudMDMUserExit interface.

#### **isPartial**

Indicates whether the transaction must fail on partial completion.

## global static getUserExitMergeContactHandler

Gets the user exit custom setting for merge of contacts.

### Returns:

A string with the name of the handler class and isPartial value separated by a colon in the format <<HandlerClass>>:<<Ispartial>>.

# API\_MultiOrgImpl Class Reference

If an external bean for a Spoke record is created in the Hub Org, then you can use the method in this API class to get the enriched master bean from the Hub Org to the Spoke Org. You need to invoke this API from the Spoke Org. This REST API can be accessed via the following URL:

`https://<server>.salesforce.com/services/apexrest/DSE/MasterData/`

## Package Methods

- global static doPost ()  
Sends a request from a Spoke Org to the Hub Org to get the updated master bean from the Hub Org.

## Method Documentation

### global static doPost()

While making a request to this API, Request object must be set in the HTTP request body.

```
public class GetMasterRequest
{
    public Set<String> sObjectIds;
    public String spokeOrgName;
    public Datetime hubLastChangeTime;
    public String sObjectType;
}
```

#### Parameters:

##### **sObjectIds**

The list of record IDs for which you want to get master data.

##### **spokeOrgName**

The Spoke Org name as defined in the data source on the Hub Org.

##### **hubLastChangeTime**

The time when the record was previously synchronizd with the Hub Org. This is used when a real-time callout is made from the Spoke Org user interface.

##### **sObjectType**

This must always be set to "Account".

The method returns success or error response from the Hub Org. If the master beans are found, then the response is a list of GetMasterResponse Object for each input record with 200 as response status code.

```
public class GetMasterResponse
{
    public String spokeSObjectId;
    public Map<String,String> fieldNameValuePair;
    public String responseMsg;
    public DateTime lastUpdateTimeFromHub;
    public String errorMsg;
}
```

#### Parameters:

##### **spokeSObjectId**

Spoke Org record ID.

##### **fieldNameValuePair**

Map that contains the list of enriched fields as keys and their respective values.

##### **responseMsg**

Contains the response status. The following are the response codes:

- CMDM\_RESPONSE\_MB\_FOUND = 1, if MB is found for the Spoke's external bean.

- CMDM\_RESPONSE\_MB\_NOT\_FOUND= '2', if MB is not found, this can be because the external bean for the spoke is not created by Informatica Cloud Services or de-duplication Jobs are not run yet.
- CMDM\_RESPONSE\_MB\_NO\_UPDATE\_FOUND = '3', if there has been not update found on the MB since the last update time.
- CMDM\_RESPONSE\_MB\_DELETED= '4', if the master bean was existing and later found to be deleted on the Hub Org.

#### **lastUpdateTimeFromHub**

Provides the last update time stamp of the master bean.

## API\_Compare Class Reference

Provides methods to compare bean to bean, master bean to master bean, bean to master bean, or master bean to Bean and returns the following:

- Fuzzy comparison score
- Status that indicates whether duplicates found or not
- Status that indicates whether match found or not

### Package Methods

- global static Decimal `getScore (Id sObjectId1, Id sObjectId2, Boolean isPartial , Decimal threshold, String settingName)`  
Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns the fuzzy comparison score.
- global static Decimal `getScore (Id sObjectId1, Id sObjectId2, String settingName)`  
Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns the fuzzy comparison score.
- global static boolean `isDuplicate (Id sObjectId1, Id sObjectId2, String settingName)`  
Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns True if objects are duplicates.
- global static boolean `isMatch (Id sObjectId1, Id sObjectId2, String settingName)`  
Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns True if objects match.

### Method Documentation

#### **global static Decimal `getScore (Id sObjectId1, Id sObjectId2, Boolean isPartial , Decimal threshold, String settingName)`**

Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns the fuzzy comparison score. The match score is calculated using the specified match setting. If any

field with weightage > 100 does not match, score is returned as zero. Otherwise, a score is returned regardless of the value in the Duplicate Check Threshold and High Matching Threshold.

#### Parameters:

##### **sObjectId1**

The first Salesforce object ID.

##### **sObjectId2**

The second Salesforce object ID.

##### **isPartial**

Default is true. isPartial causes an early exit from the comparison when the negative score exceeds threshold.

##### **threshold**

The threshold score. If you do not specify a value, the parameter uses the Duplicate Check Threshold from the match setting.

##### **settingName**

The name of the match setting. For example, account.

#### Returns:

The fuzzy comparison score.

### global static Decimal getScore (Id sObjectId1, Id sObjectId2, String settingName)

Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns the fuzzy comparison score. The match score is calculated using the specified match setting. If any field with weightage > 100 does not match, score is returned as zero. Otherwise, a score is returned regardless of the value in the Duplicate Check Threshold and High Matching Threshold.

#### Parameters:

##### **sObjectId1**

The first Salesforce object ID.

##### **sObjectId2**

The second Salesforce object ID.

##### **settingName**

The name of the match setting. For example, account.

#### Returns:

The fuzzy comparison score.

## global static Boolean isDuplicate (Id sObjectId1, Id sObjectId2, String settingName)

Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns True if objects compared are duplicates. The score is calculated using the specified match setting. If the Total Score >= Duplicate Check Threshold of the match setting, the pair is considered a duplicate.

### Parameters:

#### **sObjectId1**

The first Salesforce object ID.

#### **sObjectId2**

The second Salesforce object ID.

#### **settingName**

The name of the match setting.

### Returns:

True or False. True indicates that the records are duplicate.

## global static Boolean isMatch (Id sObjectId1, Id sObjectId2, String settingName)

Compares a bean to bean, master bean to master bean, bean to master bean, or master bean to bean and returns True if objects compared match each other. The score is calculated using the specified match setting. If the Total Score >= High Matching Threshold from the match setting, the pair is considered a match.

### Parameters:

#### **sObjectId1**

The first Salesforce object ID.

#### **sObjectId2**

The second Salesforce object ID.

#### **settingName**

The name of the match setting.

### Returns:

True or False. True indicates that the records match.

# API\_ContactTriggerHandler Class Reference

Provides methods to control the execution of the Cloud MDM - Customer 360 for Salesforce (CC360) Contact trigger.

You can:

- Enable or disable the trigger.
- Check the status of the trigger.

- Initialize and execute the trigger.
- Invoke the trigger logic for insert, update, and delete operations.

**Note:** If you use the methods in this API, disable the CC360 Contact trigger to ensure that the trigger is not executed twice.

## Package Methods

- `global API_ContactTriggerHandler ()`  
The constructor for the Contact Trigger Handler class.
- `global void disableCloudMDMTrigger ()`  
Disables the CC360 contact trigger.
- `global void enableCloudMDMTrigger ()`  
Enables the CC360 contact trigger.
- `global Boolean getCloudMDMTriggerStatus ()`  
Checks if the CC360 contact trigger is active.
- `global void initTrigger ()`  
Initializes the CC360 contact trigger.
- `global void executeTrigger ()`  
Executes the CC360 contact trigger.
- `global void Trigger_InsertBefore_Handler ()`  
Invokes the trigger logic that must be executed before a new contact is inserted.
- `global void Trigger_InsertAfter_Handler ()`  
Invokes the trigger logic that must be executed after a new contact is inserted.
- `global void Trigger_UpdateBefore_Handler ()`  
Invokes the trigger logic that must be executed before a contact is updated.
- `global void Trigger_UpdateAfter_Handler ()`  
Invokes the trigger logic that must be executed after a contact is updated.
- `global void Trigger_DeleteBefore_Handler ()`  
Invokes the trigger logic that must be executed before a contact is deleted.
- `global void Trigger_DeleteAfter_Handler ()`  
Invokes the trigger logic that must be executed after a contact is deleted.

## Constructor & Destructor Documentation

### `global API_ContactTriggerHandler ()`

The constructor for the Contact Trigger Handler class.

## Method Documentation

### `global void disableCloudMDMTrigger ()`

Disables the CC360 contact trigger.

## global void enableCloudMDMTrigger ()

Enables the CC360 contact trigger.

## global void executeTrigger ()

Executes the CC360 contact trigger.

This is a single wrapper method that executes the trigger logic for operations: insert, update, and delete (before and after).

## global Boolean getCloudMDMTriggerStatus ()

Checks if the CC360 contact trigger is active.

### Returns:

TRUE if the contact trigger is active.

## global void initTrigger ()

Initializes the CC360 contact trigger.

### Exceptions:

DS_CloudMDMSkipTriggerException	when contact trigger logic is skipped.
---------------------------------	--

## global void Trigger\_DeleteAfter\_Handler ()

Invokes the trigger logic that must be executed after a contact is deleted.

## global void Trigger\_DeleteBefore\_Handler ()

Invokes the trigger logic that must be executed before a contact is deleted.

## global void Trigger\_InsertAfter\_Handler ()

Invokes the trigger logic that must be executed after a new contact is inserted.

## global void Trigger\_InsertBefore\_Handler ()

Invokes the trigger logic that must be executed before a new contact is inserted.

## global void Trigger\_UpdateAfter\_Handler ()

Invokes the trigger logic that must be executed after a contact is updated.

## global void Trigger\_UpdateBefore\_Handler ()

Invokes the trigger logic that must be executed before a contact is updated.

# API\_CustomScoutClass Class Reference

Use this API to synchronize the custom objects.

The custom trigger of the respective custom object invokes this class.

## Package Methods

- `global API_CustomScoutClass (string aObjName)`  
The constructor for the Custom Scout Class.
- `global void triggerSynchronize (List< SObject > newObjects, List< SObject > oldObjects, boolean isInsert, boolean isUpdate, boolean isDelete, boolean isUnDelete, boolean isBefore, boolean isAfter)`  
Triggers the synchronization process that creates beans for the custom objects based on the trigger state. CC360 does not trigger the synchronization process if you do not define the synchronization settings for the custom object and do not select the Synchronize option in the synchronization settings of the custom object.

## Constructor & Destructor Documentation

### `global API_CustomScoutClass (string aObjName)`

The constructor for the Custom Scout Class.

Parameters:

**aObjName**

The name of the custom object to be synchronized.

## Method Documentation

### `public void triggerSynchronize (List<SObject> newObjects, List<SObject> oldObjects, boolean isInsert, boolean isUpdate, boolean isDelete, boolean isUnDelete, boolean isBefore, boolean isAfter)`

Triggers the synchronization process that creates beans for the custom objects based on the trigger state. The `triggerSynchronize()` method triggers the synchronization process only if you define the synchronization settings for the custom object and select the Synchronize option in the synchronization settings of the custom object.

Parameters:

**newObjects**

List of new versions of custom objects.

**oldObjects**

List of old versions of custom objects.

**isInsert**

Indicates whether to trigger the synchronization process for the insert operation.

Specify true to trigger the synchronization process, or specify false to not trigger the process.

#### **isUpdate**

Indicates whether to trigger the synchronization process for the update operation.

Specify true to trigger the synchronization process, or specify false to not trigger the process.

#### **isDelete**

Indicates whether to trigger the synchronization process for the delete operation.

Specify true to trigger the synchronization process, or specify false to not trigger the process.

#### **isUnDelete**

Indicates whether to trigger the synchronization process if the record is recovered from the Recycle Bin.

Specify true to trigger the synchronization process, or specify false to not trigger the process.

#### **isBefore**

Indicates whether to trigger the synchronization process before you save a record.

Specify true to trigger the synchronization process, or specify false to not trigger the process.

#### **isAfter**

Indicates whether to trigger the synchronization process after you save a record.

Specify true to trigger the synchronization process, or specify false to not trigger the process.

## API\_DataManager Class Reference

Provides methods to retrieve beans and master beans for a list of accounts, contacts, and leads.

### Static Package Functions

- global static list< DS\_Bean\_\_c > getBeans (list< Account > accounts)  
Gets the beans for the list of specified accounts.
- global static list< DS\_Bean\_\_c > getBeans (list< Contact > contacts)  
Gets the beans for the list of specified contacts.
- global static list< DS\_Bean\_\_c > getBeans (list< Lead > leads)  
Gets the beans for the list of specified leads.
- global static list< DS\_Bean\_\_c > getBeans (list< DS\_Master\_Bean\_\_c > masterBeans)  
Gets the beans for the list of specified master beans.
- global static list< DS\_Master\_Bean\_\_c > getMasterBeans (list< Account > accounts)  
Gets the master beans for the list of specified accounts.
- global static list< DS\_Master\_Bean\_\_c > getMasterBeans (list< Contact > contacts)  
Gets the master beans for the list of specified contacts.
- global static list< DS\_Master\_Bean\_\_c > getMasterBeans (list< Lead > leads)  
Gets the master beans for the list of specified leads.

## Method Documentation

`global static list<DS_Bean__c> getBeans (list< Account > accounts)`

Gets the beans for the list of specified accounts.

**Parameters:**

**accounts**

The list of accounts for which you want to get the beans.

**Returns:**

The beans for the specified accounts.

`global static list<DS_Bean__c> getBeans (list< Contact > contacts)`

Gets the beans for the list of specified contacts.

**Parameters:**

**contacts**

The list of contacts for which you want to get the beans.

**Returns:**

The beans for the specified contacts.

`global static list<DS_Bean__c> getBeans (list< DS_Master_Bean__c > masterBeans)`

Gets the beans for the list of specified master beans.

**Parameters:**

**masterBeans**

the list of master beans for which you want to the beans.

**Returns:**

The beans for the specified master beans.

`global static list<DS_Bean__c> getBeans (list< Lead > leads)`

Gets the beans for the list of specified leads.

**Parameters:**

**leads**

The list of leads for which you want to get the beans.

**Returns:**

The beans for the specified leads.

`global static list<DS_Master_Bean__c> getMasterBeans (list< Lead > leads)`

Gets the master beans for the list of specified leads.

**Parameters:**

**leads**

The list of leads for which you want to get the master beans.

**Returns:**

The master beans for the specified leads.

`global static list<DS_Master_Bean__c> getMasterBeans (list< Account > accounts)`

Gets the master beans for the list of specified accounts.

**Parameters:**

**accounts**

The list of accounts for which you want to get the master beans.

**Returns:**

The master beans for the specified accounts.

`global static list<DS_Master_Bean__c> getMasterBeans (list< Contact > contacts)`

Gets the master beans for the list of specified contacts.

**Parameters:**

**contacts**

The list of contacts for which you want to get the master beans.

**Returns:**

The master beans for the specified contacts.

## API\_DisableDaaSTrigger Class Reference

Disables or enables Data as a Service (DaaS) for standard and custom Salesforce objects.

### Static Package Functions

- `global static DisableDaaSTrigger_(Integer sObjectKeyPrefix, Integer Value)`  
Disables or enables DaaS for an object with the specified key prefix.
- `global static DisableDaaSTrigger_(String sObjectName, Integer Value)`  
Disables or enables DaaS for a specified object.

## Method Documentation

### global static DisableDaaSTrigger\_(Integer sObjectKeyPrefix, Integer Value)

Disables or enables DaaS for an object with the specified key prefix.

#### Parameters:

##### **sObjectKeyPrefix**

Indicates the key prefix of the object.

##### **Value**

Specify 1 to disable DaaS, and specify 0 to enable DaaS.

### global static DisableDaaSTrigger\_(String sObjectName, Integer Value)

Disables or enables DaaS for a specified object.

#### Parameters:

##### **sObjectName**

Indicates the name of the object.

##### **Value**

Specify 1 to disable DaaS, and specify 0 to enable DaaS.

## API\_DuplicateSearch Class Reference

Provides methods to search for duplicates by using the basic search or fuzzy search capability.

## Static Package Functions

- global static list< DS\_Bean\_\_c > basicSearch (sObject obj, String searchMode, Set< String > searchSources, String sortOrder)  
Matches the fields in the object passed through the method directly with the fields in the database and returns the duplicate records.
- global static list< DS\_Bean\_\_c > fuzzySearch (sObject obj, Set< String > searchSources, String sortOrder)  
Uses the CC360 pattern matching algorithms to match the fields in the object passed through this method with the fields in the database and returns the duplicate records.

## Method Documentation

## global static list<DS\_Bean\_\_c> basicSearch (sObject obj, String searchMode, Set< String > searchSources, String sortOrder)

Matches the fields in the object passed through the method directly with the fields in the database and returns the duplicate records.

### Parameters:

#### **obj**

The salesforce sObject to be searched for duplicates. You can use any salesforce sObject in the method. You can pass the object to the method without casting the object as an sObject type. The object to be searched need not exist in the database.

#### **searchMode**

Specifies whether the search matches all the fields or any one of the fields. Specify AND to return records by matching all the fields. Specify OR to return records by matching any one field. When you specify OR, the search might return a large number of records.

#### **searchSources**

The salesforce object to be compared with the sObject. You can compare the sObject passed through the method with any other type of salesforce object that is synchronized with CC360. You must define the object in CC360 data sources as part of custom settings. To search for duplicates, CC360 uses the match settings defined as part of custom settings.

#### **sortOrder**

Controls the sort order of the beans returned by the search. The recommended value is null.

### Returns:

The list of duplicate records for the specified sObject.

## global static list<DS\_Bean\_\_c> fuzzySearch (sObjectobj, Set< String > searchSources, String sortOrder)

Uses the CC360 pattern matching algorithms to match the fields in the object passed through this method with the fields in the database and returns the duplicate records.

### Parameters:

#### **obj**

The salesforce sObject to be searched for duplicates. You can use any salesforce sObject in the method. You can pass the object to the method without casting the object as an sObject type. The object to be searched need not exist in the database.

#### **searchSources**

The salesforce object to be compared with the sObject. You can compare the sObject passed through the method with any other type of salesforce object that is synchronized with CC360. You must define the object in CC360 data sources as part of custom settings. CC360 uses the match settings defined as part of custom settings to search for duplicates.

#### **sortOrder**

Controls the sort order of the beans returned by the search. The recommended value is null.

### Returns:

The list of duplicate records for the specified sObject.

# API\_EventQueueManager Class Reference

Provides a method to create data cleansing requests for historical accounts, contacts, and leads.

## Static Package Functions

`global static void loadDataQualityEvents(String sObjectName, List<Subject> subjRecords)`

Creates transaction entries in the Event Queue table for a list of accounts, contacts, and leads. When the External Cleansing batch job is run, the batch job picks up records from the Event Queue table and sends the records to AddressDoctor® for cleansing addresses.

## Method Documentation

`global static void loadDataQualityEvents(String sObjectName, List<Subject> subjRecords)`

Creates transaction entries in the Event Queue table for a list of accounts, contacts, and leads. When the External Cleansing batch job is run, the batch job picks up records from the Event Queue table and sends the records to AddressDoctor for cleansing addresses.

**Parameters:**

**sObjectName**

The salesforce object type; account, contact, or lead.

**subjRecords**

The list of records corresponding to the Salesforce object type. For example, if you specify account as sObjectName, then you must specify a list of accounts for this parameter.

**Note:** Include all the relevant address fields for records that you pass as subjRecords.

# API\_HierarchyHandler Class Reference

Provides methods to lock and unlock hierarchies based on root bean ID and account name.

When Cloud MDM - Customer 360 for Salesforce (CC360) performs an asynchronous operation on a hierarchy, the hierarchy must be locked to prevent users from modifying it.

## Static Package Functions

- `global static void LockCloudMDMHierarchy (Id rootNodeId)`  
Locks the hierarchy for the specified root bean ID.
- `global static void LockCloudMDMHierarchy (Set< Id > beanIds)`  
Locks the hierarchies for the specified root bean IDs.
- `global static void LockCloudMDMHierarchy (Account account)`  
Locks the hierarchy that contains the specified account.

- global static void `UnLockCloudMDMHierarchy (Id rootNodeId)`  
Unlocks the hierarchy for the specified root bean ID.
- global static void `UnLockCloudMDMHierarchy (Set< Id > beanIds)`  
Unlocks the hierarchies for the specified root bean IDs.
- global static void `UnLockCloudMDMHierarchy (Account account)`  
Unlocks the hierarchy that contains the specified account.

## Method Documentation

### global static void `LockCloudMDMHierarchy (Id rootNodeId)`

Locks the hierarchy for the specified root bean ID.

#### Parameters:

##### **rootNodeId**

The root bean ID of the hierarchy to be locked.

#### Exceptions:

DS_CloudMDM_HierarchyAPIException	
-----------------------------------	--

### global static void `LockCloudMDMHierarchy (Set< Id > beanIds)`

Locks the hierarchies for the specified root bean IDs.

#### Parameters:

##### **beanIds**

The root bean IDs of the hierarchies to be locked.

#### Exceptions:

DS_CloudMDM_HierarchyAPIException	
-----------------------------------	--

### global static void `LockCloudMDMHierarchy (Account account)`

Locks the hierarchy that contains the specified account.

#### Parameters:

##### **account**

The name of the account to be used to lock a hierarchy.

#### Exceptions:

DS_CloudMDM_HierarchyAPIException	
-----------------------------------	--

### global static void UnLockCloudMDMHierarchy (Id rootNodeId)

Unlocks the hierarchy for the specified root bean ID.

#### Parameters:

##### **rootNodeId**

The root bean ID of the hierarchy to be unlocked.

#### Exceptions:

DS_CloudMDM_HierarchyAPIException	
-----------------------------------	--

### global static void UnLockCloudMDMHierarchy (Set< Id > beanIds)

Unlocks the hierarchies for the specified root bean IDs.

#### Parameters:

##### **beanIDs**

The root bean IDs of the hierarchies to be unlocked.

#### Exceptions:

DS_CloudMDM_HierarchyAPIException	
-----------------------------------	--

### global static void UnLockCloudMDMHierarchy (Account account)

Unlocks the hierarchy that contains the specified account.

#### Parameters:

##### **account**

The name of the account to be used to unlock a hierarchy.

#### Exceptions:

DS_CloudMDM_HierarchyAPIException	
-----------------------------------	--

## API\_JobManager Class Reference

Use this API to manage the different Cloud MDM - Customer 360 for Salesforce (CC360) batch jobs.

You can:

- Run a batch job.
- Run a batch job concurrently.
- Abort a batch job.

In addition, you can instantiate the following batch classes:

- Duplicate check and duplicate bean check

- Matching
- Consolidation
- Conversion
- Merge account, contact, and lead
- Migration

## Static Package Functions

- global static boolean runJob (String jobName)  
Runs the specified CC360 batch job.
- global static boolean runConcurrentJob (String jobName, Integer concurrentBatchJobs)  
Runs the specified CC360 batch job.
- global static boolean abortJob (String jobName)  
Aborts the specified CC360 batch job.
- global static DS\_DuplicateBatchClass instantiateDuplicateBatchClass (set< Id > jobIdSet, List< DS\_Master\_Bean\_\_c > selectedMBeans, List< DS\_Master\_Bean\_\_c > selectedCompMBeans)  
Creates an instance of the duplicate check batch class.
- global static DS\_DuplicateBeanBatchClass instantiateDuplicateBeanBatchClass (set< Id > jobIdSet, List< DS\_Bean\_\_c > selectedBeans, List< DS\_Bean\_\_c > selectedCompBeans)  
Creates an instance of the duplicate bean check batch class.
- global static DS\_MatchingBatchClass instantiateMatchingBatchClass (set< Id > jobIdSet, List< DS\_Bean\_\_c > selectedBeans, List< DS\_Master\_Bean\_\_c > selectedMBeans)  
Creates an instance of the matching batch class to match beans with master beans.
- global static DS\_ConsolidationBatchClass instantiateConsolidationBatchClass (set< Id > jobIdSet, List< DS\_Bean\_\_c > selectedBeans, List< DS\_Master\_Bean\_\_c > selectedMBeans)  
Creates an instance of the consolidation batch class.
- global static DS\_BeanConversionBatchClass instantiateBeanConversionBatchClass (set< Id > jobIdSet, List< DS\_Bean\_\_c > selectedBeans, List< DS\_Bean\_\_c > selectedCompBeans)  
Creates an instance of the bean conversion batch class job to convert beans into accounts, contacts, or leads.
- global static DS\_MergeAccountBatchClass instantiateMergeAccountBatchClass (List< DS\_Duplicates\_\_c > selectedDupes)  
Creates an instance of the merge accounts batch class to merge duplicate accounts.
- global static DS\_MergeContactBatchClass instantiateMergeContactBatchClass (List< DS\_DuplicateBean\_\_c > selectedDupes)  
Creates an instance of the merge contacts batch class to merge duplicate contacts.
- global static DS\_MergeLeadBatchClass instantiateMergeLeadBatchClass (List< DS\_DuplicateBean\_\_c > selectedDupes)  
Creates an instance of the merge leads batch class to merge duplicate leads.
- global static DS\_MigrationBatchClass instantiateMigrationBatchClass (set< Id > jobIdSet, String objName)  
Creates an instance of the migration batch class to migrate accounts, contacts, or leads.

## Method Documentation

## global static boolean abortJob (String jobName)

Aborts the specified CC360 batch job.

### Parameters:

#### **jobName**

The name of the job you want to abort.

### Returns:

True if the job is successfully aborted.

## global static DS\_BeanConversionBatchClass

## instantiateBeanConversionBatchClass (set< Id > jobIdSet, List< DS\_Bean\_\_c > selectedBeans, List< DS\_Bean\_\_c > selectedCompBeans)

Creates an instance of the bean conversion batch class job to convert beans into accounts, contacts, or leads.

### Parameters:

#### **jobIdSet**

The list of bean IDs.

#### **selectedBeans**

The list of beans to be converted through the conversion job. The list is compared with the list of beans specified for the selectetCompBeans parameter. The list consists of beans for which the DS\_Conversion\_Status\_c flag is set to To Be Converted.

#### **selectedCompBeans**

The list of beans to be used for comparison.

### Returns:

The instance of the class.

## global static DS\_ConsolidationBatchClass instantiateConsolidationBatchClass (set< Id > jobIdSet, List< DS\_Bean\_\_c > selectedBeans, List< DS\_Master\_Bean\_\_c > selectedMBeans)

Creates an instance of the consolidation batch class.

### Parameters:

#### **jobIdSet**

The list of bean IDs.

#### **selectedBeans**

The list of beans to be consolidated through the consolidation batch job. The list consists of beans for which the DS\_Consolidated\_c flag is disabled.

#### **selectedMBeans**

The list of master beans to be consolidated.

### Returns:

The instance of the class.

`global static DS_DuplicateBatchClass instantiateDuplicateBatchClass (set< Id > jobIdSet, List< DS_Master_Bean__c > selectedMBeans, List< DS_Master_Bean__c > selectedCompMBeans)`

Creates an instance of the duplicate check batch class.

**Parameters:**

**jobIdSet**

The list of master bean IDs.

**selectedMBeans**

The list of master beans to be compared with the list of master beans specified for the selectedCompMBeans parameter. The list consists of master beans for which the DS\_Duplicate\_Checked\_c flag is disabled.

**selectedCompMBeans**

The list of master beans to be used for comparison.

**Returns:**

The instance of the class.

`global static DS_DuplicateBeanBatchClass instantiateDuplicateBeanBatchClass (set< Id > jobIdSet, List< DS_Bean__c > selectedBeans, List< DS_Bean__c > selectedCompBeans)`

Creates an instance of the duplicate bean check batch class.

**Parameters:**

**jobIdSet**

The list of bean IDs.

**selectedBeans**

The list of beans to be compared with the list of beans specified for the selectedCompBeans parameter. The list consists of beans for which the DS\_Duplicate\_Checked\_c flag is disabled.

**selectedCompBeans**

The list of beans to be used for comparison.

**Returns:**

The instance of the class.

`global static DS_MatchingBatchClass instantiateMatchingBatchClass (set< Id > jobIdSet, List< DS_Bean__c > selectedBeans, List< DS_Master_Bean__c > selectedMBeans)`

Creates an instance of the matching batch class to match beans with master beans.

**Parameters:**

**jobIdSet**

The list of bean IDs.

**selectedBeans**

The list of beans to be matched through the matching batch job. The list is matched with the list of master beans specified for the selectedMBeans parameter.

**selectedMBeans**

The list of master beans to be used for matching.

**Returns:**

The instance of the class.

**global static DS\_MergeAccountBatchClass**  
**instantiateMergeAccountBatchClass (List< DS\_Duplicates\_\_c >**  
**selectedDupes)**

Creates an instance of the merge accounts batch class to merge duplicate accounts.

**Parameters:****selectedDupes**

The list of duplicate accounts to be merged.

**Returns:**

The instance of the class.

**global static DS\_MergeContactBatchClass**  
**instantiateMergeContactBatchClass (List< DS\_DuplicateBean\_\_c >**  
**selectedDupes)**

Creates an instance of the merge contacts batch class to merge duplicate contacts.

**Parameters:****selectedDupes**

The list of duplicate contacts to be merged.

**Returns:**

The instance of the class.

**global static DS\_MergeLeadBatchClass instantiateMergeLeadBatchClass**  
**(List< DS\_DuplicateBean\_\_c > selectedDupes)**

Creates an instance of the merge leads batch class to merge duplicate leads.

**Parameters:****selectedDupes**

The list of duplicate leads to be merged.

**Returns:**

The instance of the class.

## global static DS\_MigrationBatchClass instantiateMigrationBatchClass (set< Id > jobIdSet, String objName)

Creates an instance of the migration batch class to migrate accounts, contacts, or leads.

### Parameters:

#### **jobIdSet**

The list of sObjects to be migrated.

#### **objName**

sObject type for which beans and master beans have to be created.

### Returns:

The instance of the class.

## global static boolean runConcurrentJob (String jobName, Integer concurrentBatchJobs)

Runs the specified CC360 batch job.

### Parameters:

#### **jobName**

The name of the job you want to run.

#### **concurrentBatchJobs**

The number of batch jobs that you want to run concurrently.

### Returns:

True if the job runs successfully.

## global static boolean runJob (String jobName)

Runs the specified CC360 batch job.

### Parameters:

#### **jobName**

The name of the job you want to run. Use one of the following values for the job name:

- Matching
- DuplicateCheck
- DuplicateBeanCheck
- Consolidation
- BeanConversion
- MergeAccount
- MergeLead
- MergeContact
- MigrateAccount
- MigrateContact

- MigrateLead
- Maintenance
- SyncReportingData
- Data as a Service - <Template Name>

#### Returns:

True if the job runs successfully.

## API\_LeadTriggerHandler Class Reference

Provides methods to control the execution of the Cloud MDM - Customer 360 for Salesforce (CC360) Lead trigger.

You can:

- Enable or disable the trigger.
- Check the status of the trigger.
- Initialize and execute the trigger.
- Invoke the trigger logic for insert, update, and delete operations.

**Note:** If you use the methods in this API, disable the CC360 Lead trigger to ensure that the trigger is not executed twice.

### Package Methods

- global API\_LeadTriggerHandler ()  
The constructor for the Lead Trigger Handler class.
- global void disableCloudMDMTrigger ()  
Disables the CC360 lead trigger.
- global void enableCloudMDMTrigger ()  
Enables the CC360 lead trigger.
- global Boolean getCloudMDMTriggerStatus ()  
Checks if the CC360 lead trigger is active.
- global void initTrigger ()  
Initializes the CC360 lead trigger.
- global void executeTrigger ()  
Executes the CC360 lead trigger.
- global void Trigger\_InsertBefore\_Handler ()  
Invokes the trigger logic that must be executed before a new lead is inserted.
- global void Trigger\_InsertAfter\_Handler ()  
Invokes the trigger logic that must be executed after a new lead is inserted.
- global void Trigger\_UpdateBefore\_Handler ()  
Invokes the trigger logic that must be executed before a lead is updated.
- global void Trigger\_UpdateAfter\_Handler ()  
Invokes the trigger logic that must be executed after a lead is updated.

- `global void Trigger_DeleteBefore_Handler ()`  
Invokes the trigger logic that must be executed before a lead is deleted.
- `global void Trigger_DeleteAfter_Handler ()`  
Invokes the trigger logic that must be executed after a lead is deleted.

## Constructor & Destructor Documentation

### `global API_LeadTriggerHandler ()`

The constructor for the Lead Trigger Handler class.

## Method Documentation

### `global void disableCloudMDMTrigger ()`

Disables the CC360 lead trigger.

### `global void enableCloudMDMTrigger ()`

Enables the CC360 lead trigger.

### `global void executeTrigger ()`

Executes the CC360 lead trigger.

This is a single wrapper method that executes the trigger logic for operations: insert, update, and delete (before and after).

### `global Boolean getCloudMDMTriggerStatus ()`

Checks if the CC360 lead trigger is active.

#### Returns:

TRUE if the lead trigger is active.

### `global void initTrigger ()`

Initializes the CC360 lead trigger.

#### Exceptions:

<code>DS_CloudMDMSkipTriggerException</code>	when lead trigger logic is skipped.
--	-------------------------------------

### `global void Trigger_DeleteAfter_Handler ()`

Invokes the trigger logic that must be executed after a lead is deleted.

### global void Trigger\_DeleteBefore\_Handler ()

Invokes the trigger logic that must be executed before a lead is deleted.

### global void Trigger\_InsertAfter\_Handler ()

Invokes the trigger logic that must be executed after a new lead is inserted.

### global void Trigger\_InsertBefore\_Handler ()

Invokes the trigger logic that must be executed before a new lead is inserted.

### global void Trigger\_UpdateAfter\_Handler ()

Invokes the trigger logic that must be executed after a lead is updated.

### global void Trigger\_UpdateBefore\_Handler ()

Invokes the trigger logic that must be executed before a lead is updated.

## API\_LicenseManager Class Reference

Provides methods to enable a Cloud MDM - Customer 360 for Salesforce (CC360) feature based on certain parameters.

### Static Package Functions

- global static void setFeature (String featureName, boolean enabled, String value, Date expirationDate)  
Enables a CC360 feature based on certain parameters.
- global static void setFeature (String featureName, boolean enabled)  
Enables the specified CC360 feature.
- global static void setFeature (String featureName, boolean enabled, String value, Date expirationDate, string password)  
Enables a CC360 feature based on certain parameters.
- global static void setFeature (String featureName, boolean enabled, string password)  
Enables a CC360 feature based on certain parameters.
- global static boolean isFeatureEnabled (String featureName)  
Checks if a CC360 feature is enabled or not and returns the status.

### Method Documentation

## global static boolean isFeatureEnabled (String featureName)

Checks if a CC360 feature is enabled or not and returns the status.

### Parameters:

#### **featureName**

The name of the feature.

### Returns:

The status of the feature (enabled or disabled).

## global static void setFeature (String featureName, boolean enabled)

Enables the specified CC360 feature.

### Parameters:

#### **featureName**

The name of the feature to be enabled.

#### **enabled**

Specify True to enable the feature.

## global static void setFeature (String featureName, boolean enabled, string password)

Enables a CC360 feature based on certain parameters.

### Parameters:

#### **featureName**

The name of the feature to be enabled.

#### **enabled**

Specify True to enable the feature.

#### **password**

The password to access the feature.

## global static void setFeature (String featureName, boolean enabled, String value, Date expirationDate, String password)

Enables a CC360 feature based on certain parameters.

### Parameters:

#### **featureName**

The name of the feature to be enabled.

#### **enabled**

Specify True to enable the feature.

#### **value**

The value of the feature.

**expirationDate**

The date on which the feature will expire.

**password**

The password to access the feature.

**global static void setFeature (String featureName, boolean enabled, String value, Date expirationDate)**

Enables a CC360 feature based on certain parameters.

**Parameters:****featureName**

The name of the feature to be enabled.

**enabled**

Specify True to enable the feature.

**value**

The value of the feature.

**expirationDate**

The date on which the feature will expire.

## API\_QueueManager Class Reference

Provides methods to integrate an external apex batch into Cloud MDM - Customer 360 for Salesforce (CC360) Batch Queue.

The Salesforce platform limits the number of apex batches to 5. To overcome this limit, you can integrate apex batches into the CC360 Batch Queue. This class contains two parts:

- Integrate or Insert external apex batch job into CC360 Job Queue.
- Static function that must be invoked from the external apex batch job code to be integrated.

To integrate an external apex batch job into the CC360 batch queue:

- Instantiate the CC360 Queue Manager class (API\_QueueManager qManager = new API\_QueueManager ('CustomBatch', 'ETL\_CustomApexBatchJob');)
- Set optional quick parameters (if required).
- Set optional extended parameters (if required).
- Submit the external apex job to the CC360 Batch Queue

## Static Public Attributes

- static final integer MAX\_JOBNAME\_SZ = 25

## Package Methods

- global API\_QueueManager (String jobName, String jobClassName)  
The constructor for the CC360 Queue Manager class.
- global void setQuickParameters (List< String > quickParameters)  
Sets quick parameters for the external apex job to be integrated.
- global void pushExtendedParameters (String parameterName, List< String > parameterValues)  
Pushes extended parameters for the external apex job to be integrated.
- global Id submitJob ()  
Submits the external apex batch job to the CC360 Batch Queue.
- global Id submitJob (Integer batchSize)  
Submits the external apex batch job to the CC360 Batch Queue with information about the size of the batch job.
- global Id submitJob (Boolean allowConcurrentExecution)  
Submits the external apex batch job to the CC360 Batch Queue with the flag to enable concurrent execution.
- global Id submitJob (Boolean allowConcurrentExecution, Id dependsOnQueueEntry)  
Submits the external apex batch job to the CC360 Batch Queue with the flag to enable concurrent execution and the queue ID of an existing job in the CC360 Batch Queue.
- global void setBatchSize (Integer batchSize)  
Sets the batch size for the external apex batch job to be integrated into CC360 Batch Queue.

## Static Package Functions

- global static Id start (Database.BatchableContext BC)  
Gets the queue ID from the CC360 Batch Queue using the batch ID of the apex job.
- global static void updateExecutionProgress (Id batchQueueId, Integer totalRecords, Integer itemProcessed)  
Updates the batch status with the total items available in a submitted apex job and the number of items processed by the job.
- global static void finish (Id batchQueueId, BATCH\_STATUS batchStatus)  
Triggers the next job in the queue When one submitted apex job is completed successfully.
- global static Id finish (Id batchQueueId)  
Overloaded Finish method to be used when you want to loop to next batch job.
- global static void setQuickParameters (Id batchQueueId, String phase, List< String > quickParameters)  
Sets the quick parameters for an apex job to be submitted to the CC360 Batch Queue.
- global static List< String > getQuickParameters (Id batchQueueId)  
Gets the quick parameters for the apex batch job submitted to the CC360 Batch Queue.
- global static void setExtendedParameters (Id batchQueueId, String parameterName, List< String > parameterValues)  
Updates the values of the extended parameter for the apex job submitted to the CC360 Batch Queue.
- global static void setExtendedParameters (Id batchQueueId, String parameterName, List< String > parameterValues, Boolean retainOld)  
Updates the values of the extended parameter for the apex job submitted to the CC360 Batch Queue.
- global static List< String > getExtendedParameters (Id batchQueueId, String parameterName)  
Gets the list of values of the extended parameter for the apex job submitted to the CC360 Batch Queue.

- global static Id registerJobLoop (Id batchQueueId)  
Registers a batch job loop.
- global static void submitJob (Id batchQueueId)  
Submits the specified to a batch job loop.
- global static Id registerJobLoop (Id batchQueueId, List< String > quickParameters)  
Registers a batch job loop along with quick parameters.
- global static Id registerJobLoop (Id batchQueueId, List< String > quickParameters, Boolean retainExtendedParams, Boolean skipLoopLogic)  
Registers a batch job loop along with quick parameters.
- global static void UpdateStatus (Id batchQueueId, String phase, Integer itemProcessed)  
Updates the batch status with the phase of the submitted apex job and the total items processed by the job.
- global static void UpdateStatus (Id batchQueueId, String phase, Integer itemProcessed, Boolean isItemProcessedDelta)  
Updates the batch status with the phase of the submitted apex job and the total items processed by the job.
- global static void UpdateStatus (Id batchQueueId, String phase, BATCH\_STATUS batchStatus, Integer totalRecords, Integer itemProcessed)  
Updates the batch status with:
- global static void UpdateStatus (Id batchQueueId, String phase, BATCH\_STATUS batchStatus, Integer totalRecords, Integer itemProcessed, Boolean isItemProcessedDelta)  
Updates the batch status with:
- global static String getStatus (Id batchQueueId)  
Gets the status of the submitted apex batch job from the CC360 Batch Queue.
- global static void refreshQueueManager ()  
Refreshes the CC360 Batch Queue.

## Constructor & Destructor Documentation

### global API\_QueueManager (String jobName, String jobClassName)

The constructor for the CC360 Queue Manager class.

#### Parameters:

##### **jobName**

The name of the external apex batch job to be integrated into the CC360 Batch Queue.

##### **jobClassName**

The name of the batch job class. The name must include the namespace prefix if the class is part of a managed package.

#### Exceptions:

DS_QueueManagerException	
--------------------------	--

## Method Documentation

## global static void finish (Id batchQueueId, BATCH\_STATUS batchStatus)

Triggers the next job in the queue When one submitted apex job is completed successfully.

**Note:** This method must be invoked from the external batch finish method along with the status of the apex batch.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

#### **batchStatus**

The status of the batch job (SUCCESS, ABORTED, OR FAILURE).

## global static Id finish (Id batchQueueId)

Overloaded Finish method to be used when you want to loop to next batch job.

**Note:** This method must be invoked from external batch finish method to loop to next batch job.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

### Returns:

The CC360 Batch Queue ID.

## global static List<String> getExtendedParameters (Id batchQueueId, String parameterName)

Gets the list of values of the extended parameter for the apex job submitted to the CC360 Batch Queue.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

#### **parameterName**

The name of the extended parameter.

### Returns:

The list of values of the extended parameter.

## global static List<String> getQuickParameters (Id batchQueueId)

Gets the quick parameters for the apex batch job submitted to the CC360 Batch Queue.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

### Returns:

The list of quick parameters.

### global static String getStatus (Id batchQueueId)

Gets the status of the submitted apex batch job from the CC360 Batch Queue.

The function may return any of the following values:

- Registered - Internal Status
- Waiting - Internal Status
- Looping - Internal Status
- Queued - Internal Status
- Running - Internal Status
- Completed - BATCH\_STATUS.SUCCESS
- Failed - BATCH\_STATUS.FAILURE
- Aborted - BATCH\_STATUS.ABORTED

#### Parameters:

##### **batchQueueId**

The queue ID of the submitted apex job in the CC360 Batch Queue.

#### Returns:

The current status of the job.

### global void pushExtendedParameters (String parameterName, List< String > parameterValues)

Pushes extended parameters for the external apex job to be integrated.

Each parameter is stored as a key value (list of string) pair.

**Note:** This function must be invoked multiple times to add multiple parameters.

#### Parameters:

##### **parameterName**

The name of the extended parameter to be pushed.

##### **parameterValues**

The list of values of the extended parameter.

### global static void refreshQueueManager ()

Refreshes the CC360 Batch Queue.

Invoke this function for manually refreshing the queue.

### global static Id registerJobLoop (Id batchQueueId)

Registers a batch job loop.

#### Parameters:

##### **batchQueueId**

The queue ID of a current batch job in the CC360 Batch Queue.

#### Returns:

The CC360 Batch queue ID.

### global static Id registerJobLoop (Id batchQueueId, List< String > quickParameters)

Registers a batch job loop along with quick parameters.

#### Parameters:

##### **batchQueueId**

The queue ID of a current batch job in the CC360 Batch Queue.

##### **quickParameters**

The list of quick parameters to be set. You can set a maximum of 9 quick parameters.

#### Returns:

The CC360 Batch queue ID.

### global static Id registerJobLoop (Id batchQueueId, List< String > quickParameters, Boolean retainExtendedParams, Boolean skipLoopLogic)

Registers a batch job loop along with quick parameters.

In addition, you can retain extended parameters and skip loop logic.

#### Parameters:

##### **batchQueueId**

The ID of a current batch job in the CC360 Batch Queue.

##### **quickParameters**

**Note:** The list of quick parameters to be set. No validation for quick parameters. If no quick parameters to pass, you can pass null.

##### **retainExtendedParams**

Flag to retain previously added extended parameters. If false, old parameters are deleted and added again.

##### **skipLoopLogic**

Required mainly for concurrent jobs. TRUE for non-concurrent jobs.

#### Returns:

The CC360 batch queue ID.

### global void setBatchSize (Integer batchSize)

Sets the batch size for the external apex batch job to be integrated into CC360 Batch Queue.

This function must be invoked before the submitJob functions.

#### Parameters:

##### **batchSize**

The batch size of the external apex batch job.

## Exceptions:

DS_QueueManagerException	
--------------------------	--

## global static void setExtendedParameters (Id batchQueueId, String parameterName, List< String > parameterValues)

Updates the values of the extended parameter for the apex job submitted to the CC360 Batch Queue.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

#### **parameterName**

The name of the extended parameter.

#### **parameterValues**

The list of values to be updated.

## global static void setExtendedParameters (Id batchQueueId, String parameterName, List< String > parameterValues, Boolean retainOld)

Updates the values of the extended parameter for the apex job submitted to the CC360 Batch Queue.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

#### **parameterName**

The name of the extended parameter.

#### **parameterValues**

The list of values to be updated.

#### **retainOld**

Flag to retain old parameter. If false, the old parameter is deleted and a new parameter added.

## global static void setQuickParameters (Id batchQueueId, String phase, List< String > quickParameters)

Sets the quick parameters for an apex job to be submitted to the CC360 Batch Queue.

You can set a maximum of 9 quick parameters.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

#### **phase**

The phase (Start, Execute, or Finish) of the submitted Job.

### **quickParameters**

The list of quick parameters to be set.

## **global void setQuickParameters (List< String > quickParameters)**

Sets quick parameters for the external apex job to be integrated.

### **Parameters:**

#### **quickParameters**

The list of quick parameters to be set. You can set a maximum of 9 quick parameters.

### **Exceptions:**

DS_QueueManagerException	
--------------------------	--

## **global static Id start (Database.BatchableContext BC)**

Gets the queue ID from the CC360 Batch Queue using the batch ID of the apex job.

**Note:** This function must be invoked from the external batch start method.

### **Parameters:**

#### **BC**

The external apex batch job context.

### **Returns:**

Id The CC360 batch queue ID.

## **global Id submitJob (Integer batchSize)**

Submits the external apex batch job to the CC360 Batch Queue with information about the size of the batch job.

### **Parameters:**

#### **batchSize**

The size of the batch. The input batch size overrides the batch size configured as part of Performance Settings in CC360.

### **Returns:**

The job ID in the CC360 Batch Queue.

### **Exceptions:**

DS_QueueManagerException	
--------------------------	--

## **global static void submitJob (Id batchQueueId)**

Submits the specified to a batch job loop.

**Note:** This function must be invoked immediately after 'registerJobLoop'.

#### Parameters:

##### **batchQueueId**

The queue ID in the CC360 Batch Queue.

#### global Id submitJob (Boolean allowConcurrentExecution, Id dependsOnQueueEntry)

Submits the external apex batch job to the CC360 Batch Queue with the flag to enable concurrent execution and the queue ID of an existing job in the CC360 Batch Queue.

The concurrent execution depends on the queue ID of the existing job.

#### Parameters:

##### **allowConcurrentExecution**

If TRUE, the job is enabled for concurrent execution.

##### **dependsOnQueueEntry**

The queue ID of an existing job in the CC360 Batch Queue.

#### Returns:

The job ID in the CC360 Batch Queue.

#### Exceptions:

DS_QueueManagerException	
--------------------------	--

#### global Id submitJob (Boolean allowConcurrentExecution)

Submits the external apex batch job to the CC360 Batch Queue with the flag to enable concurrent execution.

#### Parameters:

##### **allowConcurrentExecution**

If TRUE, the job is enabled for concurrent execution.

#### Returns:

The job ID in the CC360 Batch Queue.

#### Exceptions:

DS_QueueManagerException	
--------------------------	--

#### global Id submitJob ()

Submits the external apex batch job to the CC360 Batch Queue.

#### Returns:

The job ID in the CC360 Batch Queue.

## global static void updateExecutionProgress (Id batchQueueId, Integer totalRecords, Integer itemProcessed)

Updates the batch status with the total items available in a submitted apex job and the number of items processed by the job.

**Note:** This function must be invoked from the external batch execute method.

### Parameters:

#### **batchQueueId**

The queue ID in the CC360 Batch Queue.

#### **totalRecords**

The total records present in the batch job.

#### **itemProcessed**

The number of records processed by the job.

## global static void UpdateStatus (Id batchQueueId, String phase, BATCH\_STATUS batchStatus, Integer totalRecords, Integer itemProcessed)

Updates the batch status with:

The phase and status of the submitted apex job.

The total number of items in the apex job and the number of items processed by the job.

### Parameters:

#### **batchQueueId**

The queue ID of the submitted apex job in the CC360 Batch Queue.

#### **phase**

The phase of the job (Start, Execute, or Finish).

#### **batchStatus**

The status of the job (SUCCESS, ABORTED, OR FAILURE).

#### **totalRecords**

The total number of items in the job.

#### **itemProcessed**

The Total number of items processed by job.

## global static void UpdateStatus (Id batchQueueId, String phase, Integer itemProcessed, Boolean isItemProcessedDelta)

Updates the batch status with the phase of the submitted apex job and the total items processed by the job.

This function also checks if the items processed are delta items.

### Parameters:

#### **batchQueueId**

The queue ID of the submitted apex job in the CC360 Batch Queue.

**phase**

The phase of the job (Start, Execute, or Finish).

**itemProcessed**

The Total number of items processed by job.

**isItemProcessedDelta**

If True, the items are added to the total number of items processed for the itemProcessed parameter.

[global static void UpdateStatus \(Id batchQueueId, String phase, BATCH\\_STATUS batchStatus, Integer totalRecords, Integer itemProcessed, Boolean isItemProcessedDelta\)](#)

Updates the batch status with:

The phase and status of the submitted apex job.

The total number of items in the apex job and the number of items processed by the job. In addition, this function also checks if the items processed are delta items.

[Parameters:](#)

**batchQueueId**

The queue ID of the submitted apex job in the CC360 Batch Queue.

**phase**

The phase of the job (Start, Execute, or Finish).

**batchStatus**

The status of the job (SUCCESS, ABORTED, OR FAILURE).

**totalRecords**

The total number of items in the job.

**itemProcessed**

The Total number of items processed by job.

**isItemProcessedDelta**

If True, the items are added to the total number of items processed for the itemProcessed parameter.

[global static void UpdateStatus \(Id batchQueueId, String phase, Integer itemProcessed\)](#)

Updates the batch status with the phase of the submitted apex job and the total items processed by the job.

[Parameters:](#)

**batchQueueId**

The queue ID of the submitted job in the CC360 Batch Queue.

**phase**

The phase of the job (Start, Execute, or Finish).

### **itemProcessed**

The Total number of items processed by the submitted apex job.

## Member Data Documentation

final integer MAX\_JOBNAME\_SZ = 25 [static]

# API\_SettingsManager Class Reference

Provides methods to manage the different custom settings in Cloud MDM - Customer 360 for Salesforce (CC360).

You can retrieve the following settings:

- CC360 settings.
- Account synchronization settings.
- Contact synchronization settings.
- Lead synchronization settings.
- Account enrichment settings.
- Synchronization settings.
- Matching settings.
- Source settings.
- Performance settings.

In addition, you can perform the following tasks:

- Update a custom setting with a value or long value.
- Enrich the hierarchy of an account.
- Enable the comparison of a leads and contacts associated with person accounts.
- Set master response size.
- Enable default job priority.

## Static Package Functions

- global static DS\_Settings\_\_c getDataScoutSettings ()
- global static DS\_Settings\_\_c getCloudMDMSettings ()  
Gets the CC360 settings.
- global static DS\_SF\_Synchronization\_Settings\_\_c getAccountSyncSettings ()  
Gets the synchronization settings for accounts.
- global static DS\_SF\_Synchronization\_Settings\_\_c getAccountSyncSettings (String recType)  
Gets the synchronization settings of the specified account record type.
- global static DS\_SF\_Synchronization\_Settings\_\_c getPersonAccountSyncSettings ()  
Gets the synchronization settings of person accounts.
- global static DS\_SF\_Synchronization\_Settings\_\_c getPersonAccountSyncSettings (String recType)  
Gets the synchronization settings of the specified person account record type.

- `global static DS_SF_Synchronization_Settings__c getContactSyncSettings ()`  
Gets the synchronization settings for contacts.
- `global static DS_SF_Synchronization_Settings__c getContactSyncSettings (String recType)`  
Gets the synchronization settings of the specified contact record type.
- `global static DS_SF_Synchronization_Settings__c getLeadSyncSettings ()`  
Gets the synchronization settings for leads.
- `global static DS_SF_Synchronization_Settings__c getLeadSyncSettings (String recType)`  
Gets the synchronization settings of the specified lead record type.
- `global static DS_SF_Enrichment_Settings__c getAccountEnrichmentSettings ()`  
Gets the enrichment settings for accounts.
- `global static DS_SF_Enrichment_Settings__c getAccountEnrichmentSettings (String recType)`  
Gets the enrichment settings of the specified account record type.
- `global static DS_SF_Synchronization_Settings__c getSyncSettings (String objectName)`  
Gets the synchronization settings for the specified object.
- `global static DS_SF_Synchronization_Settings__c getSyncSettings (String objectName, String recType)`  
Gets the synchronization settings of the record type of the specified object.
- `global static DS_Matching__c getMatchingSettings (String objectClass, String recordTypeName)`  
Gets the matching settings for the specified object class and record type.
- `global static DS_Sources__c getSourceSettings (String sourceName)`  
Gets the source settings for the specified source.
- `global static DS_Sources__c getSourceSettings (String sourceName, String recTypeName)`  
Gets the source settings of the record type of the specified source.
- `global static DS_Performance__c getPerformanceSettings (String performanceSettingName)`  
Gets the performance settings for the specified setting name.
- `global static void updateInternalSetting (String internalSettingName, String value)`  
Updates an internal setting with the specified value.
- `global static void updateInternalSetting (String internalSettingName, long value)`  
Updates a custom setting setting with the specified long value.
- `global static void enableLeadPersonAccountComparison (boolean value)`  
If this setting is set to True, the duplicate bean check job identifies duplicates for contacts and leads associated with a person account.
- `global static void enableHierarchyAccountEnrichment (boolean value)`  
If this setting is set to True, any update to bean because of a hierarchy operation is cascaded to accounts also.
- `global static void enableDefaultPriorityForRunAutomatic (boolean value)`  
Enables the default priority for batch jobs that are flagged to run automatically.
- `global static void setMasterDataResponseSize (Integer value)`  
Allows you to limit the number of responses from the Hub Org to a Spoke Org.
- `global static void enableQueueMonitorAutomaticRefresh (Integer value)`  
Allows you to enable or disable the automatic refresh capability of the Queue Monitor.
- `global static void resetExecutionManager ()`  
Allows you to reset the execution manager.
- `global static Map<String,String> getInternalSettings ()`  
Returns values for all internal settings. If any internal setting does not have a value, then the default value is returned.
- `global static void enableExtractCountryFromPicklist (boolean value)`

Allows you to enable or disable extraction of Country Text from Country Picklists for Standard Address fields.

- `global static void resetDefaultRecordTypesValues ()`  
Resets the default record types that you explicitly set in the Default Record Type For Account and Default Record Type For Person Account internal settings.
- `global static boolean resetInternalSetting (String settingName)`  
Resets the value of the specified internal setting.
- `global static String getInternalSettingValue (String settingName)`  
Gets the value of the specified internal setting.
- `global static object getConfig (String configName, List<object> params)`  
Gets the settings for the specified configuration and passes a list of parameters to the configuration.

## Method Documentation

### `global static void enableHierarchyAccountEnrichment (boolean value)`

If this setting is set to True, any update to bean because of a hierarchy operation is cascaded to accounts also.

This is set to True by default.

#### Parameters:

##### **value**

Specify False to disable updates to the account from the beans during a hierarchy operation. If you set the value to False, the account is not updated with information from the beans in the hierarchy. In this case, run the Synchronize Reporting Data batch job to ensure there is no inconsistency between the account and the corresponding beans. You can run this job from the CC360 Queue Manager console.

### `global static void enableLeadPersonAccountComparison (boolean value)`

If this setting is set to True, the duplicate bean check job identifies duplicates for contacts and leads associated with a person account.

This is set to False by default.

#### Parameters:

##### **value**

Specify True to check for duplicate contacts and leads associated with person accounts.

### `global static DS_SF_Enrichment_Settings__c getAccountEnrichmentSettings ()`

Gets the enrichment settings for accounts.

#### Returns:

Account enrichment settings.

## global static DS\_SF\_Enrichment\_Settings\_\_c getAccountEnrichmentSettings (String recType)

Gets the enrichment settings of the specified account record type.

### Parameters:

#### **recType**

Name of the account record type for which you want to retrieve the enrichment settings.

### Returns:

Enrichment settings of the specified account record type.

## global static DS\_SF\_Synchronization\_Settings\_\_c getAccountSyncSettings ()

Gets the synchronization settings for accounts.

### Returns:

Account synchronization settings.

## global static DS\_SF\_Synchronization\_Settings\_\_c getAccountSyncSettings (String recType)

Gets the synchronization settings of the specified account record type.

### Parameters:

#### **recType**

Name of the account record type for which you want to retrieve the synchronization settings.

### Returns:

Synchronization settings of the specified account record type.

## global static DS\_SF\_Synchronization\_Settings\_\_c getPersonAccountSyncSettings ()

Gets the synchronization settings of person accounts.

### Returns:

Person account synchronization settings.

## global static DS\_SF\_Synchronization\_Settings\_\_c getPersonAccountSyncSettings (String recType)

Gets the synchronization settings of the specified person account record type.

### Parameters:

#### **recType**

Name of the person account record type for which you want to retrieve the synchronization settings.

### Returns:

Synchronization settings of the specified person account record type.

### `global static DS_Settings__c getCloudMDMSettings ()`

Gets the CC360 settings.

**Returns:**

CC360 settings.

### `global static DS_SF_Synchronization_Settings__c getContactSyncSettings ()`

Gets the synchronization settings for contacts.

**Returns:**

Contact synchronization settings.

### `global static DS_SF_Synchronization_Settings__c getContactSyncSettings (String recType)`

Gets the synchronization settings of the specified contact record type.

**Parameters:**

**recType**

Name of the contact record type for which you want to retrieve the synchronization settings.

**Returns:**

Synchronization settings of the specified contact record type.

### `global static DS_Settings__c getDataScoutSettings ()`

**Deprecated:**

Use the `getCloudMDMSettings ()` method instead.

### `global static DS_SF_Synchronization_Settings__c getLeadSyncSettings ()`

Gets the synchronization settings for leads.

**Returns:**

Lead synchronization settings.

### `global static DS_SF_Synchronization_Settings__c getLeadSyncSettings(String recType)`

Gets the synchronization settings of the specified lead record type.

**Parameters:**

**recType**

Name of the lead record type for which you want to retrieve the synchronization settings.

**Returns:**

Synchronization settings of the specified lead record type.

## global static DS\_Matching\_\_c getMatchingSettings (String objectClass, String recordTypeName)

Gets the matching settings for the specified object class.

### Parameters:

#### **objectClass**

The name of the object class, such as account, contact, or lead.

#### **recordTypeName**

Record type associated with the specified object class.

### Returns:

Matching settings.

## global static DS\_Performance\_\_c getPerformanceSettings (String jobName)

Gets the performance settings for the specified batch job.

### Parameters:

#### **jobName**

The name of the batch job.

### Returns:

Performance settings.

## global static DS\_Sources\_\_c getSourceSettings (String sourceName)

Gets the source settings for the specified source.

### Parameters:

#### **sourcename**

The name of the source for which you want to get the settings.

### Returns:

Source settings.

## global static DS\_Sources\_\_c getSourceSettings (String sourceName, String recTypeName)

Gets the source settings of the record type of the specified source.

### Parameters:

#### **sourceName**

Name of the source to which the specified record type belongs.

#### **recTypeName**

Record type name of the specified source for which you want to retrieve the source settings.

### Returns:

Source settings of the record type of the specified source.

## global static DS\_SF\_Synchronization\_Settings\_\_c getSyncSettings (String objectName)

Gets the synchronization settings for the specified object type.

### Parameters:

#### **objectname**

The name of the object, such as account, contact, or lead.

### Returns:

Synchronization settings.

## global static DS\_SF\_Synchronization\_Settings\_\_c getSyncSettings (String objectName, String recType)

Gets the synchronization settings of the record type of the specified object.

### Parameters:

#### **objectname**

Name of the object to which the specified record type belongs.

#### **recType**

Record type name of the specified object for which you want to retrieve the synchronization settings.

### Returns:

Synchronization settings of the record type of the specified object.

## global static void updateInternalSetting (String internalSettingName, String value)

Updates an internal setting with the specified value.

### Parameters:

#### **internalSettingName**

The name of the internal setting to be updated.

#### **value**

The value that will be updated for the internal setting.

## global static void updateInternalSetting (String internalSettingName, long value)

Updates an internal setting with the specified long value.

### Parameters:

#### **internalSettingName**

The name of the setting to be updated.

#### **value**

The long value that will be updated for the internal setting.

### global static void enableDefaultJobPriorityForRunAutomatic (boolean value)

Enables the default priority for batch jobs that are flagged to run automatically.

#### Parameters:

##### value

Set to True to run the batch jobs automatically with default priorities that CC360 assigns.

### global static void setMasterDataResponseSize (Integer value)

Allows you to limit the number of responses from the Hub Org to Spoke Orgs.

#### Parameters:

##### value

The number of responses that will be sent from the Hub Org to Spoke Orgs.

### global static void enableQueueManagerAutomaticRefresh (boolean value)

Allows you to enable or disable the automatic refresh capability of the Queue Monitor.

#### Parameters:

##### value

Set to True to enable automatic refresh.

### global static void resetExecutionManager ()

Allows you to reset the execution manager.

### global static Map<String, String> getInternalSettings ()

Returns values for all internal settings. If any internal setting does not have a value, then the default value is returned.

### global static void enableExtractCountryFromPicklist (boolean value)

Allows you to enable or disable extraction of Country Text from Country picklists for standard address fields. This should be enabled only if Country picklists have been enabled in the Org.

#### Parameters:

##### value

Set to True to enable extraction of Country Text from Country Picklists for Standard address fields.

### global static void resetDefaultRecordTypesValues ()

Resets the default record types that you explicitly set in the Default Record Type For Account and Default Record Type For Person Account internal settings.

You can use the `updateInternalSetting(String, String)` method to explicitly set the default record types for business or person accounts.

### global static boolean resetInternalSetting (String settingName)

Resets the value of the specified internal setting.

#### Parameters:

##### **settingName**

Name of the internal setting that you want to reset.

#### Returns:

True if the internal setting is reset or false if the internal setting is not reset.

### global static String getInternalSettingValue(String settingName)

Gets the value of the specified internal setting. If the value of the internal setting is not set, this method returns the default value of the internal setting.

#### Parameters:

##### **settingName**

Name of the internal setting for which you want to retrieve the value.

### global static object getConfig (String configName, List<object> params)

Gets the settings for the specified configuration and passes a list of parameters to the configuration.

#### Parameters:

##### **configName**

Name of the configuration for which you want to retrieve the settings.

##### **params**

List of parameters that you want to pass to the specified configuration.

## Deprecated List

### Member `API_SettingsManager.getDataScoutSettings ()`

Use the `getCloudMDMSSettings ()` method instead.