



Informatica® Multidomain MDM
10.3 HotFix 1

Installation Guide for Microsoft SQL Server with Oracle WebLogic

Informatica Multidomain MDM Installation Guide for Microsoft SQL Server with Oracle WebLogic
10.3 HotFix 1
March 2019

© Copyright Informatica LLC 2001, 2019

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, and ActiveVOS are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at <https://www.informatica.com/trademarks.html>. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2019-04-18

Table of Contents

Preface	7
Informatica Resources.	7
Informatica Network.	7
Informatica Knowledge Base.	7
Informatica Documentation.	7
Informatica Product Availability Matrices.	8
Informatica Velocity.	8
Informatica Marketplace.	8
Informatica Global Customer Support.	8
 Chapter 1: Installation Overview.....	 9
Multidomain MDM Installation.	9
Installation Topology.	11
Installation Tasks.	11
 Chapter 2: Pre-Installation Tasks.....	 12
Prepare for Installation.	12
Prepare the Environment.	13
Set Up the Database Environment.	14
Step 1. Install and Configure Microsoft SQL Server.	15
Step 2. Create a Microsoft SQL Server Data File Store.	16
Step 3. Install ODBC Driver.	16
Step 4. Create the ActiveVOS Database.	16
Set Up the Application Server Environment.	17
Configure the Java Virtual Machines.	17
Disable WebLogic Server Authentication.	20
Create the ActiveVOS Console Administrative User.	20
Additional Application Server Configuration (Optional).	21
Configuring WebLogic for Standalone Process Server Instances.	21
Configuring WebLogic for Multiple MDM Hub Master Databases.	24
Configuring the HTTPS Protocol.	24
Configuring the JTA Timeout for Informatica Platform.	24
Configure the Properties Files for Silent Installation.	24
Configuring the Informatica Platform Properties File.	25
Configuring the Hub Server Properties File.	25
Configuring the Process Server Properties File.	25
 Chapter 3: Hub Store Installation.....	 26
Create the MDM Hub Master Database.	26
Create an Operational Reference Store.	27

Import the Metadata into the MDM Hub Master Database.	28
Import the Metadata into the Operational Reference Store.	29
Chapter 4: Hub Server Installation.	31
Hub Server Installation Modes.	31
Installing the Hub Server in Graphical Mode.	31
Installing the Hub Server in Console Mode.	35
Generating a Silent Installation Properties File.	38
Installing the Hub Server in Silent Mode.	38
Installing the Hub Server on Environments with Managed Servers.	39
Chapter 5: Hub Server Post-Installation Tasks.	43
Copy the Installation Log Files.	44
Verify the Version and Build Number.	44
Installing and Configuring Elasticsearch.	45
Configure the MDM Hub Master Database Name.	45
Verify and Configure Application Server Settings (Conditional).	45
Editing the Application Server Settings.	45
Configuring the Hub Server Properties on Environments with Managed Servers.	46
Deploy the Hub Server Applications (Conditional).	46
Using a Script for Deploying the Hub Server Applications (Conditional).	47
Manually Deploying the Hub Server Applications (Conditional).	49
Step 1. Creating Data Sources.	49
Step 2. Configuring JMS Message Queues.	51
Step 3. Repackaging the Hub Server EAR Files.	53
Step 4. Deploying the Hub Server Application.	54
Step 5. Configuring JMS Message Queues on the Hub Server.	55
Step 6. Configuring Server Resources for Informatica Data Director.	56
Restart WebLogic.	57
Configuring Metadata Caching (Optional).	57
Editing Infinispan Attributes.	58
Starting the Hub Console.	59
Registering an Operational Reference Store.	59
Chapter 6: Process Server Installation.	61
Process Server Installation Modes.	61
Installing the Process Server in Graphical Mode.	61
Installing the Process Server in Console Mode.	63
Installing the Process Server in Silent Mode.	65
Installing the Process Server on Environments with Managed Servers.	65
Chapter 7: Process Server Post-Installation Tasks.	68
Copy the Installation Log Files.	68

Verify the Version and Build Number.	69
Deploy the Process Server Application (Conditional).	69
Step 1. Creating Data Sources (Conditional).	70
Step 2. Deploying the Process Server Application (Conditional).	72
Step 3. Specify the Targets for Deployments In Environments with Managed Servers (Conditional).	73
Enabling Secured Communications for Process Servers.	74
Installing and Configuring Elasticsearch.	75
Configure Match Population.	75
Enabling Match Population.	75
Configuring the Process Server with Cleanse Engines.	76

Chapter 8: ActiveVOS Post-Installation Tasks for the Application Server..... 77

Create a Trusted User in WebLogic Environments.	77
Configure WebLogic for Secure ActiveVOS Communication.	78
Editing the Default Security Realm.	78
Adding ActiveVOS Roles.	78
Configure Users and Groups in WebLogic.	79
Creating Groups.	79
Adding Users.	79
Editing the abTaskClient Role.	80

Chapter 9: ActiveVOS Post-Installation Tasks for the Business Entity Adapter..... 81

ActiveVOS Web Applications.	81
Configuring the ActiveVOS URNs for the Business Entity Workflow Adapter.	82
Set the ActiveVOS Protocol to HTTPS.	82
Configure the Primary Workflow Engine.	83
Configure the MDM Identity Services for ActiveVOS.	83
Configure Tasks.	84

Chapter 10: Resource Kit Installation..... 85

Setting Up the MDM Hub Sample Operational Reference Store.	85
Registering the Informatica MDM Hub Sample Operational Reference Store.	87
Installing the Resource Kit in Graphical Mode.	88
Installing the Resource Kit in Console Mode.	91
Installing the Resource Kit in Silent Mode.	93
Configuring the Properties File.	94
Running the Silent Installer.	96

Chapter 11: Troubleshooting the MDM Hub..... 97

Troubleshooting the Installation Process.	97
---	----

Chapter 12: Uninstallation.....	100
Uninstallation Overview.	100
Uninstalling the Hub Store.	100
Uninstalling the Process Server in Graphical Mode.	101
Uninstalling the Process Server in Graphical Mode On UNIX.	101
Uninstalling the Process Server in Graphical Mode On Windows.	101
Uninstalling the Hub Server in Graphical Mode.	102
Uninstalling the Hub Server in Graphical Mode on UNIX.	102
Uninstalling the Hub Server in Graphical Mode on Windows.	102
Uninstalling the Resource Kit in Graphical Mode.	102
Uninstalling the Resource Kit in Graphical Mode on UNIX.	102
Uninstalling the Resource Kit in Graphical Mode on Windows.	103
Uninstalling the Process Server in Console Mode.	103
Uninstalling the Hub Server in Console Mode.	103
Uninstalling the Resource Kit in Console Mode.	104
Manually Undeploying the Process Server.	104
Manually Undeploying the Hub Server.	104
 Index.	 105

Preface

The *Multidomain MDM Installation Guide* is written for database administrators, system administrators, and implementers who are responsible for installing and setting up the Informatica® MDM Hub. This guide assumes that you have knowledge of operating systems, database environments, and your application server.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit <https://network.informatica.com>.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit <https://search.informatica.com>. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit <https://docs.informatica.com>.

Informatica maintains documentation for many products on the Informatica Knowledge Base in addition to the Documentation Portal. If you cannot find documentation for your product or product version on the Documentation Portal, search the Knowledge Base at <https://search.informatica.com>.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at <https://network.informatica.com/community/informatica-network/product-availability-matrices>.

Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services and based on real-world experiences from hundreds of data management projects. Informatica Velocity represents the collective knowledge of Informatica consultants who work with organizations around the world to plan, develop, deploy, and maintain successful data management solutions.

You can find Informatica Velocity resources at <http://velocity.informatica.com>. If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at ips@informatica.com.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at <https://marketplace.informatica.com>.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:

<https://www.informatica.com/services-and-training/customer-success-services/contact-us.html>.

To find online support resources on the Informatica Network, visit <https://network.informatica.com> and select the eSupport option.

CHAPTER 1

Installation Overview

This chapter includes the following topics:

- [Multidomain MDM Installation, 9](#)
- [Installation Topology, 11](#)
- [Installation Tasks, 11](#)

Multidomain MDM Installation

Multidomain MDM is a master data management solution that enhances data reliability and data maintenance procedures. Multidomain MDM is also referred to as the MDM Hub. You can access the MDM Hub features through the Hub Console.

The MDM Hub consists of multiple components. You can install the MDM Hub in the graphical mode, the console mode, or the silent mode.

Core Components

The following table describes the core installation components:

Component	Description
MDM Hub Master Database	A schema that stores and consolidates business data for the MDM Hub. Contains the MDM Hub environment configuration settings, such as user accounts, security configuration, Operational Reference Store registry, and message queue settings. You can access and manage an Operational Reference Store from an MDM Hub Master Database. The default name of an MDM Hub Master Database is CMX_SYSTEM, but you can use a custom name. You can create multiple MDM Hub Master Databases, each with its own set of Operational Reference Stores, in the same database instance.
Operational Reference Store	A schema that stores and consolidates business data for the MDM Hub. Contains the master data, content metadata, and the rules to process and manage the master data. You can configure separate Operational Reference Store databases for different geographies, different organizational departments, and for the development and production environments. You can distribute Operational Reference Store databases across multiple server machines. The default name of an Operational Reference Store is CMX_ORS.
Hub Server	A J2EE application that you deploy on an application server. The Hub Server processes data stored within the MDM Hub and integrates the MDM Hub with external applications. The Hub Server manages core and common services for the MDM Hub.

Component	Description
Process Server	A J2EE application that you deploy on an application server. The Process Server processes batch jobs such as load, recalculate BVT, and revalidate, and performs data cleansing and match operations. The Process Server interfaces with the cleanse engine that you configure to standardize and optimize data for match and consolidation.
Provisioning tool	A tool to build business entity models, and to configure the Entity 360 framework for Data Director. After you build business entity models, you can publish the configuration to the MDM Hub.
Informatica ActiveVOS [®]	<p>A business process management (BPM) tool that is required internally by the MDM Hub for processing data. Informatica ActiveVOS supports automated business processes, including change-approval processes for data. You can also use Informatica ActiveVOS to ensure that changes to master data undergo a review-and-approval process before inclusion in the best version of the truth (BVT) records.</p> <p>When you install ActiveVOS Server as part of the Hub Server installation, you install the ActiveVOS Server, ActiveVOS Console, and Process Central. Also, you install predefined MDM workflows, tasks, and roles.</p>
Data Director (IDD)	A user interface to master and manage the data that is stored in the MDM Hub. In IDD, data is organized by business entities, such as customers, suppliers, and employees. Business entities are data groups that have significance for organizations.

Optional Components

The following table describes the optional installation components:

Component	Description
Resource Kit	Set of samples, applications, and utilities to integrate the MDM Hub into your applications and workflows. You can select the Resource Kit components that you want to install.
Informatica platform	<p>An environment that comprises the Informatica services and Informatica clients that you use to cleanse and transfer source data to the MDM Hub. You can use Informatica platform instead of the cleanse functions available in the MDM Hub to cleanse data.</p> <p>When you install the Informatica platform as part of the Hub Server installation, you install the Data Integration Service, Model Repository Service, and Informatica Developer (the Developer tool).</p>
Dynamic Data Masking	A data security tool that operates between the MDM Hub and databases to prevent unauthorized access to sensitive information. Dynamic Data Masking intercepts requests sent to databases and applies data masking rules to the request to mask the data before it is sent back to the MDM Hub.
Informatica Data Controls (IDC)	<p>Applicable to Informatica Data Director (IDD) based on the subject area data model only.</p> <p>IDC is a set of user interface controls that expose the MDM Hub data in third-party applications that are used by business users.</p>

Installation Topology

Before you install the MDM Hub, decide on the installation topology. Usually, infrastructure planners and Master Data Management solution architects determine on the topology to implement.

You can install the MDM Hub in multiple environments, such as development, test, and production. The requirements and priorities for each type of environment are unique. Therefore, the installation topology differs for each environment.

The following table describes the MDM Hub installation topologies that you can use:

Topology	Description
Standalone application server instance	All the MDM Hub components are installed on a standalone application server instance.
Multiple application server instances	The MDM Hub components are installed on multiple application server instances.
Application server cluster	The MDM Hub components are installed in an application server cluster.

For more information about installation topologies, see the *Multidomain MDM Infrastructure Planning Guide*.

Note: All the components of the MDM Hub implementation must have the same version. If you have multiple versions of the MDM Hub, install each version in a separate environment.

Installation Tasks

Complete the preinstallation tasks before you install the MDM Hub components. After the installation, complete the post-installation tasks.

To install the MDM Hub, perform the following tasks:

1. Complete the preinstallation tasks. To ensure that you can successfully run the installers for the Hub Server and the Process Server and create the Hub Store, complete the pre-installation tasks.
2. Create the MDM Hub Master Database. Create the MDM Hub Master Database before you install the Hub Server and the Process Server.
Use the setup script provided with the MDM Hub distribution to create the MDM Hub Master Database.
3. Create the Operational Reference Store. Create Operational Reference Stores at any time after you complete the preinstallation tasks.
Use the setup script provided with the MDM Hub distribution to create the Operational Reference Store.
4. Install the Hub Server. Use the MDM Hub installer to install the Hub Server.
5. Install the Process Server. Use the MDM Hub installer to install the Process Server.
6. Perform the post-installation configuration tasks. Test the database connections. To ensure that you can use the MDM Hub features, configure the Hub Server and the Process Server.

CHAPTER 2

Pre-Installation Tasks

This chapter includes the following topics:

- [Prepare for Installation, 12](#)
- [Prepare the Environment, 13](#)
- [Set Up the Database Environment, 14](#)
- [Set Up the Application Server Environment, 17](#)
- [Additional Application Server Configuration \(Optional\), 21](#)
- [Configure the Properties Files for Silent Installation, 24](#)

Prepare for Installation

Before you install the MDM Hub, prepare for the installation.

The following table describes the preparatory tasks for the installation:

Task	Description
Read the Release Notes	Read the latest <i>Multidomain MDM Release Notes</i> for updates to the installation and upgrade process. Important: Some versions of application servers and databases have known limitations when running Multidomain MDM. Ensure that you perform all suggested workarounds.
Read the Product Availability Matrix	Read the Product Availability Matrix (PAM) for information about product requirements and supported platforms. You can access PAMs at https://network.informatica.com/community/informatica-network/product-availability-matrices .
Understand the MDM infrastructure and architecture plan	Acquire and understand the plan for the MDM infrastructure and architecture from the infrastructure planners or the MDM solution architects in your organization. For more information about infrastructure planning and MDM architecture, see the <i>Multidomain MDM Infrastructure Planning Guide</i> .

Task	Description
Download and extract the installer files	<p>Download the installation files from the Informatica Electronic Software Download site to a directory on your machine. To extract the compressed files, use an extraction utility that also extracts empty folders.</p> <p>Download and extract the following installation files:</p> <ul style="list-style-type: none"> - MDM Hub installer for the operating system - Database files - ActiveVOS Server installer for the operating system <p>If you intend to install Informatica platform, download the following files:</p> <ul style="list-style-type: none"> - Informatica platform server installation files for the operating system - Informatica platform client installation files
Verify license key	<p>Verify that you have the license key, which is in an email message from Informatica. Copy the license key file to a directory accessible to the user account that installs the product.</p> <p>If you do not have a license key, contact Informatica Global Customer Support.</p>
Create an installation documentation directory	<p>Create a directory to store copies of installation files, such as the validation results, environment reports, database debug logs, and log files.</p> <p>For example, create the directory install_doc. To troubleshoot the installation, you can create an archive file of the installation documentation directory and send it to Informatica Global Customer Support for analysis.</p>

Prepare the Environment

Before you install the MDM Hub, prepare the installation environment.

The following table describes the tasks you perform to prepare the environment for the installation:

Task	Description
Verify minimum system requirements	<p>Verify that the machines meet the hardware and software requirements for the MDM Hub installation. The hardware requirements are dependent on the data, processing volumes, and business rules.</p> <p>To install the MDM Hub, the machines must meet the following minimum requirements:</p> <ul style="list-style-type: none"> - Disk space. 4.9 GB - RAM for the development environment. 4 GB <p>To verify the run-time physical memory requirements of the MDM Hub components, use the following formula:</p> $\text{Total run-time memory requirement for MDM Hub components} = \text{JDK JVM max heap size of the application server} + \text{operating system native heap size}$
Install Java Development Kit (JDK)	<p>Install a supported version of the JDK on the machine on which you want to install the MDM Hub. The JDK is not bundled with the MDM Hub installers.</p> <p>Note: Use the same Java version on the application server machines and on the machines on which you want to launch the Hub Console.</p> <p>If you want to install Informatica platform on HP-UX, install the supported version of the JDK on the HP-UX machine. The JDK is not bundled with the Informatica platform installer for HP-UX. The JDK is bundled with the Informatica platform installers for all other platforms.</p>

Task	Description
Install Visual C++ Redistributable for Visual Studio 2015 on Windows only	On Windows systems, Multidomain MDM requires Visual C++ Redistributable for Visual Studio 2015 to support the name search feature and the matching feature.
Set environment variables	<p>Set the environment variables for the MDM Hub installation.</p> <p>To use the correct JDK, set the following environment variables to point to the JDK directory:</p> <ul style="list-style-type: none"> - JAVA_HOME. Required - PATH. Required - INFA_JDK_HOME. Optional. Required if you want to install Informatica platform on AIX or HP-UX. <p>If you want to install Informatica platform with security enabled for the domain, set the INFA_TRUSTSTORE environment variable to point to the following directory:</p> <pre><Informatica platform installation directory>/Client/clients/shared/security</pre>
Set the operating system locale	Set the same operating system locale for the Hub Server, the MDM Hub Master Database, Operational Reference Store, and the Hub Console.
Set up the X Window System on UNIX	If you want to run the installer in graphical mode on UNIX, set up an X Window System. An X Window System is a graphics display server. For more information about setting up an X Window System, see the documentation for your operating system.
Disable access to the root welcome page for your application server	To improve security, disable access to the root welcome page for your application server. For instructions, see the documentation for your application server.
Disable insecure TLS cipher suites	<p>To improve security, in the Java runtime environment that is used with Multidomain MDM, disable insecure TLS cipher suites.</p> <ol style="list-style-type: none"> 1. Open the following file: <code>./jdk<version>/jre/lib/security/java.security</code> 2. Find the property <code>jdk.tls.disabledAlgorithms</code> and update the value to include the following list of insecure cipher suites: <pre>jdk.tls.disabledAlgorithms = SSLv3, RC4, MD5withRSA, DH keySize < 1024, EC keySize < 224, DES40_CBC, RC4_40, 3DES_EDE_CBC, EDH-RSA-DES-CBC3-SHA, ECDHE-RSA-DES-CBC3-SHA, DES-CBC3-SHA</pre> <p>For more information about the property, see the documentation for your JDK.</p>

For more information about product requirements and supported platforms, see the Product Availability Matrix on Informatica Network:

<https://network.informatica.com/community/informatica-network/product-availability-matrices>

Set Up the Database Environment

Before you create an MDM Hub Master Database and Operational Reference Store, set up the database environment.

To set up the database environment, perform the following tasks:

1. Install and configure Microsoft SQL Server.
2. Create a data file store.

3. Install ODBC driver.
4. Create the ActiveVOS[®] schema.

Step 1. Install and Configure Microsoft SQL Server

You can install and configure Microsoft SQL Server according to the instructions in the Microsoft SQL Server documentation.

The following table describes the Microsoft SQL Server installation and configuration tasks:

Tasks	Description
Install Microsoft SQL Server	Install the supported version of Microsoft SQL Server. Note: Ensure that you specify mixed mode as the database engine authentication security mode.
Configure distributed transactions	Configure Microsoft SQL Server for distributed transactions because the MDM Hub requires a distributed transactions environment. To configure Microsoft SQL Server for distributed transactions, enable MS DTC for XA transactions, and configure the JDBC distributed transactions component.
Enable the TCP/IP network protocol	Configure Microsoft SQL Server to use the TCP/IP network protocol that the MDM Hub environment requires.

Configuring Microsoft SQL Server for Distributed Transactions

Before you start Microsoft SQL Server, ensure that you configure it for distributed transactions. The MDM Hub requires a distributed transaction environment.

1. To ensure that the Microsoft Distributed Transaction Coordinator (MS DTC) service starts when you start Microsoft SQL Server, mark MS DTC as Automatic in the Service Manager.
2. Enable MS DTC for XA transactions.
3. Enable MS DTC for SNA LU 6.2 transactions.
4. Configure the JDBC distributed transactions component.
 - a. Download and extract the Microsoft SQL Server JDBC driver from the Microsoft website to a directory on the machine.
 - b. Copy the `sqljdbc_xa.dll` file to the `Binn` directory of the machine on which Microsoft SQL Server is installed.
 - c. Run the `xa_install.sql` script on the Microsoft SQL Server instance as an administrator.
The `xa_install.sql` script is in the `xa` directory of the JDBC driver.
 - d. Verify that the script creates the `SqlJDBCXAUser` role in the Microsoft SQL Server master database.

For more information about how to install and configure Microsoft SQL Server for distributed transactions, see the Microsoft SQL Server documentation.

Enabling the TCP/IP Network Protocol

Use SQL Server Configuration Manager to enable the TCP/IP network protocol, which the MDM Hub environment requires.

1. Start the SQL Server Configuration Manager.

2. In the console pane, expand **SQL Server Network Configuration**, and then click **Protocols for MSSQLSERVER**.
3. In the details pane, right-click **TCP/IP**, and then click **Enable**.
4. Restart the SQL Server service.

The TCP/IP network protocol is enabled.

Step 2. Create a Microsoft SQL Server Data File Store

Ensure that you create a Microsoft SQL Server data file store if one does not exist. When you create the MDM Hub Master Database and the Operational Reference Stores, you need to provide the path to the Microsoft SQL Server data file store.

Step 3. Install ODBC Driver

If you install the application server on UNIX or Linux, install an ODBC driver for Microsoft SQL Server so that data sources can be created.

- Download and install the ODBC driver for the operating system.
 - On Linux. Download the Microsoft SQL Server ODBC driver from the Microsoft website.
 - On UNIX. Download the UNIX ODBC driver from the unixODBC Project home page.

Step 4. Create the ActiveVOS Database

To install ActiveVOS, you need to create the ActiveVOS database. To create the database, run the `create_bpm` script.

If you want to create multiple MDM Hub Master Databases, create an ActiveVOS database for each MDM Hub Master Database.

1. Open a command prompt and change to the following directory:

```
<MDM Hub distribution directory>/database/bin
```

2. Run the following command:

On UNIX. `./sip_ant.sh create_bpm`

On Windows. `sip_ant.bat create_bpm`

3. Answer the prompts that appear.

The prompt displays default text in brackets. Press **Enter** to use the default value and go to the next prompt.

Property	Description
Database Type	Type of database to use. For Microsoft SQL Server, specify <code>MSSQL</code> . The database type must be the same as the database type selected for the MDM Hub Master Database and the Operational Reference Stores.
ActiveVOS User Name	User name of the ActiveVOS Server administrative user.

Property	Description
ActiveVOS User Password	Password of the administrative user.
ActiveVOS Collation Name	Name of the ActiveVOS database collation. For example, <code>Latin1_General_CI_AS</code> .
ActiveVOS Database Host Name	Name of the machine that hosts the database.
ActiveVOS Database Path	Path to the database location.
DBA User Name	User name of the SA user.
DBA Password	Password of the SA user account.

4. After you create the database, review the `sip_ant.log` file in the following directory:

```
<MDM Hub distribution directory>/database/bin
```

The `sip_ant.log` file logs any errors that might occur when you run the `sip_ant` script to create the ActiveVOS database schema.

Set Up the Application Server Environment

You can install the MDM Hub in a WebLogic cluster environment or on standalone WebLogic instances. Install and configure WebLogic according to the instructions in the WebLogic documentation.

Important: There are some known limitations with how Multidomain MDM interacts with some Oracle WebLogic versions, including version 12.2.1.3. Before you begin, see the "Installation and Upgrade" chapter of the *Multidomain MDM Release Notes*.

Before you install the Hub Server and the Process Server on the WebLogic application server, create WebLogic domains. Use the WebLogic Administration console to create domains for the Hub Server and the Process Server applications. For more information, see the WebLogic documentation.

Note: Install the application server in the same time zone as the database server.

Configure the Java Virtual Machines

To configure a Java Virtual Machine (JVM), set the Java options by using the `JAVA_OPTIONS` environment variable.

You can set the Java options in the following file:

On UNIX. `<WebLogic domain>/bin/setDomainEnv.sh`

On Windows. <WebLogic domain>\bin\setDomainEnv.cmd

The following table describes the Java options:

Java Options	Description
-server	Results in a slower startup but subsequent operations are faster.
-Djgroups.bind_addr	Interface on which JGroup must receive and send messages. Required in a multinode or clustered environment. Ensure that each node binds to its own network interface.
-Djava.net.preferIPv4Stack	Specifies whether Java uses Internet Protocol version 4 (IPv4). If the operating system uses Internet Protocol version 6 (IPv6), set to <code>true</code> .
-Djavax.wsdl.factory.WSDLFactory	Required for the WebLogic 12.2.1 or later environments to invoke a service WSDL that might have a default namespace prefix. Set to <code>com.ibm.wsdl.factory.WSDLFactoryImpl</code> .
-DANTLR_USE_DIRECT_CLASS_LOADING	Required for launching WebLogic 12.2.1 or later environments on which the MDM Hub is deployed. Set to <code>true</code> .
-Dmdm.node.groupid	Specifies a group ID for Java Virtual Machines in the MDM Hub implementation. Required only if you want logical groupings of Hub Servers and Process Servers.
-De360.mdm.host	Application server host. Set the Java option in one of the following scenarios: <ul style="list-style-type: none">- If you want to deploy the MDM Hub applications only on Managed Servers, add the Java option to the script of each Managed Server. Set to the IP address or symbolic name of the Managed Server.- If you want to deploy the MDM Hub applications on a WebLogic port other than 7001, add the Java option to the application server startup script. Set to the IP address or symbolic name of the WebLogic host. If you do not configure this parameter, Informatica Data Director screens based on the Entity 360 Framework might not work as expected
-De360.mdm.port	Application server port. Set the Java option in one of the following scenarios: <ul style="list-style-type: none">- If you want to deploy the MDM Hub applications only on Managed Servers, add the Java option to the script of each Managed Server. Set to the port number of the Managed Server.- If you want to deploy the MDM Hub applications on a WebLogic port other than 7001, add the Java option to the application server startup script and set to the port number. If you do not configure this parameter, Informatica Data Director screens based on the Entity 360 Framework might not work as expected
-Dfile.encoding -Dweblogic.http.URIDecodeEncoding	Required if you want to use Informatica Data Director and use REST APIs to search for records. Set both the Java options to <code>UTF-8</code> to ensure that you can find and save records that contain UTF-8 characters.
-DFrameworksLogConfigurationPath	Sets the <code>log4j.xml</code> file configuration path.
-DUseSunHttpHandler	Specifies whether WebLogic uses the Sun HTTP Handler for the HTTP connection between the MDM Hub and the Informatica platform. Set to <code>true</code> .

Java Options	Description
-Dtask.pageSize=<maximum number of tasks>	Specifies the maximum number of ActiveVOS tasks that are retrieved for each request. Default is 5000. Increase the number if your environment has a large number of tasks.
-Dstricttransportsecurity.flag	Specifies whether web browsers must convert all attempts to access Data Director using the HTTP requests to the HTTPS requests instead. Set to true.
WLS_MEM_ARGS_64BIT	Memory variable. Set the variable to an appropriate value.
-Xms	Initial heap size. Set to 2048m.
-Xmx	Maximum JVM heap size. Set to 4 GB or higher. For example, to set the -Xmx to 4096m, use the following JAVA_OPTIONS environment variable setting: set "JAVA_OPTIONS=-server ... -Xmx4096m"
XX:+UseCodeCacheFlushing	Specifies whether the JVM disposes of compiled code when the code cache is full.
-XX:ReservedCodeCacheSize	JIT code cache size. To enhance the performance of the MDM Hub environment, set to 512m.

Logical Grouping of Java Virtual Machine Example

By grouping Java Virtual Machines (JVMs), you get a logical group of Hub Servers and Process Servers. When you deploy the Hub Server and Process Server applications in a logical JVM group, communication between the Hub Server and Process Server applications stay within the group. To group JVMs, you assign a group ID to each JVM in the MDM Hub environment.

Note: Process Server grouping is applicable to the cleanse and match process only. A Process Server that is enabled as a Zookeeper server and is enabled for smart search is available to all the groups for indexing and search processing. The logical groups are not applied to the internal server cache of the MDM Hub.

The following table shows an example of logical JVM groups:

JVM Group	JVM	Hub Server	Process Server
Group1	JVM1	Yes	Yes
Group1	JVM4	-	Yes
Group2	JVM2	Yes	Yes
Group3	JVM3	-	Yes

For JVM1, add the following Java option in the startup script:

```
-Dmdm.node.groupid=Group1
```

For JVM2, add the following Java option in the startup script:

```
-Dmdm.node.groupid=Group2
```

For JVM3, add the following Java option in the startup script:

```
-Dmdm.node.groupid=Group3
```

For JVM4, add the following Java option in the startup script:

```
-Dmdm.node.groupid=Group1
```

After you configure the JVMs, and deploy the Hub Servers and Process Servers, the groups have the following characteristics:

- Group1 has two Process Servers, Group2 has one Process Server, and Group3 has one Process Server.
- All cleanse and batch calls stay in their own group with the exception of smart search. For example, any real-time call on the Hub Server in Group1 affects only the Group1 Process Servers (JVM1 and JVM4).

Disable WebLogic Server Authentication

The MDM Hub uses HTTP basic authentication for which you must disable WebLogic Server authentication. To disable WebLogic Server authentication, edit the `config.xml` file.

1. Navigate to the following WebLogic directory:

```
<WebLogic installation directory>/user_projects/domains/<user domain>/config
```

2. Open the `config.xml` file in a text editor.

3. Add the following element within the `<security-configuration>` element:

```
<enforce-valid-basic-auth-credentials>
  false
</enforce-valid-basic-auth-credentials>
```

Create the ActiveVOS Console Administrative User

If you want to use ActiveVOS, create the ActiveVOS Console administrative user with the `abAdmin` role. If you do not create an administrative user, the Hub Server deployment fails. Use the ActiveVOS Console administrative user name and password when the Hub Server installer prompts you to enter the administrative user credentials for the ActiveVOS Console.

1. Log in to the WebLogic console.
2. Create the `abAdmin` role.
3. Create the ActiveVOS Console administrative user.
4. Assign the administrative user to the `abAdmin` role

Additional Application Server Configuration (Optional)

Perform additional WebLogic configuration based on the requirements of the MDM Hub environment.

The following table describes the configurations that you can perform:

Configuration	Description
Configuring WebLogic for standalone Process Server instances	Required to configure WebLogic for standalone Process Server instances in the following scenarios: <ul style="list-style-type: none">- You want to install a Process Server instance on a WebLogic instance on which you do not have the Hub Server installed.- You want to install multiple, standalone Process Server instances.
Configuring WebLogic for multiple MDM Hub Master Databases	Required if you want to configure multiple MDM Hub Master Database instances.
Configuring the HTTPS protocol	Required if you want to configure the HTTPS protocol for the MDM Hub communications.
Configuring the JTA timeout for Informatica platform	Required if you want to install Informatica platform.

Configuring WebLogic for Standalone Process Server Instances

If you want to install multiple, standalone Process Server instances, configure WebLogic to use the appropriate data source. Also, if you want to install a Process Server instance on a WebLogic instance on which you do not have the Hub Server installed, configure the data source.

Perform the following tasks to configure WebLogic to use the appropriate data source:

1. Install the JDBC driver.
2. Create an MDM Hub Master Database data source.
3. Create an Operational Reference Store data source.

Step 1. Install the JDBC Driver

Before you create data sources for the MDM Hub Master Database and the Operational Reference Store (ORS), install the JDBC driver.

Contact Microsoft to get the supported version of the JDBC driver.

1. Copy the JDBC driver to the following directory:
`<WebLogic installation directory>/wlserver/server/lib`
2. Add the path to the JDBC driver to the CLASSPATH variable in the following file:

On UNIX. `<WebLogic domain>/bin/commEnv.sh`

On Windows. `<WebLogic domain>\bin\commEnv.cmd`

Note: Place the path to the JDBC driver before the path to other Weblogic Server libraries.

Step 2. Create an MDM Hub Master Database Data Source

After you install the JDBC driver, on the Process Server machine, create a data source for the MDM Hub Master Database.

1. On the WebLogic Administration Console, click the **Lock & Edit** button to acquire a lock.
2. Click **Services > JDBC > Data Sources**, and then click **New**.
The **JDBC Data Sources Properties** page appears.
3. Specify the following data source properties:

Property	Description
Name	Name of the JDBC data source. Set the name to <code>MDM Master Data Source</code> .
JNDI Name	JNDI path to where the JDBC data source will be bound. Specify <code>jdbc/siperian-cmx_system-ds</code> .
Database Type	Database type that you want to connect to. Select MS SQL Server .
Database Driver	JDBC driver that you want to use to connect to the database. Select MS SQL Server Driver (Type 4 XA) Versions: 2005 or later .

4. Click **Next**, and again click **Next**.
The **Connection Properties** page appears.
5. Enter values for the following connection properties:

Property	Description
Database Name	Name of the database you want to connect to.
Host Name	DNS name or IP address of the server that hosts the database. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Port	Port on which the database server listens for connection requests.
Database User Name	Database user name that you want to use for each connection in the data source.
Password	Password of the database user account.
Confirm Password	Password of the database user account.

6. Click **Next**.
The **Test Database Connection** page appears.
7. Click **Test Configuration** to test the driver connections.
If the test is unsuccessful, you must update the values in the **Connection Properties** page and then retry the connection until successful.
8. Click **Next**, and then select the server on which you want to deploy the data source.
9. Click **Finish**, and then click **Activate Changes**.

Step 3. Create an Operational Reference Store Data Source

On the Process Server machine, create a data source for each Operational Reference Store.

1. On the WebLogic Administration Console, click the **Lock & Edit** button to acquire a lock.
2. Click **Services > JDBC > Data Sources**, and then click **New**.
The **JDBC Data Sources Properties** page appears.
3. Specify the following data source properties:

Property	Description
Name	Name of the JDBC data source. Set the name to <code>MDM ORS Data Source</code> .
JNDI Name	JNDI path to where the JDBC data source will be bound. Specify <code>jdbc/siperian-<Microsoft SQL Server host name>-<Operational reference Store name>-ds</code> .
Database Type	Database type that you want to connect to. Select MS SQL Server .
Database Driver	JDBC driver that you want to use to connect to the database. Select MS SQL Server Driver (Type 4 XA) Versions: 2005 or later .

4. Click **Next**, and again click **Next**.
The **Connection Properties** page appears.
5. Enter values for the following connection properties:

Property	Description
Database Name	Name of the database you want to connect to.
Host Name	DNS name or IP address of the server that hosts the database. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Port	Port on which the database server listens for connection requests.
Database User Name	Database user name that you want to use for each connection in the data source.
Password	Password of the database user account.
Confirm Password	Password of the database user account.

6. Click **Next**.
The **Test Database Connection** page appears.
7. Click **Test Configuration** to test the driver connections.
If the test is unsuccessful, you must update the values in the **Connection Properties** page and then retry the connection until successful.
8. Click **Next**, and then select the server on which you want to deploy the data source.
9. Click **Finish**, and then click **Activate Changes**.

Configuring WebLogic for Multiple MDM Hub Master Databases

If you want to configure multiple MDM Hub Master Database instances, configure as many WebLogic domains as the number of MDM Hub Master Database instances. Each MDM Hub Master Database instance must have its own MDM Hub instance. Therefore, create as many WebLogic domains to deploy each MDM Hub instance on a separate WebLogic domain.

Configuring the HTTPS Protocol

You can configure the HTTPS protocol for the MDM Hub communications. Use the WebLogic Server Administration Console to configure the HTTPS protocol. Alternatively, you can use the default JDK secure certificates to enable HTTPS.

1. On the **Home Page** of the WebLogic Server Administration Console, under the **Environment** section, click **Servers**.
The **Summary of Servers** page appears.
2. In the Servers list, click the **AdminServer(admin)** link.
The **Settings for AdminServer** page appears.
3. Enable the **SSL Listen Port Enabled** option, and enter the port number in the **SSL Listen Port** field.
4. Click the **SSL** tab.
5. From the **Hostname Verification** list, select **None**, and click **Save**.

Configuring the JTA Timeout for Informatica Platform

If you want to install Informatica platform, configure the Java Transaction API (JTA) timeout. Use the WebLogic Server Administration Console to configure the JTA timeout.

1. On the **Home Page** of the WebLogic Server Administration Console, under the **Services Configurations** section, click the **JTA Configuration** link.
2. In the **Timeout Seconds** field, set the JTA timeout to 1000.

Configure the Properties Files for Silent Installation

If you want to install the Hub Server and the Process Server without user interaction in silent mode, configure the installation properties files. You might want to perform a silent installation if you need multiple installations, or if you need to install on a machine cluster. A silent installation does not show any progress or failure messages.

The installer reads the silent installation properties file to determine the installation options. Ensure that you provide correct settings in the properties file because the silent installation process might complete successfully even if the settings are incorrect.

You can configure the following silent installation properties files:

- Informatica platform. Required to install Informatica platform as part of the MDM Hub installation.
- Hub Server. Required to install the Hub Server in silent mode.
- Process Server. Required to install the Process Server in silent mode.

Note: If you do not want to manually configure the silent installation properties file, you can use the `-x` command-line option during installation to generate the silent installation properties file.

Configuring the Informatica Platform Properties File

If you want to install Informatica platform as part of the MDM Hub installation, configure the Informatica platform properties file. Specify the options for the installation in the properties file, and save the file with the name `SilentInput.properties`.

1. Find the `SilentInput.properties` file in the following directory: `<Distribution directory>/Informatica platform>`
2. Create a backup copy of the file.
3. Open the `SilentInput.properties` file in a text editor.
4. Configure the values of the installation parameters, and save the file.

Configuring the Hub Server Properties File

If you want to install the Hub Server in silent mode, configure the Hub Server properties file. Specify the options for the installation in the properties file, and save the file with a new name.

1. Find the `silentInstallServer_sample.properties` file in the following directory: `/silent_install/mrmserver`
2. Create a backup copy of the `silentInstallServer_sample.properties` file.
3. Open the file in a text editor, and configure the values of the installation parameters.
4. Save the properties file with a new name such as `silentInstallServer.properties`.

Configuring the Process Server Properties File

If you want to install the Process Server in silent mode, configure the Hub Server properties file. Specify the options for the installation in the properties file, and save the file with the new name.

1. Find the `silentInstallCleanse_sample.properties` file in the following directory: `/silent_install/mrmcleanse`
2. Create a backup copy of the `silentInstallCleanse_sample.properties` file.
3. Open the file in a text editor, and configure the values of the installation parameters.
4. Save the properties file with a name such as `silentInstallCleanse.properties`.

CHAPTER 3

Hub Store Installation

This chapter includes the following topics:

- [Create the MDM Hub Master Database, 26](#)
- [Create an Operational Reference Store, 27](#)
- [Import the Metadata into the MDM Hub Master Database, 28](#)
- [Import the Metadata into the Operational Reference Store, 29](#)

Create the MDM Hub Master Database

After you install Microsoft SQL Server, create an MDM Hub Master Database. If you want to create multiple MDM Hub Master Databases, ensure that you create each MDM Hub Master Database in a different database. The default name of the MDM Hub Master Database is `CMX_SYSTEM`, but you can use a custom name.

Note: If you change the folder names in the distribution directory, metadata import fails.

1. Open a command prompt, and navigate to the following directory:

```
<MDM Hub distribution directory>/database/bin
```

2. To create the MDM Hub Master Database, run the following command:

```
sip_ant.bat create_system
```

3. Answer the prompts described in the following table:

Note: The prompt displays default text in brackets. Press **Enter** to use the default value and go to the next prompt.

Prompts	Description
Enter the database type (ORACLE, MSSQL, DB2)	Database type. Specify <code>MSSQL</code> .
Enter the database host name [localhost]	Name of the host that runs the database. Default is <code>localhost</code> . Important: In cluster environments, specify the absolute host name or the IP address to avoid caching issues.

Prompts	Description
Enter the database port number [1433]	Port number that the database listener uses. Default is 1433. Note: You cannot create the DB2 database if the port number is not the default 50000. You must manually change the port number in the DB2 properties file.
Enter master database name [cmx_system]	Name of the MDM Hub Master Database schema. Default is cmx_system.
Enter master database user password	Password to access the MDM Hub Master Database.
Enter CMX_SYSTEM database path ("C:\MSSQLDATA")	Path to the Microsoft SQL Server data file store enclosed in double quotation marks. Note: If you create the MDM Hub Master Database from a remote Windows machine, do not use spaces in the database path.
Enter CMX_SYSTEM database collation name (Latin1_General_CI_AS)	Collation name to set a collation sequence for the MDM Hub Master Database.
Enter locale name from the list: de, en_US, fr, ja, ko, zh_CN. [en_US]	Operating system locale. Default is en_US.
Enter the DBA user name [sa]	Default is sa.
Enter the DBA password	Password of the SA user account.

- To verify that the MDM Hub Master Database was created successfully, review sip_ant.log in the following directory:

<MDM Hub distribution directory>/database/bin

The sip_ant.log file logs any errors that might occur when you run the sip_ant script to create the MDM Hub Master Database.

Create an Operational Reference Store

After you complete the preinstallation tasks, create an Operational Reference Store (ORS). The default name of the ORS is CMX_ORS.

Note: If you change the folder names in the distribution directory, metadata import fails.

- Open a command prompt, and navigate to the following directory:

<MDM Hub distribution directory>/database/bin

- To create an ORS, run the following command:

```
sip_ant.bat create_ors
```

- Answer the prompts described in the following table:

Note: The prompts display default text in brackets. Press **Enter** to use the default value and go to the next prompt.

Prompts	Description
Enter the database type (ORACLE, MSSQL, DB2)	Database type. Specify <code>MSSQL</code> .
Enter the Operational Reference Store schema host name [localhost]	Name of the host that is running the database. Default is <code>localhost</code> .
Enter the Operational Reference Store schema port number [1433]	Port number that the database listener uses. Default is <code>1433</code> .
Enter the Operational Reference Store schema name [cmx_ors]	Name of the Operational Reference Store database. Default is <code>cmx_ors</code> .
Enter CMX_ORS database path ["C:\MSSQLDATA"]	Path to the Microsoft SQL Server data file store enclosed in double quotation marks. Note: If you create the Operational Reference Store from a remote Windows machine, do not use spaces in the database path.
Enter CMX_ORS database collation name (Latin1_General_CI_AS)	Collation name to set a collation sequence for the Operational Reference Store.
Enter the Operational Reference Store database user password	Password to access the Operational Reference Store.
Enter locale name from the list: de, en_US, fr, ja, ko, zh_CN. [en_US]	Operating system locale.
Enter the DBA user name [sa]	SA user. Default is <code>sa</code> .
Enter the DBA password	Password of the SA user account.

- To verify that the ORS was created successfully, review `sip_ant.log` in the following directory:

```
<MDM Hub distribution directory>/database/bin
```

The `sip_ant.log` file logs any errors that might occur when you run the `sip_ant` script to create the ORS.

Import the Metadata into the MDM Hub Master Database

After you create the MDM Hub Master Database, import the initial metadata into the MDM Hub Master Database. The initial metadata includes repository tables and other objects that the MDM Hub requires in the Hub Store.

Note: If you change the folder names in the distribution directory, metadata import fails.

- Open a command prompt, and navigate to the following directory:

```
<MDM Hub distribution directory>/database/bin
```

2. To import the initial metadata, run the following command:

```
sip_ant.bat import_system
```

3. Answer the prompts described in the following table:

Note: The prompts display default text in brackets. Press **Enter** to use the default value and go to the next prompt.

Prompts	Description
Enter the database type (ORACLE, MSSQL, DB2)	Database type. Specify <code>MSSQL</code> .
Enter the database host name [localhost]	Name of the host that is running the database.
Enter the database port number [1433]	Port number that the database listener uses. Default is <code>1433</code> .
Connect URL [jdbc:sqlserver://localhost:1433]	Connect URL for Microsoft SQL Server. Default is <code>jdbc:sqlserver://localhost:1433</code> .
Enter master database name [cmx_system]	Name of the MDM Hub Master Database schema. Default is <code>cmx_system</code> .
Enter master database user password	Password to access the MDM Hub Master Database.
Enter locale name from the list: de, en_US, fr, ja, ko, zh_CN. [en_US]	Operating system locale. Default is <code>en_US</code> .

4. After you import the initial metadata, review the following log files for errors:

- `seed.log`. Contains database errors.
The `seed.log` file is in the following directory: `<MDM Hub installation directory>/database/bin/mssql`
- `sip_ant.log`. Contains user input errors.
The `sip_ant.log` file is in the following directory: `<distribution directory>/database/bin`

Import the Metadata into the Operational Reference Store

After you create the Operational Reference Store, import the initial metadata into the Operational Reference Store. The initial metadata includes repository tables and other objects that the MDM Hub requires in the Hub Store.

Note: If you change the folder names in the distribution directory, metadata import fails.

1. Open a command prompt, and navigate to the following directory:

```
<MDM Hub distribution directory>/database/bin
```

2. To import the initial metadata, run the following command:

```
sip_ant.bat import_ors
```

3. Answer the prompts described in the following table:

Note: The prompts display default text in brackets. Press **Enter** to use the default value and go to the next prompt.

Prompts	Description
Enter the database type (ORACLE, MSSQL, DB2)	Database type. Specify <code>MSSQL</code> .
Enter the Operational Reference Store database host name [localhost]	Name of the host that is running the database.
Enter the Operational Reference Store database port number [1433]	Port number that the database listener uses. Default is 1433.
Enter the Operational Reference Store database name [cmx_ors]	Name of the Operational Reference Store database. Default is <code>cmx_ors</code> .
Connect URL [jdbc:sqlserver://localhost:1433]	Connect URL for Microsoft SQL Server. Default is <code>jdbc:sqlserver://<host name>:<port></code> .
Enter the Operational Reference Store database user password	Password to access the Operational Reference Store.
Enter locale name from the list: de, en_US, fr, ja, ko, zh_CN. [en_US]	Operating system locale. Default is <code>en_US</code> .
Enter the integer code of Operational Reference Store Timeline Granularity: Year 5, Month 4, Day 3, Hour 2, Minute 1, Second 0 [3]	Specify timeline units to use. Default is days. Note: The timeline granularity that you configure cannot be modified later. For more information about timeline, see the <i>Multidomain MDM Configuration Guide</i> .

4. After you import the initial metadata, review the following log files for errors:
 - `seed.log`. Contains database errors.
The `seed.log` file is in the following directory: `<MDM Hub installation directory>/database/bin/mssql`
 - `sip_ant.log`. Contains user input errors.
The `sip_ant.log` file is in the following directory: `<MDM Hub distribution directory>/database/bin`

CHAPTER 4

Hub Server Installation

This chapter includes the following topics:

- [Hub Server Installation Modes, 31](#)
- [Installing the Hub Server in Graphical Mode, 31](#)
- [Installing the Hub Server in Console Mode, 35](#)
- [Generating a Silent Installation Properties File, 38](#)
- [Installing the Hub Server in Silent Mode, 38](#)
- [Installing the Hub Server on Environments with Managed Servers, 39](#)

Hub Server Installation Modes

You can use any of the following modes to install the Hub Server:

- Graphical mode
- Console mode
- Silent mode

Installing the Hub Server in Graphical Mode

You can install the Hub Server in graphical mode.

You must use the same user name to install the Hub Server and the Process Server.

1. Start the application server.
2. Open a command prompt, and navigate to the Hub Server installer in the distribution directory.

By default, the installer is in the following directory:

<MDM Hub distribution directory>/<operating system name>/mrmsserver

3. Run the following command:

On UNIX. `./hub_install.bin`

On Windows. `hub_install.exe`

4. Select the language for the installation, and then click **OK**.

The **Introduction** window appears.

5. Click **Next**.

The **License Agreement** window appears.

6. Select the **I accept the terms of the License Agreement** option, and then click **Next**.

The **Choose an Install Folder** window appears.

7. Select the location of the Hub Server installation.

- To choose the default location, click **Next**.
- To enter a path, type the path to the installation folder, and click **Next**.

Note: The installation fails if you specify a path that has spaces in the directory or folder names.

- To choose another location, click **Choose**, and then click **Next**.

8. On UNIX, choose a link folder or select the option to not create links and click **Next**. On Windows, select the location to create a product icon or select the option not to create a product icon.

9. Click **Next**.

The **Enter the location of the license file** window appears.

10. Click **Choose** to select a license file, and click **Next**.

The **Advanced Security** window appears.

11. Select the security configuration for the MDM Hub.

- Optionally, in the **Customer hash key** field, enter a hashing key up to 128 bits.
- To choose the default configuration, click **Next**. The **Hub Certificate Provider** window appears.
- To choose a custom security configuration for the MDM Hub, select **Custom** and click **Next**.

12. If you selected Custom in the preceding step, the **Hashing Algorithm** page appears.

- To accept the default hashing algorithm for password hashing in the MDM Hub, click **Next**. The **Hub Certificate Provider** window appears.
- To choose a custom hashing algorithm, select **Other**, and then click **Next**.

13. If you selected Other in the preceding step, provide the following information for the custom hashing algorithm, and then click **Next**:

- Hashing algorithm name
- Location of the hashing algorithm archive.

Note: The hashing algorithm archive must be a ZIP file. If the archive contains multiple JAR files and other supporting files, ensure they are all in the ZIP file.

- Canonical class name of the hashing algorithm implementation.

Note: For example, enter `$HASHING_CLASS_NAME$`.

The **Hub Certificate Provider** window appears.

14. To select the certificate provider for the MDM Hub to authenticate trusted applications, choose one of the following options:

- To choose the default certificate provider, click **Next**. The **Application Server** window appears.
- To choose a custom certificate provider, select **Custom**.

15. If you selected Custom in the preceding step, provide the following information for the custom certificate provider:
- Enter the location of the certificate provider archive.
Note: The certificate provider archive must be a ZIP file. If you use a custom certificate provider, ensure the <MDM Hub installation directory>/server/resources/certificates directory is empty.
 - Enter the class name of the certificate provider, and then click **Next**.
The **Application Server** window appears.
16. Select WebLogic, and then click **Next**.
The **WebLogic Application Server Home** window appears.
17. Configure the following WebLogic Server settings:
- Choose a path to the WebLogic domain installation directory for the domain that you want to use for the MDM Hub. Click **Next**.
The **WebLogic Application Server Login** window appears.
 - Enter the following WebLogic Server login information:

Field Name	Description
Host	Name of the host computer that has the WebLogic installation. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Server	Name of the WebLogic Server instance in the domain on which WebLogic is deployed.
User Name	Name of the user for the WebLogic installation.
Password	Password that corresponds to the WebLogic user.
Port Number	Port number on which the WebLogic Server is listening.

18. Click **Next**.
The **Database Selection** window appears.
19. Select **Microsoft SQL Server**, and click **Next**.
The **Microsoft SQL Server Database Information** window appears.
20. Specify the following configuration parameters to create the J2EE data source, and click **Next**:

Field Name	Description
Server	Name of the server.
Port	Port number of the MDM Hub Master Database.
Database Name	Name of the MDM Hub Master Database.

Field Name	Description
DBO Username	Database owner user name of the MDM Hub Master Database.
DBO Password	Database owner password of the MDM Hub Master Database.

The **Install ActiveVOS** window appears.

21. If you want to install the bundled, licensed version of Informatica ActiveVOS, select **Yes** and perform the following substeps. Otherwise, select **No**, and click **Next**.
 - a. On the **Choose ActiveVOS Installation Folder** page, accept the default installation path or specify a preferred location. Click **Next**.
 - b. On the **Database Information** page, enter the database details that you specified when you created the ActiveVOS database schema, and click **Next**.
 - c. On the **Application Server Web URL** page, accept the default URL or specify the URL that you want to use to call ActiveVOS web services. Ensure the URL contains the correct port number for the connection to the application server. Click **Next**.
 The post installation setup script uses the URL to call ActiveVOS web services, deploy the predefined MDM workflows to ActiveVOS, and create the URN mapping.
 - d. On the **ActiveVOS Installer** page, click **Choose** and browse to the ActiveVOS_Server installation file in the distribution package. Click **Next**.
 - e. Enter the administrative user name and password to create an administrative user for the ActiveVOS Console.
Important: The user name and password must be the same as the ActiveVOS Console user name and password that was created in the application server.
 - f. Click **Next**.
22. Select one of the following Informatica platform installation options:
 - **Yes.** Install Informatica platform.
 - **No.** Does not install Informatica platform.
23. If you select **Yes** in the preceding step, click **Choose** and browse to the following Informatica platform file locations:
 - Installation response file
 - Platform installation file
24. On the Product Usage Toolkit page, select the industry to which the organization belongs and the environment type.
25. If you want to use a proxy server, select **Yes**, and enter the proxy server details. Otherwise, select **No**.
 You can enter the following proxy server details:
 - Proxy server name/IP
 - Proxy server port
 - Proxy server domain name. Leave blank if not applicable.
 - Proxy server user name. Leave blank if not applicable.
 - Proxy server password. Leave blank if not applicable.
26. Click **Next**.
 The Deploy page appears.

27. Select one of the following `postInstallSetup` script options:
 - **Yes, run the script during this installation.** Runs the `postInstallSetup` script during the installation.
 - **No, I will run it later.** Does not run the `postInstallSetup` script during the installation. After the installation, you must run the `postInstallSetup` script or manually deploy the Hub Server applications.

The `postInstallSetup` script repackages and deploys the Hub Server applications. Also, the script creates data sources and configures JMS message queues.

Important: In a WebLogic 12.2.1.3 or later environment, if you decided to install ActiveVOS or if you decided to use the WebLogic T3S protocol, select **No, I will run it later**.
28. Click **Next**.

The **Pre-Installation Summary** window appears.
29. After the Pre-Installation Summary window displays the options you want, click **Install** to start the installation process.

When the installation completes, the **Install Complete** window appears.
30. Click **Done** to exit the Hub Server installer.

Installing the Hub Server in Console Mode

You can install the Hub Server in console mode on UNIX.

1. Start the application server.
2. Open a command prompt, and navigate to the following directory in the MDM Hub distribution:
`<MDM Hub distribution directory>/<operating system name>/mrmserver`
3. Run the following command:
`./hub_install.bin -i console`
4. Enter the number of the locale you want to choose for the installation, and then press **Enter**.

The introduction information about the installation appears.
5. Press **Enter**.

The license agreement appears.
6. Read the License Agreement. Type **Y** to accept the terms of the license agreement, or type **N** if you do not want to accept the license agreement and want to exit the installation program.
7. Press **Enter**.

If you entered **Y** in the preceding step, information about the installation folder appears.
8. Choose a folder for the Hub Server installation.
 - To choose the default folder, press **Enter**.
 - To change the path, type the absolute path of the installation folder, and press **Enter**.
9. Confirm the location of the installation folder. Type **Y** to confirm the installation folder, or type **N** to change the installation folder.
10. Press **Enter**.

A list of link location options appears.

11. Enter the number of a link location option.
The prompt for the license file location appears.
12. Enter the absolute path of the license file, and press **Enter**.
A list of advanced security options appears.
13. Choose a security configuration for the MDM Hub.
 - To choose the default configuration, press **Enter**.
 - To choose a custom security configuration for the MDM Hub, type `Custom`, and press **Enter**.
 - When prompted for a customer hash key, you can enter a value up to 128 bits.
14. If you typed `Custom` in the preceding step, choose one of the following options:
 - To accept the default hashing algorithm for password hashing in the MDM Hub, press **Enter**.
 - To choose a custom hashing algorithm, type `Other`, and press **Enter**.
15. If you typed `Other` in the preceding step, provide the following information for the custom hashing algorithm:
 - Hashing algorithm name
 - Location of the hashing algorithm archive.
Note: The hashing algorithm archive must be a ZIP file. If the archive contains multiple JAR files and other supporting files, ensure they are all in the ZIP file.
 - Canonical class name of the hashing algorithm implementation.
Note: For example, enter `$HASHING_CLASS_NAME$`.

A list of certificate provider options appears.
16. To select the certificate provider for the MDM Hub to authenticate trusted applications, choose one of the following options:
 - To choose the default certificate provider, press **Enter**.
 - To choose a custom certificate provider, type `Custom` and press **Enter**.
17. If you typed `Custom` in the preceding step, provide the following information for the custom certificate provider:
 - a. Enter the location of the certificate provider archive.
Note: The certificate provider archive must be a ZIP file. If you use a custom certificate provider, ensure the `<MDM Hub installation directory>/server/resources/certificates` directory is empty. In a WebSphere environment, the MDM Hub user must also have access and write permissions for the certificates directory.
 - b. Enter the class name of the certificate provider, and then press **Enter**.

A list of application server options appears.
18. Enter the number for the application server that you want to select, and press **Enter**.
The application server information appears.
19. Configure the WebLogic settings.
 - a. Specify the path to the WebLogic domain in which you want to install the Hub Server, and press **Enter**.
The prompts for the WebLogic application server login information appears.
 - b. Enter the host name, server name, user name, password, and listener port for the WebLogic Server, or accept the default values, and press **Enter**.
20. Press **Enter**.

The database selection prompt appears.

21. Enter the number corresponding to Microsoft SQL Server, and press **Enter**.
22. Specify the settings for the Microsoft SQL Server database to which you want to connect.
Press **Enter** to accept the default values, or replace the default values with the correct values.

The following table describes the prompts:

Prompt	Description
Server	Name of the server.
Port	Port number of the MDM Hub Master Database.
Database Name	Name of the MDM Hub Master Database.
DBO Username	Database owner user name of the MDM Hub Master Database.
DBO Password	Database owner password of the MDM Hub Master Database.

23. Press **Enter**.
24. If you want to install the bundled, licensed version of the ActiveVOS Server, press **Enter** for Yes. Otherwise, type 2 for No and press **Enter**.
If you selected Yes, the installer prompts you to provide information about your ActiveVOS installation.
 - a. Specify the location where you want to install the ActiveVOS Server.
 - b. Specify the URL that you want to use to call MDM and ActiveVOS web services.
 - c. Enter information about the ActiveVOS database that you specified when you created the ActiveVOS schema.
 - d. Specify the location of the ActiveVOS Server installation file.
 - e. Enter a user name and password to create an administrative user for the ActiveVOS Server Administration Console.
Important: The user name and password must be the same as the ActiveVOS Console user name and password that was created in the application server.
25. Press **Enter**.
The Informatica platform installation prompt appears.
26. If you want to install the Informatica platform, press **Enter** for Yes. Otherwise, type 2 for No and press **Enter**.
The prompts for the Informatica platform installation response file and archive file locations appear.
27. Enter the locations of the Informatica platform installation response file and archive file, and press **Enter**.
28. Specify the Product Usage Toolkit options.
 - a. Enter the industry to which the organization belongs , and then press **Enter**.
 - b. Enter the environment type. Type 1 for Production, type 2 for Test/QA, or type 3 for Development, and then press **Enter**.
29. Select whether you have a proxy server. Press **Enter** for Yes. Otherwise, type 2 for No and then press **Enter**.

You can enter the following proxy server details:

- Proxy server name/IP
- Proxy server port
- Proxy server domain name. Leave blank if not applicable.
- Proxy server user name. Leave blank if not applicable.
- Proxy server password. Leave blank if not applicable.

The summary of the installation choices appears.

30. Choose whether you want to run the `postInstallSetup` script as part of the installation, or run it manually later.

Important: In a WebLogic 12.2.1.3 or later environment, if you decided to install ActiveVOS or if you decided to use the WebLogic T3S protocol, select **No, I will run it later**.

31. Verify the information in the pre-installation summary. If the information is correct, press **Enter** to start the installation.

The Hub Server is installed according to the configuration information you provide. When the process is complete, the installation complete message appears.

32. Press **Enter** to exit the installer.

Generating a Silent Installation Properties File

You can generate a silent properties file that you can use to run a silent installation. To generate a silent properties file, use the `-r` command-line option.

1. Start the application server.
2. Open a command prompt, and run the following command:

On UNIX. `./hub_install.bin -r <Path to response file location> installer.properties`

On Windows. `hub_install.exe -r <Path to response file location> installer.properties`

The `installer.properties` response file is generated at the specified location.

Installing the Hub Server in Silent Mode

You can install the Hub Server in silent mode. Before you start the silent installation, ensure that you configured the silent installation properties file.

1. Start the application server.
2. Open a command prompt, and run the following command:

On UNIX. `./hub_install.bin -f <Path to the Hub Server silent installation properties file>`

On Windows. `hub_install.exe -f <Path to the Hub Server silent installation properties file>`

The silent installer runs in the background. The process can take a while.

3. If you ran the `postInstallSetup` script for the Hub Server as part of the silent installation, check `postinstallSetup.log` to verify that the installation was successful.

The log file is in the following directory: `<MDM Hub installation directory>/hub/server/logs`.

Installing the Hub Server on Environments with Managed Servers

If you have an environment with an Administration Server and Managed Servers, you can install the Hub Server on the Administration Server and on each Managed Server. You can install on clustered or on nonclustered environments.

Ensure that the directory structure of the Hub Server installation is the same on all the nodes.

1. Start the WebLogic Administration Server and the Managed Servers on all the machines.
2. Open a command prompt, and navigate to the Hub Server installer in the distribution directory.

By default, the installer is in the following directory:

`<MDM Hub distribution directory>/<operating system name>/mrmsserver`

3. To start the Hub Server installer, run the following command:

On UNIX. `./hub_install.bin -DSIPERIAN_INSTALL_PREREQ_VALIDATION=false`

On Windows. `hub_install.exe -DSIPERIAN_INSTALL_PREREQ_VALIDATION=false`

Start the Hub Server installer on the Administration Server and all the Managed Servers in the cluster.

4. Select the language for the installation, and then click **OK**.

The **Introduction** window appears.

5. Click **Next**.

The **License Agreement** window appears.

6. Select the **I accept the terms of the License Agreement** option, and then click **Next**.

The **Choose an Install Folder** window appears.

7. Select the location of the Hub Server installation.

- To choose the default location, click **Next**.
- To enter a path, type the path to the installation folder, and click **Next**.

Note: The installation fails if you specify a path that has spaces in the directory or folder names.

- To choose another location, click **Choose**, and then click **Next**.

8. On UNIX, choose a link folder or select the option to not create links and click **Next**. On Windows, select the location to create a product icon or select the option not to create a product icon.

9. Click **Next**.

The **Enter the location of the license file** window appears.

10. Click **Choose** to select a license file, and click **Next**.

The **Advanced Security** window appears.

11. Select WebLogic, and then click **Next**.

The **WebLogic Application Server Home** window appears.

12. Configure the following WebLogic Server settings:

- a. Choose a path to the WebLogic domain installation directory for the domain that you want to use for the MDM Hub. Click **Next**.

The **WebLogic Application Server Login** window appears.

- b. Enter the following WebLogic Server login information:

Field Name	Description
Host	Name of the host computer that has the WebLogic installation. To deploy the MDM Hub application on a WebLogic port other than 7001, set the hostname and the IP address of the WebLogic host name. Do not use localhost.
Server	Name of the WebLogic Server instance in the domain on which WebLogic is deployed.
User Name	Name of the user for the WebLogic installation.
Password	Password that corresponds to the WebLogic user.
Port Number	Port number on which the Administration Server is listening.

13. Click **Next**.

The **Database Selection** window appears.

14. Select **Microsoft SQL Server**, and click **Next**.

The **Microsoft SQL Server Database Information** window appears.

15. Specify the following configuration parameters to create the J2EE data source, and click **Next**:

Field Name	Description
Server	Name of the server.
Port	Port number of the MDM Hub Master Database.
Database Name	Name of the MDM Hub Master Database.
DBO Username	Database owner user name of the MDM Hub Master Database.
DBO Password	Database owner password of the MDM Hub Master Database.

The **Install ActiveVOS** window appears.

16. If you want to install the bundled, licensed version of Informatica ActiveVOS, select **Yes** and perform the following substeps. Otherwise, select **No**, and click **Next**.

- a. On the **Choose ActiveVOS Installation Folder** page, accept the default installation path or specify a preferred location. Click **Next**.
- b. On the **Database Information** page, enter the database details that you specified when you created the ActiveVOS database schema, and click **Next**.

- c. On the **Application Server Web URL** page, accept the default URL or specify the URL that you want to use to call ActiveVOS web services. Ensure the URL contains the correct port number for the connection to the application server. Click **Next**.
The post installation setup script uses the URL to call ActiveVOS web services, deploy the predefined MDM workflows to ActiveVOS, and create the URN mapping.
 - d. On the **ActiveVOS Installer** page, click **Choose** and browse to the ActiveVOS_Server installation file in the distribution package. Click **Next**.
 - e. Enter the administrative user name and password to create an administrative user for the ActiveVOS Console.
Important: The user name and password must be the same as the ActiveVOS Console user name and password that was created in the application server.
 - f. Click **Next**.
17. Select one of the following Informatica platform installation options:
 - **Yes.** Install Informatica platform.
 - **No.** Does not install Informatica platform.
 18. If you select **Yes** in the preceding step, click **Choose** and browse to the following Informatica platform file locations:
 - Installation response file
 - Platform installation file
 19. On the Product Usage Toolkit page, select the industry to which the organization belongs and the environment type.
 20. If you want to use a proxy server, select **Yes**, and enter the proxy server details. Otherwise, select **No**.
You can enter the following proxy server details:
 - Proxy server name/IP
 - Proxy server port
 - Proxy server domain name. Leave blank if not applicable.
 - Proxy server user name. Leave blank if not applicable.
 - Proxy server password. Leave blank if not applicable.
 21. Click **Next**.
The Deploy page appears.
 22. Select the **No, I will run it later** post installation setup script option.
The **No, I will run it later** option allows you to manually run the post installation setup script later.
 23. Click **Next**.
The **Pre-Installation Summary** window appears.
 24. Click **Next**.
The **Pre-Installation Summary** window appears.
 25. After the Pre-Installation Summary window displays the options you want, click **Install** to start the installation process.
When the installation completes, the **Install Complete** window appears.
 26. Click **Done** to exit the Hub Server installer.
If you use the development cluster IP, you can access the Hub Server through the nodes in the cluster. If you use the production cluster IP, you can use the cluster names to access the Hub Server. After you start the

Hub Server application, the EJB clustering distributes requests between the Managed Servers and manages failovers.

CHAPTER 5

Hub Server Post-Installation Tasks

This chapter includes the following topics:

- [Copy the Installation Log Files, 44](#)
- [Verify the Version and Build Number, 44](#)
- [Installing and Configuring Elasticsearch, 45](#)
- [Configure the MDM Hub Master Database Name, 45](#)
- [Verify and Configure Application Server Settings \(Conditional\), 45](#)
- [Deploy the Hub Server Applications \(Conditional\), 46](#)
- [Using a Script for Deploying the Hub Server Applications \(Conditional\), 47](#)
- [Manually Deploying the Hub Server Applications \(Conditional\), 49](#)
- [Restart WebLogic, 57](#)
- [Configuring Metadata Caching \(Optional\), 57](#)
- [Starting the Hub Console, 59](#)
- [Registering an Operational Reference Store, 59](#)

Copy the Installation Log Files

The installation log files are useful for troubleshooting the Hub Server installation process. Copy the log files to the installation documentation directory. Informatica Global Customer Support might request copies of the log files if you contact them regarding installation issues.

The following table describes the different types of installation log files:

Log File Type	Description
Installation log	<ul style="list-style-type: none">- File name. Informatica_MDM_Hub_Server_Install_<timestamp>.xml- Location. <MDM Hub installation directory>/hub/server/UninstallerData/logs- Contents. Directories and registry entries that are created, names of the files installed and commands run, and status for each installed file.
Installation prerequisites log	<ul style="list-style-type: none">- File name. installPrereq.log- Location. <MDM Hub installation directory>/hub/server/logs- Contents. Logs of prerequisite checks performed by the installer.
Debug log	<ul style="list-style-type: none">- File name. infamdm_installer_debug.txt- Location. <MDM Hub installation directory>/hub/server- Contents. Detailed information about the choices that are made during the installation, and the actions performed by the installer.
Post-installation setup log	<ul style="list-style-type: none">- File name. postInstallSetup.log- Location. <MDM Hub installation directory>/hub/server/logs- Contents. Summary of actions performed by the installer during the post-installation process and the errors in the post-installation process.
Hub Server log	<ul style="list-style-type: none">- File name. cmxserver.log- Location. <MDM Hub installation directory>/hub/server/logs- Contents. Summary of the Hub Server operations.
WebLogic logs	<ul style="list-style-type: none">- File names. access.log, <WebLogic server>.log, and <WebLogic domain>.log- Location. <WebLogic domain>/servers/<WebLogic server>/logs- Contents. WebLogic server process information such as message processing status, JMS connection status, transaction details, java exceptions, and file access details.

Verify the Version and Build Number

Ensure that the correct version and build number of the Hub Server is installed.

1. Open a command prompt, and navigate to the following directory: <MDM Hub installation directory>/hub/server/bin

2. To verify the Hub Server version and build number, run the following command:

On UNIX. `versionInfo.sh`

On Windows. `versionInfo.bat`

Note: For AIX systems, change the `versionInfo.sh` script to run Java from the <Java home>/jre/bin directory.

Installing and Configuring Elasticsearch

To use search, install and setup Elasticsearch for the MDM Hub.

For more information about installing and configuring search, see the "Search with Elasticsearch" chapter in the *Multidomain MDM Configuration Guide*.

Configure the MDM Hub Master Database Name

If the MDM Hub Master Database has a name other than `cmx_system`, configure the MDM Hub Master Database name in the `cmxserver.properties` file.

1. Open the `cmxserver.properties` file in the following directory:
`<MDM Hub installation directory>/hub/server/resources`
2. Set the `cmx.server.masterdatabase.schemaname` property to the name that you specified for the MDM Hub Master Database.

You specified the name for the MDM Hub Master Database when you created it.

Verify and Configure Application Server Settings (Conditional)

Verify and configure application server settings based on the requirements of the MDM Hub environment.

The following table describes the configuration tasks that you can perform:

Configuration Task	Description
Editing the application server settings	Required if you run the <code>postInstallSetup</code> script during the installation and the script fails because of incorrect application server settings.
Configuring the Hub Server on environments with Managed Servers	Required if you installed the Hub Server in an environment with Managed Servers.

Editing the Application Server Settings

If you run the `postInstallSetup` script during the installation and the script fails because of incorrect application server settings, edit the `build.properties` file. Also, if you want to change any application server settings, edit the file.

1. Open `build.properties` file is in the following directory:
`<MDM Hub installation directory>/hub/server/bin`
2. Edit the application server settings and save the file.

After you edit the `build.properties` file, ensure that you run the `postInstallSetup` script to deploy the Hub Server applications.

Configuring the Hub Server Properties on Environments with Managed Servers

If you installed the Hub Server in an environment with Managed Servers, configure the Hub Server properties on the Administration Server and on each Managed Server. Configure the Hub Server properties in the `cmxserver.properties` file.

For example, a WebLogic environment has two Managed Servers that run on `host1` and `host2`, and use RMI ports 8001 and 8002. You need to configure the WebLogic cluster properties on both the Managed Servers.

1. Stop the WebLogic application server on the Administration Server and all the Managed Servers of the cluster.
2. On the Administration Server and all the Managed Servers, open the `cmxserver.properties` file in the following directory:

```
<MDM Hub installation directory>/hub/server/resources
```

3. Configure the following properties:

Property	Description
<code>cmx.appserver.hostname</code>	Specifies machine names of all the Managed Servers separated by a comma. For example, if the WebLogic environment has two Managed Servers that run on <code>host1</code> and <code>host2</code> , set the property to <code>cmx.appserver.hostname=host1,host2</code> .
<code>cmx.appserver.rmi.port</code>	Specifies RMI port numbers that the Managed Servers use separated by a comma. For example, if the Managed Servers in the WebLogic cluster environment use RMI ports 8001 and 8002, set the property to <code>cmx.appserver.rmi.port=8001,8002</code> .

In the properties description, the host name and port number of the first server are `host1` and 8001. The host name and port number of the second server are `host2` and 8002.

Deploy the Hub Server Applications (Conditional)

You must deploy the Hub Server applications on the same machine on which you install the Hub Server.

The Hub Server applications must be able to find the Hub Server installation from which you deploy them. Therefore, do not transfer the EAR files for deployment on another machine. For example, you install the Hub Server on a test machine, and then deploy the applications on the production machine. The applications that you deploy on the production machine cannot find the installation on the test machine for information such as logging configuration.

You need to deploy the Hub Server applications in any of the following scenarios:

- The installation is in an application server multi-node environment or cluster environment.
- The installation completes, but the `postInstallSetup` script that you run during the installation fails.
- You skipped the `postInstallSetup` script during the installation.

To deploy the Hub Server applications, use one of the following procedures described in the following table:

Procedure	Description
Using a script for deployment	You run the <code>postInstallSetup</code> script to deploy the Hub Server applications. Also, the script creates data sources and configures JMS message queues. If you deploy in an environment with Managed Servers, ensure that you specify the targets for deployment by using the WebLogic Server Administration Console.
Manual deployment	You manually deploy the Hub Server applications. Also, you must manually create data sources and configure JMS message queues.

Important: If the installation is in an application server multi-node or a cluster environment, firstly deploy the Hub Server applications on one node. Before you deploy the Hub Server applications on the other nodes, copy all the files from the `certificates` directory on the node with the deployment to the `certificates` directory on all the other nodes. The `certificates` directory is in the following location: `<MDM Hub installation directory>/hub/server/resources`.

Using a Script for Deploying the Hub Server Applications (Conditional)

If you skipped the `postInstallSetup` script during the installation, run the script. The post-installation process deploys the Hub Server applications, creates data sources, and configures JMS message queues.

1. If you use an environment with Managed Servers where the Administration Server and the Managed Servers are on different machines, copy the following deployment files to the MDM Hub installation directory of the Administration Server:

Deployment File Name	Description
<code>siperian-mrm.ear</code>	Required. The Hub Server application.
<code>provisioning-ear.ear</code>	Required. The Provisioning tool application.
<code>entity360view-ear.ear</code>	Optional. The Entity 360 framework.
<code>informatica-mdm-platform-ear.ear</code>	Optional. The Informatica platform application.
<code>ave_weblogic.ear</code>	Optional. The ActiveVOS server application.
<code>activevos-central.war</code>	Optional. The ActiveVOS Central application.

The deployment files are in the following directory:

`<MDM Hub installation directory>/hub/server`

2. Open a command prompt, and change to the following directory:

`<MDM Hub installation directory>/hub/server`

3. Run the `postInstallSetup` script.

Note: If you did not install the ActiveVOS version that is bundled with the MDM Hub installer, do not include the ActiveVOS user names and passwords in the command. For the WebLogic 12.2.1 or later environments, if you installed the ActiveVOS version that is bundled with the MDM Hub installer, run the script by adding the `-Dinstall.avos.patch=true` option.

On UNIX.

```
./postInstallSetup.sh -Dweblogic.password=<WebLogic password>
-Ddatabase.password=<MDM Hub Master database password>
-Davos.username=<ActiveVOS Console username>
-Davos.password=<ActiveVOS Console password>
-Davos.jdbc.database.username=<ActiveVOS database username>
-Davos.jdbc.database.password=<ActiveVOS database password>
```

Note: If you include the exclamation mark (!) in your password, you must include a backslash before the exclamation mark. For example, if your password is `!!cmx!!`, enter the following password: `\\!\\cmx\\!\\!`

On Windows.

```
postInstallSetup.bat
-Dweblogic.password=<WebLogic password>
-Ddatabase.password=<MDM Hub Master database password>
-Davos.username=<ActiveVOS Console username>
-Davos.password=<ActiveVOS Console password>
-Davos.jdbc.database.username=<ActiveVOS database username>
-Davos.jdbc.database.password=<ActiveVOS database password>
```

The ActiveVOS Console credentials are the same credentials as the administrative user in the application server.

The ActiveVOS database credentials are the same credentials that were used to run the `create_bpm` script.

4. If you deploy in an environment with Managed Servers, ensure that you specify the targets for deployments in the WebLogic Server Administration Console.
 - a. Specify all the Managed Servers as targets for the following Hub Server deployments:

Deployment File Name	Description
siperian-mrm.ear	Required. The Hub Server application.
provisioning-ear.ear	Required. The Provisioning tool application.
entity360view-ear.ear	Optional. The Entity 360 framework.
informatica-mdm-platform-ear.ear	Optional. The Informatica platform application.
ave_weblogic.ear	Optional. The ActiveVOS server application.
activevos-central.war	Optional. The ActiveVOS Central application.

- b. Specify all the Managed Servers as targets for the JMS module `SiperianModule`.
 - c. Specify all the Managed Servers as targets for the following data sources:
 - MDM Hub Master Database data source
 - Operational Reference Store datasource
 - d. Specify all the Managed Servers as targets for the startup and shutdown classes.

For more information, see the WebLogic documentation.

Manually Deploying the Hub Server Applications (Conditional)

If you skipped the `postInstallSetup` script during the installation or the `postInstallSetup` script fails, you can manually deploy the Hub Server applications. Ensure that you deploy the Hub Server applications from the Hub Server installation directory.

To deploy the Hub Server applications, perform the following tasks:

1. Creating data sources
2. Configuring JMS message queues
3. Repackaging the Hub Server applications
4. Deploying the Hub Server applications
5. Configuring JMS message queues in the Hub Server
6. Configuring server resources for Informatica Data Director (IDD)

Step 1. Creating Data Sources

Before you manually deploy the Hub Server applications, create data sources. Also, if you want to configure multiple Process Servers or troubleshoot installation issues, create data sources.

1. Install the JDBC driver.
2. Create an MDM Hub Master Database data source.
3. Create an Operational Reference Store data source.

Step 1. Install the JDBC Driver

Before you create data sources for the MDM Hub Master Database and the Operational Reference Store (ORS), install the JDBC driver.

Contact Microsoft to get the supported version of the JDBC driver.

1. Copy the JDBC driver to the following directory:
`<WebLogic installation directory>/wlserver/server/lib`
2. Add the path to the JDBC driver to the `CLASSPATH` variable in the following file:

On UNIX. `<WebLogic domain>/bin/commEnv.sh`

On Windows. `<WebLogic domain>\bin\commEnv.cmd`

Note: Place the path to the JDBC driver before the path to other Weblogic Server libraries.

Step 2. Create an MDM Hub Master Database Data Source

After you install the JDBC driver, create a data source for the MDM Hub Master Database.

1. On the WebLogic Administration Console, click the **Lock & Edit** button to acquire a lock.
2. Click **Services > JDBC > Data Sources**, and then click **New**.

The **JDBC Data Sources Properties** page appears.

3. Specify the following data source properties:

Property	Description
Name	Name of the JDBC data source. Set the name to <code>MDM Master Data Source</code> .
JNDI Name	JNDI path to where the JDBC data source will be bound. Specify <code>jdbc/siperian-cmx_system-ds</code> .
Database Type	Database type that you want to connect to. Select MS SQL Server .
Database Driver	JDBC driver that you want to use to connect to the database. Select MS SQL Server Driver (Type 4 XA) Versions: 2005 or later .

4. Click **Next**, and again click **Next**.
The **Connection Properties** page appears.
5. Enter values for the following connection properties:

Property	Description
Database Name	Name of the database you want to connect to.
Host Name	DNS name or IP address of the server that hosts the database. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Port	Port on which the database server listens for connection requests.
Database User Name	Database user name that you want to use for each connection in the data source.
Password	Password of the database user account.
Confirm Password	Password of the database user account.

6. Click **Next**.
The **Test Database Connection** page appears.
7. Click **Test Configuration** to test the driver connections.
If the test is unsuccessful, you must update the values in the **Connection Properties** page and then retry the connection until successful.
8. Click **Next**, and then select the server on which you want to deploy the data source.
9. Click **Finish**, and then click **Activate Changes**.

Step 3. Create an Operational Reference Store Data Source

Create a data source for each Operational Reference Store.

1. On the WebLogic Administration Console, click the **Lock & Edit** button to acquire a lock.
2. Click **Services > JDBC > Data Sources**, and then click **New**.
The **JDBC Data Sources Properties** page appears.

3. Specify the following data source properties:

Property	Description
Name	Name of the JDBC data source. Set the name to <code>MDM ORS Data Source</code> .
JNDI Name	JNDI path to where the JDBC data source will be bound. Specify <code>jdbc/siperian-<Microsoft SQL Server host name>-<Operational reference Store name>-ds</code> .
Database Type	Database type that you want to connect to. Select MS SQL Server .
Database Driver	JDBC driver that you want to use to connect to the database. Select MS SQL Server Driver (Type 4 XA) Versions: 2005 or later .

4. Click **Next**, and again click **Next**.
The **Connection Properties** page appears.
5. Enter values for the following connection properties:

Property	Description
Database Name	Name of the database you want to connect to.
Host Name	DNS name or IP address of the server that hosts the database. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Port	Port on which the database server listens for connection requests.
Database User Name	Database user name that you want to use for each connection in the data source.
Password	Password of the database user account.
Confirm Password	Password of the database user account.

6. Click **Next**.
The **Test Database Connection** page appears.
7. Click **Test Configuration** to test the driver connections.
If the test is unsuccessful, you must update the values in the **Connection Properties** page and then retry the connection until successful.
8. Click **Next**, and then select the server on which you want to deploy the data source.
9. Click **Finish**, and then click **Activate Changes**.

Step 2. Configuring JMS Message Queues

Before you manually deploy the Hub Server applications, configure JMS message queues. Also, to troubleshoot issues, you might need to manually configure JMS message queues. For example, if the

automated queue creation process fails or the queues accidentally drop after installation, you need to manually configure message queues.

The Services Integration Framework (SIF) uses a message-driven bean on the JMS message queue to process incoming asynchronous SIF requests. Configure the message queue and the connection factory for the application server that you use for the MDM Hub implementation. When you configure a JMS message queue, you also create a connection factory.

To configure the JMS message queue, perform the following tasks:

1. Create a JMS server and module.
2. Create a connection factory for the module.
3. Add JMS message queues to the module.
4. Create a subdeployment queue.
5. Add a JMS message queue for smart search.

Note: When you create JMS message queues for the MDM Hub in a clustered environment, ensure that you select a target server that you can migrate. When you configure the JMS module, make the target **“All servers in the cluster”**. For more information, see the WebLogic documentation.

Step 1. Create a JMS Server and Module

Use the Weblogic Administration Console to create a JMS message queue. Create a JMS server and a module for the message queue.

1. Start the WebLogic Console, and click **Lock & Edit**.
2. Navigate to **Services > Messaging > JMS Servers**.
3. Create a JMS Server with the name `SiperianJMSServer`, and click **Next**.
4. Select the server name in the **Target** list, and click **Finish**.
5. Navigate to **Services > Messaging > JMS Modules**.
6. Create a JMS Module with the name `SiperianModule`, and click **Next**.
7. Select the **Target Server** check box.
8. Click **Next**, and then click **Finish**.

Step 2. Configure a Connection Factory for the Module

Create and configure a connection factory for the module that you created.

1. Navigate to the `SiperianModule` that you created in [“Step 1. Create a JMS Server and Module” on page 52](#).
2. Click **New** under **Summary of Resources**.
3. Choose **Connection Factory**, and click **Next**.
4. Specify `siperian.mrm.jms.xaconnectionfactory` for both the name and the JNDI name, and click **Next**.
5. Select **Target Server**, and click **Finish**.
The `siperian.mrm.jms.xaconnectionfactory` connection factory is created.
6. Under **Configuration**, go to the `siperian.mrm.jms.xaconnectionfactory` connection factory that you created.
7. Click **Transactions**.
8. Enable **XA Connection Factory Enabled**, and click **Save**.

Step 3. Add Message Queues to the Module

You can add JMS message queues to the module that you created.

1. Navigate to **SiperianModule**, and click **New** under **Summary of Resources**.
2. Choose **Queue**, and click **Next**.
3. Specify `siperian.sif.jms.queue` for both the name and the JNDI name, and click **Next**.
4. Choose the JMS Server that you created in ["Step 1. Create a JMS Server and Module" on page 52](#), and click **Finish**.
5. Click **Activate Changes**.

Step 4. Create a Subdeployment Queue

After you add JMS message queues to the module that you created, create a subdeployment queue.

1. Under **Summary of Resources**, go to **SiperianModule**, and click **New**.
2. Choose **Queue**, and click **Next**.
3. Click the **Create a new Subdeployment** button.
4. Verify that the **Subdeployment Name** is `siperian.sif.jms.queue`, and click **OK**.
5. Specify `siperian.sif.jms.queue` for both the name and the JNDI name, and click **Next**.
6. Choose the JMS Server that you created, and click **Finish**.
7. Click **Activate Changes**.

Step 3. Repackaging the Hub Server EAR Files

If you edit the `cmx.home` property in the `cmxserver.properties` file or if you installed in an application server cluster, repackage the Hub Server EAR files on the Administration Server.

1. Create a directory named `EAR`.
 - a. Navigate to the following directory:
`<MDM Hub installation directory>/hub/server/lib`
 - b. Run the following command:
`mkdir ear`
2. If you have custom JAR files, copy each custom JAR file to the `EAR` directory that you created in the preceding step.

To copy a custom JAR file to the `EAR` directory, run the following command:

```
copy <location of custom JAR file>/< custom JAR file name>.jar ear
```

You might require custom JAR files for custom user exits.
3. Repackage the `EAR` files.
 - a. Navigate to the following directory:
`<MDM Hub installation directory>/hub/server/bin`
 - b. Run the following command:
On UNIX. `./sip_ant.sh repackage`
On Windows. `sip_ant.bat repackage`

Step 4. Deploying the Hub Server Application

You can manually deploy the Hub Server applications. Ensure that you deploy the Hub Server applications from the Hub Server installation directory.

1. If you have any existing deployments, use the WebLogic Server Administration Console to undeploy the following deployment files:

Deployment File Name	Description
siperian-mrm.ear	Required. The Hub Server application.
provisioning-ear.ear	Required. The Provisioning tool application.
entity360view-ear.ear	Optional. The Entity 360 framework.
informatica-mdm-platform-ear.ear	Optional. The Informatica platform application.
ave_weblogic.ear	Optional. The ActiveVOS server application.
activevos-central.war	Optional. The ActiveVOS Central application.

2. Use the WebLogic Server Administration Console to deploy the deployment files.
3. If you deploy in an environment with Managed Servers, ensure that you specify the targets for deployments in the WebLogic Server Administration Console.
 - a. Specify all the Managed Servers as targets for the following Hub Server deployments:

Deployment File Name	Description
siperian-mrm.ear	Required. The Hub Server application.
provisioning-ear.ear	Required. The Provisioning tool application.
entity360view-ear.ear	Optional. The Entity 360 framework.
informatica-mdm-platform-ear.ear	Optional. The Informatica platform application.
ave_weblogic.ear	Optional. The ActiveVOS server application.
activevos-central.war	Optional. The ActiveVOS Central application.

- b. Specify all the Managed Servers as targets for the JMS module `SiperianModule`.
- c. Specify all the Managed Servers as targets for the following data sources:
 - MDM Hub Master Database data source
 - Operational Reference Store datasource
- d. Specify all the Managed Servers as targets for the startup and shutdown classes.

For more information, see the WebLogic Server documentation.

Step 5. Configuring JMS Message Queues on the Hub Server

After you manually deploy the Hub Server applications, configure JMS message queues on the Hub Server.

To configure the JMS message queue on the Hub Server, perform the following tasks:

1. Start the Hub Console.
2. Add a message queue server.
3. Add a message queue.

Step 1. Start the Hub Console

To access the MDM Hub, start the Hub Console.

1. Open a browser window and enter the following URL:
`http://<MDM Hub host>:<port number>/cmx/`
Check with your administrator for the correct port number.
The **Hub Console launch** window appears.
2. Launch the Hub Console.
3. Enter your user name and password, and then click **Log in**.
Java Web Start downloads application files.
The **Informatica MDM Hub Login** dialog box appears.
4. Enter your user name and password, and click **OK**.
The **Change database** dialog box appears.
5. Select the target database.
The target database is the MDM Hub Master Database.
6. Select a language from the list, and click **Connect**.
The Hub Console user interface appears in the language that you select. If you need to change the language in which the Hub Console user interface appears, restart the Hub Console with the language of your choice.

Step 2. Add a Message Queue Server

Before you add a message queue, you must add a message queue server to the MDM Hub implementation.

1. In the Hub Console, click **Message Queues** under the Configuration workbench.
2. Click **Write Lock > Acquire Lock**.
3. Right-click the middle pane of the Message Queues tool, and then click **Add Message Queue Server**.
The **Add Message Queue Server** dialog box appears.
4. Enter the message queue server details.

The following table describes the fields that you use to configure the JMS message queue server:

Field Name	Value
Connection Factory Name	Name of the connection factory. Specify <code>siperian.mrm.jms.xaconnectionfactory</code> .
Display Name	Name of the message queue server that must appear in the Hub Console. Specify <code>siperian.mrm.jms.xaconnectionfactory</code> .

5. Click **OK**.

The message queue server is added.

Step 3. Add a Message Queue

You can add a message queue to a message queue server.

1. In the Hub Console, click **Message Queues** under the Configuration workbench.
2. Click **Write Lock > Acquire Lock**.
3. Right-click the message queue server in the middle pane of the Message Queues tool, and then click **Add Message Queue**.

The **Add Message Queue** dialog box appears.

4. Enter JMS message queue details.

The following table describes the JMS message queue fields:

Field Name	Value
Queue Name	Name of the message queue. Specify <code>java:/queue/siperian.sif.jms.queue</code> .
Display Name	Name of the message queue that must appear in the Hub Console. Specify <code>java:/queue/siperian.sif.jms.queue</code> .

5. Click **OK**.

The message queue is added to the message queue server.

6. In the right pane, select the **Use with message triggers** option.
7. Click **Test**.

The result of the message queue test appears.

Step 6. Configuring Server Resources for Informatica Data Director

If you want to use Informatica Data Director (IDD), configure the JNDI URL resource.

1. Copy the `weblogic-jndi-startup-1.3.jar` file from the source to the target directory:

Source: `<MDM Hub installation directory>/hub/server/lib`

Target: `<WebLogic installation directory>/domains/<domain name>/lib`

2. On the WebLogic Server Administration Console, click **Environment > Startup and Shutdown Classes**.

3. To configure the JNDI URL resource, set the following properties for the JndiServerDir startup class:

Class Property	Value
Class name	nz.co.senanque.jndi.WebLogicJndiStartup
Deployment order	1000
Argument	url/hubserver/home<java.net.URL>=file:///<Hub Server installation directory>

4. Set targets for the startup class.

Restart WebLogic

The installation process enables the `AnonymousAdminLookupEnabled` method of the WebLogic Server. The `AnonymousAdminLookupEnabled` method must be enabled for the registration of the Operational Reference Store. If you do not restart WebLogic Server after you install the Hub Server, the Operational Reference Store fails.

Configuring Metadata Caching (Optional)

Metadata caches manage items such as data objects, repository objects, and search tokens. The MDM Hub uses Infinispan for metadata caching. Infinispan is installed with the Hub Server. For the caches that the Hub Server uses, the Infinispan configuration file contains default attribute values.

Run the MDM Hub with the default attribute values for the caches. If you experience performance issues, you can fine-tune the attribute values to better suit your environment.

The following table summarizes the default attribute values:

Infinispan Element and Attribute	Default Value	Description
locking acquire-timeout	60000	Maximum time during which the Hub Server can try to acquire a lock.
transaction stop-timeout	30000	When a cache stops, this attribute sets the maximum time that Infinispan waits while the Hub Server finishes remote and local transactions.
transport cluster	infinispan-cluster	Name for the underlying group communication cluster.
transport stack	UDP	Type of configuration: UDP or TCP. The configurations are defined in the <code>jgroups-udp.xml</code> file and the <code>jgroups-tcp.xml</code> file.

Infinispan Element and Attribute	Default Value	Description
transport node-name	\$node\$	Name of the current node. The Hub Server sets this attribute. The node-name defaults to a combination of the host name and a random number. The number differentiates multiple nodes on the same host.
transport machine	\$machine\$	ID of the machine where the node runs. The Hub Server sets this attribute.
expiration lifespan	--	Maximum lifespan of a cache entry in milliseconds. When a cache entry exceeds its lifespan, the entry expires within the cluster. If you need to optimize performance, increase the lifespan for the following caches: DISABLE_WHEN_LOCK, DATA_OBJECTS, and REPOS_OBJECTS. For example, you can increase the lifespan from one hour (3600000) to one day (86400000). Each cache has its own default value for this attribute. To find the default values, open the <code>infinispanConfig.xml</code> file.
expiration interval	--	Maximum interval for checking the lifespan. If you need to optimize performance, increase the interval for the following caches: DISABLE_WHEN_LOCK, DATA_OBJECTS, and REPOS_OBJECTS. For example, you can increase the interval from five seconds (5000) to five minutes (300000). Each cache has its own default value for this attribute. To find the default values, open the <code>infinispanConfig.xml</code> file.

Editing Infinispan Attributes

To configure metadata caching attributes, edit the `infinispanConfig.xml` file for the Hub Server. For help with the Infinispan configuration, see the Infinispan documentation.

Note: The Process Server also has an Infinispan configuration file. The default attribute values should be sufficient, however if you notice issues with the performance of the Process Server, you can fine-tune the attribute values.

1. Navigate to the following directory: `<MDM Hub installation directory>/hub/server/resources`
2. Make a backup copy of the following file: `infinispanConfig.xml`
3. Open the `infinispanConfig.xml` file and find the Infinispan version number, which appears in the `xsi:schemaLocation` attribute.
4. Review the documentation for the Infinispan version.

Note: In the following URLs, substitute the version number wherever the path contains `##`.

- To view the configuration schema, go to the URL that is contained in the `xsi:schemaLocation` attribute in the file.
 - To learn about the attributes, go to <https://docs.jboss.org/infinispan/<##.x>/configdocs/>
 - To learn about Infinispan, go to <http://infinispan.org/docs/<##.x>/> and select the "Frequently Asked Questions" link.
5. Edit the file and save it.

Starting the Hub Console

To access the MDM Hub, start the Hub Console. Use an HTTP or HTTPS connection to start the Hub Console. Ensure that you have a user name and password set up before you start the Hub Console.

1. Open a browser window and enter the following URL:

`http://<MDM Hub host>:<port number>/cmx/`

Check with your administrator for the correct port number.

The **Hub Console launch** window appears.

2. Launch the Hub Console.
3. Enter your user name and password, and then click **Log in**.

Java Web Start downloads application files.

The **Informatica MDM Hub Login** dialog box appears.

4. Enter your user name and password, and click **OK**.

The **Change database** dialog box appears.

5. Select the target database.

The target database is the MDM Hub Master Database.

6. Select a language from the list, and click **Connect**.

The Hub Console user interface appears in the language that you select. If you need to change the language in which the Hub Console user interface appears, restart the Hub Console with the language of your choice.

Registering an Operational Reference Store

After you create an Operational Reference Store, you must register it through the Hub Console. Register an Operational Reference Store with a single MDM Hub Master Database.

1. Start the Hub Console.

The **Change database** dialog box appears.

2. Select **MDM Hub Master Database**, and click **Connect**.

3. Under the **Configuration** workbench, click the **Databases** tool.

4. From the **Write Lock** menu, click **Acquire Lock**.

5. In the Databases pane, click the **Register database** button.

The **Informatica MDM Hub Connection Wizard** appears.

6. Select the Microsoft SQL Server database type option, and click **Next**.

7. Configure connection properties for the database.

- a. In the Connection Properties page, specify the connection properties, and then click **Next**.

The following table describes the connection properties:

Property	Description
Database Display Name	Name for the Operational Reference Store that must appear in the Hub Console.
Machine Identifier	Prefix given to keys to uniquely identify records from the Hub Store instance.
Database hostname	IP address or name of the server that hosts the Microsoft SQL Server database.
Port	Port of the Microsoft SQL Server database. The default is 1433.
Database Name	Name of the Operational Reference Store.
Password	Password associated with the user name for the Operational Reference Store.
DDM connection URL	Optional. URL to connect to the Dynamic Data Masking application. The URL is similar to the URL that you use to connect to the database, except that the Dynamic Data Masking application URL uses the Dynamic Data Masking host name and port number.

- b. In the Connection Properties page, specify the connection properties, and then click **Next**.
- c. Review the summary, and specify additional connection properties.

The following table lists additional connection properties that you can configure:

Property	Description
Connection URL	Connect URL. The Connection Wizard generates the connect URL by default.
Create data source after registration	Select to create the data source on the application server after registration. If you do not select the option, you must manually configure the data source. Note: In application server cluster environments, manually create the data sources and connection pools for the Operational Reference Stores.

8. Click **Finish**.
The **Registering Database** dialog box appears.
9. Click **OK**.
The MDM Hub registers the Operational Reference Store.
10. Select the Operational Reference Store that you registered, and click the **Test database connection** button.
The Test Database dialog box displays the result of the database connection test.
11. Click **OK**.
The Operational Reference Store is registered, and the connection to the database is tested.

CHAPTER 6

Process Server Installation

This chapter includes the following topics:

- [Process Server Installation Modes, 61](#)
- [Installing the Process Server in Graphical Mode, 61](#)
- [Installing the Process Server in Console Mode, 63](#)
- [Installing the Process Server in Silent Mode, 65](#)
- [Installing the Process Server on Environments with Managed Servers, 65](#)

Process Server Installation Modes

You can use any of the following modes to install the Process Server:

- Graphical mode
- Console mode
- Silent mode

Installing the Process Server in Graphical Mode

You can install the Process Server in graphical mode.

You must use the same user name to install the Hub Server and the Process Server.

Note: When you install the Process Server on RedHat Linux, do not use the root user. The root user does not have a `.profile`, which InstallAnywhere requires. Instead, create and use a separate user profile to install the Process Server.

1. Start the application server.
2. Open a command prompt, and navigate to the following directory:
`<MDM Hub distribution directory>/<operating system name>/mrncleanse`
3. Run the following command:
On UNIX. `hub_cleanse_install.bin`
On Windows. `hub_cleanse_install.exe`

4. Select the language for the installation, and then click **OK**.
The **Introduction** window appears.
5. Click **Next**.
The **License Agreement** window appears.
6. Select the **I accept the terms of the License Agreement** option, and then click **Next**.
The **Choose Install Folder** window appears.
7. Choose the default location to install the Process Server, or browse to choose a different location. Click **Next**.
Important: Process Server fails to load if the total length of the path exceeds 256 characters or includes spaces in the directory or folder names.
On UNIX, the **Choose Link Folder** window appears.
On Windows, the **Choose Shortcut Folder** window appears.
8. Select a location for the product icons, and click **Next**.
The **Enter Location of License File** window appears.
9. Click **Choose** to select a license file, and click **Next**.
The **Application Server** window appears.
10. Select WebLogic, and then click **Next**.
The **WebLogic Application Server Home** window appears.
11. Configure the following WebLogic Server settings:
 - a. Choose a path to the WebLogic domain installation directory for the domain you want to use for the MDM Hub. Click **Next**.
The **WebLogic Application Server Login** window appears.
 - b. Enter values for the login parameters.
The following table describes the login parameters:

Parameter	Description
Host	Name of the host computer on which WebLogic is installed. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Server	Name of the WebLogic Server instance in the domain on which WebLogic is deployed. For example, AdminServer.
User Name	Name of the user for the WebLogic installation.
Password	Password that corresponds to the WebLogic user.
Port Number	Port number on which the WebLogic Server is listening.

12. Configure cleanse engine settings for the cleanse engine you use.
 - If you use Informatica Address Verification, specify the Configuration file and Parameters file locations and the Correction Type parameter.
 - If you use Business Objects DQ XI, specify the Host, Port, and Sub File parameters for the Business Objects DQ XI cleanse engine.
13. On the Product Usage Toolkit page, select the **Environment Type**.

14. If you have a proxy server, select **Yes**, and enter the proxy server details. Otherwise, select **No**, and click **Next**.

You can enter the following proxy server details:

- Proxy server name/IP
 - Proxy server port
 - Proxy server domain name. Leave blank if not applicable.
 - Proxy server user name. Leave blank if not applicable.
 - Proxy server password. Leave blank if not applicable.
15. In the **Deploy** page, select the **No, I will run it later** option, which allows you to manually run the post installation script later.
 16. Click **Next**.
The **Pre-Installation Summary** window appears.
 17. After the summary window displays the options you want, click **Install** to start the installation process.
When the installation completes, the **Install Complete** window appears.
 18. Choose to restart the system now or later.
 19. Click **Done** to exit the Process Server installer.

After installation, you must perform additional configuration for the cleanse engine according to the instructions in the *Multidomain MDM Cleanse Adapter Guide*.

Installing the Process Server in Console Mode

You can install the Process Server in console mode on UNIX.

Note: When you install the Process Server on RedHat Linux, do not use the root user. The root user does not have a `.profile`, which InstallAnywhere requires. Instead, create and use a separate user profile to install the Process Server.

1. Start the application server.
2. Open a command prompt, and navigate to the Process Server installer in the following directory:
`<MDM Hub distribution directory>/<operating system name>/mrmcleanse`
3. Run the following command from the command prompt:
`./hub_cleanse_install.bin -i console`
4. Enter the number of the locale you want to choose for the installation, and then press **Enter**.
The introduction information about the installation appears.
5. Press **Enter**.
The license agreement appears.
6. Read the License Agreement. Type **Y** to accept the license agreement, or type **N** if you do not want to accept the license agreement and want to exit the installation program.
7. Press **Enter**.
If you entered **Y** in the preceding step, information about the installation folder appears.

8. Choose the folder for the Process Server installation.
 - To choose the default location, press **Enter**.
 - To change the path, type the absolute path of the installation folder, and press **Enter**.
9. Confirm the location of the installation folder. Type **Y** to confirm the installation folder, or type **N** to change the installation folder.
10. Press **Enter**.

The prompt for the license file location appears.
11. Enter the absolute path of the license file, and press **Enter**.

A list of application server options appears.
12. Type the number for the application server that you want to select, and press **Enter**.

The application server information appears.
13. Configure the WebLogic settings.
 - a. Specify the path to the WebLogic domain in which you want to install the Hub Server, and press **Enter**.

The prompts for the WebLogic application server login information appears.
 - b. Enter the host name, server name, user name, password, and listener port for the WebLogic Server, or accept the default values, and press **Enter**.
14. Press **Enter**.
15. Configure the cleanse engine settings.
 - If you use Informatica Address Verification, configure the following parameters:
 - Specify the configuration file location, and press **Enter**.
 - Specify the parameters file location, and press **Enter**.
 - Specify the default correction type, and press **Enter**.
 - If you use Business Objects DQ XI, configure the following parameters:
 - Specify the host name, and press **Enter**.
 - Specify the port, and press **Enter**.
 - Specify the sub file, and press **Enter**.
16. From the Product Usage Toolkit options, select the environment type. Type 1 for Production, type 2 for Test/QA, or type 3 for Development, and then press **Enter**.
17. Select whether you have a proxy server. Press **Enter** for Yes. Otherwise, type 2 for No and then press **Enter**.

You can enter the following proxy server details:

 - Proxy server name/IP
 - Proxy server port
 - Proxy server domain name. Leave blank if not applicable.
 - Proxy server user name. Leave blank if not applicable.
 - Proxy server password. Leave blank if not applicable.

The summary of the installation choices appears.
18. Choose whether you want to run the `postInstallSetup` script as part of the installation, or run it manually later.
19. Press **Enter**.

The summary of the installation choices appears.

20. Verify the information in the pre-installation summary. If the information is correct, press **Enter** to start the installation. If you need to make changes, type **BACK** to the specific information and make changes.

The Hub Server is installed according to the configuration information you provide. When the process is complete, the installation complete information appears.

21. Press **Enter**.

The Process Server is installed according to the information you specify, and the install complete information appears.

22. Press **Enter** to exit the installer.

Installing the Process Server in Silent Mode

You can install the Process Server in silent mode. Before you start the silent installation, ensure that you configured the silent installation properties file.

Note: When you install the Process Server on RedHat Linux, do not use the root user. The root user does not have a `.profile`, which InstallAnywhere requires. Instead, create and use a separate user profile to install the Process Server.

1. Start the application server.
2. Open a command prompt, and run the following command:

On UNIX. `./hub_cleanse_install.bin -f <Path to the Process Server silent installation properties file>`

On Windows. `hub_cleanse_install.exe -f <Path to the Process Server silent installation properties file>`

The silent installer runs in the background. The process can take a while.

3. If you ran the `postInstallSetup` script for the Process Server as part of the silent installation, check `postinstallSetup.log` to verify that the installation was successful.

The log file is in the following directory: `<MDM Hub installation directory>/hub/cleanse/logs`.

Installing the Process Server on Environments with Managed Servers

Install the Process Server on the Administration Server and on all the Managed Servers to which you must deploy the Process Server application. In a clustered environment, ensure that the path for the Process Server installation is the same on all the cluster nodes.

Note: When you install the Process Server on RedHat Linux, do not use the root user. The root user does not have a `.profile`, which InstallAnywhere requires. Instead, create and use a separate user profile to install the Process Server.

1. Start the WebLogic Administration Server and the Managed Servers on all the machines.
2. Open a command prompt, and navigate to the following directory:

<MDM Hub distribution directory>/<operating system name>/mrmcleanse

3. To start the Process Server installer, run the following command:

On UNIX. `./hub_cleanse_install.bin -DSIPERIAN_INSTALL_PREREQ_VALIDATION=false`

On Windows. `hub_cleanse_install.exe -DSIPERIAN_INSTALL_PREREQ_VALIDATION=false`

4. Select the language for the installation, and then click **OK**.

The **Introduction** window appears.

5. Click **Next**.

The **License Agreement** window appears.

6. Select the **I accept the terms of the License Agreement** option, and then click **Next**.

The **Choose Install Folder** window appears.

7. Choose the default location to install the Process Server, or browse to choose a different location. Click **Next**.

Important: Process Server fails to load if the total length of the path exceeds 256 characters or includes spaces in the directory or folder names.

On UNIX, the **Choose Link Folder** window appears.

On Windows, the **Choose Shortcut** Folder window appears.

8. Select a location for the product icons, and click **Next**.

The **Enter Location of License File** window appears.

9. Click **Choose** to select a license file, and click **Next**.

The **Application Server** window appears.

10. Select WebLogic, and then click **Next**.

The **WebLogic Application Server Home** window appears.

11. Configure the following WebLogic Server settings:

- a. Choose a path to the WebLogic domain installation directory for the domain you want to use for the MDM Hub. Click **Next**.

The **WebLogic Application Server Login** window appears.

- b. Enter values for the login parameters.

The following table describes the login parameters:

Parameter	Description
Host	Name of the host computer on which WebLogic Administration Server is created. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Server	Name of the WebLogic Server instance in the domain on which WebLogic is deployed. For example, AdminServer.
User Name	Name of the user for the WebLogic installation.

Parameter	Description
Password	Password that corresponds to the WebLogic user.
Port Number	If the cluster is set up with the development cluster IP address, specify the Administration Server port number for any node in the WebLogic cluster. If you use the production cluster IP address, specify the cluster port number.

12. Configure cleanse engine settings for the cleanse engine you use.
 - If you use Informatica Address Verification, specify the Configuration file and Parameters file locations and the Correction Type parameter.
 - If you use Business Objects DQ XI, specify the Host, Port, and Sub File parameters for the Business Objects DQ XI cleanse engine.
13. On the Product Usage Toolkit page, select the **Environment Type**.
14. If you have a proxy server, select **Yes**, and enter the proxy server details. Otherwise, select **No**, and click **Next**.
You can enter the following proxy server details:
 - Proxy server name/IP
 - Proxy server port
 - Proxy server domain name. Leave blank if not applicable.
 - Proxy server user name. Leave blank if not applicable.
 - Proxy server password. Leave blank if not applicable.
15. In the **Deploy** page, select the **No, I will run it later** post installation setup script option.
The **No, I will run it later** option allows you to manually run the post installation script later.
16. Click **Next**.
The **Pre-Installation Summary** window appears.
17. After the summary window displays the options you want, click **Install** to start the installation process.
When the installation completes, the **Install Complete** window appears.
18. Choose to restart the system now or later.
19. Click **Done** to exit the Process Server installer.

CHAPTER 7

Process Server Post-Installation Tasks

This chapter includes the following topics:

- [Copy the Installation Log Files, 68](#)
- [Verify the Version and Build Number, 69](#)
- [Deploy the Process Server Application \(Conditional\), 69](#)
- [Enabling Secured Communications for Process Servers, 74](#)
- [Installing and Configuring Elasticsearch, 75](#)
- [Configure Match Population, 75](#)
- [Configuring the Process Server with Cleanse Engines, 76](#)

Copy the Installation Log Files

The installation log files are useful for troubleshooting the Process Server installation process. Copy the log files to the installation documentation directory. Informatica Global Customer Support might request copies of the log files if you contact them regarding installation issues.

The following table describes the different types of installation log files:

Log File Type	Description
Installation log	<ul style="list-style-type: none">- File name. Informatica_MDM_Cleanse_Match_Server_Install_<timestamp>.xml- Location. <MDM Hub installation directory>/hub/cleanse/UninstallerData/Logs- Contents. Directories created, names of the files installed and commands run, and status for each installed file.
Installation prerequisites log	<ul style="list-style-type: none">- File name. installPrereq.log- Location. <MDM Hub installation directory>/hub/cleanse/Logs- Contents. Logs of prerequisite checks performed by the installer.
Debug log	<ul style="list-style-type: none">- File name. infamdm_installer_debug.txt- Location. <MDM Hub installation directory>/hub/cleanse/- Contents. Detailed information about the choices that are made during installation and the actions performed by the installer.

Log File Type	Description
Post-installation setup log	<ul style="list-style-type: none"> - File name. <code>postInstallSetup.log</code> - Location. <code><MDM Hub installation directory>/hub/cleanse/logs</code> - Contents. Summary of actions performed by the installer during the post-installation process and the errors in the post-installation process.
Process Server log	<ul style="list-style-type: none"> - File name. <code>cmxserver.log</code> - Location. <code><MDM Hub installation directory>/hub/cleanse/logs</code> - Contents. Summary of the Process Server operations.
WebLogic Server logs	<ul style="list-style-type: none"> - File names. <code>access.log</code>, <code><WebLogic server>.log</code>, and <code><WebLogic domain>.log</code> - Location. <code><Weblogic domain>/servers/<Weblogic server>/logs</code> - Contents. Contains message processing status, JMS connection status, transaction details, java exceptions, and file access details.

Verify the Version and Build Number

Ensure that the correct version and build number of the Process Server is installed.

1. Open a command prompt, and navigate to the following directory: `<MDM Hub installation directory>/hub/cleanse/bin`
2. To verify the Process Server version and build number, run the following command:

On UNIX. `versionInfo.sh`

On Windows. `versionInfo.bat`

Note: For AIX systems, change the `versionInfo.sh` script to run Java from the `<Java home>/jre/bin` directory.

Deploy the Process Server Application (Conditional)

If you have a scenario that requires deployment of the Process Server application, deploy the Process Server application.

You need to deploy the Process Server application in any of the following scenarios:

- The installation is in an application server multi-node environment or cluster environment.
- The installation completes, but the `postInstallSetup` script that you run during the installation fails.
- You skipped the `postInstallSetup` script during the installation.

Perform the following steps to deploy the Process Server application:

1. If the Process Server is not installed on the same application server instance as the Hub Server, create data sources.
2. Deploy the Process Server application `siperian-mrm-cleanse.ear`.
3. If you deploy in an environment with Managed Servers, specify the targets for deployment.

Step 1. Creating Data Sources (Conditional)

If the Process Server is not deployed on the same application server instance as the Hub Server, configure the data sources for the application server.

1. Install the JDBC driver.
2. Create an MDM Hub Master Database data source.
3. Create an Operational Reference Store data source.

Step 1. Install the JDBC Driver

Before you create data sources for the MDM Hub Master Database and the Operational Reference Store (ORS), install the JDBC driver.

Contact Microsoft to get the supported version of the JDBC driver.

1. Copy the JDBC driver to the following directory:
`<WebLogic installation directory>/wlserver/server/lib`
2. Add the path to the JDBC driver to the `CLASSPATH` variable in the following file:

On UNIX. `<WebLogic domain>/bin/commEnv.sh`

On Windows. `<WebLogic domain>\bin\commEnv.cmd`

Note: Place the path to the JDBC driver before the path to other Weblogic Server libraries.

Step 2. Create an MDM Hub Master Database Data Source

After you install the JDBC driver, create a data source for the MDM Hub Master Database.

1. On the WebLogic Administration Console, click the **Lock & Edit** button to acquire a lock.
2. Click **Services > JDBC > Data Sources**, and then click **New**.
The **JDBC Data Sources Properties** page appears.
3. Specify the following data source properties:

Property	Description
Name	Name of the JDBC data source. Set the name to <code>MDM Master Data Source</code> .
JNDI Name	JNDI path to where the JDBC data source will be bound. Specify <code>jdbc/siperian-cmx_system-ds</code> .
Database Type	Database type that you want to connect to. Select MS SQL Server .
Database Driver	JDBC driver that you want to use to connect to the database. Select MS SQL Server Driver (Type 4 XA) Versions: 2005 or later .

4. Click **Next**, and again click **Next**.
The **Connection Properties** page appears.

5. Enter values for the following connection properties:

Property	Description
Database Name	Name of the database you want to connect to.
Host Name	DNS name or IP address of the server that hosts the database. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Port	Port on which the database server listens for connection requests.
Database User Name	Database user name that you want to use for each connection in the data source.
Password	Password of the database user account.
Confirm Password	Password of the database user account.

6. Click **Next**.
The **Test Database Connection** page appears.
7. Click **Test Configuration** to test the driver connections.
If the test is unsuccessful, you must update the values in the **Connection Properties** page and then retry the connection until successful.
8. Click **Next**, and then select the server on which you want to deploy the data source.
9. Click **Finish**, and then click **Activate Changes**.

Step 3. Create an Operational Reference Store Data Source

Create a data source for each Operational Reference Store.

1. On the WebLogic Administration Console, click the **Lock & Edit** button to acquire a lock.
2. Click **Services > JDBC > Data Sources**, and then click **New**.
The **JDBC Data Sources Properties** page appears.
3. Specify the following data source properties:

Property	Description
Name	Name of the JDBC data source. Set the name to <code>MDM ORS Data Source</code> .
JNDI Name	JNDI path to where the JDBC data source will be bound. Specify <code>jdbc/siperian- <Microsoft SQL Server host name>-<Operational reference Store name>-ds</code> .
Database Type	Database type that you want to connect to. Select MS SQL Server .
Database Driver	JDBC driver that you want to use to connect to the database. Select MS SQL Server Driver (Type 4 XA) Versions: 2005 or later .

4. Click **Next**, and again click **Next**.
The **Connection Properties** page appears.

5. Enter values for the following connection properties:

Property	Description
Database Name	Name of the database you want to connect to.
Host Name	DNS name or IP address of the server that hosts the database. To deploy the MDM Hub application on a WebLogic port other than 7001, set the host name and the IP address of the WebLogic host. Do not use localhost.
Port	Port on which the database server listens for connection requests.
Database User Name	Database user name that you want to use for each connection in the data source.
Password	Password of the database user account.
Confirm Password	Password of the database user account.

6. Click **Next**.
The **Test Database Connection** page appears.
7. Click **Test Configuration** to test the driver connections.
If the test is unsuccessful, you must update the values in the **Connection Properties** page and then retry the connection until successful.
8. Click **Next**, and then select the server on which you want to deploy the data source.
9. Click **Finish**, and then click **Activate Changes**.

Step 2. Deploying the Process Server Application (Conditional)

If the installation is in an application server multi-node environment or cluster environment, or the `postInstallSetup` script was skipped or fails, deploy the Process Server application.

Deploy the Process Server application on the same machine on which you installed the Process Server. The Process Server application must be able to find the Process Server installation associated with it. Therefore, do not copy the application EAR file for deployment on another machine. For example, you install the Process Server on a test machine, and then deploy the application on the production machine. The application that you deploy on the production machine cannot find the installation on the test machine.

Deploy the Process Server application by using one of the following procedures:

Using a script for deployment

You run the `postInstallSetup` script to deploy the Process Server application.

Manual deployment

You manually deploy the Process Server application.

Using a Script for Deploying the Process Server Application (Conditional)

You can run the `PostInstallSetup` script to deploy the Process Server application. You must run the `PostInstallSetup` script on the WebLogic Administration Server.

Important: If the installation is in an application server multi-node or a cluster environment, first deploy the Process Server application on one node, and then deploy the Process Server application on the other nodes.

Ensure that you deploy the Process Server application on the same machine on which you installed the Process Server.

1. Start WebLogic. If you installed in an environment with Managed Servers, start the WebLogic Administration Server and all the Managed Servers.
2. If you use an environment with Managed Servers where the Administration Server and the Managed Servers are on different machines, copy the `siperian-mrm-cleanse.ear` deployment file to the Process Server installation directory of the Administration Server.

The deployment file is in the following directory: `<MDM Hub installation directory>/hub/cleanse`

3. Open a command prompt, and change to the following directory:

`<MDM Hub installation directory>/hub/cleanse`

4. Run the `PostInstallSetup` script.

On UNIX. `./postInstallSetup.sh -Dweblogic.password=<weblogic Password> -Ddatabase.password=<Database Password>`

On Windows. `postInstallSetup.bat -Dweblogic.password=<weblogic Password> -Ddatabase.password=<Database Password>`

For more information, see the WebLogic documentation.

Manually Deploying the Process Server Application (Conditional)

You can manually deploy the Process Server on the WebLogic application server. You must deploy the Process Server application from the Process Server installation directory.

1. If you have any existing deployments, use the WebLogic Server Administration Console to undeploy `siperian-mrm-cleanse.ear`.
2. Use the WebLogic Server Administration Console to deploy `siperian-mrm-cleanse.ear`.
You must deploy the EAR file from the Process Server installation directory.

For more information about deploying applications, see the WebLogic documentation.

Step 3. Specify the Targets for Deployments In Environments with Managed Servers (Conditional)

If you deploy in an environment with Managed Servers, specify the targets for deployments in the WebLogic Server Administration Console.


1. Start the WebLogic Server Administration Console.
2. Specify all the Managed Servers as targets for the `siperian-mrm-cleanse.ear` deployment.
3. If the Process Server and the Hub Server instances are on different Managed Servers, specify all the Managed Servers of the Process Server instances as targets for the following data sources:
 - MDM Hub Master Database data source
 - Operational Reference Store data source
4. Verify that all the Managed Servers are targets for the startup and shutdown classes.

For more information, see the WebLogic documentation.

Enabling Secured Communications for Process Servers

Each Process Server requires a signed certificate. Use the Hub Console to enable the HTTPS protocol and specify a secure port for each Process Server.

1. Create signed certificates for the Process Servers in the certificate store.
2. Ensure that the application server can access the certificate store.
3. Log in to the Hub Console.
4. Select an Operational Reference Store database.
5. Acquire a write lock.
6. In the **Utilities** workbench, select **Process Server**.
7. Select a Process Server and click the **Edit Process Server** icon.
The Add/Edit Process Server dialog box opens.
8. Verify that the **Port** is a secure port.
9. Select the **Enable Secured Connection (HTTPS)** check box.



The screenshot shows the 'Add/Edit Process Server' dialog box with the following settings:

Process Server Information	
Server	192.168.1.1
Port	8443
Enable Cleanse Operations	<input checked="" type="checkbox"/>
Threads for Cleanse Operations	2
Cleanse Mode	Online and Batch
Enable Match Processing	<input checked="" type="checkbox"/>
Match Mode	Online and Batch
Offline	<input type="checkbox"/>
Enable Batch Processing	<input checked="" type="checkbox"/>
Threads for Batch Processing	20
CPU Rating	1.0
Enable Search Processing	<input checked="" type="checkbox"/>
Enable Secured Connection (HTTPS)	<input checked="" type="checkbox"/>

10. Click **OK**.
11. Verify other Process Servers that appear in the list.

Installing and Configuring Elasticsearch

To use search, install and setup Elasticsearch for the MDM Hub.

For more information about installing and configuring search, see the "Search with Elasticsearch" chapter in the *Multidomain MDM Configuration Guide*.

Configure Match Population

The match population contains the standard population set to use for the match process. Each supported country, language, or population has a standard population set. You must enable the match population to use for the match rules.

The match population is available as a *population.ysp* file with the Informatica MDM Hub installation. The population name is the same as the ysp file name. If you add a Japanese population, and want to use the Person_Name_Kanji match field, add _Kanji to the population name. For example, Japan_Kanji or Japan_i_Kanji. If you do this, the standard Person_Name match field is not available.

The population that you use must be compatible with the SSA-Name3 version of the MDM Hub. If you need additional population files or if you need an updated population file to upgrade to a later version, contact Informatica Global Customer Support. The first population file that you request with the product is free. You might need population files for other countries or you might need an updated population file to upgrade to a later version of the MDM Hub.

Enabling Match Population

You must enable the match population to use for the match rules.

1. Copy the *<population>.ysp* files to the following location:
On UNIX. *<infamdm_install_directory>/hub/cleanse/resources/match*
On Windows. *<infamdm_install_directory>\hub\cleanse\resources\match*
2. In the C_REPOS_SSA_POPULATION metadata table, verify that the population is registered.
The seed database for the MDM Hub installation has some populations registered in the C_REPOS_SSA_POPULATION table, but not enabled.
3. If the C_REPOS_SSA_POPULATION table does not contain the population, add it to the table and enable it.
The population name is the same as the ysp file name. For example, if the ysp file name is *US.ysp*, the population name is US.
To add the population to an Operational Reference Store, use the following steps:
 - a. Run the *add_std_ssa_population.bat* script in the following directory:
<infamdm_install_directory>\server\resources\database\custom_scripts\MSSQL

- b. Answer the prompts described in the following table:

Prompt	Description
Host name with Microsoft SQL Server instance for CMX_ORS database ("localhost")	Host name of the Microsoft SQL Server instance.
cmx_ors user name ("cmx_ors")	User name of the Operational Reference Store.
cmx_ors user password	Password of the Operational Reference Store.
Enter the population name (Note: If you use Person_Name_Kanji for the Japan population or Japan_i population, add the suffix '_Kanji' to the end of the name) DEFAULT (" ")	Name of the population.
Enter a value for ROWID_SSA_POP (example: INFA.0001) DEFAULT (INFA.0001)	Unique value for the ROWID_SSA_POP column of the C_REPOS_SSA_POPULATION metadata table.

The population is registered in the C_REPOS_SSA_POPULATION table.

- c. Run the following command to enable the population:

```
USE <Operational Reference Store user>
GO
UPDATE [dbo].[C_REPOS_SSA_POPULATION] SET ENABLED_IND = 1 WHERE POPULATION_NAME
= '<Your Population>'
```

- Restart the Process Server after you enable populations.
- Log in to the Hub Console to verify that the population is enabled.

The population appears in the **Match/Merge Setup** user interface for base objects.

Configuring the Process Server with Cleanse Engines

After you install the Process Server, you can configure a cleanse engine with the Process Server.

For more information about cleanse engine configuration, see the *Multidomain MDM Cleanse Adapter Guide*.

CHAPTER 8

ActiveVOS Post-Installation Tasks for the Application Server

This chapter includes the following topics:

- [Create a Trusted User in WebLogic Environments, 77](#)
- [Configure WebLogic for Secure ActiveVOS Communication, 78](#)
- [Editing the Default Security Realm, 78](#)
- [Adding ActiveVOS Roles, 78](#)
- [Configure Users and Groups in WebLogic, 79](#)

Create a Trusted User in WebLogic Environments

To use the ActiveVOS workflow engine, create a trusted user with the role of abTrust, abServiceConsumer, and abTaskClient in the application server.

The trusted user is the same user as the ActiveVOS workflow adapter user in the Hub Console. The name of the trusted user cannot be the same name as the application server administrative user.

1. In the WebLogic console, create the following roles:
 - abTrust
 - abServiceConsumer
 - abTaskClient
2. In the WebLogic console, create the trusted user, and then assign the user to the abTrust, abServiceConsumer, and abTaskClient roles.
3. Restart the application server.

Configure WebLogic for Secure ActiveVOS Communication

To use the HTTP Secure (HTTPS) protocol for communication between ActiveVOS and the MDM Hub, you must configure the application server.

1. In the WebLogic console, enable the SSL listen port for the application server.
2. Open a command prompt.
3. Navigate to the following directory:

```
<MDM Hub installation directory>\hub\server
```

4. Run the following command:

For UNIX:

```
postinstallSetup.sh -Ddatabase.password=<MDM Hub Master Database password> -  
Dweblogic.password=<WebLogic password>
```

For Windows:

```
postinstallSetup.bat -Ddatabase.password=<MDM Hub Master Database password> -  
Dweblogic.password=<WebLogic password>
```

5. Restart the application server.

Editing the Default Security Realm

In WebLogic, a security realm is a container for managing user credentials and roles.

1. In the WebLogic Server Administration Console, in the MDM10 domain, click **Security Realms**.
2. Click the default realm, called **myRealm**.
3. Click the **Providers** tab, and then click the **Authentication** tab.
4. On the Authentication tab, click **DefaultAuthenticator**.
5. Click the **Configuration** tab, and then click the **Common** tab.
6. From the Control Flag list, select **OPTIONAL**.
7. Click **Save**.
8. Restart the WebLogic instance.

Adding ActiveVOS Roles

Add the ActiveVOS roles to the security realm.

1. In the WebLogic Server Administration Console, in the MDM10 domain, click **Security Realms**.
2. Select the security realm.
3. Click the **Roles and Policies** tab, and then click the **Realm Roles** tab.
4. On the Realm Roles tab, expand **Global Roles**, and then click **Roles**.

5. Click **New**.
6. In the Name field, type the ActiveVOS role `abAdmin` and click **OK**.
7. Click **New**.
8. In the Name field, type the ActiveVOS role `abTaskClient` and click **OK**.
9. Click **New**.
10. In the Name field, type the ActiveVOS role `abServiceConsumer` and click **OK**.
11. Click **New**.
12. In the Name field, type the ActiveVOS role `abTrust` and click **OK**.

Configure Users and Groups in WebLogic

If you are using the recommended BE ActiveVOS workflow engine, you can skip this section. The BE ActiveVOS workflow engine uses the MDM Identity Services for ActiveVOS.

If you use any other workflow engines, create users and groups in WebLogic that match the MDM user roles.

Creating Groups

Create a group for MDM Hub administrators and another group for MDM Hub users.

1. In the WebLogic Server Administration Console, in the MDM10 domain, click **Security Realms**.
2. Select the realm you created.
3. Click the **Users and Groups** tab.
4. Click **Groups**.
5. Click **New**.
6. In the Name field, type `MDMAVadmins` and click **OK**.
7. Click **New**.
8. In the Name field, type `MDMAVusers` and click **OK**.

Adding Users

Add the MDM Hub administrators and users that you want to authenticate with the ActiveVOS Server.

1. Add users with user credentials that match MDM Hub administrators and MDM Hub users.
 - a. On the Users and Groups tab, click **Users**.
 - b. Click **New**.
 - c. In the Name field, type the user name of an MDM Hub administrator or user.
 - d. In the Password fields, type and retype the password for this user name.
 - e. Click **OK**.
 - f. Repeat to add all the MDM Hub administrators and users that you want to authenticate with the ActiveVOS Server.

2. Assign the administrators to the MDMAVadmins group.
 - a. On the Users and Groups tab, click an MDM Hub administrator.
 - b. Click **Groups**.
 - c. In the Available list, select the **MDMAVadmins** group and move it to the Chosen list.
 - d. Click **Save**.
 - e. Repeat to add the rest of the MDM Hub administrators.
3. Assign the users to the MDMAVusers group.

Editing the abTaskClient Role

Edit the abTaskClient role, and add a security policy to permit users in the MDMAVusers group to authenticate with the ActiveVOS Server.

1. Click the **Roles and Policies** tab, and then click the **Realm Roles** tab.
2. On the Realm Roles tab, expand **Global Roles > Roles**.
3. In the **abTaskClient** row, click **View Role Conditions**.
4. Click **Add Conditions**.
5. From the Predicate List, select **Group**.
6. Click **Next**.
7. In the Group Argument Name field, type `MDMAVusers` and click **Add**.
8. Click **Finish**.
9. Click **Save**.

CHAPTER 9

ActiveVOS Post-Installation Tasks for the Business Entity Adapter

This chapter includes the following topics:

- [ActiveVOS Web Applications, 81](#)
- [Configuring the ActiveVOS URNs for the Business Entity Workflow Adapter, 82](#)
- [Set the ActiveVOS Protocol to HTTPS, 82](#)
- [Configure the Primary Workflow Engine, 83](#)
- [Configure the MDM Identity Services for ActiveVOS, 83](#)
- [Configure Tasks, 84](#)

ActiveVOS Web Applications

When you install the bundled, licensed version of the ActiveVOS Server, you are also licensed to use two ActiveVOS web applications. After you add users to the application server container, you can use these applications.

You use the web applications for different purposes:

ActiveVOS Console

Administrators use the ActiveVOS Console to manage deployed processes, the alerting system, and endpoint locations. You can also configure the engine for performance monitoring and management.

ActiveVOS Central

Business users can use ActiveVOS Central to manage tasks, requests, and reports. However, in general, business users use an Data Director (IDD) application to manage tasks because they can open the entities to review from the Task Manager.

To use ActiveVOS Central, you must add the MDM Hub users to the application server container.

For more information about the web applications, see the Informatica ActiveVOS documentation.

Configuring the ActiveVOS URNs for the Business Entity Workflow Adapter

The ActiveVOS Server has two predefined uniform resource names (URNs) that it uses internally. You need to update the URL in the URN mappings to use the host name and the port number where the ActiveVOS Server runs.

1. Launch the ActiveVOS Console. In a browser, type the following URL, substituting the correct host name and port number:
Encrypted connections. `https://[host]:[port]/activevos`
Non-encrypted connections. `http://[host]:[port]/activevos`
2. In the ActiveVOS Console, on the Home page, click **Administration > Configure Server > URN Mappings**.
3. For the following URNs, update the paths to reflect the host name and port number of the ActiveVOS Server:

URN	URL Path
ae:internal-reporting	Encrypted connections. <code>https://[host]:[port]/activevos/internalreports</code> Non-encrypted connections. <code>http://[host]:[port]/activevos/internalreports</code>
ae:task-inbox	Encrypted connections. <code>https://[host]:[port]/activevos-central/avc</code> Non-encrypted connections. <code>http://[host]:[port]/activevos-central/avc</code>

4. Verify that **urn:mdm:service** is mapped to the host name and port number of the MDM Hub Server:
Encrypted connections. `https://[host]:[port]/cmx/services/BeServices`
Non-encrypted connections. `http://[host]:[port]/cmx/services/BeServices`

Set the ActiveVOS Protocol to HTTPS

To enable secure communication between ActiveVOS and the MDM Hub, set the protocol to HTTPS in the Hub Console Workflow Manager.

You must first configure the application server for HTTPS communications.

1. Start the Hub Console.
2. Acquire a write lock.
3. Click **Workflow Manager** under the Configuration workbench.
4. In the Workflow Manager, click the **Workflow Engines** tab.
5. Select the ActiveVOS workflow engine, and then click the **Edit** button.
6. In the Edit Workflow dialog box, set the protocol to HTTPS.
7. In a WebLogic environment, in the Edit Workflow dialog box, enter the user name and password of the user that belongs to the abAdmin role.

Configure the Primary Workflow Engine

To configure the primary workflow engine, add a workflow engine for ActiveVOS workflows based on business entities. The secondary workflow engine is for existing customers who want to process existing tasks with a deprecated workflow engine.

1. In the Hub Console, click **Workflow Manager** in the Configuration workbench.
2. Acquire a write lock.
3. Select the **Workflow Engines** tab and click the **Add** button.
4. In the **Add Workflow** dialog box, enter the workflow engine properties.

The following table describes the workflow engine properties:

Field	Description
Workflow Engine	The display name of the workflow engine
Adapter Name	Select BE ActiveVOS for the ActiveVOS workflow adapter based on business entities.
Host	The host name of the Informatica ActiveVOS instance.
Port	The port name of the Informatica ActiveVOS instance.
Username	The user name of the trusted user.
Password	The password of the trusted user.
Protocol	The protocol for communication between the MDM Hub and ActiveVOS. The protocol can be http or https.

5. Click **OK**.

Configure the MDM Identity Services for ActiveVOS

If you use embedded ActiveVOS, ensure that you configure ActiveVOS to use MDM Identity Services. To configure the MDM Identity Services for ActiveVOS, use the ActiveVOS Console to set the Identity Services password to the password of the MDM Hub workflow engine user.

1. In the ActiveVOS console, select **Admin > Configure Services > Identity Services**.
2. In the Provider Configuration section, enable the **Enable** check box and select **MDM** from the **Provider Type** list.
3. In the Connection tab, enter the password of the MDM Hub user with the user name `admin`.
Note: If you later change the password for the admin user, you must enter the new password in the ActiveVOS identity services settings.
4. Click **Update**.

5. Test that ActiveVOS can log in to the MDM Hub as the `admin` user, and that ActiveVOS can retrieve a list of roles for the user you specify as the **User for test**.
 - a. Select the **Test** tab.
 - b. In the **User for test** field, enter an MDM Hub user that is assigned to a role.
 - c. Click **Test Settings**.

Note: The test fails if an Operational Reference Store is not configured, the user for test does not belong to a role, or the role name contains spaces.

Configure Tasks

Before you begin using task workflows in Informatica Data Director, configure task templates, task triggers, and task types in the Provisioning tool.

For more information, see the *Multidomain MDM Provisioning Tool Guide*.

CHAPTER 10

Resource Kit Installation

This chapter includes the following topics:

- [Setting Up the MDM Hub Sample Operational Reference Store, 85](#)
- [Registering the Informatica MDM Hub Sample Operational Reference Store, 87](#)
- [Installing the Resource Kit in Graphical Mode, 88](#)
- [Installing the Resource Kit in Console Mode, 91](#)
- [Installing the Resource Kit in Silent Mode, 93](#)

Setting Up the MDM Hub Sample Operational Reference Store

Before you can use the MDM Hub sample Operational Reference Store, you must set it up. Before you install the Resource Kit, set up the MDM Hub sample Operational Reference Store. To set up the MDM Hub sample Operational Reference Store, create an Operational Reference Store and import `mdm_sample` into it.

1. Navigate to the following location in the distribution directory:

On UNIX. `<distribution directory>/database/bin`

On Windows. `<distribution directory>\database\bin`

2. Run the following command:

On UNIX. `./sip_ant.sh create_ors`

On Windows. `sip_ant.bat create_ors`

3. Answer the prompts that appear.

Note: The prompt displays default text in brackets. Press **Enter** to use the default value and go to the next prompt.

Enter database type. (ORACLE, MSSQL, DB2)

Database type. Specify `MSSQL`.

Enter the Operational Reference Store database host name. [localhost]

Name of the machine that hosts the database. Default is `localhost`.

Enter the Operational Reference Store database port number. [1433]

Port number that the database uses. Default is `1433`.

Connect URL. [jdbc:sqlserver://<host name>:<port>]

Connect URL for the database connection.

Enter CMX_ORS database path. ['C:\MSSQLDATA']

Path to the Microsoft SQL Server data file store enclosed in double quotation marks.

Enter CMX_SYSTEM database collation name [Latin1_General_CI_AS]

Collation name to set a collation sequence for the MDM Hub Master Database.

Enter the Operational Reference Store database user password.

Password of the MDM Hub sample Operational Reference Store user.

Enter a locale name from the list: de, en_US, fr, ja, ko, zh_CN. [en_US]

Operating system locale. Default is en_US.

Enter the DBA user name. [sa]

Default is sa.

Enter the DBA password.

Password of the SA user account.

4. After you create the sample Operational Reference Store, review `sip_ant.log` in the following directory:

On UNIX. `<distribution directory>/database/bin`

On Windows. `<distribution directory>\database\bin`

The `sip_ant.log` file logs any errors that might occur when you run the `sip_ant` script to create the Operational Reference Store.

5. To import `mdm_sample`, run the following command:

On UNIX. `./sip_ant.sh import_schema`

On Windows. `sip_ant.bat import_schema`

6. Answer the prompts that appear.

Note: The prompt displays default text in brackets. Press **Enter** to use the default value and go to the next prompt.

Enter database type. (ORACLE, MSSQL, DB2)

Database type. Specify `MSSQL`.

Enter the Operational Reference Store database host name. [localhost]

Name of the machine that hosts the database. Default is `localhost`.

Enter the Operational Reference Store database port number. [1433]

Port number that the database uses. Default is `1433`.

Connect URL. [jdbc:sqlserver://<host name>:<port>]

Connect URL for the database connection.

Enter the Operational Reference Store database user name. [cmx_ors]

Name of the MDM Hub sample Operational Reference Store database. Default is `cmx_ors`.

Enter the Operational Reference Store database user password.

Name of the MDM Hub sample Operational Reference Store database user.

Enter a locale name from the list: de, en_US, fr, ja, ko, zh_CN. [en_US]

Operating system locale. Default is `en_US`.

Enter the path to the ZIP dump file. [<distribution directory>\resources\database]

Path to the `mdm_sample.zip` file.

Enter the name of the ZIP dump file. [mdm_sample.zip]

Name of the ZIP dump file. Default is `mdm_sample.zip`.

Registering the Informatica MDM Hub Sample Operational Reference Store

After you set up the MDM Hub sample Operational Reference Store, you must register it. Register the MDM Hub sample Operational Reference Store through the Hub Console.

1. Start the Hub Console.

The **Change database** dialog box appears.

2. Select the MDM Hub Master Database, and click **Connect**.

3. Start the **Databases** tool under the Configuration workbench.

4. Click **Write Lock > Acquire Lock**.

5. Click the **Register database** button.

The **Informatica MDM Hub Connection Wizard** appears and prompts you to select the database type.

6. Select the type of database, and click **Next**.

7. Configure connection properties for the database.

- a. In the Connection Properties page, specify the connection properties, and then click **Next**.

The following table lists and describes the connection properties:

Property	Description
Database Display Name	Name for the Operational Reference Store that must appear in the Hub Console.
Machine Identifier	Prefix given to keys to uniquely identify records from the Hub Store instance.
Database hostname	IP address or name of the server that hosts the Microsoft SQL Server database.
Port	Port of the Microsoft SQL Server database. The default is 1433.
Schema Name	Name of the Operational Reference Store. Specify <code>mdm_sample</code> .
Password	Password associated with the user name for the Operational Reference Store.

- b. In the Connection Properties page, specify the connection properties, and then click **Next**.
 - c. Review the summary, and specify additional connection properties.

The following table lists additional connection properties that you can configure:

Property	Description
Connection URL	Connect URL. The Connection Wizard generates the connect URL by default.
Create data source after registration	Select to create the data source on the application server after registration.

8. Click **Finish**.

The **Registering Database** dialog box appears.

9. Click **OK**.

The MDM Hub registers the MDM Hub sample Operational Reference Store.

10. Select the MDM Hub sample Operational Reference Store that you registered, and click the **Test database connection** button to test the database settings.

The Test Database dialog box displays the result of the database connection test.

11. Click **OK**.

The Operational Reference Store is registered, and the connection to the database is tested.

Installing the Resource Kit in Graphical Mode

You can install the Resource Kit in graphical mode.

Before you install the Resource Kit, you must have installed and configured the MDM Hub.

1. Start the application server.

2. Open a command prompt and navigate to the Resource Kit installer. By default the installer is in the following directory:

On UNIX. `<distribution directory>/<operating system name>/mrmresourcekit`

On Windows. `<distribution directory>\windows\mrmresourcekit`

3. Run the following command:

On UNIX. `hub_resourcekit_install.bin`

On Windows. `hub_resourcekit_install.exe`

4. Select the language for the installation, and then click **OK**.

The **Introduction** window appears.

5. Click **Next**.

The **License Agreement** window appears.

6. Select the **I accept the terms of the License Agreement** option, and then click **Next**.

The **Installation Feature** window appears.

7. Select the Resource Kit features that you want to install and click **Next**.

You can select the following options:

Sample Schema

Installs the MDM Hub sample schema resources. You must create a sample schema and register it with the Hub Server before you install the sample applications.

Samples and Utilities

Installs the sample applications and utilities.

The list of sample applications that are deployed is stored in the `build.properties` file in the following directory:

`<Resourcekit_Home>\samples`

SIF SDK and Javadocs

Installs the javadocs, libraries, and resources associated with the SIF SDK.

BPM SDK

Installs the resources associated with the BPM SDK.

Jaspersoft

Copies the Jaspersoft installer to the Resource Kit home.

SSA-NAME3

Copies the SSA-NAME3 installer to the Resource Kit home.

A message about the requirement of having created and registered a sample schema with the MDM Hub appears.

8. Click **OK**.

The **Choose Install Folder** window appears.

9. Select the location of the Resource Kit installation.

- To choose the default location, click **Next**.
- To enter a path, type the path to the installation folder, and click **Next**.

Note: The installation fails if you specify a path that has spaces in the directory or folder names.

- To return to the default installation location, click **Restore Default Folder**.

- To choose another location, click **Choose**, and then click **Next**.

On UNIX, the **Choose Link Folder** window appears.

On Windows, the **Choose Shortcut Folder** window appears.

10. On UNIX, choose a link folder or select the option to not create links, and click **Next**. On Windows, select the location to create a product icon or select the option not to create a product icon.

The **Configuration Selection** window appears.

11. Select a configuration option, and click **Next**.

You can select one of the following options:

Configure Samples

Installs and configures the samples.

Source Only

Installs the sources of samples but does not configure the samples.

If you select **Configure samples**, the **Resource Kit App Server** window appears. If you select **Source only**, the **Pre-Installation Summary** window appears.

12. From the **Resource Kit App Server** window, select the application server on which you want to install the Resource Kit, and click **Next**.

The **Application Server Home** window for the application server that you select appears.

13. Configure the application server settings.

- a. Choose a path to the WebLogic domain installation directory for the domain that you want to use for the MDM Hub, and click **Next**.

The **WebLogic Application Server Login** window appears.

- b. Enter the WebLogic Server login information.

Enter values in the following login parameter fields:

Host

Name of the host computer that has the WebLogic installation.

Server

Name of the WebLogic Server instance in the domain on which WebLogic is deployed.

User Name

Name of the user for the WebLogic installation.

Password

Password that corresponds to the WebLogic user.

Port Number

Port number on which the WebLogic Server is listening.

The **Informatica MDM Hub Server** window appears.

14. Enter the information for the Hub Server installation, and click **Next**.

Enter values in the following fields:

Server Name

Name of the server that hosts the Hub Server.

Server HTTP Port

Port number of the Hub Server.

Informatica MDM Administrative Password

Password to access the MDM Hub.

MDM Hub Home Directory

Directory for the Hub Server installation.

The **Resource Kit ORS ID** window appears.

15. Select a Resource Kit ORS ID from the list, and then click **Next**.

The list contains the Operational Reference Store IDs that you created. Select an Operational Reference Store ID related to the sample schema.

If you have not registered the sample schema, you will not see the Operational Reference Store ID for the sample schema. Register the sample Operational Reference Store, and then restart the installation.

The **Deployment Selection** window appears.

16. Select one of the following options and click **Next**:

Yes, run it during this installation.

Deploys and configures the Resource Kit during the installation.

No, it can be deployed later.

Select this option to deploy and configure manually at a later time.

If you chose to install the Samples and Utilities feature, you must deploy and configure the Resource Kit in this installation step. If you do not deploy the Resource Kit in this step, you cannot make changes and redeploy the samples by using the postInstallSetup script provided in the Resource Kit.

If you choose to run the post-installation setup manually, you cannot deploy the EAR file by using the postInstallSetup script at a later time. You must manually edit the EAR file and deploy it to make any changes to your installation.

The **Pre-Installation Summary** window appears.

17. Review the Pre-Installation Summary to confirm your installation choices, and then click **Install**.

When the installation completes, the **Install Complete** window appears.

18. Click **Done** to exit the Resource Kit installer.

Installing the Resource Kit in Console Mode

You can install the Resource Kit in console mode.

Ensure that you register the MDM_SAMPLE schema before you install the Resource Kit.

1. Start the application server.
2. Navigate to the following directory in the MDM Hub distribution:
On UNIX. <MDM Hub distribution directory>/<operating system name>/resourcekit
On Windows. <MDM Hub distribution directory>/windows/resourcekit
3. Run the following command from the command prompt:
On UNIX. ./hub_resourcekit_install.bin -i console
On Windows. hub_resourcekit_install.exe -i console
4. Enter the number of the locale you want to choose for the installation, and then press **Enter**.

The introduction information about the installation appears.

5. Press **Enter**.

The license agreement appears.

6. Read the License Agreement. Type **Y** to accept the terms of the license agreement, or type **N** if you do not want to accept the license agreement and want to exit the installation program.

7. Press **Enter**.

If you entered **Y** in the preceding step, information about the installation folder appears.

8. Enter the numbers of the Resource Kit features that you want to install separated by commas, and press **Enter**.

The prompt for the sample schema installation appears.

9. Choose a folder for the Resource Kit installation.

- To choose the default folder, press **Enter**.
- To change the path, type the absolute path of the installation folder, and press **Enter**.

10. Confirm the location of the installation folder. Type **OK** to confirm the installation folder or type **Cancel** to change the installation folder.

11. Press **Enter**.

A list of link location options appears.

12. Enter the number of a link location option.

The prompt for the link file location appears.

13. Enter the absolute path of the link file, and press **Enter**.

The source sample configuration options appears.

14. Enter a configuration option, and press **Enter**.

Option	Description
1	Installs and configures the samples
2	Installs the sources of samples but does not configure the samples

If you enter **1**, a list of application server options appears. If you enter **2**, the pre-Installation summary appears.

15. If you entered **1**, enter the number for the application server that you want to select, and press **Enter**.

The application server information prompts appear.

16. Configure the WebLogic settings.

- a. Specify the path to the WebLogic domain in which you want to install the Resource Kit, and press **Enter**.

The prompts for the WebLogic application server login information appears.

- b. Enter the host name, server name, user name, password, and listener port for the WebLogic Server, or accept the default values, and press **Enter**.

The Hub Server installation information prompts appear.

17. Enter the information for the Hub Server installation, and press **Enter**.

The following table describes the prompts for the Hub Server installation information:

Prompt	Description
Server Name	Name of the server that hosts the Hub Server.
Server HTTP Port	Port number of the Hub Server.
Informatica MDM Administrative password	Password to access the MDM Hub.
MDM Hub Home Directory	Directory for the Hub Server installation.

A list of MDM Hub ORS IDs appears.

18. Enter the Operational Reference Store ID of the MDM sample schema, and press **Enter**.
If you did not register the sample schema, you will not see the Operational Reference Store ID for the sample schema. Register the sample Operational Reference Store, and then restart the installation.
The deployment selection prompt appears.
19. Choose whether you want to run the `postInstallSetup` script as part of the installation, or run it manually later.
20. Press **Enter**.
The summary of the installation choices appears.
21. Verify the information in the pre-installation summary. If the information is correct, press **Enter** to start the installation.
The Resource Kit is installed according to the configuration information you provide. When the process is complete, the installation complete information appears.
22. Press **Enter** to exit the installer.

Installing the Resource Kit in Silent Mode

You can install the Resource Kit without user interaction in silent mode. You might want to perform a silent installation if you need multiple installations, or if you need to install on a machine cluster. A silent installation does not show any progress or failure messages.

Before you run the silent installation for the Resource Kit, you must configure the properties file for the silent installation. The installer reads the file to determine the installation options. The silent installation process might complete successfully even if you provide incorrect settings, such as an incorrect application server path or port. You must ensure that you provide correct settings in the properties file.

Copy the Resource Kit installation files to the hard disk on the machine where you plan to install the Resource Kit. To install in silent mode, complete the following tasks:

1. Configure the installation properties file and specify the installation options in the properties file.
2. Run the installer with the installation properties file.

Configuring the Properties File

Informatica provides a sample properties file that includes the parameters that the installer requires. You can customize the sample properties file to specify the options for the installation. Then run the silent installation.

The silent installer does not validate the settings in the properties files. You must ensure that you specify correct settings and verify them before you run the silent installer.

1. Find the `silentInstallResourceKit_sample.properties` file in the following directory:

On UNIX. `/silent_install/mrmresourcekit`

On Windows. `\silent_install\mrmresourcekit`

After you customize the file, save it. You can rename the file and put it anywhere on the machine.

Note: In the silent properties file, slash and backslash are special characters. You must enter two of each of these characters when you enter information in the file, such as when you enter an installation path. For example, to enter the path to the server directory, you must enter `\\u1\\infamdm\\hub\\resourcekit`.

2. Create a backup copy of the `silentInstallResourceKit_sample.properties` file.
3. Use a text editor to open the file and change the values of the installation parameters.
4. Save the properties file with a new name such as `silentInstallresourcekit.properties`.

The following table describes the installation parameters that you can change:

Property Name	Description
INSTALLER_UI	Specifies the mode of installation. Set to <code>silent</code> .
SIP.INSTALL.TYPE	Specifies the type of installation. Set to <code>SIPERIAN_SAMPLE_INSTALL</code> .
SIP.INSTALL.SAMPLE.SCHEMA	Specifies if you want to install the sample schema. Specify one of the following values: <ul style="list-style-type: none">- 0. Does not install the sample schema- 1. Installs the sample schema
SIP.INSTALL.SAMPLES	Specifies if you want to install samples and utilities. Specify one of the following values: <ul style="list-style-type: none">- 0. Does not install samples and utilities- 1. Installs samples and utilities
SIP.INSTALL.SIF.SDK	Specifies if you want to install the Services Integration Framework (SIF) SDK. Specify one of the following values: <ul style="list-style-type: none">- 0. Does not install the SIF SDK- 1. Installs SIF SDK
SIP.INSTALL.BPM.SDK	Specifies if you want to install the BPM SDK. Specify one of the following values: <ul style="list-style-type: none">- 0. Does not install the BPM SDK- 1. Installs the SIF SDK
SIP.INSTALL.JASPERSOFT	Specifies if you want to install the Jaspersoft reporting tool. Specify one of the following values: <ul style="list-style-type: none">- 0. Does not install the BPM SDK- 1. Installs the SIF SDK

Property Name	Description
SIP.INSTALL.SSNAME3	Specifies if you want to install SSA-NAME3. Specify one of the following values: - 0. Does not install SSA-NAME3 - 1. Installs SSA-NAME3
USER_INSTALL_DIR	Directory where you want to install the Resource Kit, such as C:\:\<infamdm_install_directory>\hub\resourcekit.
RUN_CONFIGURE_FLAG	Specifies if you want to configure samples. - 0. Does not configure samples - 1. Installs and configures samples Default is 1. If you set the RUN_CONFIGURE_FLAG property to 1, comment out or set the RUN_CONFIGURE_SETUP property to 0. To configure samples, ensure that the application server and the Hub Server are started and the sample schema is registered in the Hub Console.
RUN_CONFIGURE_SETUP	Specifies if you want to configure only source samples. - 0. Does not install sources of samples - 1. Installs sources of samples If you set the RUN_CONFIGURE_SETUP property to 1, comment out or set the RUN_CONFIGURE_FLAG property to 0. If you set the RUN_CONFIGURE_SETUP property to 1, you cannot configure and deploy samples later.
SIP.AS.CHOICE	Name of the application server. Specify WebLogic.
SIP.AS.HOME	The path to the WebLogic installation directory.
SIP.APPSERVER.HOST	Host name such as localhost.
SIP.APPSERVER.SERVER	Admin Server name such as AdminServer.
SIP.APPSERVER.USERNAME	User name to access WebLogic.
SIP.APPSERVER.PASSWORD	Password to access WebLogic.
WEBLOGIC.AS.PORT	Application server port number.
SIP.SERVER.NAME	Name of the server on which the Hub Server is deployed.
SIP.SERVER.HTTP.PORT	Port on which the Hub Server is listening.
SIP.ADMIN.PASSWORD	Password to access the Hub Server.
HUB_SERVER_HOME	Directory for the Hub Server installation.
SIP.ORS.ID	Operational Reference Store ID of the MDM Hub sample schema.
RUN_DEPLOYMENT_FLAG	Runs the postInstallSetup script as part of the silent installation. - 0. Does not run the postInstallSetup script - 1. Runs the postInstallSetup script

Running the Silent Installer

After you configure the properties file, you can start the silent installation.

1. Ensure that the application server is running.
2. Open a command window.
3. Run the following command:

On UNIX. `./hub_resourcekit_install.bin -f
<location_of_silent_properties_file_for_resourcekit>`

On Windows. `.\hub_resourcekit_install.exe -f
<location_of_silent_properties_file_for_resourcekit>`

The silent installer runs in the background. The process can take a while. Check the `postinstallSetup.log` files to verify that the installation was successful.

The log file is available in the following directory:

On UNIX. `<infamdm_install_directory>/logs/postInstall.log`

On Windows. `<infamdm_install_directory>\logs\postInstall.log`

CHAPTER 11

Troubleshooting the MDM Hub

This chapter includes the following topic:

- [Troubleshooting the Installation Process, 97](#)

Troubleshooting the Installation Process

If the installation fails, use the following information to troubleshoot the failure.

MDM Hub users cannot login

If you re-create the CMX_SYSTEM schema after installation of the Hub Server, the MDM Hub cannot recognize the hashed passwords. As a result, users cannot log in to the MDM Hub.

To resolve the issue, run the `postInstallSetup` script again manually. This script ensures that the passwords of the MDM Hub users are hashed again and users can log in.

Alternatively, if you do not want to run the `postInstallSetup` script again, run the following commands to migrate the user passwords to hashed passwords and create application users.

On UNIX.

```
cd <MDM Hub installation directory>/server/bin
./sip_ant.sh hash_users_passwords
./sip_ant.sh add_application_users
```

On Windows.

```
cd <MDM Hub installation directory>\server\bin
sip_ant.bat hash_users_passwords
sip_ant.bat add_application_users
```

Note: In a WebSphere environment, the MDM Hub user must have access and write permissions for the following directory:

```
<MDM Hub installation directory>/server/bin/resources/certificates
```

WebLogic instance redirects to Data Director

If you install MDM Hub on a WebLogic port other than 7001, the instance is redirected to Data Director with the following error:

```
javax.faces.application.ViewExpiredException: viewId:/config/config_login.jsf - View /
config/config_login.jsf could not be restored.
```

To resolve the issue, set to the host name and the IP address of the WebLogic host. Do not use localhost.

PostInstallSetUp script fails because the ActiveVOS server deployment times out

When you install the Hub Server, the post-installation setup process might fail after trying to deploy the ActiveVOS server.

To resolve the issue, increase the value of the `deploy.wait.time` property in the `build.properties` file in the following directory:

On UNIX. `<infamdm installation directory>/hub/server/bin`

On Windows. `<infamdm installation directory>\hub\server\bin`

The Hub Server cannot connect to the cmx_system schema

To verify that the Hub Server cannot connect to the `cmx_system` schema, review the application server log.

To resolve the issue, resolve the database connection issue. Use the application server console to test the connection to the database. If you cannot resolve the connection to the `cmx_system` schema, re-create the `cmx_system` schema.

Failed to verify the need to tokenize records

When you run the Match process, you might receive the following error:

```
SIP-16062: Failed to verify the need to tokenize records.
```

Verify the following environment variable settings:

- The `PATH` environment variable must contain the following path:

On UNIX. `<infamdm_install_directory>/hub/cleanse/lib`

On Windows. `<infamdm_install_directory>\hub\cleanse\lib`

- The `SSAPR` environment variable must include the following path for all users:

On UNIX. `<infamdm_install_directory>/server_install_dir/cleanse/resources`

On Windows. `<infamdm_install_directory>\server_install_dir\cleanse\resources`

major.minor version errors when loading the Process Server

If you see multiple `major.minor` console errors when you try to load the Process Server, check that the system has the correct Java version installed.

Informatica Address Verification exception during certification

Informatica Address Verification generates an exception during certification. Ensure that the stack size for the JVM is sufficient.

1. Navigate to the WebLogic home directory.
2. Open the following file in a text editor.
On UNIX. `setDomainEnv.sh`
On Windows. `startWeblogic.cmd`
3. Use the following command to set the `MEM_ARGS` variable:
On UNIX.

```
set MEM_ARGS=${MEM_ARGS} -Xss2000k
```


On Windows.

```
set MEM_ARGS=%MEM_ARGS% -Xss2000k
```
4. Save and close the file.

Operational Reference Store does not have a workflow engine configured

If you install the MDM Hub and then import an Operational Reference Store (ORS) from a previous version, you see a fatal error that indicates that the ORS does not have a workflow engine configured. This error occurs because the Siperian BPM workflow engine is not registered by default. Use the Workflow Manager to register the Siperian BPM workflow engine with the name that the ORS expects to find.

CHAPTER 12

Uninstallation

This chapter includes the following topics:

- [Uninstallation Overview, 100](#)
- [Uninstalling the Hub Store, 100](#)
- [Uninstalling the Process Server in Graphical Mode, 101](#)
- [Uninstalling the Hub Server in Graphical Mode, 102](#)
- [Uninstalling the Resource Kit in Graphical Mode, 102](#)
- [Uninstalling the Process Server in Console Mode, 103](#)
- [Uninstalling the Hub Server in Console Mode, 103](#)
- [Uninstalling the Resource Kit in Console Mode, 104](#)
- [Manually Undeploying the Process Server, 104](#)
- [Manually Undeploying the Hub Server, 104](#)

Uninstallation Overview

To uninstall the MDM Hub, you need to remove the Process Server, the Hub Server, and the Hub Store from the MDM Hub implementation.

Use the following steps to uninstall the MDM Hub:

1. Uninstall the Hub Store.
2. Uninstall the Process Server.
3. Uninstall the Hub Server.

Uninstalling the Hub Store

You can uninstall the Hub Store by dropping the Hub Store schemas and removing the user logins for the Hub Store schemas. Before you drop the Hub Store schemas, use the Hub Console to unregister the Hub Store schemas.

You must have administrator privileges to drop the Hub Store schemas.

1. Start the Hub Console.

2. Click the **Databases** tool under the **Configuration** workbench.
The **Database Information** page appears.
3. Click **Write Lock > Acquire Lock**.
4. From the list of databases, select the Operational Reference Store to unregister.
5. Click the **Unregister database** button.
The Databases tool prompts you to confirm unregistering the Operational Reference Store.
6. Click **Yes**.
7. Use Microsoft SQL Management Studio to connect to the Microsoft SQL Server instance.
8. Right-click each Hub Store schema, and then click **Delete**.
The **Delete Object** window appears.
9. Click **OK**.
The Hub Store schema is dropped.

Uninstalling the Process Server in Graphical Mode

You can uninstall the Process Server in graphical mode.

Uninstalling the Process Server in Graphical Mode On UNIX

To uninstall the MDM Hub, you must remove the Process Server. You must perform the steps to uninstall the Process Server for each Process Server in the MDM Hub implementation.

1. Stop the application server.
2. Navigate to the following directory:
`<infamdm_install_directory>/hub/cleanse/UninstallerData`
3. Run the uninstaller.
`./"Uninstall Informatica MDM Hub Cleanse Match Server"`
4. Click **Uninstall**.
When the uninstallation process is complete, the Uninstall Complete window appears.
5. Click **Done**.

Uninstalling the Process Server in Graphical Mode On Windows

To uninstall the MDM Hub, you must remove the Process Server. You must perform the steps to uninstall the Process Server for each Process Server in the MDM Hub implementation.

1. Stop the application server.
2. Click **Start** and then click **Programs > Infamdm > Hub > Cleanse > Uninstaller Data > Uninstall Informatica MDM Hub Cleanse Match Server**.
The Uninstall introduction window appears.
3. Click **Uninstall**.
When the uninstallation process is complete, the Uninstall Complete window appears.
4. Click **Done**.

Uninstalling the Hub Server in Graphical Mode

You can uninstall the Hub Server in graphical mode.

Uninstalling the Hub Server in Graphical Mode on UNIX

To uninstall the MDM Hub, you must remove the Hub Server from the MDM Hub implementation.

1. Ensure that you stop the application server.
2. Navigate to the following directory:

```
<infamdm_install_directory>/hub/server/UninstallerData
```

3. Run the uninstaller.

```
./"Uninstall Informatica MDM Hub Server"
```

The Uninstall introduction window appears.

4. Click **Uninstall**.

When the uninstallation process is complete, the Uninstall Complete window appears.

5. Click **Done**.

Uninstalling the Hub Server in Graphical Mode on Windows

To uninstall the MDM Hub, you must remove the Hub Server from the MDM Hub implementation.

1. Ensure that you stop the application server.
2. Click **Start** and then click **Programs > Infamdm > Hub > Server > UninstallerData > Uninstall Informatica MDM Hub Server**.

The Uninstall introduction window appears.

3. Click **Uninstall**.

When the uninstallation process is complete, the Uninstall Complete window appears.

4. Click **Done**.

Uninstalling the Resource Kit in Graphical Mode

You can uninstall the Resource Kit in graphical mode.

Uninstalling the Resource Kit in Graphical Mode on UNIX

To uninstall the Resource Kit, you must remove the Resource Kit from the MDM Hub implementation.

1. Stop the application server.
2. Navigate to the following directory:

```
<infamdm_install_directory>/hub/resourcekit/UninstallerData
```

3. Run the following command:

```
./"Uninstall Informatica MDM Hub Resource Kit"
```

The **Uninstall Informatica MDM Hub Resource Kit** window appears.

4. Click **Uninstall**.

The **Uninstall Complete** window appears with a list of items that could not be removed.

5. Click **Done**.

6. Manually remove the following directory:

```
<infamdm_install_dir>/hub/resourcekit
```

Uninstalling the Resource Kit in Graphical Mode on Windows

To uninstall the Resource Kit, you must remove the Resource Kit from the MDM Hub implementation.

1. Stop the application server.

2. Navigate to the following directory:

```
<ResourceKit_install_dir>\deploy\UninstallerData
```

3. Double-click **Uninstall Informatica MDM Hub Resource Kit.exe**

The **Uninstall Informatica MDM Hub Resource Kit** window appears.

4. Click **Uninstall**.

The **Uninstall Complete** window appears with a list of items that could not be removed.

5. Click **Done**.

6. Manually remove the following directory:

```
<infamdm_install_dir>\hub\resourcekit
```

Uninstalling the Process Server in Console Mode

You can uninstall the Process Server in console mode on UNIX. If you installed the Process Server in console mode, uninstall the Process Server in console mode.

1. Go to the following directory:

```
<infamdm_install_dir>/hub/cleanse/UninstallerData
```

2. Type the following command to run the uninstaller:

```
./"Uninstall Informatica MDM Hub Cleanse Match Server"
```

Uninstalling the Hub Server in Console Mode

You can uninstall the Hub Server in console mode on UNIX. If you installed the Hub Server in console mode, uninstall the Hub Server in console mode.

1. Go to the following directory:

```
<infamdm_install_dir>/hub/server/UninstallerData
```

2. Type the following command to run the uninstaller:

```
./"Uninstall Informatica MDM Hub Server"
```

Uninstalling the Resource Kit in Console Mode

You can uninstall the Resource Kit in console mode. If you installed the Resource Kit in console mode, uninstall the Resource Kit in console mode.

1. Go to the following directory:

On UNIX. `<infamdm_install_dir>/hub/resourcekit/UninstallerData`

On Windows. `<infamdm_install_dir>\hub\resourcekit\UninstallerData`

2. Run the following command from the command prompt:

On UNIX. `"Uninstall Informatica MDM Hub Resource Kit.bin" -i console`

On Windows. `"Uninstall Informatica MDM Hub Resource Kit.exe" -i console`

Manually Undeploying the Process Server

You might need to manually undeploy the Process Server from the WebLogic Server environment.

- Use the WebLogic Server Administration Console to manually undeploy the `siperian-mrmcleanse.ear` file.

For more information, see the WebLogic documentation.

Manually Undeploying the Hub Server

You might need to manually undeploy the Hub Server from the WebLogic Server environment.

- Use the WebLogic Server Administration Console to undeploy the following deployment files:

Deployment File Name	Description
<code>siperian-mrm.ear</code>	Required. The Hub Server application.
<code>entity360view-ear.ear</code>	Optional. The Entity 360 framework.
<code>informatica-mdm-platform-ear.ear</code>	Optional. The Informatica platform application.

For more information, see the WebLogic documentation.

INDEX

A

- abTaskClient role
 - editing [80](#)
- ActiveVOS
 - URN, setting [82](#)
- ActiveVOS Console administrative user
 - abAdmin role [20](#)
 - creating [20](#)

C

- configuring Microsoft SQL Server for the MDM Hub [15](#)

D

- databases
 - target database [59](#)

H

- HTTPS
 - for Process Servers [74](#)
- Hub Console
 - starting [55](#), [59](#)
- Hub Server
 - build number [44](#)
 - deploying on WebLogic cluster [39](#)
 - deployment [46](#)
 - deployment script [46](#)
 - installation log files [44](#)
 - installing [31](#), [35](#), [88](#)
 - manual deployment [46](#), [49](#)
 - postInstallSetup script [47](#)
 - repackaging custom JAR files [53](#)
 - repackaging EAR files [53](#)
 - silent installation [38](#), [93](#)
 - uninstalling [103](#), [104](#)
 - version information [44](#)
- Hub Server installation mode
 - console [31](#)
 - graphical [31](#)
 - silent [31](#)
- Hub Server properties file
 - configuring [25](#)
- Hub Store
 - uninstalling [100](#)

I

- Infinispan
 - configuring [57](#), [58](#)
- Informatica ActiveVOS
 - creating the schema [16](#)
- Informatica platform
 - properties file [25](#)
- installing
 - Hub Server [31](#), [35](#)
 - Process Server [61](#), [63](#)
 - Resource Kit [88](#), [91](#)

J

- JMS message queues
 - configuring [52](#), [55](#)

L

- log file
 - debug log file [44](#), [68](#)
 - Hub Server log file [44](#)
 - installation log file [44](#), [68](#)
 - installation prerequisites log file [44](#), [68](#)
 - JBoss log file [44](#), [68](#)
 - post install setup log file [44](#), [68](#)
 - Process Server log file [68](#)

M

- Master Database
 - creating [26](#)
 - importing metadata [28](#)
- match population
 - enabling [75](#)
- MDM Hub
 - components [9](#)
 - designing the installation [11](#)
 - installation tasks [11](#)
 - installation topology [11](#)
 - introduction [9](#)
 - Java Development Kit (JDK) requirement [13](#)
 - setting environment variables [13](#)
 - setting operating system locale [13](#)
 - system requirements [13](#)
- MDM Hub EAR files
 - repackaging [53](#)
- message queues
 - adding to the module [53](#)
- Microsoft SQL Server
 - configuring [15](#)
 - data file store [16](#)

Microsoft SQL Server (*continued*)
distributed transactions [15](#)
installing [15](#)
ODBC Driver [16](#)
unixODBC Driver [16](#)

O

Operational Reference Store
creating [27](#)
importing metadata [29](#)
registering [59](#)

P

postinstallsetup script
running [72](#)
postInstallSetup script
for Hub Server [47](#)
for Process Server [72](#)
running [47](#)
Process Server
build number [69](#)
create data sources [69](#)
deploying [72](#)
deploying on WebLogic cluster [65](#)
deployment [69](#), [72](#)
deployment script [69](#), [72](#)
installation log files [68](#)
installing [61](#), [63](#)
manual deployment [69](#), [72](#)
postInstallSetup script [72](#)
redeploying [73](#)
uninstalling [103](#)
version information [69](#)
Process Server installation mode
console [61](#)
graphical [61](#)
silent [61](#)
Process Server properties file
configuring [25](#)
Process Servers
HTTPS, enabling [74](#)

R

Resource Kit
installing [88](#), [91](#)
silent properties file [94](#)

Resource Kit (*continued*)
uninstalling [103](#)
roles
abTaskClient, editing [80](#)
ActiveVOS, adding [78](#)

S

Sample Schema
installing [85](#)
registering [87](#)
secure communications
enabling, in the Process Server [74](#)
security realm
default, editing [78](#)
silent installation
Generating response files for [38](#)
of Hub Server [38](#)
silent installer
running [65](#)

T

target database
selecting [59](#)
troubleshooting
post-installation process [97](#)

U

uninstalling
Hub Server [103](#), [104](#)
Hub Store [100](#)
Process Server [103](#)
URN
setting ActiveVOS [82](#)

W

WebLogic
configuring [17](#)
settings [45](#)
WebLogic cluster
deploying Hub Server [39](#)
deploying Process Server [65](#)
workflow engines
adding [83](#)